

## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ANTI-TERRA-205  
UFI : Q3R0-G0C9-700Y-0N20  
Product code : 000000000000105973

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Wetting & Dispersing Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735  
  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

Europe +44 1235 239670  
Middle East/Africa +44 1235 239671  
Americas +1 215 207 0061  
East/South East Asia +65 3158 1074  
(Local India: 000 800 100 7479)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Hazardous components which must be listed on the label:

- 162627-17-0 Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine
- 107-98-2 1-methoxy-2-propanol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Solution of a polycarboxylic acid salt of polyamine amides

#### Components

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine	162627-17-0 01-2119970640-38-0000	Skin Sens. 1A; H317	>= 50 - <= 100
1-methoxy-2-propanol	107-98-2 203-539-1 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
naphtha (petroleum)	64741-65-7 01-2119471991-29	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 12,5 - < 20

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
  
Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0

SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020

Print Date 15.05.2025

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Nitrogen oxides (NO<sub>x</sub>)  
Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
------------	---------	-------------------------------	--------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0

SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020

Print Date 15.05.2025

1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	150 ppm 568 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1-methoxy-2-propanol	Workers	Inhalation	Acute local effects	553,5 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	50,6 mg/kg
	Workers	Inhalation	Long-term systemic effects	369 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	18,1 mg/kg
	Consumers	Inhalation	Long-term systemic effects	43,9 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	3,3 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1-methoxy-2-propanol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Intermittent releases	100 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	41,6 mg/kg
	Marine sediment	4,17 mg/kg
	Soil	2,47 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber  
Break through time : > 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

If the product contaminates rivers and lakes or drains inform respective authorities.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	amber
Odour	:	musty
Odour Threshold	:	No data available
Melting point/range	:	< 0 °C Method: derived
Initial boiling point	:	120,00 °C Method: derived
Upper explosion limit / Upper flammability limit	:	13,10 %(V)
Lower explosion limit / Lower flammability limit	:	0,60 %(V)
Flash point	:	24,00 °C Method: 48 (Abel-Pensky)
Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	6 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	123 mm <sup>2</sup> /s (40 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	13,0000000 hPa (20,00 °C) Method: derived
Relative density	:	No data available
Density	:	0,9000 g/cm <sup>3</sup> (20,00 °C) Method: 4 (20°C oscillating U-tube)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0

SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020

Print Date 15.05.2025

Bulk density : Not applicable

Relative vapour density : No data available

### 9.2 Other information

Flammability (liquids) : Sustains combustion

Evaporation rate : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: No data available

##### Components:

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Acute oral toxicity : LD50 Oral (Rat, male and female): > 10.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

#### **1-methoxy-2-propanol:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

Acute oral toxicity : LD50 (Rat, male and female): 4.016 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2.000 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.3.  
GLP: yes

### **naphtha (petroleum):**

Acute oral toxicity : LD50 (Rat, male and female): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 4.951 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: no

Acute dermal toxicity : LD50 (Rabbit, male and female): > 5.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### **Skin corrosion/irritation**

#### **Product:**

Remarks : May cause skin irritation and/or dermatitis.

#### **Components:**

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

#### **1-methoxy-2-propanol:**

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.4.  
Result : No skin irritation  
GLP : yes

#### **naphtha (petroleum):**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

### Serious eye damage/eye irritation

#### Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

#### Components:

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

#### **1-methoxy-2-propanol:**

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.5.  
Result : No eye irritation  
GLP : yes

#### **naphtha (petroleum):**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### Respiratory or skin sensitisation

#### Product:

Remarks : Causes sensitisation.

#### Components:

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Test Type : Mouse Local Lymph Node assay (LLNA)  
Species : Mouse  
Assessment : May cause sensitisation by skin contact.  
Method : OECD Test Guideline 429  
Result : May cause sensitisation by skin contact.  
GLP : yes

#### **1-methoxy-2-propanol:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : Directive 67/548/EEC, Annex V, B.6.  
Result : Does not cause skin sensitisation.  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

### naphtha (petroleum):

Exposure routes : Intradermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available  
Genotoxicity in vivo : Remarks: No data available

#### Components:

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes

Test Type: Chromosome aberration test in vitro  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative  
GLP: yes

Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative  
GLP: yes

### naphtha (petroleum):

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

#### Product:

Remarks : No data available

## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

### Components:

#### **naphtha (petroleum):**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Reproductive toxicity**

##### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### **STOT - single exposure**

##### Product:

Remarks : No data available

#### **STOT - repeated exposure**

##### Product:

Remarks : No data available

#### **Repeated dose toxicity**

##### Product:

Remarks : No data available

### Components:

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Species : Rat, male and female  
NOAEL : > 1.000 mg/kg  
Application Route : Oral  
Method : OECD Test Guideline 422  
GLP : yes

#### **Aspiration toxicity**

##### Product:

No data available

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

#### Components:

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 150 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: DIN 38412  
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : ErL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to microorganisms : IC50 (Pseudomonas putida): > 430 mg/l  
End point: Biomass  
Exposure time: 16 h  
Method: DIN 38412, L 8  
GLP: no

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL50: > 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

Method: OECD Test Guideline 211  
GLP: yes

### 1-methoxy-2-propanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6.812 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: DIN 38412  
GLP: no

### naphtha (petroleum):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to fish (Chronic toxicity) : NOELR: 0,192 mg/l

## 12.2 Persistence and degradability

### Product:

Biodegradability : Remarks: No data available

### Components:

#### **Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301  
GLP: yes

### 1-methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301  
GLP: yes

### naphtha (petroleum):

## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation : Remarks: No data available

**Components:**

**1-methoxy-2-propanol:**

Partition coefficient: n-  
octanol/water : log Pow: 0,37 (20 °C)  
pH: 6,8  
Method: OECD Test Guideline 117  
GLP: No information available.

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADR** : UN 1993  
**IMDG** : UN 1993  
**IATA** : UN 1993

#### 14.2 UN proper shipping name

**ADR** : FLAMMABLE LIQUID, N.O.S.  
(1-Methoxy-2-propanol, naphtha (petroleum))  
**IMDG** : FLAMMABLE LIQUID, N.O.S.  
(1-Methoxy-2-propanol, naphtha (petroleum))  
**IATA** : Flammable liquid, n.o.s.  
(1-Methoxy-2-propanol, naphtha (petroleum))

#### 14.3 Transport hazard class(es)

**ADR** : 3  
**IMDG** : 3  
**IATA** : 3

#### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : D/E  
**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : IMDG Code segregation group - none

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344

## ANTI-TERRA-205

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

### 15.2 Chemical safety assessment

Not applicable

---

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H317 : May cause an allergic skin reaction.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## ANTI-TERRA-205

Version 2.0

SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020

Print Date 15.05.2025

Flam. Liq.	:	Flammable liquids
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

## **ANTI-TERRA-205**

Version 2.0  
SDB\_IS

Revision Date: 19.01.2023

Date of last issue: 30.09.2020  
Print Date 15.05.2025

---

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG\_EU / EN