

**ANTI-TERRA-U SG**Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : ANTI-TERRA-U SG  
Product code : 000000000000114200

**Manufacturer or supplier's details**

Company : BYK USA LLC  
Address : South Cherry Street 524  
06492 Wallingford  
Telephone : +1 203-265-2086  
Telefax :  
E-mail address : BRIEF.BYK.NAFTA@altana.com  
Emergency telephone number : 18000 74234 (toll –free number, access from Australia  
only)  
+61 2 8014 4558

**Importer**

Company : IMCD Australia Pty Ltd  
Level 1, 352 Wellington Road  
Mulgrave  
VIC 3170  
Australia  
Telephone: +61 3 8544 3100

Use of the Sub-  
stance/Mixture : Wetting & Dispersing Additive

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3  
Skin corrosion/irritation : Category 2  
Carcinogenicity : Category 1B  
Specific target organ toxicity - : Category 3 (Respiratory system)  
single exposure  
Specific target organ toxicity - : Category 2 (hearing organs)  
repeated exposure  
Aspiration hazard : Category 1  
Long-term (chronic) aquatic : Category 3  
hazard

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

**GHS label elements**

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H335 May cause respiratory irritation.  
H350 May cause cancer.  
H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
Chemical nature : Solution of a salt of unsaturated polyamine amides and lower molecular weight acidic polyesters

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Polyamine amide salt	-	$\geq 50$ - $\leq 100$
Xylene, mixture of isomers	1330-20-7	$\geq 30$ - $< 50$
ethylbenzene	100-41-4	$\geq 7$ - $< 10$
iso-butanol	78-83-1	$\geq 3$ - $< 5$
propane-1,2-diol	57-55-6	$\geq 3$ - $< 5$
cumene	98-82-8	$\geq 0.25$ - $< 0.5$
toluene	108-88-3	$\geq 0.1$ - $< 0.25$

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and : No information available.  
May be fatal if swallowed and enters airways.

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

delayed Causes skin irritation.  
May cause respiratory irritation.  
May cause cancer.  
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : No information available.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)  
Sulphur oxides

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Hazchem Code : •3Y

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Neutralize with chalk, alkali solution or ammonia.  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against : Do not spray on a naked flame or any incandescent material.

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

fire and explosion	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
Conditions for safe storage	: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Further information on storage stability	: No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	TWA	80 ppm 350 mg/m <sup>3</sup>	AU OEL
		STEL	150 ppm 655 mg/m <sup>3</sup>	AU OEL
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 434 mg/m <sup>3</sup>	AU OEL
		STEL	125 ppm 543 mg/m <sup>3</sup>	AU OEL
iso-butanol	78-83-1	TWA	20 ppm	ACGIH
		TWA	50 ppm 152 mg/m <sup>3</sup>	AU OEL
propane-1,2-diol	57-55-6	TWA	50 ppm	ACGIH
		TWA (particulate)	10 mg/m <sup>3</sup>	AU OEL
		TWA (Total (vapour and particles))	150 ppm 474 mg/m <sup>3</sup>	AU OEL

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

cumene	98-82-8	TWA	25 ppm 125 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		STEL	75 ppm 375 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		TWA	5 ppm	ACGIH
toluene	108-88-3	TWA	50 ppm 191 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		STEL	150 ppm 574 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		TWA	20 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Xylene, mixture of iso-mers	1330-20-7	Methylhip-puric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g cre-atinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxalic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

## Hand protection

Material : Fluorinated rubber  
Break through time :  $\geq 480$  min  
Glove thickness : 0.4 mm

Remarks : Wear suitable gloves.  
Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : light brown

Odour : aromatic

Odour Threshold : No data available

pH : 4  
Concentration: 1 %  
Method: Universal pH-value indicator

Melting point/ range :  $< 10$  °C  
Method: derived

Initial boiling point : 106.00 °C  
Method: derived

Flash point : 25.00 °C  
Method: 48 (Abel-Pensky) DIN 51755

Evaporation rate : No data available

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : 10.70 %(V)

Lower explosion limit / Lower flammability limit : 1.20 %(V)

Vapour pressure : 11 hPa (20.00 °C)  
Method: derived

Relative vapour density : No data available

Relative density : No data available

Density : 0.9400 g/cm<sup>3</sup> (20.00 °C, 1,013 hPa)

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

---

	Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: > 200 °C Method: DIN 51794
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 15.217 mm <sup>2</sup> /s ( 40 °C) Method: calculated

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified due to lack of data.

**Product:**

Acute oral toxicity	: LD50 (Rat): 12,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

**Components:****Xylene, mixture of isomers:**

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg  
GLP: No information available.

**iso-butanol:**

Acute oral toxicity : LD50 (Rat, male): > 2,830 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : May irritate skin.  
May cause skin irritation in susceptible persons.

Species : Rabbit  
Assessment : Irritating to skin.  
Method : OECD Test Guideline 404  
Result : Skin irritation

**Components:****iso-butanol:**

Species : Rabbit  
Result : Skin irritation

**propane-1,2-diol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

**Product:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405

Remarks : Vapours may cause irritation to the eyes, respiratory system  
and the skin.

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026**Components:****iso-butanol:**

Species : Rabbit  
Result : Eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

**propane-1,2-diol:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified due to lack of data.

**Respiratory sensitisation**

Not classified due to lack of data.

**Product:**

Remarks : No data available

**Components:****iso-butanol:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

**propane-1,2-diol:**

Test Type : Mouse Local Lymph Node assay (LLNA)  
Exposure routes : Dermal  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : Does not cause skin sensitisation.

**Chronic toxicity****Germ cell mutagenicity**

Not classified due to lack of data.

**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

**Carcinogenicity**

May cause cancer.

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

---

**Product:**

Remarks : No data available

**Reproductive toxicity**

Not classified due to lack of data.

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**STOT - single exposure**

May cause respiratory irritation.

**Product:**

Remarks : No data available

**STOT - repeated exposure**

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

**Product:**

Remarks : No data available

**Repeated dose toxicity**

**Product:**

Remarks : No data available

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Components:**

**iso-butanol:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks : Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

**Product:**

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other :

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

aquatic invertebrates                      Remarks: No data available

**Components:**

**Polyamine amide salt:**

Toxicity to fish                               : LC50 (Oncorhynchus mykiss (rainbow trout)): > 48 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other           : EC50 (Daphnia magna (Water flea)): > 30 mg/l  
aquatic invertebrates                      Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

**Xylene, mixture of isomers:**

Toxicity to daphnia and other           : EC50 (Daphnia magna (Water flea)): 1 mg/l  
aquatic invertebrates                      Exposure time: 24 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic                 : EC50 (Selenastrum capricornutum (green algae)): 2.2 mg/l  
plants   Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.44 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-           : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
icity)    Exposure time: 56 d

Toxicity to daphnia and other           : NOEC (Daphnia sp. (water flea)): 1.17 mg/l  
aquatic invertebrates (Chron-            Exposure time: 7 d  
ic toxicity)                                    NOEC (Daphnia sp. (water flea)): 0.96 mg/l  
Exposure time: 7 d

**iso-butanol:**

Toxicity to fish                               : LC50 (Pimephales promelas (fathead minnow)): 1,430 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other           : EC50 (Daphnia pulex (Water flea)): 1,100 mg/l  
aquatic invertebrates                      Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic                 : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,799

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

plants mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 20 mg/l  
aquatic invertebrates (Chronic toxicity) : End point: Reproduction  
Exposure time: 21 d  
Test Type: semi-static test

**propane-1,2-diol:**

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata): 34,100 mg/l  
plants : Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Components:****Xylene, mixture of isomers:**

Biodegradability : aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

**iso-butanol:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D

**propane-1,2-diol:**

Biodegradability : aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Components:****Xylene, mixture of isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 25.9  
Exposure time: 56 d

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

GLP: no

Partition coefficient: n-octanol/water : Pow: 3.2 (20 °C)  
pH: 7

**iso-butanol:**

Partition coefficient: n-octanol/water : log Pow: 1  
Method: OECD Test Guideline 117  
GLP: yes

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, Isobutanol)  
Class : 3  
Packing group : III  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Xylene, Isobutanol)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo) : 366

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

aircraft)  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, Isobutanol)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no  
Remarks : IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Xylene, Isobutanol)  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : •3Y

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

---

**SECTION 16. OTHER INFORMATION**

Revision Date : 22.01.2026  
Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
AU OEL / TWA : Exposure standard - time weighted average

## ANTI-TERRA-U SG

Version 3.0  
SDS\_AU

Revision Date: 22.01.2026

Date of last issue: 14.03.2025  
Print Date 28.01.2026

AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN