

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 1. IDENTIFICATION**

Product name : BYK-1791

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Air Release Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Eye irritation : Category 2B

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H320 Causes eye irritation.Precautionary statements : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting  
equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**

## BYK-1791

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : solution of polyolefin

**Hazardous components**

Component	CAS-No.	Concentration (%)
Naphtha, petroleum, heavy alkylate	64741-65-7	>= 30 - < 60

### SECTION 4. FIRST AID MEASURES

If inhaled : Remove to fresh air. Administer artificial respiration if necessary. Get medical aid as soon as possible.

In case of skin contact : Remove contaminated clothing. Wash thoroughly with soap and water.

In case of eye contact : Immediately flush with plenty of water for at least 20 minutes. Get medical aid.

If swallowed : Do not induce vomiting; aspiration hazard. Dilute with 1-2 glasses of water. Get medical aid. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.  
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : No information available.

### SECTION 5. FIREFIGHTING MEASURES

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

- Suitable extinguishing media : Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : No information available.
- Specific hazards during firefighting : Will not explode on mechanical impact.
- Hazardous combustion products : Carbon oxides
- Further information : Keep away from heat and sources of ignition.  
Keep away from oxidizing agents.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Eliminate all sources of ignition. Wear protective equipment: safety glasses, gloves and an appropriate respirator.
- Environmental precautions : Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.
- Methods and materials for containment and cleaning up : Stop leak. Dike and contain spill.  
Absorb with suitable material and remove with sparkless shovel and/or scoop.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid contact with skin and eyes.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Keep container closed when not in use.  
Take precautionary measures against static discharges.
- Conditions for safe storage : Keep in a dry, cool and well-ventilated place.  
Keep product and empty container away from heat and sources of ignition.  
Take measures to prevent the build up of electrostatic charge.
- Materials to avoid : Keep away from oxidizing agents.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha, petroleum, heavy	64741-65-7	TWA	500 ppm	OSHA Z-1

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

alkylate			2,000 mg/m3	
Naphtha, petroleum, heavy alkylate		TWA	400 ppm 1,600 mg/m3	OSHA P0

**Engineering measures** : Use with local exhaust ventilation.

**Personal protective equipment**

Respiratory protection : If handling heated or misted product in a poorly ventilated area, wear a properly fitted respirator (NIOSH) during exposure.

Hand protection  
Material : Neoprene gloves

Eye protection : Goggles  
Safety glasses with side-shields

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
Clean long legged, long sleeved work clothes.  
If splashing is possible, wear chemically resistant protective clothing.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid  
Colour : light yellow  
Odour : mild  
Odour Threshold : No data available

pH : 7, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator

Melting point/ range : < 41 °F (< 5 °C)  
Method: derived

Initial boiling point : 334 °F (168 °C)  
Method: derived

Vapour pressure : 2 hPa (68 °F (20 °C))  
Method: derived

Flash point : 99 °F (37 °C)  
Method: 48 (Abel-Pensky) DIN 51755

Upper explosion limit : No data available

Lower explosion limit : No data available

Evaporation rate : No data available

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

Relative vapour density	:	No data available
Relative Density/Specific Gravity	:	No data available
Density	:	0.802 g/cm <sup>3</sup> (68 °F (20 °C)) Method: 4 (20°C oscillating U-tube)
Solubility(ies)	:	
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 392 °F (> 200 °C) Method: M0062 (Analytics Wesel)
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	26.4 mm <sup>2</sup> /s (104 °F (40 °C))

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable; polymerization will not occur
Possibility of hazardous reactions	:	No data available
Conditions to avoid	:	None known.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	None expected

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Ingestion  
Eyes  
Skin Absorption  
Skin contact

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

**Acute toxicity****Product:**

Acute oral toxicity : Remarks: No data available

**Components:****64741-65-7 Naphtha, petroleum, heavy alkylate:**

Acute oral toxicity : LD50 (Rat): 34,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3684 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: No data available

**Components:****64741-65-7 Naphtha, petroleum, heavy alkylate:**

Species: Rabbit

Result: slight irritation

**Serious eye damage/eye irritation****Product:**

Remarks: No data available

**Components:****64741-65-7 Naphtha, petroleum, heavy alkylate:**

Species: Rabbit

Result: Mild eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks: No data available

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Carcinogenicity**

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

**Product:**

Remarks: No data available

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**STOT - single exposure****Product:**

Remarks: No data available

**STOT - repeated exposure****Product:**

Remarks: No data available

**Repeated dose toxicity****Product:**

Remarks: Chronic skin contact with petroleum distillates has caused dermatitis.

**Aspiration toxicity****Product:**

No data available

**Experience with human exposure****Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness,

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

		loss of coordination and fatigue).
Skin contact:	Symptoms:	Contact may cause irritation.
Eye contact:	Symptoms:	Contact may cause irritation.
Ingestion:	Symptoms:	Ingestion may irritate the digestive tract; high dosages may cause CNS depression.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There is no data available for this product.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 3295  
Proper shipping name : Hydrocarbons, liquid, n.o.s.  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 3295  
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : yes  
Remarks : IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : UN 3295  
Proper shipping name : Hydrocarbons, liquid, n.o.s.  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

ERG Code : 128  
Marine pollutant : yes (naphtha (petroleum))  
Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 41.0 %  
Method: 23 (20min/150°C)  
DIN EN ISO 3251  
Non-volatile information is not a specification.

**BYK-1791**

Version 7

Revision Date 05/17/2026

Print Date 06/18/2026

**Massachusetts Right To Know**

No components are subject to the Massachusetts Right to Know Act.

**Pennsylvania Right To Know**

Naphtha, petroleum, heavy alkylate	64741-65-7
Polymer	-

**New Jersey Right To Know**

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-5279

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

TSCA	: We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
TSCA Inventory Active List	: All components of this product are listed active and/or are exempt
DSL	: We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.