

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYK-306
Product code : 000000000000102992

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Surface Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel
Telephone : +49 281 670-0
Telefax : +49 281 65735

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|--|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Acute toxicity, Category 4 | H332: Harmful if inhaled. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure, Category 2 | H373: May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters airways. |
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

Persistent, bioaccumulative and toxic EUH440: Accumulates in the environment and living organisms including in humans.

Very persistent and very bioaccumulative EUH441: Strongly accumulates in the environment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB





Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

|| **and living organisms including in humans.**

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

| | | |
|--------------------------|---|--|
| Hazard pictograms | : |     |
| Signal word | : | Danger |
| Hazard statements | : | H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H332 Harmful if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects. EUH441 Strongly accumulates in the environment and living organisms including in humans. |
| Precautionary statements | : | Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant. |

Hazardous components which must be listed on the label:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

- 1330-20-7 Xylene, mixture of isomers
- 122-99-6 2-phenoxyethanol
- 556-67-2 octamethylcyclotetrasiloxane [D4]

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solution of a polyether modified polydimethylsiloxane

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|----------------------------|---|--|---------------------------|
| Xylene, mixture of isomers | 1330-20-7 01-2119488216-32 | Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Aquatic Chronic 3; H412 | >= 30 - < 50 |
| 2-phenoxyethanol | 122-99-6 204-589-7 01-2119488943-21 | Acute Tox. 4; H302 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Acute toxicity estimate Acute oral toxicity: 1.394 mg/kg 1.394 mg/kg | >= 20 - < 25 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

| | | | |
|-----------------------------------|---|---|---------------------|
| ethylbenzene | 100-41-4 202-849-4 | Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | $\geq 12,5 - < 20$ |
| Alkenyl-alkyl-polyglycoether | - | Acute Tox. 4; H302 Acute toxicity estimate Acute oral toxicity: 1.502 mg/kg | $\geq 1 - < 3$ |
| octamethylcyclotetrasiloxane [D4] | 556-67-2 209-136-7 01-2119529238-36 | Repr. 2; H361f Aquatic Chronic 1; H410 PBT; EUH440 vPvB; EUH441 Flam. Liq. 3; H226 M-Factor (Chronic aquatic toxicity): 1010 | $\geq 0,1 - < 0,25$ |
| decamethylcyclopentasiloxane | 541-02-6 208-764-9 | PBT; EUH440 vPvB; EUH441 | $\geq 0,1 - < 0,25$ |
| toluene | 108-88-3 203-625-9 | Aquatic Chronic 3; H412 Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 | $\geq 0,1 - < 0,25$ |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

advice.

- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible
tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty
of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
Harmful if inhaled.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated
exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

firefighting courses.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|----------------------------|--|-------------------------------|----------------------------------|------------|
| Xylene, mixture of isomers | 1330-20-7 | TWA | 50 ppm 221 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | STEL | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | TWA | 50 ppm 220 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 100 ppm | GB EH40 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

| | | | | |
|--------------|--|------|----------------------------------|------------|
| | | | 441 mg/m ³ | |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| ethylbenzene | 100-41-4 | TWA | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | STEL | 200 ppm 884 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | TWA | 100 ppm 441 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 125 ppm 552 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| toluene | 108-88-3 | TWA | 50 ppm 192 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | STEL | 100 ppm 384 mg/m ³ | 2006/15/EC |
| | Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | |
| | | TWA | 50 ppm 191 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 100 ppm 384 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|----------------------------|-----------|--|---------------|----------------|
| Xylene, mixture of isomers | 1330-20-7 | methyl hippuric acid: 650 Millimoles per mole creatinine (Urine) | After shift | GB EH40 BAT |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|----------------|---------|-----------------|--------------------------|-------|
|----------------|---------|-----------------|--------------------------|-------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

| | | | | |
|-----------------------------------|-----------|--------------|--|------------------------|
| Xylene, mixture of isomers | Workers | Inhalation | Long-term systemic effects | 221 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 442 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 212 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 65,3 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 125 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1,5 mg/kg |
| | Consumers | Inhalation | Acute local effects | 260 mg/m ³ |
| 2-phenoxyethanol | Workers | Inhalation | Long-term exposure, Systemic effects, Local effects | 8,07 mg/m ³ |
| | Workers | Skin contact | Long-term exposure, Systemic effects | 34,72 mg/kg |
| | Consumers | Inhalation | Long-term exposure, Short-term exposure, Local effects | 2,5 mg/m ³ |
| | Consumers | Skin contact | Long-term exposure, Local effects | 20,83 mg/kg |
| | Consumers | Ingestion | Long-term exposure, Short-term exposure, Systemic effects | 17,43 mg/kg |
| octamethylcyclotetrasiloxane [D4] | Consumers | Oral | Acute systemic effects, Long-term systemic effects | 3,7 mg/kg |
| | Consumers | Inhalation | Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects | 13 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects | 73 mg/m ³ |
| Xylene, mixture of isomers | Workers | Inhalation | Long-term systemic effects | 221 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 442 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 212 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 65,3 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 125 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 1,5 mg/kg |
| | Consumers | Inhalation | Acute local effects | 260 mg/m ³ |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

| | | | | |
|-----------------------------------|-----------|--------------|---|------------------------|
| 2-phenoxyethanol | Workers | Inhalation | Long-term exposure, Systemic effects, Local effects | 8,07 mg/m ³ |
| | Workers | Skin contact | Long-term exposure, Systemic effects | 34,72 mg/kg |
| | Consumers | Inhalation | Long-term exposure, Short-term exposure, Local effects | 2,5 mg/m ³ |
| | Consumers | Skin contact | Long-term exposure, Local effects | 20,83 mg/kg |
| | Consumers | Ingestion | Long-term exposure, Short-term exposure, Systemic effects | 17,43 mg/kg |
| octamethylcyclotetrasiloxane [D4] | Consumers | Oral | Acute systemic effects, Long-term systemic effects | 3,7 mg/kg |
| | Consumers | Inhalation | Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects | 13 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects | 73 mg/m ³ |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|-----------------------------------|---------------------------|--------------|
| Xylene, mixture of isomers | Fresh water | 0,327 mg/l |
| | Marine water | 0,327 mg/l |
| | Fresh water sediment | 12,46 mg/kg |
| | Marine sediment | 12,46 mg/kg |
| | Soil | 2,31 mg/kg |
| | Sewage treatment plant | 6,58 mg/l |
| | Intermittent releases | 0,327 mg/l |
| 2-phenoxyethanol | Fresh water | 0,943 mg/l |
| | Marine water | 0,0943 mg/l |
| | Intermittent releases | 3,44 mg/l |
| | Fresh water sediment | 7,2366 mg/kg |
| | Marine sediment | 0,7237 mg/kg |
| | Soil | 1,26 mg/kg |
| | Sewage treatment plant | 24,8 mg/l |
| octamethylcyclotetrasiloxane [D4] | Fresh water | 1,5 µg/l |
| | Marine water | 0,15 µg/l |
| | Fresh water sediment | 0,64 mg/kg |
| | Soil | 0,84 mg/kg |
| | Sewage treatment plant | 10 mg/l |
| | Marine sediment | 0,064 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

| | | |
|--|---|----------|
| | Hazard for predators: secondary poisoning | 41 mg/kg |
|--|---|----------|

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Fluorinated rubber
Break through time : > 480 min
Glove thickness : > 0,4 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : light yellow

Odour : aromatic

Odour Threshold : No data available

Melting point/ range : < 0 °C
Method: derived

Initial boiling point : 137,00 °C
Method: derived

Upper explosion limit / Upper flammability limit : 7,00 %(V)

Lower explosion limit / Lower flammability limit : 1,20 %(V)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

| | | |
|--|---|---|
| Flash point | : | 25,00 °C Method: 48 (Abel-Pensky) DIN 51755 |
| Auto-ignition temperature | : | > 200 °C Method: DIN 51 794/ DIN prEN 14 522 |
| Decomposition temperature | : | No data available |
| pH | : | 5 (20 °C) Concentration: 1 % Method: Universal pH-value indicator |
| Viscosity | | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | 2 mm ² /s (40 °C) |
| Solubility(ies) | | |
| Water solubility | : | immiscible |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Vapour pressure | : | 8 hPa (20 °C) Method: derived |
| Relative density | : | No data available |
| Density | : | 0,9280 g/cm ³ (20,00 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube) |
| Bulk density | : | Not applicable |
| Relative vapour density | : | No data available |

9.2 Other information

| | | |
|------------------------|---|---------------------|
| Flammability (liquids) | : | Sustains combustion |
| Evaporation rate | : | No data available |
| Surface tension | : | No data available |

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 16,54 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Xylene, mixture of isomers:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 4.200 mg/kg
GLP: No information available.

2-phenoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.394 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

No. 1272/2008

Acute toxicity estimate: 1.394 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 (Rat): 1.840 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute inhalation toxicity : LC50 (Rat): > 1 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 412
GLP: yes
Assessment: The substance or mixture has no acute
inhalation toxicity

Alkenyl-alkyl-polyglycoether:

Acute oral toxicity : LD50 (Rat): 1.502 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May irritate skin.
May cause skin irritation in susceptible persons.

Components:

2-phenoxyethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Alkenyl-alkyl-polyglycoether:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-phenoxyethanol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

Species : Rabbit
Method : OECD Test Guideline 405
Result : Eye irritation

Alkenyl-alkyl-polyglycolether:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:

2-phenoxyethanol:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

octamethylcyclotetrasiloxane [D4]:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

2-phenoxyethanol:

Effects on foetal development : Species: Rat
Application Route: Oral
Duration of Single Treatment: 14 d
General Toxicity Maternal: NOAEL: 300 mg/kg body weight
Teratogenicity: NOAEL: 1.000 mg/kg body weight
Method: OECD Test Guideline 414

Species: Rabbit
Application Route: Dermal
Duration of Single Treatment: 14 d
General Toxicity Maternal: NOAEL: 300 mg/kg body weight
Teratogenicity: NOAEL: 600 mg/kg body weight

STOT - single exposure

May cause respiratory irritation.

Product:

Remarks : No data available

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

Components:

2-phenoxyethanol:

Species : Rat
NOAEL : 700 mg/kg
Application Route : Oral
Method : OECD Test Guideline 408

Species : Rat

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

NOAEL : 0,0482 mg/l
Application Route : Inhalation
Method : OECD Test Guideline 412
Target Organs : Respiratory organs

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Components:

Xylene, mixture of isomers:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 24 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia sp. (water flea)

NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Daphnia sp. (water flea)

2-phenoxyethanol:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): min. 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to fish (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 34 d
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9,43 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

Xylene, mixture of isomers:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

2-phenoxyethanol:

Biodegradability : Biodegradation: > 70 %
Exposure time: 28 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

Method: OECD Test Guideline 301A

Alkenyl-alkyl-polyglycolether:

Biodegradability : Biodegradation: < 20 %
Exposure time: 28 d
Method: OECD Test Guideline 302B

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

Xylene, mixture of isomers:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Exposure time: 56 d
Bioconcentration factor (BCF): 25,9
GLP: no

Partition coefficient: n-
octanol/water : Pow: 3,2 (20 °C)
pH: 7

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to
be either persistent, bioaccumulative and toxic (PBT), or very
persistent and very bioaccumulative (vPvB).

Components:

octamethylcyclotetrasiloxane [D4]:

Assessment : Persistent, Bioaccumulative and Toxic (PBT).
: Very persistent and very bioaccumulative (vPvB).

decamethylcyclopentasiloxane:

Assessment : Persistent, Bioaccumulative and Toxic (PBT).
: Very persistent and very bioaccumulative (vPvB).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1993
ADR : UN 1993
RID : UN 1993
IMDG : UN 1993
IATA : UN 1993

14.2 UN proper shipping name

ADN : FLAMMABLE LIQUID, N.O.S.
(Xylene, Ethylbenzene)
ADR : FLAMMABLE LIQUID, N.O.S.
(Xylene, Ethylbenzene)
RID : FLAMMABLE LIQUID, N.O.S.
(Xylene, Ethylbenzene)
IMDG : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Ethylbenzene)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

IATA : Flammable liquid, n.o.s.
(Xylene, Ethylbenzene)

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : IMDG Code segregation group - none

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction : 355
(passenger aircraft)
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 5: benzene

Number on list 48: toluene

Number on list 70:
octamethylcyclotetrasiloxane [D4],
decamethylcyclopentasiloxane

Number on list 72: benzene

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

For further information see eSDS.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

| | |
|--------|---|
| EUH440 | : Accumulates in the environment and living organisms including in humans. |
| EUH441 | : Strongly accumulates in the environment and living organisms including in humans. |
| H225 | : Highly flammable liquid and vapour. |
| H226 | : Flammable liquid and vapour. |
| H302 | : Harmful if swallowed. |
| H304 | : May be fatal if swallowed and enters airways. |
| H312 | : Harmful in contact with skin. |
| H315 | : Causes skin irritation. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H332 | : Harmful if inhaled. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H361d | : Suspected of damaging the unborn child. |
| H361f | : Suspected of damaging fertility. |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H410 | : Very toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

| | |
|-------------------|--|
| Acute Tox. | : Acute toxicity |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Asp. Tox. | : Aspiration hazard |
| Eye Dam. | : Serious eye damage |
| Eye Irrit. | : Eye irritation |
| Flam. Liq. | : Flammable liquids |
| PBT | : Persistent, bioaccumulative and toxic |
| Repr. | : Reproductive toxicity |
| Skin Irrit. | : Skin irritation |
| STOT RE | : Specific target organ toxicity - repeated exposure |
| STOT SE | : Specific target organ toxicity - single exposure |
| vPvB | : Very persistent and very bioaccumulative |
| 2000/39/EC | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| 2006/15/EC | : Europe. Indicative occupational exposure limit values |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 BAT | : UK. Biological monitoring guidance values |
| 2000/39/EC / TWA | : Limit Value - eight hours |
| 2000/39/EC / STEL | : Short term exposure limit |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

| | | |
|-------------------|---|--|
| 2006/15/EC / TWA | : | Limit Value - eight hours |
| 2006/15/EC / STEL | : | Short term exposure limit |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : | Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 3 | H226 |
| Acute Tox. 4 | H332 |
| Skin Irrit. 2 | H315 |
| Eye Dam. 1 | H318 |
| STOT SE 3 | H335 |
| STOT RE 2 | H373 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

| | | |
|------------|---------------|---------------------------|
| PBT | EUH440 | Calculation method |
|------------|---------------|---------------------------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

vPvB

EUH441

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-306

Version: 17.0
SDB_GB

Revision Date: 20.03.2026

Date of last issue: 03.09.2024
Print Date: 31.03.2026

Annex: Exposure Scenarios

Table of Contents

| Number | Title |
|--------|-------|
|--------|-------|