

**BYK-306**Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026**Section 1: Identification**

Product name : BYK-306  
Product code : 000000000000102992

**Manufacturer or supplier's details**

Company : BYK-Chemie GmbH  
Address : Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com  
Emergency telephone number : 0800 446 881 (toll-free number, access from New Zealand only)  
+64 9 929 1483

**Importer**

Company : Alchemy Agencies Ltd  
Level 2, 20 Centre St  
Freemans Bay  
Auckland 1010 NZ  
Tel: +64(0)93770613

Use of the Substance/Mixture : Surface Additive

**Section 2: Hazard identification****GHS Classification**

Flammable liquids : Category 3  
Acute toxicity (Oral) : Category 4  
Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 1  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)  
Specific target organ toxicity - repeated exposure : Category 2

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

Hazardous to the aquatic environment - chronic hazard : Category 3

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

attention.  
P332 + P313 If skin irritation occurs: Get medical advice/  
attention.  
P362 + P364 Take off contaminated clothing and wash it before  
reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or  
alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container  
tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste  
disposal plant.

**Other hazards which do not result in classification**

None known.

**Section 3: Composition/information on ingredients**

Substance / Mixture : Mixture  
Chemical nature : Solution of a polyether modified polydimethylsiloxane

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Xylene, mixture of isomers	1330-20-7	>= 30 -< 50
2-phenoxyethanol	122-99-6	>= 20 -< 25
ethylbenzene	100-41-4	>= 12.5 -< 20
Alkenyl-alkyl-polyglycoether	-	>= 1 -< 3
octamethylcyclotetrasiloxane [D4]	556-67-2	>= 0.1 -< 0.25
toluene	108-88-3	>= 0.1 -< 0.25

**Section 4: First-aid measures**

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical  
advice.  
If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible  
tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty  
of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

If swallowed	:	<p>Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.</p>
Most important symptoms and effects, both acute and delayed	:	<p>No information available. Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.</p>
Notes to physician	:	No information available.

---

**Section 5: Fire-fighting measures**

Suitable extinguishing media	:	<p>Alcohol-resistant foam Carbon dioxide (CO<sub>2</sub>) Dry chemical</p>
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides
Specific extinguishing methods	:	<p>Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.</p>
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Hazchem Code	:	3Y

---

**Section 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures	:	<p>Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.</p>
Environmental precautions	:	Prevent product from entering drains.

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

**Section 7: Handling and storage**

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

---

**Section 8: Exposure controls/personal protection**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	WES-TWA	50 ppm 217 mg/m <sup>3</sup>	NZ OEL
Further information: Ototoxin, Exposure can also be estimated by				

# SAFETY DATA SHEET



## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

	biological monitoring			
Xylene, mixture of isomers		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m <sup>3</sup>	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m <sup>3</sup>	NZ OEL
	Further information: Ototoxin, Skin absorption			
ethylbenzene		TWA	20 ppm	ACGIH
toluene	108-88-3	WES-TWA	20 ppm 75 mg/m <sup>3</sup>	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring, Skin absorption			
		WES-STEL	100 ppm 377 mg/m <sup>3</sup>	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring, Skin absorption			
toluene		TWA	20 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenylglyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	Urine	End of exposure or end of shift	0.03 mg/l	NZ BEI
		o-Cresol	Urine	End of exposure or end of shift	0.3 mg/g creatinine	NZ BEI
		Toluene	In blood	Prior to last shift of	0.02 mg/l	ACGIH BEI

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

				workweek		
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection  
 Material : Fluorinated rubber  
 Break through time : > 480 min  
 Glove length : > 0.4 mm
- Remarks : Wear suitable gloves.
- Eye protection : Eye wash bottle with pure water  
 Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Section 9: Physical and chemical properties**

- Appearance : liquid
- Colour : light yellow
- Odour : aromatic
- Odour Threshold : No data available
- pH : 5 (20 °C)  
 Concentration: 1 %  
 Method: Universal pH-value indicator
- Melting point/ range : < 0 °C  
 Method: derived
- Initial boiling point : 137.00 °C  
 Method: derived
- Flash point : 25.00 °C

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

---

	Method: 48 (Abel-Pensky) DIN 51755
Evaporation rate	: No data available
Flammability (liquids)	: Sustains combustion
Upper explosion limit / Upper flammability limit	: 7.00 %(V)
Lower explosion limit / Lower flammability limit	: 1.20 %(V)
Vapour pressure	: 8 hPa (20 °C) Method: derived
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.9280 g/cm <sup>3</sup> (20.00 °C, 1,013 hPa) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: > 200 °C Method: DIN 51 794/ DIN prEN 14 522
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 2 mm <sup>2</sup> /s ( 40 °C)
Surface tension	: No data available

---

**Section 10: Stability and reactivity**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition	: No decomposition if stored and applied as directed.

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

products

**Section 11: Toxicological information****Acute toxicity**

Harmful if swallowed.

**Product:**Acute oral toxicity : Acute toxicity estimate: 935.08 mg/kg  
Method: Calculation methodAcute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method**Components:****Xylene, mixture of isomers:**Acute oral toxicity : LD50 (Rat): 4,300 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: noAcute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg  
GLP: No information available.**2-phenoxyethanol:**Acute oral toxicity : LD50 (Rat): 1,840 mg/kg  
Method: OECD Test Guideline 401  
GLP: noAcute inhalation toxicity : LC50 (Rat): > 1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 412  
GLP: yes  
Assessment: The substance or mixture has no acute  
inhalation toxicity**Alkenyl-alkyl-polyglycolether:**Acute oral toxicity : LD50 (Rat): 1,502 mg/kg  
Method: OECD Test Guideline 401**Skin corrosion/irritation**

Causes skin irritation.

**Product:**Remarks : May irritate skin.  
May cause skin irritation in susceptible persons.

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026**Components:****2-phenoxyethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Alkenyl-alkyl-polyglycolether:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Product:**

Remarks : May cause irreversible eye damage.

**Components:****2-phenoxyethanol:**

Species : Rabbit  
Result : Eye irritation  
Method : OECD Test Guideline 405

**Alkenyl-alkyl-polyglycolether:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified due to lack of data.

**Respiratory sensitisation**

Not classified due to lack of data.

**Product:**

Remarks : No data available

**Components:****2-phenoxyethanol:**

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

**octamethylcyclotetrasiloxane [D4]:**

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

---

GLP : yes

**Chronic toxicity****Germ cell mutagenicity**

Not classified due to lack of data.

**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

**Carcinogenicity**

Suspected of causing cancer.

**Product:**

Remarks : No data available

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**Components:****2-phenoxyethanol:**Effects on foetal development : Species: Rat  
Application Route: Oral  
Duration of Single Treatment: 14 d  
General Toxicity Maternal: NOAEL: 300 mg/kg body weight  
Teratogenicity: NOAEL: 1,000 mg/kg body weight  
Method: OECD Test Guideline 414Species: Rabbit  
Application Route: Dermal  
Duration of Single Treatment: 14 d  
General Toxicity Maternal: NOAEL: 300 mg/kg body weight  
Teratogenicity: NOAEL: 600 mg/kg body weight**STOT - single exposure**

May cause respiratory irritation.

**Product:**

Remarks : No data available

**STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Product:**

Remarks : No data available

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026**Repeated dose toxicity****Product:**

Remarks : No data available

**Components:****2-phenoxyethanol:**Species : Rat  
NOAEL : 700 mg/kg  
Application Route : Oral  
Method : OECD Test Guideline 408Species : Rat  
Application Route : Inhalation  
Method : OECD Test Guideline 412  
Target Organs : Respiratory organs**Aspiration toxicity**

Not classified due to lack of data.

**Product:**

No data available

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**Section 12: Ecological information****Ecotoxicity****Product:**

Toxicity to fish : Remarks: No data available

**Components:****Xylene, mixture of isomers:**Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1 mg/l  
aquatic invertebrates : Exposure time: 24 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 2.2 mg/l  
plants : Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.44

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

---

	mg/l Exposure time: 72 h Test Type: Growth inhibition Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l Exposure time: 56 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia sp. (water flea)): 1.17 mg/l Exposure time: 7 d  NOEC (Daphnia sp. (water flea)): 0.96 mg/l Exposure time: 7 d
<b>2-phenoxyethanol:</b>	
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia (water flea)): min. 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to fish (Chronic toxicity)	: NOEC: 23 mg/l Exposure time: 34 d Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia (water flea)): 9.43 mg/l Exposure time: 21 d Test Type: semi-static test Method: OECD Test Guideline 211

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Components:****Xylene, mixture of isomers:**Biodegradability : aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes**2-phenoxyethanol:**Biodegradability : Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301A**Alkenyl-alkyl-polyglycoether:**Biodegradability : Biodegradation: < 20 %  
Exposure time: 28 d  
Method: OECD Test Guideline 302B

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Components:****Xylene, mixture of isomers:**Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 25.9  
Exposure time: 56 d  
GLP: noPartition coefficient: n-  
octanol/water : Pow: 3.2 (20 °C)  
pH: 7**Mobility in soil**

No data available

**Other adverse effects****Product:**Additional ecological  
information : An environmental hazard cannot be excluded in the event of  
unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.**Section 13: Disposal considerations****Disposal methods**Waste from residues : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.  
Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.**Section 14: Transport information****International Regulations****UNRTDG**UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, Ethylbenzene)  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no**IATA-DGR**

UN/ID No. : UN 1993

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

Proper shipping name : Flammable liquid, n.o.s.  
(Xylene, Ethylbenzene)

Class : 3

Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo aircraft) : 366

Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, Ethylbenzene)

Class : 3

Packing group : III

Labels : 3

EmS Code : F-E, S-E

Marine pollutant : no

Remarks : IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****NZS 5433**

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Xylene, Ethylbenzene)

Class : 3

Packing group : III

Labels : 3

Hazchem Code : 3Y

Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**Section 15: Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002502 Additives Process Chemicals and Raw Materials Flammable Carcinogenic Group Standard

## Tolerable Exposure Limits (TEL)

Chemical name	Environmental compartment	Reference concentration
xylene	Air	0.87 mg/m <sup>3</sup>
	Water	0.6 mg/l

## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

---

Environmental Exposure Limits (EEL)

Not applicable

**HSW Controls**

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

---

**Section 16: Other information**

Revision Date : 14.04.2026  
Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
NZ BEI : New Zealand. Biological Exposure Indices  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average  
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods;

# SAFETY DATA SHEET



## BYK-306

Version 1.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 20.01.2025  
Print Date 15.04.2026

---

vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN