

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYK-315 N

UFI : VWYA-60JW-4001-UE9U

Product code : 000000000000129307

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Surface Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel

Telephone : +49 281 670-0  
Telefax : +49 281 65735

Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label:

- 122-99-6 2-phenoxyethanol
- 108-65-6 2-methoxy-1-methylethyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Solution of a polyester modified polymethylalkylsiloxane

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-phenoxyethanol	122-99-6 204-589-7 01-2119488943-21	Acute Tox. 4; H302 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) <hr/> Acute toxicity estimate  Acute oral toxicity: 1.394 mg/kg 1.840 mg/kg	>= 30 - < 50
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 30 - < 50

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.  
Risks : Causes serious eye damage.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.  
Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)  
Sulphur oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : No smoking. Keep container tightly closed in a dry and well-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

areas and containers                      ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability                      : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s)                      : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		OELV - 8 hrs (TWA)	50 ppm 275 mg/m <sup>3</sup>	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	100 ppm 550 mg/m <sup>3</sup>	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
2-phenoxyethanol	Workers	Inhalation	Long-term exposure, Systemic effects, Local effects	8,07 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term exposure, Systemic effects	34,72 mg/kg
	Consumers	Inhalation	Long-term exposure, Short-term exposure, Local effects	2,5 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term exposure, Local effects	20,83 mg/kg
	Consumers	Ingestion	Long-term exposure, Short-term exposure,	17,43 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

			Systemic effects	
2-methoxy-1-methylethyl acetate	Workers	Skin contact	Long-term systemic effects	796 mg/kg
	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Acute local effects	33 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2-phenoxyethanol	Fresh water	0,943 mg/l
	Marine water	0,0943 mg/l
	Intermittent releases	3,44 mg/l
	Fresh water sediment	7,2366 mg/kg
	Marine sediment	0,7237 mg/kg
	Soil	1,26 mg/kg
	Sewage treatment plant	24,8 mg/l
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent releases	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg
	Marine sediment	0,329 mg/kg
	Soil	0,29 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

### Hand protection

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : 0,5 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

### Environmental exposure controls

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : light brown, clear - slight cloudy

Odour : solvent-like

Odour Threshold : No data available

Melting point/ range : -5 °C  
Method: derived

Initial boiling point : 146,00 °C  
Method: derived

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 51,00 °C  
Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature : > 200 °C  
Method: DIN 51 794/ DIN prEN 14 522

Decomposition temperature : No data available

pH : 6 (20 °C)  
Concentration: 1 %  
Method: Universal pH-value indicator

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : No data available

Solubility(ies)

    Water solubility : immiscible

    Solubility in other solvents : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	2 hPa (20,00 °C) Method: derived
Relative density	:	No data available
Density	:	1,0300 g/cm <sup>3</sup> (20,00 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube)
Relative vapour density	:	No data available

### 9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	No decomposition if stored and applied as directed.
		Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

### 10.5 Incompatible materials

Materials to avoid	:	Strong acids and oxidizing agents
--------------------	---	-----------------------------------

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

### Components:

#### **2-phenoxyethanol:**

Acute oral toxicity : Acute toxicity estimate: 1.394 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

LD50 (Rat): 1.840 mg/kg  
Method: OECD Test Guideline 401  
GLP: no

Acute toxicity estimate: 1.840 mg/kg  
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): > 1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 412  
GLP: yes  
Assessment: The substance or mixture has no acute  
inhalation toxicity

#### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

#### **Skin corrosion/irritation**

Not classified due to lack of data.

### Product:

Remarks : No data available

### Components:

#### **2-phenoxyethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### **2-methoxy-1-methylethyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

Result : No skin irritation  
GLP : yes

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Product:

Remarks : May cause irreversible eye damage.

#### Components:

##### 2-phenoxyethanol:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Eye irritation

##### 2-methoxy-1-methylethyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Product:

Remarks : No data available

#### Components:

##### 2-phenoxyethanol:

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

##### 2-methoxy-1-methylethyl acetate:

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : yes

### Germ cell mutagenicity

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

### **Carcinogenicity**

Not classified due to lack of data.

### Product:

Remarks : No data available

### **Reproductive toxicity**

Not classified due to lack of data.

### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### Components:

#### **2-phenoxyethanol:**

Effects on foetal development : Species: Rat  
Application Route: Oral  
Duration of Single Treatment: 14 d  
General Toxicity Maternal: NOAEL: 300 mg/kg body weight  
Teratogenicity: NOAEL: 1.000 mg/kg body weight  
Method: OECD Test Guideline 414

Species: Rabbit  
Application Route: Dermal  
Duration of Single Treatment: 14 d  
General Toxicity Maternal: NOAEL: 300 mg/kg body weight  
Teratogenicity: NOAEL: 600 mg/kg body weight

### **STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

### Product:

Remarks : No data available

### **STOT - repeated exposure**

Not classified due to lack of data.

### Product:

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

### Repeated dose toxicity

#### Product:

Remarks : No data available

#### Components:

##### 2-phenoxyethanol:

Species : Rat  
NOAEL : 700 mg/kg  
Application Route : Oral  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL : 0,0482 mg/l  
Application Route : Inhalation  
Method : OECD Test Guideline 412  
Target Organs : Respiratory organs

### Aspiration toxicity

Not classified due to lack of data.

#### Product:

No data available

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

##### Components:

##### **2-phenoxyethanol:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): min. 100 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

Toxicity to fish (Chronic toxicity) : NOEC: 23 mg/l  
Exposure time: 34 d  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9,43 mg/l  
Exposure time: 21 d  
Species: Daphnia (water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211

##### **2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: no

#### 12.2 Persistence and degradability

##### Product:

Biodegradability : Remarks: No data available

##### Components:

##### **2-phenoxyethanol:**

Biodegradability : Biodegradation: > 70 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

Exposure time: 28 d  
Method: OECD Test Guideline 301A

### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

### **12.3 Bioaccumulative potential**

#### **Product:**

Bioaccumulation : Remarks: No data available

#### **Components:**

### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n- : log Pow: 1,2 (20 °C)  
octanol/water pH: 6,8  
Method: OECD Test Guideline 117  
GLP: yes

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### **Product:**

Additional ecological : No data available  
information

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 3272  
RID : UN 3272  
IMDG : UN 3272  
IATA : UN 3272

#### 14.2 UN proper shipping name

- ADR : ESTERS, N.O.S.  
(1-Methoxy-2-propanol acetate)  
RID : ESTERS, N.O.S.  
(1-Methoxy-2-propanol acetate)  
IMDG : ESTERS, N.O.S.  
(1-Methoxy-2-propanol acetate)  
IATA : Esters, n.o.s.  
(1-Methoxy-2-propanol acetate)

#### 14.3 Transport hazard class(es)

- ADR : 3  
RID : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

- ADR  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : D/E

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Remarks : IMDG Code segregation group - none

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

Number on list 72: benzene

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Fire Hazard Class : A II: Flash point 21 °C to 55 °C, at 15 °C not miscible in water

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

### 15.2 Chemical safety assessment

Not applicable

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H302 : Harmful if swallowed.  
H318 : Causes serious eye damage.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Eye Dam. : Serious eye damage  
Flam. Liq. : Flammable liquids  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)  
IE OEL / OELV - 15 min (STEL) : Occupational exposure limit value (15-minute reference period)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Eye Dam. 1	H318
STOT SE 3	H336
STOT SE 3	H335

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-315 N

Version 11.0  
SDB\_IE

Revision Date: 12.06.2025

Date of last issue: 15.07.2024  
Print Date 17.06.2025

---

## Annex: Exposure Scenarios

### Table of Contents

Number	Title
--------	-------