

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYK-354

UFI : 25E7-905T-000N-H1KM

Product code : 000000000000100750

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Acrylic Leveling Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735

Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage.

### Hazardous components which must be listed on the label:

- 64742-95-6 Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Solution of a polyacrylate

#### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

	Index-No. Registration number		
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 30 - < 50
2,6-dimethylheptan-4-one	108-83-8 203-620-1 01-2119474441-41	Flam. Liq. 3; H226 STOT SE 3; H335 (Respiratory system)  specific concentration limit STOT SE 3; H335 >= 10 %	>= 3 - < 5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Solvent naphtha (petroleum), light arom.;	Workers	Skin contact	Long-term exposure, Systemic effects	25 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Low boiling point naphtha -unspecified				
	Workers	Inhalation	Long-term exposure, Systemic effects	150 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term exposure, Systemic effects	11 mg/kg
	Consumers	Inhalation	Long-term exposure, Systemic effects	32 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term exposure, Systemic effects	11 mg/kg
2,6-dimethylheptan-4-one	Workers	Inhalation	Acute systemic effects, Acute local effects, Long-term local effects	290 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	80 mg/kg
	Workers	Inhalation	Long-term systemic effects	479 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects, Acute local effects, Long-term local effects	145 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	28,5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	171 mg/kg
	Consumers	Ingestion	Long-term systemic effects	7,14 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,6-dimethylheptan-4-one	Fresh water	0,03 mg/l
	Marine water	0,003 mg/l
	Intermittent releases	0,3 mg/l
	Fresh water sediment	0,46 mg/kg
	Marine sediment	0,046 mg/kg
	Sewage treatment plant	2,55 mg/l
	Soil	0,0746 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection  
Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : > 0,4 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : colourless  
Odour : not significant  
Odour Threshold : No data available

**Melting point/range** : **< 0 °C**  
Method: **derived**

Initial boiling point : 160,00 °C  
Method: derived

Upper explosion limit / Upper flammability limit : 7,50 %(V)

Lower explosion limit / Lower flammability limit : 1,00 %(V)

Flash point : 45,00 °C  
Method: 48 (Abel-Pensky) DIN 51755

**Auto-ignition temperature** : **> 200 °C**  
Method: **M0062 (Analytics Wesel)**

Decomposition temperature : No data available

pH : 5 (20 °C)  
Concentration: 1 %  
Method: Universal pH-value indicator

### Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 398,000 mm<sup>2</sup>/s (20,00 °C)  
262 mm<sup>2</sup>/s (40,00 °C)

### Solubility(ies)

Water solubility : immiscible  
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

---

Vapour pressure	:	4 hPa (20 °C) Method: derived
Relative density	:	No data available
Density	:	0,9480 g/cm <sup>3</sup> (20,00 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Relative vapour density	:	No data available

### 9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available
Surface tension	:	No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	No decomposition if stored and applied as directed.
		Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

### 10.5 Incompatible materials

Materials to avoid	:	Acids Strong oxidizing agents
--------------------	---	----------------------------------

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity	:	Remarks: No data available
---------------------	---	----------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : Remarks: No data available  
Acute inhalation toxicity : Remarks: No data available  
Acute dermal toxicity : LD50 (Rabbit, male and female): > 3.160 mg/kg  
Method: OECD Test Guideline 402

#### **2,6-dimethylheptan-4-one:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes  
Acute inhalation toxicity : LC50 (Rat): > 14 mg/l  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: no  
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### **Skin corrosion/irritation**

#### Product:

Remarks : No data available

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

#### **2,6-dimethylheptan-4-one:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

### **Serious eye damage/eye irritation**

#### Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### 2,6-dimethylheptan-4-one:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : no

### Respiratory or skin sensitisation

#### Product:

Remarks : No data available

#### Components:

#### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

### 2,6-dimethylheptan-4-one:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : yes

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

#### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

#### Product:

Remarks : No data available

## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

---

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Reproductive toxicity**

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### **STOT - single exposure**

#### Product:

Remarks : No data available

### **STOT - repeated exposure**

#### Product:

Remarks : No data available

### **Repeated dose toxicity**

#### Product:

Remarks : No data available

### **Aspiration toxicity**

#### Product:

No data available

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

#### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish : LL50 (Fish): 9,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata): 2,6 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

#### **2,6-dimethylheptan-4-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 30 mg/l  
Exposure time: 96 h  
Test Type: flow-through test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 37,2 mg/l  
Exposure time: 48 h  
Test Type: semi-static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 46,9 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201

## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

GLP: yes

### 12.2 Persistence and degradability

**Product:**

Biodegradability : Remarks: No data available

**Components:**

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F

**2,6-dimethylheptan-4-one:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D  
GLP: no

### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation : Remarks: No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 1993
- IMDG : UN 1993
- IATA : UN 1993

#### 14.2 UN proper shipping name

- ADR : FLAMMABLE LIQUID, N.O.S.  
(Solvent naphtha, Diisobutyl ketone)
- IMDG : FLAMMABLE LIQUID, N.O.S.  
(SOLVENT NAPHTHA, Diisobutyl ketone)
- IATA : Flammable liquid, n.o.s.  
(Solvent naphtha, Diisobutyl ketone)

#### 14.3 Transport hazard class(es)

- ADR : 3
- IMDG : 3
- IATA : 3

#### 14.4 Packing group

- ADR**
- Packing group : III
- Classification Code : F1
- Hazard Identification Number : 30
- Labels : 3
- Tunnel restriction code : D/E
- IMDG**
- Packing group : III
- Labels : 3
- EmS Code : F-E, S-E
- Remarks : IMDG Code segregation group - none

#### IATA (Cargo)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### 15.2 Chemical safety assessment

Not applicable

### SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
STOT SE	:	Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
STOT SE 3	H335
Aquatic Chronic 2	H411

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MT / EN

## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

## Annex: Exposure Scenarios

### Table of Contents

Number	Title
ES 1	Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).
ES 2	Use in coatings; Industrial uses (SU3).
ES 3	Use in coatings; Professional uses (SU22).
ES 4	Cleaning; Industrial uses (SU3).
ES 5	Cleaning; Professional uses (SU22).
ES 6	Use in laboratories; Industrial uses (SU3).
ES 7	Use in laboratories; Professional uses (SU22).
ES 8	Cleaning; Consumer uses (SU21).
ES 9	Use in coatings; Consumer uses (SU21).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### ES 1: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).

#### 1.1. Title section

<b>Exposure Scenario name</b>	: Formulation & (re)packing of substances and mixtures
<b>Structured Short Title</b>	: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).

Environment		
<b>CS 1</b>	<b>Formulation into mixture, Use of non-reactive processing aid at industrial site (no inclusion into or onto article)</b>	ERC2, ERC4
Worker		
<b>CS 2</b>	<b>Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</b>	PROC1
<b>CS 3</b>	<b>Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</b>	PROC2
<b>CS 4</b>	<b>Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Mixing or blending in batch processes, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Transfer of substance or mixture into small containers (dedicated filling line, including weighing), Tableting, compression, extrusion, pelettisation, granulation, Use as laboratory reagent</b>	PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

#### 1.2. Conditions of use affecting exposure

##### 1.2.1. Control of environmental exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 50 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 730000 kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Release type	: Continuous release
Emission days	: 100
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal sewage treatment plant
STP sludge treatment	: No application of sewage sludge to soil Sewage sludge should be incinerated, contained or reclaimed.
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

### 1.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Technical and organisational conditions and measures</b>	
Store substance within a closed system.	
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### 1.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Technical and organisational conditions and measures</b>	
Store substance within a closed system.	
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Tableting, compression, extrusion, pelettisation, granulation (PROC14) / Use as laboratory reagent (PROC15)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

### 1.3. Exposure estimation and reference to its source

#### 1.3.1. Environmental release and exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Release route	Release rate	Release estimation method
Air	10 kg/day	
Waste	0,2 kg/day	
Soil	0,1 kg/day	

### 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### ES 2: Use in coatings; Industrial uses (SU3).

#### 2.1. Title section

<b>Exposure Scenario name</b>	: Use in coatings
<b>Structured Short Title</b>	: Use in coatings; Industrial uses (SU3).

Environment		
<b>CS 1</b>	<b>Use of non-reactive processing aid at industrial site (no inclusion into or onto article)</b>	ERC4
Worker		
<b>CS 2</b>	<b>Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</b>	PROC1
<b>CS 3</b>	<b>Industrial spraying</b>	PROC7
<b>CS 4</b>	<b>Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Mixing or blending in batch processes, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Transfer of substance or mixture into small containers (dedicated filling line, including weighing), Roller application or brushing, Treatment of articles by dipping and pouring, Tableting, compression, extrusion, pelettisation, granulation, Use as laboratory reagent</b>	PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15

#### 2.2. Conditions of use affecting exposure

##### 2.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Release type	: Continuous release
Emission days	: 300
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal Sewage Treatment Plant
STP sludge treatment	: Sewage sludge should be incinerated, contained or reclaimed.
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Waste treatment	: External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

### 2.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Technical and organisational conditions and measures</b>	
Store substance within a closed system.	
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### 2.2.3. Control of worker exposure: Industrial spraying (PROC7)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: 480 min
Use frequency	: 5 days per week
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear a respirator conforming to EN140.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

**2.2.4. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Roller application or brushing (PROC10) / Treatment of articles by dipping and pouring (PROC13) / Tableting, compression, extrusion, pelettisation, granulation (PROC14) / Use as laboratory reagent (PROC15)**

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: 480 min

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Use frequency	: 5 days per week
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

### 2.3. Exposure estimation and reference to its source

#### 2.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Release route	Release rate	Release estimation method
Air	980 kg/day	
Waste	0,7 kg/day	
Soil	0 kg/day	

### 2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### ES 3: Use in coatings; Professional uses (SU22).

#### 3.1. Title section

<b>Exposure Scenario name</b>	: Use in coatings
<b>Structured Short Title</b>	: Use in coatings; Professional uses (SU22).

Environment		
<b>CS 1</b>	<b>Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor), Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)</b>	ERC8a, ERC8d
Worker		
<b>CS 2</b>	<b>Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</b>	PROC1
<b>CS 3</b>	<b>Non-industrial spraying</b>	PROC11
<b>CS 4</b>	<b>Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Mixing or blending in batch processes, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Roller application or brushing, Treatment of articles by dipping and pouring, Use as laboratory reagent, Manual activities involving hand contact</b>	PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC13, PROC15, PROC19

#### 3.2. Conditions of use affecting exposure

**3.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)**

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### 3.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: 480 min
Use frequency	: 5 days per week
Technical and organisational conditions and measures	
Store substance within a closed system.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

### 3.2.3. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: 480 min
Use frequency	: 5 days per week
Technical and organisational conditions and measures	
Handle in a fume cupboard or under extract ventilation.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

**3.2.4. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Roller application or brushing (PROC10) / Treatment of articles by dipping and pouring (PROC13) / Use as laboratory reagent (PROC15) / Manual activities involving hand contact (PROC19)**

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: 480 min
Use frequency	: 5 days per week
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

### 3.3. Exposure estimation and reference to its source

**3.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)**

Release route	Release rate	Release estimation method
Air	980 kg/day	
Waste	10 kg/day	
Soil	10 kg/day	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

---

### 3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see  
<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### ES 4: Cleaning; Industrial uses (SU3).

#### 4.1. Title section

<b>Exposure Scenario name</b>	: Cleaning
<b>Structured Short Title</b>	: Cleaning; Industrial uses (SU3).

Environment		
<b>CS 1</b>	<b>Use of non-reactive processing aid at industrial site (no inclusion into or onto article)</b>	ERC4
Worker		
<b>CS 2</b>	<b>Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</b>	PROC1
<b>CS 3</b>	<b>Industrial spraying</b>	PROC7
<b>CS 4</b>	<b>Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Roller application or brushing, Treatment of articles by dipping and pouring</b>	PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC13

#### 4.2. Conditions of use affecting exposure

##### 4.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 100000 kg
Release type	: Continuous release
Emission days	: 20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal Sewage Treatment Plant
STP sludge treatment	: No application of sewage sludge to soil Sewage sludge should be incinerated, contained or reclaimed.
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 1.000

### 4.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Technical and organisational conditions and measures</b>	
Store substance within a closed system.	
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### 4.2.3. Control of worker exposure: Industrial spraying (PROC7)

<b>Product (article) characteristics</b>	
Covers concentrations up to 5 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Technical and organisational conditions and measures</b>	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

**4.2.4. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Roller application or brushing (PROC10) / Treatment of articles by dipping and pouring (PROC13)**

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week

## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

### 4.3. Exposure estimation and reference to its source

#### 4.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Release route	Release rate	Release estimation method
Air	1.000 kg/day	
Waste	0,003 kg/day	
Soil	0 kg/day	

### 4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see  
<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### ES 5: Cleaning; Professional uses (SU2).

#### 5.1. Title section

<b>Exposure Scenario name</b>	: Cleaning
<b>Structured Short Title</b>	: Cleaning; Professional uses (SU2).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	ERC8a
CS 2	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)	ERC8d
Worker		
CS 3	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 4	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 5	Roller application or brushing	PROC10
CS 6	Non-industrial spraying	PROC11
CS 7	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Treatment of articles by dipping and pouring	PROC2, PROC3, PROC4, PROC8b, PROC13

#### 5.2. Conditions of use affecting exposure

##### 5.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Annual amount per site	: 1000000 kg
Release type	: Continuous release
Emission days	: 365
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal Sewage Treatment Plant
STP sludge treatment	: No application of sewage sludge to soil Sewage sludge should be incinerated, contained or reclaimed.
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

### 5.2.2. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Annual amount per site	: 1000000 kg
Release type	: Continuous release
Emission days	: 365
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal Sewage Treatment Plant
STP sludge treatment	: No application of sewage sludge to soil Sewage sludge should be incinerated, contained or reclaimed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

### 5.2.3. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: 480 min
Use frequency	: 5 days per week
Technical and organisational conditions and measures	
Store substance within a closed system.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

### 5.2.4. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 240 min
Use frequency	: 5 days per week
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

### 5.2.5. Control of worker exposure: Roller application or brushing (PROC10)

<b>Product (article) characteristics</b>	
Covers concentrations up to 25 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

### 5.2.6. Control of worker exposure: Non-industrial spraying (PROC11)

<b>Product (article) characteristics</b>	
Covers concentrations up to 1 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

**5.2.7. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Treatment of articles by dipping and pouring (PROC13)**

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 5 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### 5.3. Exposure estimation and reference to its source

#### 5.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Air	20 kg/day	
Waste	0,001 kg/day	
Soil	0 kg/day	

#### 5.3.2. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Release route	Release rate	Release estimation method
Air	20 kg/day	
Waste	0,001 kg/day	
Soil	0 kg/day	

### 5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

### ES 6: Use in laboratories; Industrial uses (SU3).

#### 6.1. Title section

<b>Exposure Scenario name</b>	:	Use in laboratories
<b>Structured Short Title</b>	:	Use in laboratories; Industrial uses (SU3).
<b>Environment</b>		
<b>CS 1</b>	<b>Formulation into mixture, Use of non-reactive processing aid at industrial site (no inclusion into or onto article)</b>	ERC2, ERC4
<b>Worker</b>		
<b>CS 2</b>	<b>Roller application or brushing, Use as laboratory reagent</b>	PROC10, PROC15

#### 6.2. Conditions of use affecting exposure

##### 6.2.1. Control of environmental exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 50 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Annual amount per site	: 730000 kg
Release type	: Continuous release
Emission days	: 100
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal sewage treatment plant
STP sludge treatment	: No application of sewage sludge to soil Sewage sludge should be incinerated, contained or reclaimed.
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

External recovery and recycling of waste should comply with applicable local and/or national regulations.	
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

### 6.2.2. Control of worker exposure: Roller application or brushing (PROC10) / Use as laboratory reagent (PROC15)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: 480 min
Use frequency	: 5 days per week
<b>Other conditions affecting workers exposure</b>	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Assumes a good basic standard of occupational hygiene is implemented	

### 6.3. Exposure estimation and reference to its source

#### 6.3.1. Environmental release and exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Release route	Release rate	Release estimation method
Air	10 kg/day	
Waste	0,2 kg/day	
Soil	0,1 kg/day	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

---

### 6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see  
<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### ES 7: Use in laboratories; Professional uses (SU22).

#### 7.1. Title section

<b>Exposure Scenario name</b>	:	Use in laboratories
<b>Structured Short Title</b>	:	Use in laboratories; Professional uses (SU22).
<b>Environment</b>		
<b>CS 1</b>	<b>Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)</b>	ERC8a
<b>Worker</b>		
<b>CS 2</b>	<b>Roller application or brushing, Use as laboratory reagent</b>	PROC10, PROC15

#### 7.2. Conditions of use affecting exposure

##### 7.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Annual amount per site	: 1 kg
Release type	: Continuous release
Emission days	: 365
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal Sewage Treatment Plant
STP sludge treatment	: No application of sewage sludge to soil Sewage sludge should be incinerated, contained or reclaimed.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Local marine water dilution factor	:	100
------------------------------------	---	-----

### 7.2.2. Control of worker exposure: Roller application or brushing (PROC10) / Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: 480 min
Use frequency	: 5 days per week
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

### 7.3. Exposure estimation and reference to its source

#### 7.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Air	0,01 kg/day	
Waste	0,01 kg/day	
Soil	0 kg/day	

### 7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

**BYK-354**

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

---

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### ES 8: Cleaning; Consumer uses (SU21).

#### 8.1. Title section

<b>Exposure Scenario name</b>	: Cleaning
<b>Structured Short Title</b>	: Cleaning; Consumer uses (SU21).

Environment		
<b>CS 1</b>	<b>Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)</b>	ERC8a
<b>CS 2</b>	<b>Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)</b>	ERC8d
Consumer		
<b>CS 3</b>	Air care products	PC3
<b>CS 4</b>	Coatings and paints, thinners, paint removers	PC9a
<b>CS 5</b>	Coatings and paints, thinners, paint removers	PC9a
<b>CS 6</b>	Washing and cleaning products (including solvent based products)	PC35
<b>CS 7</b>	Coatings and paints, thinners, paint removers	PC9a
<b>CS 8</b>	Washing and cleaning products	PC35
<b>CS 9</b>	Washing and cleaning products (including solvent based products)	PC35
<b>CS 10</b>	Washing and cleaning products (including solvent based products)	PC35

#### 8.2. Conditions of use affecting exposure

##### 8.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 2,6 kg
Release type	: Continuous release

**BYK-354**

Version 12.1  
 SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
 Print Date 21.05.2025

Emission days	: 365
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

**8.2.2. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)**

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Annual amount per site	: 2,6 kg
Release type	: Continuous release
Emission days	: 365
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

**8.2.3. Control of consumer exposure: Air care products (PC3)**

Air care, continuous action (solid and liquid) (PC3\_2)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Product (article) characteristics	
Covers concentrations up to 10 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,48 g/event
Duration	: 480 min
Use frequency	: 365 days per year
Other conditions affecting consumers exposure	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 8.2.4. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Waterborne latex wall paint (PC9a\_1, PC15\_1)

Product (article) characteristics	
Covers concentrations up to 1 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 2,760 kg
Duration	: 132 min
Use frequency	: 4 days per year
Other conditions affecting consumers exposure	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 8.2.5. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Solvent rich, high solid, water borne paint (PC9a\_2, PC15\_2)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Product (article) characteristics	
Covers concentrations up to 27,5 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,744 kg
Duration	: 132 min
Use frequency	: 6 days per year
Other conditions affecting consumers exposure	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 8.2.6. Control of consumer exposure: Washing and cleaning products (including solvent based products) (PC35)

Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) (PC8\_2, PC35\_2)

Product (article) characteristics	
Covers concentrations up to 50 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,215 kg
Duration	: 19,8 min
Use frequency	: 2 days per year
Other conditions affecting consumers exposure	
Room size	: 24 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 8.2.7. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Removers (paint-, glue-, wall paper-, sealant-remover) (PC9a\_4, PC15\_4)

Product (article) characteristics	
Covers concentrations up to 50 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,491 kg
Duration	: 120 min
Use frequency	: 3 days per year
Other conditions affecting consumers exposure	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 8.2.8. Control of consumer exposure: Washing and cleaning products (PC35)

Laundry and dish washing products (PC35\_1, PC8\_1)

Product (article) characteristics	
Covers concentrations up to 5 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 15 g/event
Duration	: 30 min
Use frequency	: 365 days per year
Other conditions affecting consumers exposure	
Room size	: 20 m <sup>3</sup>

### 8.2.9. Control of consumer exposure: Washing and cleaning products (including solvent based products) (PC35)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) (PC8\_2, PC35\_2)

<b>Product (article) characteristics</b>	
Covers concentrations up to 5 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Amount used per event	: 27 g/event
Duration	: 19,8 min
Use frequency	: 128 days per year
<b>Other conditions affecting consumers exposure</b>	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 8.2.10. Control of consumer exposure: Washing and cleaning products (including solvent based products) (PC35)

Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (PC8\_3, PC35\_3)

<b>Product (article) characteristics</b>	
Covers concentrations up to 15 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Amount used per event	: 35 g/event
Duration	: 10,2 min
Use frequency	: 128 days per year
<b>Other conditions affecting consumers exposure</b>	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### 8.3. Exposure estimation and reference to its source

#### 8.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Air	950 kg/day	
Waste	25 kg/day	
Soil	25 kg/day	

#### 8.3.2. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Release route	Release rate	Release estimation method
Air	950 kg/day	
Waste	25 kg/day	
Soil	25 kg/day	

### 8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

### ES 9: Use in coatings; Consumer uses (SU21).

#### 9.1. Title section

<b>Exposure Scenario name</b>	: Use in coatings
<b>Structured Short Title</b>	: Use in coatings; Consumer uses (SU21).

Environment		
<b>CS 1</b>	<b>Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)</b>	ERC8a
<b>CS 2</b>	<b>Wide dispersive indoor use of reactive substances in open systems</b>	ERC8b
Consumer		
<b>CS 3</b>	Adhesives, sealants	PC1
<b>CS 4</b>	Coatings and paints, thinners, paint removers	PC9a

#### 9.2. Conditions of use affecting exposure

##### 9.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 130 kg
Daily amount per site	: 370 kg
Regional use tonnage	: 270000 kg
Release type	: Continuous release
Emission days	: 365
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

applicable local and/or national regulations.	
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

### 9.2.2. Control of environmental exposure: Wide dispersive indoor use of reactive substances in open systems (ERC8b)

<b>Product (article) characteristics</b>	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Annual amount per site	: 130 kg
Daily amount per site	: 370 kg
Regional use tonnage	: 270000 kg
Release type	: Continuous release
Emission days	: 365
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
<b>Other conditions affecting environmental exposure</b>	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

### 9.2.3. Control of consumer exposure: Adhesives, sealants (PC1)

Glues, hobby use (PC1\_1)

<b>Product (article) characteristics</b>	
Covers concentrations up to 30 %	
Physical form of product	: Liquid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1

SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023

Print Date 21.05.2025

Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Amount used per event	: 9 g/event
Duration	: 240 min
Use frequency	: 365 days per year
<b>Other conditions affecting consumers exposure</b>	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 9.2.4. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

<b>Product (article) characteristics</b>	
Covers concentrations up to 50 %	
Physical form of product	: Liquid
Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Amount used per event	: 0,491 kg
Duration	: 120 min
Use frequency	: 3 days per year
<b>Other conditions affecting consumers exposure</b>	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 9.2.5. Control of consumer exposure:

Plasters and floor equalizers (PC9b\_2)

Fillers and putty (PC9b\_1)

<b>Product (article) characteristics</b>	
Covers concentrations up to 2 %	
Physical form of product	: Liquid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-354

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

Vapour pressure	: 10 hPa
Temperature	: 20 °C
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Amount used per event	: 13,8 kg
Duration	: 120 min
Use frequency	: 12 days per year
<b>Other conditions affecting consumers exposure</b>	
Room size	: 20 m <sup>3</sup>
Ventilation rate	: Covers use under typical household ventilation.

### 9.3. Exposure estimation and reference to its source

#### 9.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Air	985 kg/day	
Waste	10 kg/day	
Soil	5 kg/day	

#### 9.3.2. Environmental release and exposure: Wide dispersive indoor use of reactive substances in open systems (ERC8b)

Release route	Release rate	Release estimation method
Air	985 kg/day	
Waste	10 kg/day	
Soil	5 kg/day	

### 9.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

<http://www.ecetoc.org/tra>

For scaling see

Further details on scaling and control technologies are provided in SPERC factsheet.

**BYK-354**

Version 12.1  
SDB\_MT

Revision Date: 26.03.2024

Date of last issue: 31.07.2023  
Print Date 21.05.2025

---