

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

SECTION 1. IDENTIFICATION

Product name : BYK-3900 P

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Leveling Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Combustible dust :

GHS label elements

Signal word : Warning

Hazard statements : May form combustible dust concentrations in air.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Polyacrylate, adsorbed on silicon dioxide

Hazardous components

| Component | CAS-No. | Concentration (%) |
|-------------------|-------------|-------------------|
| Silica, amorphous | 112926-00-8 | >= 30 - < 60 |

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

| | |
|---|---|
| In case of skin contact | : advice. If symptoms persist, call a physician. Remove contaminated clothing. Wash thoroughly with soap and water. |
| In case of eye contact | : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : No information available. |

SECTION 5. FIREFIGHTING MEASURES

| | |
|---|---|
| Suitable extinguishing media | : Foam Carbon dioxide (CO ₂) Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Cool closed containers exposed to fire with water spray. Will not explode on mechanical impact. |
| Hazardous combustion products | : Carbon oxides silicone compounds |
| Further information | : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Avoid dust formation. |
| Environmental precautions | : Prevent further leakage or spillage if safe to do so. |
| Methods and materials for containment and cleaning up | : Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

- Advice on safe handling : Avoid contact with skin and eyes.
Keep container closed when not in use.
Handle as an industrial chemical.
Avoid creating dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------|-------------|----------------------------------|---|-----------|
| Silica, amorphous | 112926-00-8 | TWA | 6 mg/m ³ | OSHA P0 |
| Silica, amorphous | | TWA (Dust) | 20 Million particles per cubic foot (Silica) | OSHA Z-3 |
| Silica, amorphous | | TWA (Dust) | 80 mg/m ³ / %SiO ₂ (Silica) | OSHA Z-3 |
| Silica, amorphous | | TWA | 6 mg/m ³ (Silica) | NIOSH REL |

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.

Hand protection

Material : Neoprene gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses with side-shields
Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection

: Dust impervious protective suit
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Clean long legged, long sleeved work clothes.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : solid
Colour : white
Odour : acrylic-like
Odour Threshold : No data available

pH : 7, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator

Melting point/ range : No data available
Boiling point/boiling range : Not applicable
Vapour pressure : No data available

Flash point : > 212.00 °F (> 100.00 °C)
Method: 49 (Pensky-Martens)

Upper explosion limit : No data available
Lower explosion limit : No data available
Evaporation rate : No data available

Flammability (solid, gas) : May form combustible dust concentrations in air.

Relative vapour density : No data available

Relative Density/Specific Gravity : No data available
Density : ca. 1.2800 g/cm³ (68.00 °F (20.00 °C))
Method: 4 (20°C oscillating U-tube)

Bulk density : 640 kg/m³

Solubility(ies)
Water solubility : (68 °F (20 °C), 1,013 hPa)
immiscible

Solubility in other solvents : No data available

Partition coefficient: n- : No data available

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

octanol/water
Ignition temperature : Not applicable

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Conditions to avoid : Excessive dusting may cause potentially explosive air/dust mix.
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : None expected

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

Skin corrosion/irritation**Product:**

Remarks: No data available

Serious eye damage/eye irritation**Product:**

Remarks: No data available

Respiratory or skin sensitisation**Product:**

Remarks: No data available

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: No known chronic health effects.

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

Aspiration toxicity**Product:**

No data available

Experience with human exposure**Product:**

Inhalation:

Symptoms:

Dust particles may cause irritation of the respiratory tract.

Skin contact:

Symptoms:

Contact may cause irritation.

Eye contact:

Symptoms:

Contact may cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract.

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 100.00 %
Non-volatile information is not a specification.

Massachusetts Right To Know

Silica, amorphous 112926-00-8


Pennsylvania Right To Know

Polyacrylate -
Silica, amorphous 112926-00-8

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5132

California Prop. 65

 **WARNING:** This product can expose you to chemicals including 2-Ethylhexyl Acrylate, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

BYK-3900 P

Version 5

Revision Date 05/17/2026

Print Date 06/18/2026

The components of this product are reported in the following inventories:

| | |
|-------------------|--|
| TSCA | : All substances listed as active on the TSCA inventory |
| Section 5a | : No substances are subject to a Significant New Use Rule. |
| Section 4 / 12(b) | : No substances are subject to TSCA 12(b) export notification requirements. |
| DSL | : We certify that all of the components of this product are listed on the DSL. |

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.