

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

Section 1: Identification

Product name : BYK-A 500
Product code : 000000000000105208

Manufacturer or supplier's details

Company : BYK-Chemie GmbH

Address : Abelstrasse 45
46483 Wesel

Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

Emergency telephone number : 0800 446 881 (toll-free number, access from New Zealand only)
+64 9 929 1483

Importer

Company : Alchemy Agencies Ltd
Level 2, 20 Centre St
Freemans Bay
Auckland 1010 NZ
Tel: +64(0)93770613

Use of the Substance/Mixture : Air Release Additive

Section 2: Hazard identification

GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Aspiration hazard : Category 1

Hazardous to the aquatic environment - chronic hazard : Category 2

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture
Chemical nature : solution of polyolefin

Components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.; Low	64742-95-6	>= 50 -<= 100

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

boiling point naphtha -unspecified		
2-methoxy-1-methylethyl acetate	108-65-6	>= 5 -< 7
2,6-di-tert-butyl-p-cresol	128-37-0	>= 0.25 -< 0.5

Section 4: First-aid measures

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	No information available. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness.
Notes to physician	:	No information available.

Section 5: Fire-fighting measures

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides
Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment	:	Wear self-contained breathing apparatus for firefighting if

BYK-A 500

Version 1.1

Date of last issue: 22.01.2025

SDS_NZ

Revision Date: 14.04.2026

Print Date 15.04.2026

 for firefighters necessary.

 Hazchem Code : 3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Ensure adequate ventilation.
 Remove all sources of ignition.
 Evacuate personnel to safe areas.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Section 7: Handling and storage

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
 Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.
 Do not breathe vapours/dust.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Further information on : No decomposition if stored and applied as directed.

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

storage stability

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,6-di-tert-butyl-p-cresol	128-37-0	WES-TWA	10 mg/m ³	NZ OEL
Further information: Skin sensitiser				
2,6-di-tert-butyl-p-cresol		TWA (Inhalable fraction and vapor)	2 mg/m ³	ACGIH

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Nitrile rubber

Break through time : > 480 min

Glove length : 0.4 mm

Remarks : Wear suitable gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Section 9: Physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : not significant

Odour Threshold : No data available

pH : 5 (20 °C)
Concentration: 1 %
Method: Universal pH-value indicator

Melting point/ range : < 0 °C
Method: derived

Initial boiling point and boiling range : 146.00 °C
Method: derived

Flash point : 45.00 °C
Method: 48 (Abel-Pensky) DIN 51755

SAFETY DATA SHEET



BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	12.00 %(V)
Lower explosion limit / Lower flammability limit	:	1.00 %(V)
Vapour pressure	:	5.0000000 hPa (20.00 °C) Method: derived
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8800 g/cm ³ (20.00 °C, 1,013 hPa) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	5 mm ² /s (40.00 °C)
Surface tension	:	27.30 mN/m, ring dynamometer

Section 10: Stability and reactivity

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026**Section 11: Toxicological information****Acute toxicity**

Not classified due to lack of data.

Product:Acute oral toxicity : LD50 (Rat): 4,200.000000 mg/kg
Method: OECD Test Guideline 401**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,160 mg/kg
Method: OECD Test Guideline 402**2-methoxy-1-methylethyl acetate:**Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

2,6-di-tert-butyl-p-cresol:Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg
Method: OECD Test Guideline 401
GLP: yesAcute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

Product:Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

GLP : yes

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Respiratory or skin sensitisation**Skin sensitisation**

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

2-methoxy-1-methylethyl acetate:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

Chronic toxicity**Germ cell mutagenicity**

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Result: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity - : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available
Effects on foetal : Remarks: No data available
development

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Product:

Remarks : No data available

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026**STOT - repeated exposure**

Not classified due to lack of data.

Product:

Remarks : No data available

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information**Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.**Section 12: Ecological information****Ecotoxicity****Product:**

Toxicity to fish : Remarks: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish	:	LL50 (Fish): 9.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3.2 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata): 2.6 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 GLP: yes

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026**2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: no

2,6-di-tert-butyl-p-cresol:

Toxicity to fish : LC50 : 199 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 0.42 mg/l
Exposure time: 72 h
Test Type: static test
Method: Regulation (EC) No. 440/2008, Annex, C.3
GLP: yes

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

1

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026**Components:****2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-
octanol/water : log Pow: 1.2 (20 °C)
pH: 6.8
Method: OECD Test Guideline 117
GLP: yes

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological
information : An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Section 13: Disposal considerations**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Section 14: Transport information**International Regulations****UNRTDG**

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Solvent naphtha, 1-Methoxy-2-propanol acetate)
Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Solvent naphtha, 1-Methoxy-2-propanol acetate)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo
aircraft) : 366
Packing instruction : 355

BYK-A 500

Version 1.1
SDS_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2025
Print Date 15.04.2026

(passenger aircraft)

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Solvent naphtha, 1-Methoxy-2-propanol acetate)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**NZS 5433**

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Solvent naphtha, 1-Methoxy-2-propanol acetate)
Class : 3
Packing group : III
Labels : 3
Hazchem Code : 3Y
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002495 Additives Process Chemicals and Raw Materials Flammable Group Standard

Tolerable Exposure Limits (TEL)

Not applicable

Environmental Exposure Limits (EEL)

Not applicable

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

Section 16: Other information

Revision Date : 14.04.2026

BYK-A 500

Version 1.1

Date of last issue: 22.01.2025

SDS_NZ

Revision Date: 14.04.2026

Print Date 15.04.2026

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN