

BYK-GO 8710

Multifunctional, liquid paraffin solution for crude oil and condensate applications to lower the overall pour point of the system by keeping paraffin crystals dispersed. Additionally effective at minimizing paraffin deposition.

Product Data

Composition

Solution of a modified hyperbranched polymer

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Pour point:	-3 °C
Active substance:	52 %
Density (20 °C):	0.92 g/ml
Solvents:	Aromatic hydrocarbons
Flash point:	47 °C

Applications

Pour point depressant

- Paraffin inhibitor
- Paraffin dispersant

Special Features and Benefits

BYK-GO 8710 performs as a pour point depressant, paraffin inhibitor, and dispersant in crude oils. Additionally, BYK-GO 8710 is effective in cold weather climates where winterization is required, as the product is compatible with many of the commonly used solvent packages.

Recommended Levels

Dosage will typically range from 100-2000 ppm evaluated in laboratory or field tests.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.