

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

SECTION 1: Identification of the hazardous chemical and of the supplier**Product identifier**

Product name : BYK-MAX HS 4317

Recommended use : Additive for plastics

Manufacturer or supplier's details

Company : BYK USA LLC

Address : South Cherry Street 524
06492 Wallingford

Telephone : +1 203-265-2086

Telefax :

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone number : +60 3 6207 4347 (Malay and English)
+65 3158 1074 (All languages)**SECTION 2: Hazards identification****Classification of the hazardous chemical**

Acute toxicity (Oral) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye
irritation : Category 1

Skin sensitisation : Category 1

Specific target organ toxicity -
repeated exposure : Category 1 (Central nervous system)Specific target organ toxicity -
repeated exposure (Oral) : Category 1 (Thyroid)Hazardous to the aquatic
environment - acute hazard : Category 1Hazardous to the aquatic
environment - chronic hazard : Category 3**Label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H372 Causes damage to organs (Thyroid) through prolonged or repeated exposure if swallowed.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P391 Collect spillage.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture
Chemical nature : Additive concentrate

Components

Chemical name	CAS-No.	Concentration (% w/w)
triphenylphosphine	603-35-0	>= 25 -< 30
potassium bromide	7758-02-3	>= 20 -< 25
N,N'-ethylenedi(stearamide)	110-30-5	>= 12.5 -< 20
hydroxyaluminium distearate	-	>= 12.5 -< 20
copper iodide	7681-65-4	>= 10 -< 12.5
calcium distearate	-	>= 1 -< 3

SECTION 4: First aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

In case of eye contact	:	If on clothes, remove clothes. Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	No information available.
Notes to physician	:	No information available.

SECTION 5: Firefighting measures**Extinguishing media**

Suitable extinguishing media	:	Foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	High volume water jet

Physicochemical hazards arising from the chemical

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses. Do not allow run-off from fire fighting to enter drains or water courses.
--------------------------------------	---	--

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Avoid dust formation. Avoid breathing dust.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling****Precautions for safe handling**

Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Storage**Conditions for safe storage, including any incompatibilities**

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection**Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N,N'-ethylenedi(stearamide)	110-30-5	TWA	10 mg/m ³	MY PEL
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

hydroxyaluminium distearate	-	TWA	10 mg/m3	MY PEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH
		TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
copper iodide	7681-65-4	TWA (Inhalable particulate matter)	0.01 mg/m3 (Iodine)	ACGIH
calcium distearate	-	TWA	10 mg/m3	MY PEL

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Dust impervious protective suit
- Hand protection
- Material : Nitrile rubber
Break through time : > 480 min
- Remarks : Wear suitable gloves.
Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

- Appearance : pellet
- Colour : off-white - light grey
- Odour : characteristic
- pH : insoluble
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : ca. 276 °C
- Method: derived

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

Flammability (solid, gas) : May form combustible dust concentrations in air.

Combustible Solids

Upper explosion limit / Upper flammability limit : Upper explosion limit not determined

Lower explosion limit / Lower flammability limit : Lower explosion limit not determined

Density : 3 g/cm³ (20 °C, 1,013 hPa)Bulk density : 0.67 g/cm³ (20 °C)
Method: 34 (bulk density)Solubility(ies)
Water solubility : insoluble

Auto-ignition temperature : Not combustible.

Viscosity
Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

SECTION 10: Stability and reactivityReactivity : No decomposition if stored and applied as directed.
No decomposition if stored and applied as directed.Chemical stability : No decomposition if stored and applied as directed.
No decomposition if stored and applied as directed.Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Dust may form explosive mixture in air.

Conditions to avoid : No data available

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity**Product:**Acute oral toxicity : Acute toxicity estimate: 1,334 mg/kg
Method: Calculation method**Components:****N,N'-ethylenedi(stearamide):**Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

GLP: yes

Acute inhalation toxicity : LC50 (Rat, male and female): > 6.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation**Product:**

Remarks : May irritate skin.
May cause skin irritation and/or dermatitis.

Remarks : No data available

Serious eye damage/eye irritation**Product:**

Remarks : May cause irreversible eye damage.

Remarks : No data available

Respiratory or skin sensitisation**Product:**

Remarks : Causes sensitisation.

Components:**N,N'-ethylenedi(stearamide):**

Test Type : Mouse Local Lymph Node assay (LLNA)
Species : Mouse
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.
GLP : yes

Repeated dose toxicity**Product:**

Remarks : No data available

Further information**Product:**

Remarks : No data available

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

SECTION 12: Ecological information**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates Remarks: No data available

Components:**N,N'-ethylenedi(stearamide):**

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates nominal
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): > 100 mg/l nominal
aquatic invertebrates Exposure time: 21 d
(Chronic toxicity) Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

copper iodide:

M-Factor (Acute aquatic : 10
toxicity)
M-Factor (Chronic aquatic : 1
toxicity)

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Components:**N,N'-ethylenedi(stearamide):**

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301B
GLP: yes

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal information**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information**International Regulations****IATA-DGR**

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(copper iodide)
Class : 9
Packing group : III
Labels : Miscellaneous Dangerous Goods
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(copper iodide)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information**Safety, health, and environmental regulations specific for the hazardous chemical**

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

ACGIH / TWA : 8-hour, time-weighted average

MY PEL / TWA : Eight-hour time-weighted average airborne concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand

BYK-MAX HS 4317

Product code: 000000000000129145

Version 3.2 SDS_APJ_MY

Revision Date 12.05.2026

Print Date 26.05.2026

Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN