

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

SECTION 1. IDENTIFICATION

Product name : BYK-MAX LS 4125

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Compound for UV stabilization

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Serious eye damage : Category 1

Skin sensitization : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.Precautionary Statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

attention.
 P363 Wash contaminated clothing before reuse.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Additive formulation

Hazardous ingredients

Component	CAS-No.	Concentration (%)
Hindered amine derivative	86403-32-9	>= 10 - < 30

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Consult a physician.
 Show this material safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 Continue rinsing eyes during transport to hospital.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.

If swallowed : If eye irritation persists, consult a specialist.
 : Keep respiratory tract clear.
 Do NOT induce vomiting.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

SECTION 5. FIRE-FIGHTING MEASURES

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

Suitable extinguishing media	: Foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Avoid dust formation. Avoid breathing dust.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of respirable particles. Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Conditions for safe storage	: Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Hazardous components without workplace control parameters

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Dust impervious protective suit
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: granular
Color	: off-white
Odor	: fatty odor
Odor Threshold	: No data available
pH	: 7, Concentration: 1 % (68 °F (20 °C))
Melting point/ range	: 302 - 338 °F (150 - 170 °C) Method: derived
Initial boiling point and boiling range	: No data available
Vapor pressure	: No data available
Flash point	: No data available
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Combustible Solids
Relative vapor density	: Not applicable
Density	: 0.95 g/cm ³ (68 °F (20 °C))

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

Method: calculated

Bulk density : 400 - 550 kg/m³
Method: 34 (bulk density)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n- : No data available

octanol/water

Ignition temperature : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : No data available

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation

Ingestion

Eye contact

Skin contact

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Respiratory or skin sensitization**Product:**

Remarks: Causes sensitization.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

STOT-single exposure
Product:

Remarks: No data available

STOT-repeated exposure
Product:

Remarks: No data available

Aspiration toxicity
Product:

No data available

Further information
Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA-DGR

UN/ID No.	: UN 3077
Proper shipping name	: Environmentally hazardous substance, solid, n.o.s. (hindered amine derivative)
Class	: 9
Packing group	: III
Labels	: Miscellaneous Dangerous Goods
Packing instruction (cargo aircraft)	: 956
Packing instruction (passenger aircraft)	: 956

IMDG-Code

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (hindered amine derivative)
	:)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes
Remarks	: IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation
49 CFR

Not regulated as a dangerous good
49 CFR (DOT): Not a hazardous material in non-bulk packaging

SECTION 15. REGULATORY INFORMATION

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

EPCRA - Emergency Planning and Community Right-to-Know
US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : No data available

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know

Polypropylene	-
Hindered amine derivative	86403-32-9
Hexadecyl 3,5-bis-tert-butyl-4-hydroxybenzoate	-

New Jersey Right To Know

BYK-MAX LS 4125

Version 2

Revision Date 09/30/2025

Print Date 04/30/2026

**New Jersey Trade Secret
Registry Number for the
product (NJ TSRN)** : 800963-6077

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 09/30/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.