

**BYK-P 104**Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026**Section 1: Identification**

Product name : BYK-P 104  
Product code : 000000000000101126

**Manufacturer or supplier's details**

Company : BYK-Chemie GmbH  
Address : Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com  
Emergency telephone number : 0800 446 881 (toll-free number, access from New Zealand only)  
+64 9 929 1483

**Importer**

Company : Alchemy Agencies Ltd  
Level 2, 20 Centre St  
Freemans Bay  
Auckland 1010 NZ  
Tel: +64(0)93770613  
Use of the Substance/Mixture : Wetting & Dispersing Additive

**Section 2: Hazard identification****GHS Classification**

Flammable liquids : Category 3  
Acute toxicity (Oral) : Category 4  
Respiratory sensitisation : Category 1  
Skin sensitisation : Category 1  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 2  
Specific target organ toxicity - repeated exposure : Category 2  
Hazardous to the aquatic environment - chronic hazard : Category 3

**GHS label elements**

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	<p>H226 Flammable liquid and vapour.  H302 Harmful if swallowed.  H317 May cause an allergic skin reaction.  H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  H351 Suspected of causing cancer.  H361 Suspected of damaging fertility or the unborn child.  H373 May cause damage to organs through prolonged or repeated exposure.  H412 Harmful to aquatic life with long lasting effects.</p>
Precautionary statements	:	<p><b>Prevention:</b>  P201 Obtain special instructions before use.  P202 Do not handle until all safety precautions have been read and understood.  P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  P233 Keep container tightly closed.  P240 Ground and bond container and receiving equipment.  P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  P242 Use non-sparking tools.  P243 Take action to prevent static discharges.  P260 Do not breathe mist or vapours.  P264 Wash skin thoroughly after handling.  P270 Do not eat, drink or smoke when using this product.  P272 Contaminated work clothing should not be allowed out of the workplace.  P273 Avoid release to the environment.  P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  P284 Wear respiratory protection.</p> <p><b>Response:</b>  P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  P308 + P313 IF exposed or concerned: Get medical advice/ attention.  P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  P362 + P364 Take off contaminated clothing and wash it before reuse.  P370 + P378 In case of fire: Use dry sand, dry chemical or</p>

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**Section 3: Composition/information on ingredients**

Substance / Mixture : Mixture  
Chemical nature : Solution of a lower molecular weight unsaturated polycarboxylic acid polymer

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Fatty acids, C14-18 and C16-18-unsatd., maleated	85711-46-2	>= 50 -<= 100
Xylene, mixture of isomers	1330-20-7	>= 30 -< 50
ethylbenzene	100-41-4	>= 12.5 -< 20
2,6-dimethylheptan-4-one	108-83-8	>= 3 -< 5
maleic anhydride	108-31-6	>= 0.5 -< 1

**Section 4: First-aid measures**

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : Call a physician or poison control centre immediately.  
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No information available.  
Harmful if swallowed.  
May cause an allergic skin reaction.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

---

Notes to physician : May cause damage to organs through prolonged or repeated exposure.  
: No information available.

---

**Section 5: Fire-fighting measures**

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Hazchem Code : 3Y

---

**Section 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Neutralize with chalk, alkali solution or ammonia.  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

**Section 7: Handling and storage**

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

Advice on protection against fire and explosion	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
Conditions for safe storage	:	No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Further information on storage stability	:	No decomposition if stored and applied as directed.

---

**Section 8: Exposure controls/personal protection**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	WES-TWA	50 ppm 217 mg/m <sup>3</sup>	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
Xylene, mixture of isomers		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	WES-TWA	20 ppm 88 mg/m <sup>3</sup>	NZ OEL
	Further information: Ototoxin, Skin absorption			
		WES-STEL	40 ppm 176 mg/m <sup>3</sup>	NZ OEL
	Further information: Ototoxin, Skin absorption			
ethylbenzene		TWA	20 ppm	ACGIH
2,6-dimethylheptan-4-one	108-83-8	WES-TWA	25 ppm	NZ OEL

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

			145 mg/m3	
2,6-dimethylheptan-4-one		TWA	25 ppm	ACGIH
maleic anhydride	108-31-6	WES-TWA (Inhalable Fraction and Vapour)	0.0025 ppm 0.01 mg/m3	NZ OEL
Further information: Sensitiser				
maleic anhydride		TWA (Inhalable fraction and vapor)	0.01 mg/m3	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenylglyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection : Fluorinated rubber  
Material : Fluorinated rubber  
Break through time : > 480 min  
Glove length : >= 0.4 mm
- Remarks : Wear suitable gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Section 9: Physical and chemical properties**

# SAFETY DATA SHEET



## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

---

Appearance	:	liquid
Colour	:	yellow
Odour	:	aromatic
Odour Threshold	:	No data available
pH	:	3 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Melting point/ range	:	< 5 °C Method: derived
Initial boiling point	:	137.00 °C Method: derived
Flash point	:	28.00 °C  Method: 48 (Abel-Pensky) DIN 51755
Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	7.60 %(V)
Lower explosion limit / Lower flammability limit	:	0.80 %(V)
Vapour pressure	:	9 hPa (20 °C) Method: derived
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9500 g/cm <sup>3</sup> (20.00 °C) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 40 mm <sup>2</sup> /s ( 40.00 °C)

---

**Section 10: Stability and reactivity**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong acids Strong oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.

---

**Section 11: Toxicological information**
**Acute toxicity**

Harmful if swallowed.

**Product:**

Acute oral toxicity	: Remarks: No data available  Acute toxicity estimate: 1,425 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Acute oral toxicity	: LD50 (Rat, female): > 2,000 mg/kg Method: OECD Test Guideline 423 GLP: yes
---------------------	--

**Xylene, mixture of isomers:**

Acute oral toxicity	: LD50 (Rat): 4,300 mg/kg Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral) GLP: no
Acute dermal toxicity	: LD50 (Rabbit): > 4,200 mg/kg GLP: No information available.

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026**2,6-dimethylheptan-4-one:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 14 mg/l  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: no

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

**maleic anhydride:**

Acute oral toxicity : LD50 (Rat, male and female): 1,090 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, female): 2,620 mg/kg  
GLP: No information available.

**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

**Product:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation

Remarks : May cause skin irritation and/or dermatitis.

**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Species : EPISKIN human epidermis skin constructs  
Assessment : Irritating to skin.  
Method : OECD Test Guideline 439  
Result : Irritating to skin.  
GLP : yes

**2,6-dimethylheptan-4-one:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

**maleic anhydride:**

Species : Rabbit  
Method : No information available.  
Result : Corrosive to skin  
GLP : no

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026**Serious eye damage/eye irritation**

Based on available data, the classification criteria are not met.

**Product:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

**2,6-dimethylheptan-4-one:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
GLP : no

**maleic anhydride:**

Species : Rabbit  
Result : Corrosive to eyes  
GLP : yes

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Product:**

Remarks : Causes sensitisation.

**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Test Type : Mouse Local Lymph Node assay (LLNA)  
Species : Mouse  
Assessment : May cause sensitisation by skin contact.  
Method : OECD Test Guideline 429  
Result : May cause sensitisation by skin contact.  
GLP : yes

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026**2,6-dimethylheptan-4-one:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : yes

**maleic anhydride:**

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Causes sensitisation.  
GLP : yes

**Chronic toxicity****Germ cell mutagenicity**

Not classified due to lack of data.

**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes

Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative  
GLP: yes

Test Type: Chromosome aberration test in vitro  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative  
GLP: yes

**Carcinogenicity**

Suspected of causing cancer.

**Product:**

Remarks : No data available

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

---

### **Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

#### **Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### **STOT - single exposure**

Not classified due to lack of data.

#### **Product:**

Remarks : No data available

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

#### **Product:**

Remarks : No data available

### **Repeated dose toxicity**

#### **Product:**

Remarks : No data available

### **Components:**

#### **Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Species : Rat, male and female  
NOAEL : 1,000 mg/kg  
Application Route : Oral  
Method : OECD Test Guideline 422  
GLP : yes  
Target Organs : Stomach

### **Aspiration toxicity**

Not classified due to lack of data.

#### **Product:**

No data available

### **Further information**

#### **Product:**

Remarks : Solvents may degrease the skin.

**Section 12: Ecological information****Ecotoxicity****Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

- Toxicity to fish : LL50 (Leuciscus idus (Golden orfe)): > 150 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: DIN 38412  
GLP: no
- Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates  
Exposure time: 48 h  
Test Type: semi-static test  
Method: OECD Test Guideline 202  
GLP: yes
- Toxicity to algae/aquatic : ErL50 (Pseudokirchneriella subcapitata (green algae)): > 100  
plants  
mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes
- Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l  
Exposure time: 3 h  
Test Type: static test  
Method: OECD Test Guideline 209  
GLP: yes

**Xylene, mixture of isomers:**

- Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1 mg/l  
aquatic invertebrates  
Exposure time: 24 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 2.2 mg/l  
plants  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes
- NOEC (Pseudokirchneriella subcapitata (green algae)): 0.44  
mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
toxicity)  
Exposure time: 56 d
- Toxicity to daphnia and other : NOEC (Daphnia sp. (water flea)): 1.17 mg/l  
aquatic invertebrates  
Exposure time: 7 d

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

(Chronic toxicity)

NOEC (Daphnia sp. (water flea)): 0.96 mg/l  
Exposure time: 7 d**2,6-dimethylheptan-4-one:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 30 mg/l  
Exposure time: 96 h  
Test Type: flow-through test  
Method: OECD Test Guideline 203  
GLP: yesToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 37.2 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Test Type: semi-static test  
Method: OECD Test Guideline 202  
GLP: yesToxicity to algae/aquatic : (Pseudokirchneriella subcapitata (green algae)): 46.9 mg/l  
plants : Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes**maleic anhydride:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 75 mg/l  
Exposure time: 96 h  
Test Type: static test  
GLP: noToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 42.81 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yesToxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata): 74.35 mg/l  
plants : Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yesToxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 10 mg/l  
aquatic invertebrates : Exposure time: 21 d  
(Chronic toxicity) : GLP: no**Persistence and degradability****Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301  
GLP: yes**Xylene, mixture of isomers:**

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

---

Biodegradability : aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

**2,6-dimethylheptan-4-one:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D  
GLP: no

**maleic anhydride:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301B  
GLP: yes

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Components:****Xylene, mixture of isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 25.9  
Exposure time: 56 d  
GLP: no

Partition coefficient: n-  
octanol/water : Pow: 3.2 (20 °C)  
pH: 7

**maleic anhydride:**

Partition coefficient: n-  
octanol/water : log Pow: -2.61 (19.8 °C)  
pH: 4 - 9  
Method: OECD Test Guideline 107  
GLP: yes

**Mobility in soil****Components:****maleic anhydride:**

Distribution among  
environmental compartments : Koc: 42, log Koc: 1.63

**Other adverse effects****Product:**

Additional ecological  
information : An environmental hazard cannot be excluded in the event of  
unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

---

**Section 13: Disposal considerations**
**Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**Section 14: Transport information**
**International Regulations****UNRTDG**

- UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, Diisobutyl ketone)  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

**IATA-DGR**

- UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Xylene, Diisobutyl ketone)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

- UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, Diisobutyl ketone)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no  
Remarks : IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****NZS 5433**

- UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

(Xylene, Diisobutyl ketone)

Class	:	3
Packing group	:	III
Labels	:	3
Hazchem Code	:	3Y
Marine pollutant	:	no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**Section 15: Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002502 Additives Process Chemicals and Raw Materials Flammable Carcinogenic Group Standard

## Tolerable Exposure Limits (TEL)

Chemical name	Environmental compartment	Reference concentration
xylene	Air	0.87 mg/m <sup>3</sup>
	Water	0.6 mg/l

## Environmental Exposure Limits (EEL)

Not applicable

**HSW Controls**

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

**Section 16: Other information**

Revision Date : 14.04.2026  
Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA	:	8-hour, time-weighted average
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for

## BYK-P 104

Version 2.1  
SDS\_NZ

Revision Date: 14.04.2026

Date of last issue: 22.01.2026  
Print Date 15.04.2026

Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN