

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

SECTION 1. IDENTIFICATION

Product name : BYK-W 980

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number : 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 4

Skin irritation : Category 2

Specific target organ toxicity : Category 2 (Kidney)
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.
H315 Causes skin irritation.
H373 May cause damage to organs (Kidney) through prolonged
or repeated exposure.Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ eye protection/ face protection.
Response:

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P314 Get medical advice/ attention if you feel unwell.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
 P403 + P235 Store in a well-ventilated place. Keep cool.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Solution of a salt of unsaturated polyamine amides and lower molecular weight acidic polyesters

Hazardous components

HMIRA# 9961 Filing Date 21.04.2016

Component	CAS-No.	Concentration (%)
Polyamine amide salt	-	>= 60 - < 80
2-Butoxyethanol	111-76-2	>= 10 - < 20

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Consult a physician.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

- If swallowed : If eye irritation persists, consult a specialist.
: Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : No information available.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.
Will not explode on mechanical impact.
- Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep in a dry, cool and well-ventilated place.
Keep product and empty container away from heat and sources of ignition.
Take measures to prevent the build up of electrostatic charge.
No smoking.
Keep in a well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from strong bases.
Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
2-Butoxyethanol		TWA	50 ppm 240 mg/m ³	OSHA Z-1

Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.

Filter type : Type A

Hand protection

Material : Impervious butyl rubber gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: brown
Odour	: alcohol-like
Odour Threshold	: No data available
pH	: 7, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/freezing point	: < 64 °F (< 18 °C) Method: derived
Initial boiling point and boiling range	: 278.60 °F (137.00 °C) Method: derived
Vapour pressure	: 1 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 150.80 °F (66.00 °C) Method: 49 (Pensky-Martens)
Upper explosion limit	: 10.60 %(V)
Lower explosion limit	: 1.00 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.9900 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents Alkalis
Hazardous decomposition products	: None known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute oral toxicity	: LD50 (Rat): 6,750 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: Acute toxicity estimate : 55.27 mg/l Exposure time: 4 h

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Skin corrosion/irritation**Product:**

Species: Rabbit
Assessment: Irritating to skin.
Method: Draize Test
Result: Skin irritation

Remarks: May cause skin irritation in susceptible persons.

Components:**111-76-2 2-Butoxyethanol:**

Species: Rabbit
Result: Skin irritation

Serious eye damage/eye irritation**Product:**

Species: Rabbit
Result: No eye irritation
Assessment: No eye irritation
Method: Draize Test

Remarks: Causes serious eye irritation.

Components:**111-76-2 2-Butoxyethanol:**

Species: Rabbit
Result: Eye irritation
Method: OECD Test Guideline 405
GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**111-76-2 2-Butoxyethanol:**

Test Type: Maximisation Test

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

Exposure routes: Dermal
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.
GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

Remarks: Absorption of 2-Butoxyethanol by inhalation and/or repeated skin contact may cause injury to liver, kidney and blood damage.
2-Butoxyethanol is considered fetotoxic; has caused toxic reproductive effects in laboratory animals at maternally toxic doses.
2-Butoxyethanol had both positive and negative results in in vitro mutagenicity studies.
In a 2 yr. cancer study, the NTP has determined 2-butoxyethanol has a potential to cause cancer (potentially carcinogenic to mice) but there is not enough evidence to list 2-butoxyethanol as a carcinogen. The relevance to humans is unknown.

Aspiration toxicity**Product:**

No data available

Experience with human exposure**Product:**

Inhalation:

Symptoms:	High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).
-----------	---

Skin contact:

Symptoms:	Contact will probably cause irritation.
-----------	---

Eye contact:

Symptoms:	Contact will probably cause irritation.
-----------	---

Ingestion:

Symptoms:	Ingestion may irritate the digestive tract; high dosages may cause CNS depression.
-----------	--

Further information**Product:**

Remarks: Absorption of 2-Butoxyethanol may cause acute red blood cell damage and kidney effects. Inhalation of 2-Butoxyethanol has damaged the kidneys of laboratory animals. OSHA PEL-TWA for 2-butoxyethanol = 50 ppm (skin)

Remarks: No data available

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : Not applicable.

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.**SECTION 14. TRANSPORT INFORMATION****International Regulations**

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

2-Butoxyethanol	111-76-2	19.9 %
-----------------	----------	--------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

2-Butoxyethanol	111-76-2	19.9 %
-----------------	----------	--------

Non-volatile (Wt) : 78 - 82 %
 Method: 22 (10min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

Massachusetts Right To Know

2-Butoxyethanol	111-76-2
-----------------	----------

Pennsylvania Right To Know

Polyamine amide salt	-
2-Butoxyethanol	111-76-2

New Jersey Right To Know

New Jersey Trade Secret : 800963-5039
Registry Number for the product (NJ TSRN)

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Propylene oxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 07/11/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

BYK-W 980

Version 7

Revision Date 07/11/2024

Print Date 04/30/2026

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.