

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

SECTION 1: Identification of the hazardous chemical and of the supplier**Product identifier**

Product name : BYK-W 996 SG

Recommended use : Wetting & Dispersing Additive

Manufacturer or supplier's details

Company : BYK USA LLC

Address : South Cherry Street 524
06492 Wallingford

Telephone : +1 203-265-2086

Telefax :

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : +60 3 6207 4347 (Malay and English)
+65 3158 1074 (All languages)

SECTION 2: Hazards identification**Classification of the hazardous chemical**

Flammable liquids : Category 3

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Hazardous to the aquatic environment - chronic hazard : Category 3

Label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P273 Avoid release to the environment.

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture
Chemical nature : solution of polymeric phosphoric acid ester

Components

Chemical name	CAS-No.	Concentration (% w/w)
Phosphoric acid esters	162627-21-6	>= 50 -<= 100
2-methoxy-1-methylethyl acetate	108-65-6	>= 20 -< 25
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	>= 20 -< 25
phosphoric acid	7664-38-2	>= 1 -< 3

SECTION 4: First aid measures

General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No information available.

Notes to physician : No information available.

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

SECTION 5: Firefighting measures**Extinguishing media**

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Physicochemical hazards arising from the chemical

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Oxides of phosphorus
Sulfur oxides

Special protective equipment and precautions for fire-fighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Neutralize with chalk, alkali solution or ammonia.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling****Precautions for safe handling**

Advice on protection against : Do not spray on a naked flame or any incandescent material.

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

- fire and explosion Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Storage**Conditions for safe storage, including any incompatibilities**

- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection**Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
phosphoric acid	7664-38-2	TWA	1 mg/m ³	MY PEL
		TWA	1 mg/m ³	ACGIH
		STEL	3 mg/m ³	ACGIH

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hand protection
- Material : Nitrile rubber
- Break through time : > 480 min
- Remarks : Wear suitable gloves.

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

Respiratory protection : In the case of vapor formation use a respirator with an approved filter.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : liquid

Color : light brown

Odor : ester-like

Odor Threshold : No data available

pH : 3.2 (20 °C)
Concentration: 1 %
Method: DIN 19268 (1% in water)

Melting point/freezing point : < 0 °C
Method: derived

Initial boiling point and boiling range : 146.00 °C
Method: derived

Flash point : 40 °C
Method: 48 (Abel-Pensky) DIN 51755

Evaporation rate : No data available

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : 10.30 %(V)

Lower explosion limit / Lower flammability limit : 1.50 %(V)

Vapor pressure : 4 hPa (20.00 °C)
Method: derived

Relative vapor density : No data available

Relative density : No data available

Density : 1.0350 g/cm³ (20.00 °C)
Method: 4 (20°C oscillating U-tube)

Bulk density : Not applicable

Solubility(ies)**Water solubility : immiscible**

Solubility in other solvents : No data available

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	> 200.00 °C Method: DIN 51794
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	38.000 mm ² /s (20.00 °C) 28 mm ² /s (40.00 °C)
Surface tension	:	No data available

SECTION 10: Stability and reactivity

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air. Metals Gives off hydrogen by reaction with metals.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids Strong oxidizing agents Metals
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity**Product:**

Acute oral toxicity : LD50 (Rat, male and female): 8,000.000000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Components:**2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,160 mg/kg
Method: OECD Test Guideline 402

phosphoric acid:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation**Product:**

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Components:**2-methoxy-1-methylethyl acetate:**

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

phosphoric acid:

Remarks : No data available

Serious eye damage/eye irritation**Product:**

Species : Rabbit

Result : Eye irritation

Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

GLP : yes

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

Remarks : Causes serious eye irritation.

Components:**2-methoxy-1-methylethyl acetate:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

phosphoric acid:

Remarks : No data available

Respiratory or skin sensitization**Product:**

Remarks : No data available

Components:**2-methoxy-1-methylethyl acetate:**

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Test Type : Maximization Test
Routes of exposure : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitization.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity - : Classified based on benzene content < 0.1% (Regulation (EC))

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

Assessment 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity**Product:**

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

STOT-single exposure**Product:**

Remarks : No data available

STOT-repeated exposure**Product:**

Remarks : No data available

Repeated dose toxicity**Product:**

Remarks : No data available

Aspiration toxicity**Product:**

No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness,

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates Remarks: No data available

Components:**2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): >
plants 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: no

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish : LL50 (Fish): 9.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 3.2 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata): 2.6 mg/l
plants Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

phosphoric acid:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Components:**2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)
pH: 6.8
Method: OECD Test Guideline 117
GLP: yes

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal information**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

Contaminated packaging : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**International Regulations****IATA-DGR**

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Solvent naphtha, 1-Methoxy-2-propanol acetate)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Solvent naphtha, 1-Methoxy-2-propanol acetate)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information**Safety, health, and environmental regulations specific for the hazardous chemical**

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

BYK-W 996 SG

Product code: 000000000000114227

Version 3.0 SDS_APJ_MY

Revision Date 06.11.2025

Print Date 05.01.2026

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
MY PEL / TWA : Eight-hour time-weighted average airborne concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN