

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYKJET-9131

UFI : 1YD8-Y0Y9-Y009-YKSS

Product code : 000000000000126033

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Wetting & Dispersing Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735

Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 3	H331: Toxic if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

Hazard pictograms	:	 
Signal word	:	<b>Danger</b>
Hazard statements	:	H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H331 Toxic if inhaled. H336 May cause drowsiness or dizziness.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

### Hazardous components which must be listed on the label:

- 111-76-2 2-butoxyethanol
- 108-65-6 2-methoxy-1-methylethyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Structured copolymer

#### Components

Chemical name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

	EC-No. Index-No. Registration number		(% w/w)
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute Tox. 4; H302 <b>Acute Tox. 3; H331</b> Skin Irrit. 2; H315 Eye Irrit. 2; H319 <hr/> Acute toxicity estimate  Acute oral toxicity: 1.200 mg/kg	$\geq 30 - < 50$
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	$\geq 25 - < 30$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
------------	---------	------------------	--------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

		of exposure)		
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 98 mg/m <sup>3</sup>	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		STEL	50 ppm 246 mg/m <sup>3</sup>	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		STEL	100 ppm 550 mg/m <sup>3</sup>	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Skin contact	Acute systemic effects	89 mg/kg
	Workers	Inhalation	Acute systemic effects	135 ppm
	Workers	Inhalation	Acute local effects	50 ppm
	Workers	Skin contact	Long-term systemic effects	75 mg/kg
	Workers	Inhalation	Long-term systemic effects	20 ppm
	Consumers	Skin contact	Acute systemic effects	44,5 mg/kg
	Consumers	Inhalation	Acute systemic effects	426 mg/m <sup>3</sup>
	Consumers	Ingestion	Acute systemic effects	13,4 mg/kg
	Consumers	Inhalation	Acute local effects	123 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

	Consumers	Skin contact	Long-term systemic effects	38 mg/kg
	Consumers	Inhalation	Long-term systemic effects	49 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	3,2 mg/kg
2-methoxy-1-methylethyl acetate	Workers	Skin contact	Long-term systemic effects	796 mg/kg
	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg
	Workers	Inhalation	Acute local effects	550 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	33 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	2,8 mg/kg
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent releases	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg
	Marine sediment	0,329 mg/kg
	Soil	0,29 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

### Hand protection

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : 0,5 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

Filter type : Type A (A)

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : Molten form  
Colour : yellow - brown  
Odour : characteristic  
Odour Threshold : No data available

Melting point/freezing point : < 0 °C  
Method: derived

Initial boiling point and boiling range : ca. 144 °C  
Method: derived

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 42 °C  
Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature : > 200 °C  
Method: DIN 51794

Decomposition temperature : No data available

pH : 6 (20 °C)  
Concentration: 10 %  
Method: Universal pH-value indicator

Viscosity  
Viscosity, dynamic : No data available  
Viscosity, kinematic : 154 mm<sup>2</sup>/s (20 °C)

Solubility(ies)  
Water solubility : completely miscible  
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available  
Vapour pressure : 2 hPa (20 °C)  
Method: derived

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

---

Relative density	:	No data available
Density	:	1,000 g/cm <sup>3</sup> (20 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Relative vapour density	:	No data available

### 9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available
Surface tension	:	No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 9,64 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0  
SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023  
Print Date 16.05.2025

Method: Calculation method

### Components:

#### **2-butoxyethanol:**

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute inhalation toxicity : LC50 (Guinea pig): 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

#### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

### **Skin corrosion/irritation**

#### Product:

Remarks : May irritate skin.  
May cause skin irritation in susceptible persons.

### Components:

#### **2-butoxyethanol:**

Species : Rabbit  
Result : Skin irritation

#### **2-methoxy-1-methylethyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

### **Serious eye damage/eye irritation**

#### Product:

Remarks : Causes serious eye irritation.

### Components:

#### **2-butoxyethanol:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Eye irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0  
SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023  
Print Date 16.05.2025

GLP : yes

### 2-methoxy-1-methylethyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### Respiratory or skin sensitisation

#### Product:

Remarks : No data available

#### Components:

### 2-butoxyethanol:

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

### 2-methoxy-1-methylethyl acetate:

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : yes

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

### Carcinogenicity

#### Product:

Remarks : No data available

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

## BYKJET-9131

Version 10.0  
SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023  
Print Date 16.05.2025

---

### STOT - single exposure

**Product:**

Remarks : No data available

**Components:**

**2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

**Product:**

Remarks : No data available

### Repeated dose toxicity

**Product:**

Remarks : No data available

### Aspiration toxicity

**Product:**

No data available

## 11.2 Information on other hazards

### Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0  
SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023  
Print Date 16.05.2025

### Components:

#### **2-butoxyethanol:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.550 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 204
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211

#### **2-methoxy-1-methylethyl acetate:**

- Toxicity to fish : LC50 (Fish): 100 - 180 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: no
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: no

### 12.2 Persistence and degradability

#### Product:

- Biodegradability : Remarks: No data available

#### Components:

#### **2-butoxyethanol:**

- Biodegradability : Test Type: aerobic

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0  
SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023  
Print Date 16.05.2025

Result: Readily biodegradable.  
Method: OECD Test Guideline 301B

### 2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### 2-butoxyethanol:

Partition coefficient: n- : log Pow: 0,81 (25 °C)  
octanol/water pH: 7

##### 2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)  
octanol/water pH: 6,8  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 3272
- IMDG : UN 3272
- IATA : UN 3272

#### 14.2 UN proper shipping name

- ADR : ESTERS, N.O.S.  
(1-Methoxy-2-propanol acetate)
- IMDG : ESTERS, N.O.S.  
(1-Methoxy-2-propanol acetate)
- IATA : Esters, n.o.s.  
(1-Methoxy-2-propanol acetate)

#### 14.3 Transport hazard class(es)

- ADR : 3
- IMDG : 3
- IATA : 3

#### 14.4 Packing group

- ADR**
- Packing group : III
- Classification Code : F1
- Hazard Identification Number : 30
- Labels : 3
- Tunnel restriction code : D/E
- IMDG**
- Packing group : III
- Labels : 3
- EmS Code : F-E, S-D
- Remarks : IMDG Code segregation group - none
- IATA (Cargo)**
- Packing instruction (cargo) : 366

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

aircraft)  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Fire Hazard Class : B II: Flash point  $\geq 21$  °C to  $\leq 55$  °C; water soluble at 15 °C

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. H2 ACUTE TOXIC

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving P5c FLAMMABLE LIQUIDS

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0

SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023

Print Date 16.05.2025

dangerous substances.

### 15.2 Chemical safety assessment

Not applicable

### SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H336	:	May cause drowsiness or dizziness.

#### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
MT OEL	:	Malta. Occupational Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
MT OEL / TWA	:	Long term exposure limit
MT OEL / STEL	:	Occupational exposure limit value Short-term, 15 minute

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYKJET-9131

Version 10.0  
SDB\_MT

Revision Date: 09.11.2023

Date of last issue: 26.01.2023  
Print Date 16.05.2025

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
<b>Acute Tox. 3</b>	<b>H331</b>
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336

#### Classification procedure:

Based on product data or assessment
<b>Calculation method</b>
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MT / EN