

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYKJET-9132
UFI : 2XE8-J0JP-A00R-8C6G
Product code : 000000000000126032

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel
Telephone : +49 281 670-0
Telefax : +49 281 65735

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

Hazard pictograms	:	 
Signal Word	:	Warning
Hazard Statements	:	H226 Flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.
Precautionary Statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

- 111-76-2 2-butoxyethanol
- 108-65-6 2-methoxy-1-methylethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : solution of polymethacrylate

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg Acute inhalation toxicity (vapor): 3 mg/l	>= 25 - < 30
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	STOT SE 3; H336 Flam. Liq. 3; H226	>= 25 - < 30

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	10 ppm 49 mg/m ³	CH SUVA
	Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases, Health and Safety Executive (Occupational Medicine and Hygiene Laboratory), Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	20 ppm 98 mg/m ³	CH SUVA
	Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases, Health and Safety Executive (Occupational Medicine and Hygiene Laboratory), Harm to the unborn child is not to be expected when the OEL-value is respected			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	CH SUVA
	Further information: Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	50 ppm	CH SUVA

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

		275 mg/m3	
Further information: Harm to the unborn child is not to be expected when the OEL-value is respected			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	2-butoxy acetic acid: 150 mg/g creatinine (Urine)	Immediately after exposure or after working hours, In case of long-term exposure: after more than one shift	CH BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Routes of exposure	Potential health effects	Value
2-butoxyethanol	Workers	Skin contact	Acute systemic effects	89 mg/kg
	Workers	Inhalation	Acute systemic effects	135 ppm
	Workers	Inhalation	Acute local effects	50 ppm
	Workers	Skin contact	Long-term systemic effects	75 mg/kg
	Workers	Inhalation	Long-term systemic effects	20 ppm
	Consumers	Skin contact	Acute systemic effects	44,5 mg/kg
	Consumers	Inhalation	Acute systemic effects	426 mg/m3
	Consumers	Ingestion	Acute systemic effects	13,4 mg/kg
	Consumers	Inhalation	Acute local effects	123 mg/m3
	Consumers	Skin contact	Long-term systemic effects	38 mg/kg
	Consumers	Inhalation	Long-term systemic effects	49 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,2 mg/kg
2-methoxy-1-methylethyl acetate	Workers	Skin contact	Long-term systemic effects	796 mg/kg
	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Acute local effects	33 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8,8 mg/l
	Sea water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Sea sediment	3,46 mg/kg
2-methoxy-1-methylethyl acetate	Soil	2,8 mg/kg
	Fresh water	0,635 mg/l
	Sea water	0,0635 mg/l
	Intermittent releases	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg
	Sea sediment	0,329 mg/kg
	Soil	0,29 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapor formation use a respirator with an approved filter.

Filter type : Type A (A)

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : brown

Odor : characteristic

Odor Threshold : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

Melting point/freezing point	:	< 0 °C Method: derived
Initial boiling point and boiling range	:	145 °C Method: derived
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	49 °C Method: 48 (Abel-Pensky) DIN 51755
Autoignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	6 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity		
Viscosity, dynamic	:	73 mPa.s (20 °C) Method: P/K 20°C
Viscosity, kinematic	:	72 mm ² /s (20 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapor pressure	:	3,37 hPa Method: derived
Relative density	:	No data available
Density	:	1,009 g/cm ³ (20 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube)
Relative vapor density	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids and bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 10,03 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Test atmosphere: vapor
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May irritate skin.
May cause skin irritation in susceptible persons.

Components:

2-butoxyethanol:

Species : Rabbit
Result : Skin irritation

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Causes serious eye irritation.

Components:

2-butoxyethanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Eye irritation
GLP : yes

2-methoxy-1-methylethyl acetate:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Product:

Remarks : No data available

Components:

2-butoxyethanol:

Test Type : Maximization Test
Routes of exposure : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitization.
GLP : yes

2-methoxy-1-methylethyl acetate:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Components:

2-butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.550 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: no

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

2-butoxyethanol:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301B

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

2-butoxyethanol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

Partition coefficient: n-octanol/water : log Pow: 0,81 (25 °C)
pH: 7

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)
pH: 6,8
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 3272
ADR	:	UN 3272
RID	:	UN 3272
IMDG	:	UN 3272
IATA	:	UN 3272

14.2 UN proper shipping name

ADN	:	ESTERS, N.O.S. (1-Methoxy-2-propanol acetate)
ADR	:	ESTERS, N.O.S. (1-Methoxy-2-propanol acetate)
RID	:	ESTERS, N.O.S. (1-Methoxy-2-propanol acetate)
IMDG	:	ESTERS, N.O.S. (1-Methoxy-2-propanol acetate)
IATA	:	Esters, n.o.s. (1-Methoxy-2-propanol acetate)

14.3 Transport hazard class(es)

ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: D/E
RID	
Packing group	: III
Classification Code	: F1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

Hazard Identification Number : 30

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, S-D

Remarks : IMDG Code segregation group - none

IATA (Cargo)

Packing instruction (cargo aircraft) : 366

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355

(passenger aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	:	Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor. This product does not contain substances of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Fire Hazard Class	:	A II: Flash point 69.8 °F to 131 °F, at 59 °F not miscible in water
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FLAMMABLE LIQUIDS
Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 59,48 %

15.2 Chemical Safety Assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226	:	Flammable liquid and vapor.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H336	:	May cause drowsiness or dizziness.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
CH BAT	:	Switzerland. List of BAT-values
CH SUVA	:	Switzerland. Limit values at the work place

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0

SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025

Print Date: 16.12.2025

2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
CH SUVA / TWA	: Time Weighted Average
CH SUVA / STEL	: Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKJET-9132

Version: 11.0
SDB_CH

Revision Date: 11.12.2025

Date of last issue: 29.09.2025
Print Date: 16.12.2025

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN