

**CLOISITE-Ca++**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 1. IDENTIFICATION**

Product name : CLOISITE-Ca++

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)Emergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Polymer Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Carcinogenicity : Category 1A

Specific target organ toxicity : Category 1 (Lungs)  
- repeated exposure  
(Inhalation)**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

## CLOISITE-Ca++

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**Response:**

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance  
 Chemical nature : Natural phyllosilicate

**Hazardous components**

Component	CAS-No.	Concentration (%)
Crystalline silica (quartz)	14808-60-7	>= 1 - < 5

### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. Wash thoroughly with soap and water.

In case of eye contact : Flush eyes with water as a precaution.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.  
 Keep respiratory tract clear.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : No information available.

**CLOISITE-Ca++**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : None known.
- Hazardous combustion products : No hazardous combustion products are known
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid formation of respirable particles.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.

**CLOISITE-Ca++**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Crystalline silica (quartz)	14808-60-7	TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
Crystalline silica (quartz)		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
Crystalline silica (quartz)		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
Crystalline silica (quartz)		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
Crystalline silica (quartz)		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
Crystalline silica (quartz)		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
Crystalline silica (quartz)		PEL (respirable)	0.05 mg/m <sup>3</sup>	OSHA CARC

**Further occupational exposure limits**

Description	Value type	Control parameters	Basis
inert or nuisance dust	TWA	50Million particles per cubic foot total dust	OSHA Z-3
	TWA	15 mg/m <sup>3</sup> total dust	OSHA Z-3
	TWA	5 mg/m <sup>3</sup> respirable fraction	OSHA Z-3
	TWA	15Million particles per cubic foot respirable fraction	OSHA Z-3

**Engineering measures** : Engineering and/or work practice controls should be implemented to maintain exposure to respirable crystalline silica below the permissible exposure limit.

**Personal protective equipment**

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.  
Dust safety masks are recommended when the dust

## CLOISITE-Ca++

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Hand protection	concentration is more than 10 mg/m <sup>3</sup> .
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Dust impervious protective suit Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: powder
Colour	: off-white
Odour	: odourless
Odour Threshold	: Not applicable
pH	: 4.6 - 7.6, Concentration: 2 % (68 °F (20 °C)) Method: DIN 19268 (2% in water)
Melting point/ range	: Not applicable
Boiling point/boiling range	: Not applicable
Vapour pressure	: Not applicable
Flash point	: Not applicable
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not expected to form explosive dust-air mixtures.
Minimum Explosible Concentration	: Not applicable
Relative vapour density	: Not applicable
Relative Density/Specific Gravity	: No data available
Particle size	: No data available
Density	: 2.6 g/cm <sup>3</sup> (68 °F (20 °C))
Bulk density	: 500 - 1,100 kg/m <sup>3</sup>

**CLOISITE-Ca++**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-  
octanol/water : No data available

Ignition temperature : Not applicable

Thermal decomposition : No data available

Viscosity  
Viscosity, dynamic : Not applicable

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.  
Chemical stability : No decomposition if stored and applied as directed.  
Possibility of hazardous  
reactions : No decomposition if stored and applied as directed.  
Dust may form explosive mixture in air.

Conditions to avoid : No data available  
Incompatible materials : Strong oxidizing agents  
Hazardous decomposition  
products : No data available

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Ingestion  
Eye contact  
Skin contact

**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : 2,577 mg/kg  
Method: Calculation method

**Skin corrosion/irritation****Product:**

Remarks: No data available

**CLOISITE-Ca++**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**Serious eye damage/eye irritation**
**Product:**

Remarks: No data available

**Respiratory or skin sensitisation**
**Product:**

Remarks: No data available

**Carcinogenicity**

<b>IARC</b>	Group 1: Carcinogenic to humans	
	Crystalline silica (quartz)	14808-60-7
<b>OSHA</b>	OSHA specifically regulated carcinogen	
	Crystalline silica (quartz)	14808-60-7
<b>NTP</b>	Known to be human carcinogen	
	Crystalline silica (quartz)	14808-60-7

**Repeated dose toxicity**
**Product:**

Remarks: Long term inhalation of crystalline silica dusts may cause lung disease (silicosis). Crystalline silica has been classified as a probable human carcinogen by IARC. Epidemiological studies suggest that respirable crystalline silica has caused both immune system and kidney effects. The mechanisms causing these effects are unclear and a dose-response relationship has not been determined.

**Experience with human exposure**
**Product:**

Inhalation:

Symptoms: Dust particles may cause irritation of the respiratory tract.

Skin contact:

Symptoms: Contact may cause irritation.

Eye contact:

Symptoms: Contact may cause irritation.

## CLOISITE-Ca++

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Ingestion:

Symptoms:

Ingestion will probably cause irritation of the digestive tract.

### Further information

#### Product:

Remarks: No data available

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Toxicity to fish

:

Remarks: No data available

Toxicity to daphnia and other  
aquatic invertebrates

:

Remarks: No data available

### Persistence and degradability

#### Product:

Biodegradability

:

Remarks: No data available

### Bioaccumulative potential

#### Product:

Bioaccumulation

:

Remarks: No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

#### Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological  
information

:

No data available

**CLOISITE-Ca++**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s) : Not applicable.

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2

## CLOISITE-Ca++

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : No data available

### Massachusetts Right To Know

Crystalline silica (quartz)	14808-60-7
-----------------------------	------------

### Pennsylvania Right To Know

Phyllosilicate	-
Crystalline silica (quartz)	14808-60-7

### New Jersey Right To Know

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-1006

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including Crystalline silica (quartz), which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.

DSL : We certify that all of the components of this product are listed

**CLOISITE-Ca++**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

on the DSL.

**SECTION 16. OTHER INFORMATION**

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits.

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.