

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

**SECTION 1. IDENTIFICATION**

Product name : DISPERBYK-182

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting &amp; Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.Precautionary statements : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting  
equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.

## DISPERBYK-182

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
 Chemical nature : Solution of modified polyurethane

**Hazardous components**

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate	108-65-6	>= 20 - < 30
2-Methoxymethylethoxypropanol [DPM]	34590-94-8	>= 10 - < 30
n-Butyl Acetate	123-86-4	>= 10 - < 20

### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Symptoms of poisoning may appear several hours later.  
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.

## DISPERBYK-182

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

If swallowed	Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: No information available.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## DISPERBYK-182

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from strong acids.  
Keep away from strong bases.  
Keep away from oxidizing agents.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
2-Methoxymethylethoxypropanol [DPM]	34590-94-8	TWA	100 ppm 600 mg/m <sup>3</sup>	OSHA Z-1
2-Methoxymethylethoxypropanol [DPM]		TWA	50 ppm	ACGIH
n-Butyl Acetate	123-86-4	TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA Z-1
n-Butyl Acetate		TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA P0
n-Butyl Acetate		STEL	200 ppm 950 mg/m <sup>3</sup>	OSHA P0
n-Butyl Acetate		TWA	150 ppm 710 mg/m <sup>3</sup>	NIOSH REL

## DISPERBYK-182

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

n-Butyl Acetate		ST	200 ppm 950 mg/m <sup>3</sup>	NIOSH REL
n-Butyl Acetate		TWA	50 ppm	ACGIH
n-Butyl Acetate		STEL	150 ppm	ACGIH

**Engineering measures** : Use with local exhaust ventilation.

### Personal protective equipment

**Respiratory protection** : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.  
In the case of vapour formation use a respirator with an approved filter.

**Hand protection**

**Material** : Impervious butyl rubber gloves

**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection**

: Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection**

: Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures**

: When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid  
**Colour** : colourless, light yellow  
**Odour** : ester-like  
**Odour Threshold** : No data available

**pH** : 8, Concentration: 10 % (68 °F (20 °C)) Method: Universal pH-value indicator

**Melting point/ range** : < 32 °F (< 0 °C)  
Method: derived

**Initial boiling point** : 255.20 °F (124.00 °C)  
Method: derived

**Vapour pressure** : 6 hPa (68.00 °F (20.00 °C))  
Method: derived

**Flash point** : 100.40 °F (38.00 °C)  
Method: 48 (Abel-Pensky) DIN 51755

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

Upper explosion limit	: 12.00 %(V)
Lower explosion limit	: 1.20 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.0250 g/cm <sup>3</sup> (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392.00 °F (> 200.00 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Surface tension	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.  Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Acids Strong oxidizing agents Alkalis
Hazardous decomposition products	: None expected

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Skin Absorption  
Inhalation  
Eyes  
Ingestion

**Acute toxicity****Product:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Acute toxicity estimate : 170.92 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

Acute oral toxicity : LD50 (Rat): 5,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 50 mg/l

Acute dermal toxicity : LD50 (Rabbit): 9,500 mg/kg

**123-86-4 n-Butyl Acetate:**

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg  
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg  
Method: OECD Test Guideline 402

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

**Skin corrosion/irritation****Product:**

Remarks: No data available

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

**34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

Species: Rabbit

Result: slight irritation

**123-86-4 n-Butyl Acetate:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

**Serious eye damage/eye irritation****Product:**

Remarks: No data available

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

**34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

Species: Rabbit

Result: Mild eye irritation

**123-86-4 n-Butyl Acetate:**

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

**Respiratory or skin sensitisation****Product:**

Remarks: No data available

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Not a skin sensitizer.  
GLP: yes

**34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

Result: Does not cause skin sensitisation.

**123-86-4 n-Butyl Acetate:**

Test Type: Buehler Test  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitisation.

**Germ cell mutagenicity****Product:**

Genotoxicity in vivo : Remarks: No data available

**Carcinogenicity****Product:**

Remarks: No data available

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**STOT - single exposure****Product:**

Remarks: No data available

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

**STOT - repeated exposure****Product:**

Remarks: No data available

**Repeated dose toxicity****Product:**

Remarks: No data available

**Aspiration toxicity****Product:**

No data available

**Components:****34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Experience with human exposure****Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause CNS depression (drowsiness, loss of coordination and fatigue); narcosis.

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract; high dosages may cause CNS depression.

**Further information****Product:**

Remarks: Skin absorption of 10-20 ml/kg of DPM has caused CNS depression (in rabbits).  
ACGIH-TLV-TWA for DPM = 100 ppm (skin)

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other :  
aquatic invertebrates Remarks: No data available

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available  
Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : No data available  
information

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste : D001: Ignitable  
Code(s)

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

Contaminated packaging : Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.  
 : Empty remaining contents.  
 Dispose of as unused product.  
 Do not re-use empty containers.  
 Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**
**International Regulations**
**IATA-DGR**

UN/ID No. : UN 3272  
 Proper shipping name : Esters, n.o.s.  
 (Butyl acetate, 1-Methoxy-2-propanol acetate)  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 3272  
 Proper shipping name : ESTERS, N.O.S.  
 (BUTYL ACETATE, 1-Methoxy-2-propanol acetate)  
 : )  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-D  
 Marine pollutant : no  
 Remarks : IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**
**49 CFR**

UN/ID/NA number : UN 3272  
 Proper shipping name : Esters, n.o.s.  
 (Butyl acetate, 1-Methoxy-2-propanol acetate)  
 Class : 3  
 Packing group : III  
 Labels : FLAMMABLE LIQUID  
 ERG Code : 127

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

Marine pollutant : no  
 Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know Act**
**US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
n-Butyl Acetate	123-86-4	5000	34185

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

n-Butyl Acetate	123-86-4	14.6 %
-----------------	----------	--------

Non-volatile (Wt) : 41 - 45 %  
 Method: 23 (20min/150°C)

**DISPERBYK-182**

Version 8

Revision Date 03/24/2025

Print Date 05/14/2026

DIN EN ISO 3251

Non-volatile information is not a specification.

**Massachusetts Right To Know**

2-Methoxymethylethoxypropanol [DPM]	34590-94-8
n-Butyl Acetate	123-86-4

**Pennsylvania Right To Know**

Polymer	-
1-Methoxy-2-propanol acetate	108-65-6
2-Methoxymethylethoxypropanol [DPM]	34590-94-8
n-Butyl Acetate	123-86-4
n-Butanol	71-36-3

**New Jersey Right To Know**

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-5168

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**

Revision Date : 03/24/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.