

SCONA TSPE 1013 GALL

Adhesion promoter for multi-layer and single-layer polyethylene films on metal and similar polar substrates.

Product data

Composition

Chemically modified linear low density polyethylene

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Grafting functionality:	maleic anhydride
Grafting level:	0.6 %
MFR (190 °C, 2.16 kg):	3 g/10 min
Drying loss (180 min, 110 °C):	< 0.5 %
Color:	off-white
Delivery form:	pellet

Storage and transportation

Product shelf life in unopened original packaging: 36 months

Moisture sensitive. Store in sealed containers in a cool, dry, and well-ventilated place. To be stored and transported at a temperature below 40 °C.

Applications

Thermoplastics

Special features and benefits

SCONA TSPE 1013 GALL is an adhesion promoter for use in polyethylene and is suitable for cast and blown films that need to adhere to metal, wood, or polar plastics such as polyamide. Adhesion is achieved through a combination of chain entanglement, covalent bonds, hydrogen bonds, dipole-dipole interactions, and van der Waals forces. This creates a durable bond for high-quality composite materials in industrial applications.

Recommended use

SCONA TSPE 1013 GALL can be used in a wide range of coextrusion processes to bond different materials together and give a range of end products the desired properties.

Recommended levels

20-100 % additive (as supplied) based upon the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive is added directly at the extruder using proven dosing technology and is optimally matched to the usual processing conditions for polyethylene films. This ensures precise and reliable processing, guaranteeing consistently high quality and maximum process reliability.



Your local
contact

BYK-Chemie GmbH

Abelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
info@byk.com
www.byk.com



Download
our app:
byk.com/app

ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, NANOBYK®, OPTIBENT®, OPTIGEL®, PURABYK®, RECYCLOBYK®, RHEOBYK®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information contained herein is based on our current knowledge and experience. No warranties, guarantees and/or assurances of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. Any information about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. Contractual terms and conditions, in particular agreed product specifications, always take precedence. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. We reserve the right to make any changes and to update the information herein without notice.