

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ANTI-TERRA-U

UFI : RRP7-W06G-N004-N5V2

Product code : 000000000000102324

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel

Telephone : +49 281 670-0
Telefax : +49 281 65735

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone number

Europe +44 1235 239670
Middle East/Africa +44 1235 239671
Americas +1 215 207 0061
East/South East Asia +65 3158 1074
(Local India: 000 800 100 7479)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard,	H412: Harmful to aquatic life with long lasting

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Category 3

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist or vapours.
P264	Wash skin thoroughly after handling.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 1330-20-7 Xylene, mixture of isomers

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solution of a salt of unsaturated polyamine amides and lower molecular weight acidic polyesters

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Polyamine amide salt	-	Skin Irrit. 2; H315	>= 50 - <= 100
Xylene, mixture of isomers	1330-20-7 01-2119488216-32	Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Aquatic Chronic 3; H412	>= 25 - < 30
ethylbenzene	100-41-4 202-849-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 12,5
iso-butanol	78-83-1 201-148-0 01-2119484609-23	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 3 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

- advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Sulphur oxides

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

- Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Xylene, mixture of isomers	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Substance name	End Use	Exposure routes	Potential health effects	Value
Xylene, mixture of isomers	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Dermal	Long-term systemic effects	212 mg/kg
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	125 mg/kg
	Consumers	Oral	Long-term systemic effects	1,5 mg/kg
iso-butanol	Consumers	Inhalation	Acute local effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	310 mg/m3
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg
propane-1,2-diol	Consumers	Inhalation	Long-term local effects	55 mg/m3
	Consumers	Inhalation	Long-term local effects	10 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50 mg/m3
	Workers	Inhalation	Long-term systemic effects	168 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Xylene, mixture of isomers	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Soil	2,31 mg/kg
	Sewage treatment plant	6,58 mg/l
	Intermittent releases	0,327 mg/l
iso-butanol	Fresh water	0,4 mg/l
	Marine water	0,04 mg/l
	Fresh water sediment	1,56 mg/kg
	Marine sediment	0,156 mg/kg
	Soil	0,0765 mg/kg
	Sewage treatment plant	10 mg/l
	Intermittent releases	11 mg/l
propane-1,2-diol	Fresh water	260 mg/l
	Intermittent releases	183 mg/l
	Marine water	26 mg/l
	Fresh water sediment	572 mg/kg
	Marine sediment	57,2 mg/kg
	Soil	50 mg/kg
	Sewage treatment plant	20000 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection
Material : Fluorinated rubber
Break through time : ≥ 480 min
Glove thickness : 0,4 mm

Remarks : The suitability for a specific workplace should be discussed
with the producers of the protective gloves.
Skin and body protection : Impervious clothing
Choose body protection according to the amount and
concentration of the dangerous substance at the work place.
Respiratory protection : In the case of vapour formation use a respirator with an
approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : light brown
Odour : aromatic
Odour Threshold : No data available
Melting point/ range : < 10 °C
Method: derived
Initial boiling point : 106,00 °C
Method: derived
Upper explosion limit / Upper
flammability limit : 10,70 %(V)
Lower explosion limit / Lower
flammability limit : 1,20 %(V)
Flash point : 25,00 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	4 Concentration: 1 % Method: Universal pH-value indicator
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	15,217 mm ² /s (40 °C) Method: calculated
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	11 hPa (20,00 °C) Method: derived
Relative density	:	No data available
Density	:	0,9400 g/cm ³ (20,00 °C) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Relative vapour density	:	No data available

9.2 Other information

Oxidizing properties	:	None.
Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : LD50 (Rat): 12.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Xylene, mixture of isomers:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 4.200 mg/kg
GLP: No information available.

iso-butanol:

Acute oral toxicity : LD50 (Rat, male): > 2.830 mg/kg
Method: OECD Test Guideline 401

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Skin irritation

Remarks : May irritate skin.
May cause skin irritation in susceptible persons.

Components:

iso-butanol:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system
and the skin.

Components:

iso-butanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Eye irritation
GLP : yes

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Product:

Remarks : No data available

Components:

iso-butanol:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause respiratory irritation.

Product:

Remarks : No data available

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Remarks : No data available

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

No data available

Components:

iso-butanol:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Components:

Polyamine amide salt:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 48 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 30 mg/l
Exposure time: 48 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Method: OECD Test Guideline 202
GLP: yes

Xylene, mixture of isomers:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 24 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia sp. (water flea)

NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Daphnia sp. (water flea)

iso-butanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.430 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 1.100 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.799 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 20 mg/l
End point: Reproduction
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

Xylene, mixture of isomers:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

iso-butanol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

Xylene, mixture of isomers:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Exposure time: 56 d
Bioconcentration factor (BCF): 25,9
GLP: no

Partition coefficient: n-octanol/water : Pow: 3,2 (20 °C)
pH: 7

iso-butanol:

Partition coefficient: n-octanol/water : log Pow: 1
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1993

IMDG : UN 1993

IATA : UN 1993

14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, N.O.S.
(Xylene, Isobutanol)

IMDG : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Isobutanol)

IATA : Flammable liquid, n.o.s.
(Xylene, Isobutanol)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: D/E
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
Remarks	: IMDG Code segregation group - none

IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing group	: III
Labels	: Flammable Liquids

IATA (Passenger)	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids

14.5 Environmental hazards

ADR	
Environmentally hazardous	: no

IMDG	
Marine pollutant	: no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 Number on list 5: benzene Number on list 72: benzene Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

For further information see eSDS.

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : Prolonged storage of the product can cause the stabiliser to lose its effectiveness.
Information taken from reference works and the literature.
Take notice of the directions of use on the label.

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Annex: Exposure Scenarios

Table of Contents

Number	Title
ES 1	Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).; Formulation [mixing] of preparations and/or re-packaging (SU10).
ES 2	Use in coatings; Industrial uses (SU3).
ES 3	Use in laboratories; Industrial uses (SU3).; Formulation [mixing] of preparations and/or re-packaging (SU10).
ES 4	Use in coatings; Professional uses (SU22).
ES 5	Use in laboratories; Professional uses (SU22).
ES 6	Use in coatings; Consumer uses (SU21).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

ES 1: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).; Formulation [mixing] of preparations and/or re-packaging (SU10).

1.1. Title section

Exposure Scenario name	: Formulation & (re)packing of substances and mixtures
Structured Short Title	: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).; Formulation [mixing] of preparations and/or re-packaging (SU10).
Substance	: xylenes <u>CAS-No.:</u> 1330-20-7

Environment		
CS 1	Formulation into mixture	ERC2
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Use in closed batch process (synthesis or formulation)	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 8	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Chemical production where opportunity for exposure arises	PROC4
CS 11	Use as laboratory reagent	PROC15

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Formulation into mixture (ERC2)

Product (article) characteristics
--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount used in the EU	: 150000000 kg
Fraction of regional tonnage used locally	: 15000000 kg
Emission days	: 300
Technical and organisational conditions and measures	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite sewage treatment plant
STP sludge treatment	: No application of sewage sludge to soil
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Waste treatment	: External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

1.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system. Ensure material transfers are under containment or extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system. Ensure material transfers are under containment or extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure material transfers are under containment or extract ventilation. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Transfer via enclosed lines. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Clear spills immediately. Return IBCs or tanks to supplier for re-use.	

1.2.9. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Transfer via enclosed lines. Put lids on containers immediately after use. Clear spills immediately.	

1.2.10. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

1.2.11. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle in a fume cupboard or under extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Formulation into mixture (ERC2)

Release route	Release rate	Release estimation method
Air	0,2 kg/day	
Waste	3 kg/day	
Soil	1 kg/day	

Protection Target	Exposure estimate	RCR
Freshwater	0,0796 mg/L	0,244
Freshwater sediment	0,854 mg/kg wet weight	0,854

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Marine water	0,00796 mg/L	0,024
Marine sediment	0,0853 mg/kg wet weight	0,085
Sewage treatment plant	0,791 mg/L	0,120

1.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,01 ppm	0
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0

1.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	10 ppm	0,56
dermal	systemic	long-term	1,37 mg/kg bw/day	0,01
combined routes				0,57

1.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	17,5 ppm	0,99
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0,99

1.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	14 ppm	0,79
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,83

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

1.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	13,71 mg/kg bw/day	0,08
combined routes				0,92

1.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	13,71 mg/kg bw/day	0,04
combined routes				0,92

1.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	1,50 ppm	0,08
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,12

1.3.9. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,88

1.3.10. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure	Exposure	RCR
----------------	---------------	----------	----------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

		indicator	estimate	
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	3,43 mg/kg bw/day	0,02
combined routes				0,87

1.3.11. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	10 ppm	0,56
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0,57

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

ES 2: Use in coatings; Industrial uses (SU3).

2.1. Title section

Exposure Scenario name	: Use in coatings
Structured Short Title	: Use in coatings; Industrial uses (SU3).
Substance	: xylenes CAS-No.: 1330-20-7

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)	ERC4
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Use in closed batch process (synthesis or formulation)	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Industrial spraying	PROC7
CS 8	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 9	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 10	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 11	Roller application or brushing	PROC10
CS 12	Treatment of articles by dipping and pouring	PROC13
CS 13	Chemical production where opportunity for exposure arises	PROC4
CS 14	Use as laboratory reagent	PROC15

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount used in the EU	: 50000000 kg
Fraction of regional tonnage used locally	: 5000000 kg
Emission days	: 300
Conditions and measures related to sewage treatment plant	
STP type	: Onsite sewage treatment plant
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Waste treatment	: External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

2.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system. Ensure material transfers are under containment or extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system. Ensure material transfers are under containment or extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure material transfers are under containment or extract ventilation. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.7. Control of worker exposure: Industrial spraying (PROC7)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Carry out in a vented booth provided with laminar airflow.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics
--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Drain down system prior to equipment break-in or maintenance. Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.9. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Clear spills immediately. Return IBCs or tanks to supplier for re-use.	

2.2.10. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Transfer via enclosed lines. Put lids on containers immediately after use.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Clear spills immediately.

2.2.11. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide extract ventilation to points where emissions occur.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.12. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Technical and organisational conditions and measures	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Clear up spills immediately and dispose of waste safely. Avoid manual contact with wet work pieces.	

2.2.13. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Assumes a good basic standard of occupational hygiene is implemented

2.2.14. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle in a fume cupboard or under extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,0375 mg/L	0,115
Marine water	0,00375 mg/L	0,012
Freshwater sediment	0,402 mg/kg wet weight	0,148
Marine sediment	0,0402 mg/kg wet weight	0,015

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Sewage treatment plant	0,369 mg/L	0,056
------------------------	------------	-------

2.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,01 ppm	0
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0

2.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	10 ppm	0,56
dermal	systemic	long-term	1,37 mg/kg bw/day	0,01
combined routes				0,57

2.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	17,5 ppm	0,99
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0,99

2.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	14 ppm	0,79
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,83

2.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure	Exposure	RCR
----------------	---------------	----------	----------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

		indicator	estimate	
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	0,07 mg/kg bw/day	0,08
combined routes				0,85

2.3.7. Worker exposure: Industrial spraying (PROC7)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	12,50 ppm	0,71
dermal	systemic	long-term	2,14 mg/kg bw/day	0,01
combined routes				0,72

2.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5 ppm	0,28
dermal	systemic	long-term	1,37 mg/kg bw/day	0,01
combined routes				0,29

2.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	1,50 ppm	0,08
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,12

2.3.10. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,88

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

2.3.11. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5 ppm	0,28
dermal	systemic	long-term	27,43 mg/kg bw/day	0,15
combined routes				0,43

2.3.12. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	13,71 mg/kg bw/day	0,08
combined routes				0,92

2.3.13. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	3,43 mg/kg bw/day	0,02
combined routes				0,87

2.3.14. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,60 ppm	0,03
dermal	systemic	long-term	0,03 mg/kg bw/day	0
combined routes				0,03

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

ES 3: Use in laboratories; Industrial uses (SU3).; Formulation [mixing] of preparations and/or re-packaging (SU10).

3.1. Title section

Exposure Scenario name	: Use in laboratories
Structured Short Title	: Use in laboratories; Industrial uses (SU3).; Formulation [mixing] of preparations and/or re-packaging (SU10).
Substance	: xylenes CAS-No.: 1330-20-7

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or ERC4, ERC2 onto article), Formulation of preparations	
Worker		
CS 2	Roller application or brushing	PROC10
CS 3	Use as laboratory reagent	PROC15

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4) / Formulation of preparations (ERC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount used in the EU	: 1000000 kg
Fraction of regional tonnage used locally	: 100000 kg
Emission days	: 300
Technical and organisational conditions and measures	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Conditions and measures related to sewage treatment plant	
STP type	: Onsite sewage treatment plant
STP sludge treatment	: No application of sewage sludge to soil
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

3.2.2. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Use long handled tools.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

Assumes a good basic standard of occupational hygiene is implemented

3.2.3. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4) / Formulation of preparations (ERC2)

Protection Target	Exposure estimate	RCR
Freshwater	0,00217 mg/L	0,066
Marine water	0,000217 mg/L	0,007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Freshwater sediment	0,0233 mg/kg wet weight	0,086
Marine sediment	0,0232 mg/kg wet weight	0,009
Soil	0,266 mg/kg wet weight	0,131
Sewage treatment plant	0,211 mg/L	0,032

3.3.2. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	1,37 mg/kg bw/day	0,01
combined routes				0,86

3.3.3. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	10 ppm	0,56
dermal	systemic	long-term	0,03 mg/kg bw/day	0
combined routes				0,56

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

ES 4: Use in coatings; Professional uses (SU22).

4.1. Title section

Exposure Scenario name	: Use in coatings
Structured Short Title	: Use in coatings; Professional uses (SU22).
Substance	: xylenes <u>CAS-No.:</u> 1330-20-7

Environment		
CS 1	Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems	ERC8a, ERC8d
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Use in closed batch process (synthesis or formulation)	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 8	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Roller application or brushing	PROC10
CS 11	Non-industrial spraying	PROC11
CS 12	Treatment of articles by dipping and pouring	PROC13
CS 13	Chemical production where opportunity for exposure arises	PROC4
CS 14	Use as laboratory reagent	PROC15
CS 15	Manual activities involving hand contact	PROC19

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a) / Wide dispersive outdoor use of processing aids in open systems (ERC8d)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount used in the EU	: 50000000 kg
Fraction of regional tonnage used locally	: 5000000 kg
Emission days	: 300
Technical and organisational conditions and measures	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type	: Onsite sewage treatment plant
STP type	: Municipal Sewage Treatment Plant
STP effluent	: 2.000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

4.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system. Ensure material transfers are under containment or extract ventilation.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle substance within a closed system. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Use drum pumps.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Clear up spills immediately and dispose of waste safely.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

4.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour per day.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Technical and organisational conditions and measures	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour per day.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Transfer via enclosed lines. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Assumes a good basic standard of occupational hygiene is implemented

4.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Transfer via enclosed lines. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Clear spills immediately. Return IBCs or tanks to supplier for re-use.	

4.2.9. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Transfer via enclosed lines. Put lids on containers immediately after use. Clear spills immediately.	

4.2.10. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.11. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Carry out in a vented booth provided with laminar airflow.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.12. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide extract ventilation to points where emissions occur. Avoid carrying out activities involving exposure for more than 1 hour per day.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented Clear up spills immediately and dispose of waste safely. Avoid manual contact with wet work pieces.	

4.2.13. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.14. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Handle in a fume cupboard or under extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.15. Control of worker exposure: Manual activities involving hand contact (PROC19)

Product (article) characteristics	
Covers concentrations up to 5 %	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a) / Wide dispersive outdoor use of processing aids in open systems (ERC8d)

Protection Target	Exposure estimate	RCR
Freshwater	0,00150 mg/L	0,005
Marine water	0,000145 mg/L	< 0,001
Freshwater sediment	0,0160 mg/kg wet weight	0,006
Marine sediment	0,0156 mg/kg wet weight	< 0,001
Soil	0,0117 mg/kg wet weight	0,006
Sewage treatment plant	0,00866 mg/L	0,001

4.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,01 ppm	0
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0

4.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	4 ppm	0,23
dermal	systemic	long-term	0,14 mg/kg bw/day	0
combined routes				0,23

4.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	7,5 ppm	0,42
dermal	systemic	long-term	0,03 mg/kg bw/day	0
combined routes				0,42

4.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	7 ppm	0,39
dermal	systemic	long-term	1,37 mg/kg bw/day	0,01
combined routes				0,40

4.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	6 ppm	0,34
dermal	systemic	long-term	13,71 mg/kg bw/day	0,08
combined routes				0,41

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

4.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	14 ppm	0,79
dermal	systemic	long-term	13,71 mg/kg bw/day	0,08
combined routes				0,87

4.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,88

4.3.9. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	6,86 mg/kg bw/day	0,04
combined routes				0,88

4.3.10. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	3 ppm	0,17
dermal	systemic	long-term	27,43 mg/kg bw/day	0,15
combined routes				0,32

4.3.11. Worker exposure: Non-industrial spraying (PROC11)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5 ppm	0,28
dermal	systemic	long-term	13,71 mg/kg bw/day	0,08
combined routes				0,29

4.3.12. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	12 ppm	0,68
dermal	systemic	long-term	0,69 mg/kg bw/day	0
combined routes				0,68

4.3.13. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	15 ppm	0,85
dermal	systemic	long-term	3,43 mg/kg bw/day	0,02
combined routes				0,87

4.3.14. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	10 ppm	0,56
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0,57

4.3.15. Worker exposure: Manual activities involving hand contact (PROC19)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	6 ppm	0,34
dermal	systemic	long-term	28,29 mg/kg bw/day	0,16
combined routes				0,50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

ES 5: Use in laboratories; Professional uses (SU22).

5.1. Title section

Exposure Scenario name	:	Use in laboratories
Structured Short Title	:	Use in laboratories; Professional uses (SU22).
Substance	:	xlenes <u>CAS-No.:</u> 1330-20-7

Environment		
CS 1	Industrial use of processing aids in processes and products, not becoming part of articles	ERC4
Worker		
CS 2	Roller application or brushing	PROC10
CS 3	Use as laboratory reagent	PROC15

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount used in the EU	: 50000000 kg
Fraction of regional tonnage used locally	: 5000000 kg
Emission days	: 300
Conditions and measures related to sewage treatment plant	
STP type	: Onsite sewage treatment plant
STP sludge treatment	: No application of sewage sludge to soil
STP type	: Municipal Sewage Treatment Plant

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

STP effluent	:	2.000 m3/d
Conditions and measures related to treatment of waste (including article waste)		
Waste treatment	:	External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure		
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100

5.2.2. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics		
Covers concentrations up to 100 %		
Physical form of product	:	Liquid
Vapour pressure	:	0,5 kPa
Temperature	:	20 °C
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	:	Covers daily exposures up to 8 hours
Technical and organisational conditions and measures		
Use long handled tools. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Handle in a fume cupboard or under extract ventilation.		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374.		
Other conditions affecting workers exposure		
Temperature	:	Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		
Assumes a good basic standard of occupational hygiene is implemented		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

5.2.3. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 10 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No specific measures identified. Handle in a fume cupboard or under extract ventilation.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,00150 mg/L	0,005
Marine water	0,000145 mg/L	< 0,000
Freshwater sediment	0,0160 mg/kg wet weight	0,006
Marine sediment	0,00156 mg/kg wet weight	0,001
Soil	0,0112 mg/kg wet weight	0,006

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Sewage treatment plant	0,00866 mg/L	0,001
------------------------	--------------	-------

5.3.2. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	14 ppm	0,78
dermal	systemic	long-term	27,43 mg/kg bw/day	0,15
combined routes				0,93

5.3.3. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	10 ppm	0,56
dermal	systemic	long-term	0,34 mg/kg bw/day	0
combined routes				0,56

5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

ES 6: Use in coatings; Consumer uses (SU21).

6.1. Title section

Exposure Scenario name	:	Use in coatings
Structured Short Title	:	Use in coatings; Consumer uses (SU21).
Substance	:	xlenes <u>CAS-No.:</u> 1330-20-7

Environment		
CS 1	Wide dispersive indoor use of processing aids in open systems, Wide dispersive outdoor use of processing aids in open systems	ERC8a, ERC8d
Consumer		
CS 2	Adhesives, sealants	PC1
CS 3	Coatings and paints, thinners, paint removers	PC9a
CS 4	Fillers, putties, plasters, modelling clay	PC9b
CS 5	Finger paints	PC9c
CS 6	Non-metal surface treatment products	PC15
CS 7	Ink and toners	PC18
CS 8	Leather treatment products	PC23
CS 9	Lubricants, greases, release products	PC24
CS 10	Polishes and wax blends	PC31
CS 11	Textile dyes, finishing and impregnating products; including bleaches and other processing aids	PC34

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a) / Wide dispersive outdoor use of processing aids in open systems (ERC8d)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount used in the EU	: 50000000 kg
Fraction of regional tonnage used locally	: 5000000 kg
Emission days	: 365
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

6.2.2. Control of consumer exposure: Adhesives, sealants (PC1)

Product (article) characteristics	
Covers concentrations up to 30 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount per use	: 0,009 kg
Use frequency	: 365 days/year
Other conditions affecting consumers exposure	
Room size	: 20 m3

6.2.3. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Product (article) characteristics	
Covers concentrations up to 0,5 %	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1

SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026

Print Date: 21.07.2026

Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 2,760 kg
Use frequency	: 4 days/year
Other conditions affecting consumers exposure	
Room size	: 20 m3

6.2.4. Control of consumer exposure: Fillers, putties, plasters, modelling clay (PC9b)

Product (article) characteristics	
Covers concentrations up to 2 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,085 kg
Use frequency	: 12 days/year
Other conditions affecting consumers exposure	
Room size	: 20 m3

6.2.5. Control of consumer exposure: Finger paints (PC9c)

Product (article) characteristics	
Covers concentrations up to 1 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,001 kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Use frequency	: 365 days/year
Other conditions affecting consumers exposure	
Room size	: 20 m3

6.2.6. Control of consumer exposure: Non-metal surface treatment products (PC15)

Product (article) characteristics	
Covers concentrations up to 0,5 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 2,760 kg
Use frequency	: 4 days/year
Other conditions affecting consumers exposure	
Room size	: 20 m3

6.2.7. Control of consumer exposure: Ink and toners (PC18)

Product (article) characteristics	
Covers concentrations up to 10 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,004 kg
Use frequency	: 365 days/year

6.2.8. Control of consumer exposure: Leather treatment products (PC23)

Product (article) characteristics	
--	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Covers concentrations up to 25 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,056 kg
Use frequency	: 29 days/year

6.2.9. Control of consumer exposure: Lubricants, greases, release products (PC24)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 2,200 kg
Use frequency	: 4 days/year
Other conditions affecting consumers exposure	
Room size	: 34 m3

6.2.10. Control of consumer exposure: Polishes and wax blends (PC31)

Product (article) characteristics	
Covers concentrations up to 10 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,142 kg
Use frequency	: 29 days/year

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Other conditions affecting consumers exposure

Room size : 20 m3

6.2.11. Control of consumer exposure: Textile dyes, finishing and impregnating products; including bleaches and other processing aids (PC34)

Product (article) characteristics

Covers concentrations up to 10 %

Physical form of product : Liquid

Vapour pressure : 0,5 kPa

Temperature : 20 °C

Amount used (or contained in articles), frequency and duration of use/exposure

Amount used per event : 0,115 kg

Use frequency : 365 days/year

Other conditions affecting consumers exposure

Room size : 20 m3

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a) / Wide dispersive outdoor use of processing aids in open systems (ERC8d)

Protection Target	Exposure estimate	RCR
Freshwater	0,00150 mg/L	0,005
Marine water	0,000145 mg/L	< 0,000
Freshwater sediment	0,0160 mg/kg wet weight	0,006
Marine sediment	0,00156 mg/kg wet weight	0,001
Soil		0,006
Sewage treatment plant		0,001

6.3.2. Consumer exposure: Adhesives, sealants (PC1)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	1,55 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,59
inhalative	systemic	long-term	5,525 mg/m ³	

6.3.3. Consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	0 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,01
inhalative	systemic	long-term	0,126 mg/m ³	

6.3.4. Consumer exposure: Fillers, putties, plasters, modelling clay (PC9b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	0 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,01
inhalative	systemic	long-term	0,176 mg/m ³	

6.3.5. Consumer exposure: Finger paints (PC9c)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	2,21 mg/kg dry weight	
oral	systemic	long-term	1,35 mg/kg dry weight	
combined routes				0,86
inhalative	systemic	long-term	0 mg/m ³	

6.3.6. Consumer exposure: Non-metal surface treatment products (PC15)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	0 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,01
inhalative	systemic	long-term	0,126 mg/m ³	

6.3.7. Consumer exposure: Ink and toners (PC18)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	1,04 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,70
inhalative	systemic	long-term	10,179 mg/m ³	

6.3.8. Consumer exposure: Leather treatment products (PC23)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	3,26 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,07
inhalative	systemic	long-term	0,607 mg/m ³	

6.3.9. Consumer exposure: Lubricants, greases, release products (PC24)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	0,74 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,01
inhalative	systemic	long-term	0,044 mg/m ³	

6.3.10. Consumer exposure: Polishes and wax blends (PC31)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ANTI-TERRA-U

Version: 8.1
SDB_IS

Revision Date: 15.07.2026

Date of last issue: 22.01.2026
Print Date: 21.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	0,50 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,07
inhalative	systemic	long-term	0,903 mg/m ³	

6.3.11. Consumer exposure: Textile dyes, finishing and impregnating products; including bleaches and other processing aids (PC34)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
dermal	systemic	long-term	0,12 mg/kg dry weight	
oral	systemic	long-term	0 mg/kg dry weight	
combined routes				0,60
inhalative	systemic	long-term	8,797 mg/m ³	

6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Further details on scaling and control technologies are provided in SPERC factsheet.