

BYK-014

VOC-free, silicone-free polymer-based defoamer for aqueous architectural coatings, plasters, adhesives as well as care products and polishes. Optimum performance at the lowest dosage.

Product Data

Composition

Compound of polyether with hydrophobic particles

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 0.97 g/ml

Active substance: 100 %

Storage and Transportation

Separation may occur. Mix well before use.

VOC-free (< 1500 ppm)
Contains no alkylphenol
ethoxylates.

Applications

Coatings Industry

Special Features and Benefits

BYK-014 is especially recommended as a defoamer in the production and application of emulsion paints and plasters within a PVC range of 30-85. The additive is free of silicones and mineral oil, and is especially suitable for VOC-free systems. It exhibits optimum performance at the lowest dosage, is stable to acids and alkalis, and can be used in the pH range 3-12.

Recommended Use

| | |
|------------------------|-------------------------------------|
| Architectural coatings | <input checked="" type="checkbox"/> |
| Coil coatings | <input type="checkbox"/> |
| Leather coatings | <input type="checkbox"/> |

especially recommended recommended

Recommended Levels

0.1-0.5 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive can be added at any time during production. Sufficiently high shear forces must be applied.

Adhesives & Sealants

Special Features and Benefits

BYK-014 is a highly effective defoamer for all current dispersion adhesives and inhibits foaming during production and application. The product is free of silicones and mineral oil, and is especially recommended for VOC-free systems. It exhibits optimum performance at the lowest dosage, is stable to acids and alkalis, and can be used in the pH range 3-12.

Recommended Levels

0.1-0.8 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive can be added at any time during production. Sufficiently high shear forces must be applied.

Care Products and Polishes

Special Features and Benefits

BYK-014 is especially recommended as a defoamer for floor care products with a high wax content. It achieves very good defoaming when applied with a microfiber mop.

Recommended Levels

0.1-0.5 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

It is preferable to add the additive after the binder and water have been premixed, but before the wax emulsions are added. However, it can be used at any stage during manufacture. Due to its very easy incorporation, high shear forces are not necessarily required.



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.