

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYK-141  
Product code : 000000000000101053

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Defoamer

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735  
  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

Europe +44 1235 239670  
Middle East/Africa +44 1235 239671  
Americas +1 215 207 0061  
East/South East Asia +65 3158 1074  
(Local India: 000 800 100 7479)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                                                                                      |                                                        |
|--------------------------------------------------------------------------------------|--------------------------------------------------------|
| Flammable liquids, Category 3                                                        | H226: Flammable liquid and vapour.                     |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.               |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                |
| Aspiration hazard, Category 1                                                        | H304: May be fatal if swallowed and enters airways.    |
| Long-term (chronic) aquatic hazard, Category 2                                       | H411: Toxic to aquatic life with long lasting effects. |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 Avoid release to the environment.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.

#### Hazardous components which must be listed on the label:

- 64742-95-6 Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Solution of foam destroying polymers and polysiloxanes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### Components

| Chemical name                                                                     | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                                                                                                                            | Concentration<br>(% w/w) |
|-----------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | 64742-95-6<br>01-2119455851-35                        | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411<br>EUH066 | >= 50 - <= 100           |
| iso-butanol                                                                       | 78-83-1<br>201-148-0<br>01-2119484609-23              | Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)                   | >= 12,5 - < 20           |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name                                                                   | End Use   | Exposure routes | Potential health effects             | Value     |
|----------------------------------------------------------------------------------|-----------|-----------------|--------------------------------------|-----------|
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified | Workers   | Skin contact    | Long-term exposure, Systemic effects | 25 mg/kg  |
|                                                                                  | Workers   | Inhalation      | Long-term exposure, Systemic effects | 150 mg/m3 |
|                                                                                  | Consumers | Skin contact    | Long-term exposure, Systemic effects | 11 mg/kg  |
|                                                                                  | Consumers | Inhalation      | Long-term exposure, Systemic effects | 32 mg/m3  |
|                                                                                  | Consumers | Ingestion       | Long-term exposure, Systemic effects | 11 mg/kg  |
| iso-butanol                                                                      | Workers   | Inhalation      | Long-term local effects              | 310 mg/m3 |
|                                                                                  | Consumers | Ingestion       | Long-term systemic effects           | 25 mg/kg  |
|                                                                                  | Consumers | Inhalation      | Long-term local effects              | 55 mg/m3  |

##### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value        |
|----------------|---------------------------|--------------|
| iso-butanol    | Fresh water               | 0,4 mg/l     |
|                | Marine water              | 0,04 mg/l    |
|                | Fresh water sediment      | 1,56 mg/kg   |
|                | Marine sediment           | 0,156 mg/kg  |
|                | Soil                      | 0,0765 mg/kg |
|                | Sewage treatment plant    | 10 mg/l      |
|                | Intermittent releases     | 11 mg/l      |

#### 8.2 Exposure controls

##### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection  
Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : 0,4 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an ap-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

proved filter.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|                                                     |                                                                           |
|-----------------------------------------------------|---------------------------------------------------------------------------|
| Physical state                                      | : liquid                                                                  |
| Colour                                              | : colourless                                                              |
| Odour                                               | : aromatic                                                                |
| Odour Threshold                                     | : No data available                                                       |
| Melting point/range                                 | : < 0 °C<br>Method: derived                                               |
| Initial boiling point                               | : 106,00 °C<br>Method: derived                                            |
| Upper explosion limit / Upper<br>flammability limit | : 10,70 %(V)                                                              |
| Lower explosion limit / Lower<br>flammability limit | : 1,00 %(V)                                                               |
| Flash point                                         | : 28,00 °C<br>Method: 48 (Abel-Pensky) DIN 51755                          |
| Auto-ignition temperature                           | : > 200 °C<br>Method: DIN 51794                                           |
| Decomposition temperature                           | : No data available                                                       |
| pH                                                  | : 7 (20 °C)<br>Concentration: 1 %<br>Method: Universal pH-value indicator |
| Viscosity                                           |                                                                           |
| Viscosity, dynamic                                  | : No data available                                                       |
| Viscosity, kinematic                                | : 4 mm <sup>2</sup> /s (40,00 °C)                                         |
| Solubility(ies)                                     |                                                                           |
| Water solubility                                    | : immiscible                                                              |
| Solubility in other solvents                        | : No data available                                                       |
| Partition coefficient: n-<br>octanol/water          | : No data available                                                       |
| Vapour pressure                                     | : 6 hPa (20,00 °C)<br>Method: derived                                     |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

---

|                         |   |                                                                            |
|-------------------------|---|----------------------------------------------------------------------------|
| Relative density        | : | No data available                                                          |
| Density                 | : | 0,8660 g/cm <sup>3</sup> (20,00 °C)<br>Method: 4 (20°C oscillating U-tube) |
| Relative vapour density | : | No data available                                                          |

### 9.2 Other information

|                        |   |                              |
|------------------------|---|------------------------------|
| Flammability (liquids) | : | Sustains combustion          |
| Evaporation rate       | : | No data available            |
| Surface tension        | : | 24,00 mN/m, ring dynamometer |

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

|                     |   |                                                     |
|---------------------|---|-----------------------------------------------------|
| Hazardous reactions | : | No decomposition if stored and applied as directed. |
|                     |   | Vapours may form explosive mixture with air.        |

### 10.4 Conditions to avoid

|                     |   |                          |
|---------------------|---|--------------------------|
| Conditions to avoid | : | Heat, flames and sparks. |
|---------------------|---|--------------------------|

### 10.5 Incompatible materials

|                    |   |                                  |
|--------------------|---|----------------------------------|
| Materials to avoid | : | Acids<br>Strong oxidizing agents |
|--------------------|---|----------------------------------|

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

|                     |   |                                                                  |
|---------------------|---|------------------------------------------------------------------|
| Acute oral toxicity | : | LD50 (Rat): 4.610,00000 mg/kg<br>Method: OECD Test Guideline 401 |
|---------------------|---|------------------------------------------------------------------|

##### Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

Acute oral toxicity : Remarks: No data available  
Acute inhalation toxicity : Remarks: No data available  
Acute dermal toxicity : LD50 (Rabbit, male and female): > 3.160 mg/kg  
Method: OECD Test Guideline 402

### iso-butanol:

Acute oral toxicity : LD50 (Rat, male): > 2.830 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes  
Acute dermal toxicity : LD50 (Rabbit, male): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### Skin corrosion/irritation

#### Product:

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

### iso-butanol:

Species : Rabbit  
Result : Skin irritation

### Serious eye damage/eye irritation

#### Product:

Species : Rabbit  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

Result : No eye irritation  
GLP : yes

### iso-butanol:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Eye irritation  
GLP : yes

### Respiratory or skin sensitisation

#### Product:

Remarks : No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

### iso-butanol:

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

#### Product:

Remarks : No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### STOT - single exposure

#### Product:

Remarks : No data available

### STOT - repeated exposure

#### Product:

Remarks : No data available

### Repeated dose toxicity

#### Product:

Remarks : No data available

### Aspiration toxicity

#### Product:

No data available

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **iso-butanol:**

No aspiration toxicity classification

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish : LL50 (Fish): 9,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata): 2,6 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

##### **iso-butanol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.430 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 1.100 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.799 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 20 mg/l  
End point: Reproduction  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F

##### **iso-butanol:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### **iso-butanol:**

Partition coefficient: n-octanol/water : log Pow: 1  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : UN 1993  
RID : UN 1993  
IMDG : UN 1993  
IATA : UN 1993

#### 14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, N.O.S.  
(Solvent naphtha, Isobutanol)  
RID : FLAMMABLE LIQUID, N.O.S.  
(Solvent naphtha, Isobutanol)  
IMDG : FLAMMABLE LIQUID, N.O.S.  
(SOLVENT NAPHTHA, Isobutanol)  
IATA : Flammable liquid, n.o.s.  
(Solvent naphtha, Isobutanol)

#### 14.3 Transport hazard class(es)

ADR : 3  
RID : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

ADR  
Packing group : III  
Classification Code : F1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0

SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022

Print Date 21.01.2025

Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : D/E

### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : IMDG Code segregation group - none

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your ven-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0  
SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022  
Print Date 21.01.2025

dor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

### 15.2 Chemical safety assessment

Not applicable

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H318 : Causes serious eye damage.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Dam. : Serious eye damage  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-141

Version 7.0

SDB\_REG\_EU

Revision Date: 11.08.2023

Date of last issue: 29.11.2022

Print Date 21.01.2025

laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| STOT SE 3         | H336 |
| STOT SE 3         | H335 |
| Asp. Tox. 1       | H304 |
| Aquatic Chronic 2 | H411 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG\_EU / EN