

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

SECTION 1. IDENTIFICATION

Product name : BYK-151

Manufacturer or supplier's details

Company : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086
Visit our web site : www.byk.com
E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Wetting & Dispersing Additive
Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Solution of an alkylolammonium salt of a polyfunctional polymer with anionic character

Hazardous components

Component	CAS-No.	Concentration (%)
2-Methoxymethylethoxypropanol [DPM]	34590-94-8	>= 5 - < 10

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.
If inhaled : If unconscious, place in recovery position and seek medical advice.

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

In case of skin contact	: If symptoms persist, call a physician. Remove contaminated clothing. Wash thoroughly with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO ₂) Dry chemical Foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet High volume water jet
Specific hazards during firefighting	: Water solution - will not support combustion. Will not explode on mechanical impact.
Hazardous combustion products	: Carbon oxides Sulphur oxides Nitrogen oxides (NO _x)
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Wear protective equipment: goggles, chemically resistant clothing and gloves, and appropriate respirator if in a confined area.
Environmental precautions	: Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.
Methods and materials for containment and cleaning up	: Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Methoxymethylethoxypropanol [DPM]	34590-94-8	TWA	100 ppm 600 mg/m ³	OSHA Z-1
2-Methoxymethylethoxypropanol [DPM]		TWA	50 ppm	ACGIH

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection
Material : Nitrile rubber

Remarks : Wear suitable gloves.
Eye protection : Safety glasses
Skin and body protection : Protective suit
Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
Colour : light yellow
Odour : not significant
Odour Threshold : No data available
- pH : 9.7, Concentration: 100 % (68 °F (20 °C)) Method: DIN 19268 (100%ig)
- Melting point/ range : < 32 °F (< 0 °C)

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

	Method: derived
Initial boiling point	: 212 °F (100 °C) Method: derived
Vapour pressure	: 24.0000000 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: > 212.00 °F (> 100.00 °C) Method: 49 (Pensky-Martens)
Upper explosion limit	: 8.70 %(V)
Lower explosion limit	: 1.30 %(V)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.09 g/cm3 (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: DPM may form peroxides of unknown stability.

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Stable under recommended storage conditions.
No hazards to be specially mentioned.

Conditions to avoid	: No data available
Incompatible materials	: Acids Strong oxidizing agents Alkalis
Hazardous decomposition products	: None expected

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

Components:**34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

Acute oral toxicity : LD50 (Rat): 5,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 50 mg/l

Acute dermal toxicity : LD50 (Rabbit): 9,500 mg/kg

Skin corrosion/irritation**Product:**

Remarks: No data available

Components:**34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

Species: Rabbit
Result: slight irritation

Serious eye damage/eye irritation**Product:**

Remarks: No data available

Components:

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

34590-94-8 2-Methoxymethylethoxypropanol [DPM]:

Species: Rabbit

Result: Mild eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

Result: Does not cause skin sensitisation.

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Repeated dose toxicity**Product:**

Remarks: No known chronic health effects.

Aspiration toxicity**Components:****34590-94-8 2-Methoxymethylethoxypropanol [DPM]:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact may cause irritation.

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Eye contact:

Symptoms:

Contact may cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract; high dosages may cause CNS depression.

Further information**Product:**

Remarks: Skin absorption of 10-20 ml/kg of DPM has caused CNS depression (in rabbits).
ACGIH-TLV-TWA for DPM = 100 ppm (skin)

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish

:

Remarks: No data available

Persistence and degradability**Product:**

Biodegradability

:

Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation

:

Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological
information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste
Code(s) : Not applicable.

Waste from residues : Dispose of in accordance with applicable local/municipal,
state/provincial and federal regulations.

Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III
Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 38 - 42 %
Method: 22 (10min/150°C)
DIN EN ISO 3251
Non-volatile information is not a specification.

Massachusetts Right To Know

2-Methoxymethylethoxypropanol [DPM] 34590-94-8

Pennsylvania Right To Know

Water 7732-18-5
Alkylolammonium salt polymer -
2-Methoxymethylethoxypropanol [DPM] 34590-94-8
Sodium linear alkylbenzene sulfonate -

New Jersey Right To Know

New Jersey Trade Secret : 800963-5352
Registry Number for the product (NJ TSRN)

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Propylene oxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

BYK-151

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: The following component(s) is/are not listed on the DSL:
CEPA Category	: Polymer
Weight percent	: 37 %
NSN Filed	: None
Max. NSN Required	: Schedule 10

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.