

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

SECTION 1. IDENTIFICATION

Product name : BYK-2616

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Additive to Eliminate Moisture

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin irritation : Category 2

Serious eye damage : Category 1

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ eye protection/ face protection.
P271 Use only outdoors or in a well-ventilated area.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

attention.

P362 Take off contaminated clothing and wash before reuse.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Storage:

P402 + P404 Store in a dry place. Store in a closed container.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

P501 Dispose of contents/ container to an approved incineration plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Combination of a specially prepared finely dispersed calcium oxide and a stabilizing wetting agent

Hazardous components

Component	CAS-No.	Concentration (%)
Calcium oxide	1305-78-8	>= 73 - < 74
Silica, amorphous	7631-86-9	>= 1 - < 2
Acidic ester	162627-31-8	>= 1 - < 2

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Consult a physician.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Remove to fresh air. Administer artificial respiration if necessary. Get medical aid as soon as possible.

In case of skin contact : Remove contaminated clothing. Wash thoroughly with soap

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

- and water.
- In case of eye contact : Immediately flush with plenty of water for at least 30 minutes. Get medical aid.
- If swallowed : Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : No information available.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Do NOT use water jet.
Reacts violently with water.
- Specific hazards during firefighting : Handle as an industrial chemical.
Will not explode on mechanical impact.
The product reacts with water and generates heat.
- Hazardous combustion products : Carbon oxides
silicone compounds
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.
- Methods and materials for containment and cleaning up : Stop leak. Dike and contain spill.
Pump into salvage tanks and/or absorb with suitable material.
Use sparkless shovels to remove material.
DO NOT USE WATER TO FLUSH SPILL OR SUPPRESS VAPORS.
Neutralise with acid.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep only in the original container in a cool, well ventilated place away from water.
Keep container closed when not in use.
Keep product and empty container away from heat and sources of ignition.
- Materials to avoid : DO NOT allow product to come in direct contact with water.
Never allow product to get in contact with water during storage.
Avoid contact with incompatible materials.
Keep away from isocyanates.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium oxide	1305-78-8	TWA	2 mg/m ³	ACGIH
Calcium oxide		TWA	5 mg/m ³	OSHA Z-1
Calcium oxide		TWA	5 mg/m ³	OSHA P0
Silica, amorphous	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
Silica, amorphous		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3

Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

Hand protection	(NIOSH approved) or dust mask during exposure.
Material	: Nitrile rubber
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: Clean long legged, long sleeved work clothes. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: light grey
Odour	: not significant
Odour Threshold	: No data available

pH : 12.1, Concentration: 1 % (68 °F (20 °C)) Method: DIN 19268

Melting point/range	: No data available
Initial boiling point	: No data available
Vapour pressure	: < 1.0000000 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 323.60 °F (162.00 °C) Method: 49 (Pensky-Martens)
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.9400 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

Bulk density	:	Not applicable
Solubility(ies)	:	
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 662.00 °F (> 350.00 °C) Method: calculated
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Reacts violently with water. Not classified as a reactivity hazard. No decomposition if stored and applied as directed.
Chemical stability	:	Stable; polymerization will not occur No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Product produces a violent reaction when in direct contact with water. Exothermic reaction with acids.
Conditions to avoid	:	Exposure to water vapour. Exposure to moisture
Incompatible materials	:	Water Strong oxidizing agents Acids Aluminium Copper alloys
Hazardous decomposition products	:	Hydrogen, by reaction with metals

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**7631-86-9 Silica, amorphous:**

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 58.8 mg/l
Exposure time: 4 h
Method: OECD Test Guideline 403
GLP: yes

162627-31-8 Acidic ester:

Acute oral toxicity : LD50 (Rat, male and female): > 4,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Skin corrosion/irritation

Causes skin irritation.

Product:

Species: **EPISKIN human epidermis skin constructs**
Exposure time: **> 4 h**
Assessment: **Irritating to skin.**
Method: **OECD Test Guideline 435**
Result: **Skin irritation**
Remarks: **Irritating to skin.**

Components:**7631-86-9 Silica, amorphous:**

Species: Rabbit
Result: No skin irritation

162627-31-8 Acidic ester:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

Serious eye damage/eye irritation**Product:**

Remarks: Causes serious eye damage.

Components:

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

7631-86-9 Silica, amorphous:

Species: Rabbit

Result: No eye irritation

162627-31-8 Acidic ester:

Species: Rabbit

Result: Eye irritation

Assessment: Irritating to eyes.

Method: OECD Test Guideline 405

GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**162627-31-8 Acidic ester:**

Remarks: No data available

Carcinogenicity

IARC	Group 1: Carcinogenic to humans	
	Silica, amorphous	7631-86-9
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	Known to be human carcinogen	
	Silica, amorphous	7631-86-9

Repeated dose toxicity**Product:**

Remarks: Chronic skin contact with calcium oxide has caused dermatitis.

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors resulting from the product being heated, misted or sprayed may cause irritation of the respiratory tract and mucous membranes.

Skin contact:

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

Eye contact:	Symptoms:	Contact will probably cause severe irritation.
	Symptoms:	Contact will probably cause severe irritation and corrosion.
Ingestion:	Symptoms:	Ingestion will probably cause irritation of the digestive tract.

Further information
Product:

Remarks: Based on toxicological data for a similar product, BYK-2616 is not considered corrosive to the skin.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Toxicity to fish : Remarks: No data available

Persistence and degradability
Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential
Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects
Product:

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Regulation 40 CFR Protection of Environment; Part 82 Protection of

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

Remarks

Stratospheric Ozone - CAA Section 602 Class I Substances

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : D003: Reactive

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 95 - 100 %
 Method: 22 (10min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

Massachusetts Right To Know

Calcium oxide	1305-78-8
Aliphatic ester	-
Silica, amorphous	7631-86-9

Pennsylvania Right To Know

Calcium oxide	1305-78-8
Aliphatic ester	-
Silica, amorphous	7631-86-9

New Jersey Right To Know

Calcium oxide	1305-78-8
Aliphatic ester	-
Silica, amorphous	7631-86-9
Acidic ester	162627-31-8

BYK-2616

Version 8

Revision Date 09/18/2020

Print Date 01/06/2026

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5405

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Silica, amorphous, Propylene oxide, 1,4-Dioxane, Ethylene oxide, which is/are known to the State of California to cause cancer, and Ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONEG Heavy Metal: We confirm that we use packaging and/or packaging components in which the sum of the incidental concentration levels of lead, mercury, cadmium and hexavalent chromium do not exceed 100 parts per million by weight.

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

Section 5 : Not applicable

TSCA Inventory Active List : All components of this product are listed active and/or are exempt

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 09/18/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.