

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

SECTION 1. IDENTIFICATION

Product name : BYK-306 SG

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Surface Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 2 (hearing organs, Kidney, Liver)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

- Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (hearing organs, Kidney, Liver) through prolonged or repeated exposure.
- Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Solution of a polyether modified polydimethylsiloxane
Hazardous components

Component	CAS-No.	Concentration (%)
Xylene	1330-20-7	>= 30 - < 60
2-Phenoxyethanol	122-99-6	>= 20 - < 30
Ethyl benzene	100-41-4	>= 10 - < 20
Polyether	-	>= 1 - < 5
Cumene	98-82-8	>= 0.1 - < 1
Toluene	108-88-3	>= 0.1 - < 1
Octamethylcyclotetrasiloxane	556-67-2	>= 0.1 - < 1

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Consult a physician.
 Show this safety data sheet to the doctor in attendance.
 Symptoms of poisoning may appear several hours later.
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 Continue rinsing eyes during transport to hospital.

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

If swallowed

- Remove contact lenses.
- Protect unharmed eye.
- Keep eye wide open while rinsing.
- If eye irritation persists, consult a specialist.
- : Keep respiratory tract clear.
- Do NOT induce vomiting.
- Do not give milk or alcoholic beverages.
- Never give anything by mouth to an unconscious person.
- If symptoms persist, call a physician.
- Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.
Will not explode on mechanical impact.

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
silicone compounds
formaldehyde

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
Xylene		STEL	150 ppm 655 mg/m ³	OSHA P0
Xylene		TWA	100 ppm 435 mg/m ³	OSHA P0
Xylene		TWA	20 ppm	ACGIH
Ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA Z-1
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA P0
Ethyl benzene		STEL	125 ppm	OSHA P0

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

			545 mg/m ³	
Ethyl benzene		ST	125 ppm 545 mg/m ³	NIOSH REL
Cumene	98-82-8	TWA	5 ppm	ACGIH
Cumene		TWA	50 ppm 245 mg/m ³	OSHA Z-1
Cumene		TWA	50 ppm 245 mg/m ³	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
Toluene		TWA	200 ppm	OSHA Z-2
Toluene		CEIL	300 ppm	OSHA Z-2
Toluene		Peak	500 ppm	OSHA Z-2
Toluene		TWA	100 ppm 375 mg/m ³	OSHA P0
Toluene		STEL	150 ppm 560 mg/m ³	OSHA P0
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL

Hazardous components without workplace control parameters

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : light yellow
- Odour : aromatic
- Odour Threshold : No data available
- pH : 5, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
- Melting point/ range : < 32 °F (< 0 °C)
Method: derived

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

Initial boiling point	: 278.60 °F (137.00 °C) Method: derived
Vapour pressure	: 8 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 77.00 °F (25.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: 7.00 %(V)
Lower explosion limit	: 1.20 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.9280 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51 794/ DIN prEN 14 522
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 2 mm ² /s (104 °F (40 °C))
Surface tension	: No data available

SECTION 10. STABILITY AND REACTIVITY

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Ingestion
Eye contact
Skin contact

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : 3,498 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 16.75 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 2,746 mg/kg
Method: Calculation method

Components:**1330-20-7 Xylene:**

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: no

Acute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg
LD50 (Rabbit): > 4,200 mg/kg
GLP: No information available.

122-99-6 2-Phenoxyethanol:

Acute oral toxicity : LD50 (Rat): 1,840 mg/kg
Method: OECD Test Guideline 401

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

GLP: no

Acute dermal toxicity : LD50 (Rabbit): 3,818 mg/kg

100-41-4 Ethyl benzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

- Polyether:Acute oral toxicity : LD50 (Rat): 1,502 mg/kg
Method: OECD Test Guideline 401**98-82-8 Cumene:**

Acute oral toxicity : LD50 (Rat): 1,400 mg/kg

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 : Remarks: No data available

108-88-3 Toluene:

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Components:**1330-20-7 Xylene:**

Species: Rabbit

Result: Moderate skin irritation

122-99-6 2-Phenoxyethanol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

100-41-4 Ethyl benzene:

Species: Rabbit

Result: Moderate skin irritation

- Polyether:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: slight irritation

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**1330-20-7 Xylene:**

Species: Rabbit

Result: Eye irritation

122-99-6 2-Phenoxyethanol:

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

100-41-4 Ethyl benzene:

Species: Rabbit

Result: Moderate eye irritation

- Polyether:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: Mild eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**122-99-6 2-Phenoxyethanol:**

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

556-67-2 Octamethylcyclotetrasiloxane:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

GLP: yes

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

Group 2B: Possibly carcinogenic to humans

Ethyl benzene 100-41-4

Cumene 98-82-8

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Reasonably anticipated to be a human carcinogen

Cumene 98-82-8

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:**122-99-6 2-Phenoxyethanol:**

Effects on foetal development : Species: Rat
Application Route: Oral
Duration of Single Treatment: 14 d
General Toxicity Maternal: No observed adverse effect level:
300 mg/kg body weight
Teratogenicity: No observed adverse effect level: 1,000 mg/kg
body weight
Method: OECD Test Guideline 414

Species: Rabbit
Application Route: Dermal
Duration of Single Treatment: 14 d
General Toxicity Maternal: No observed adverse effect level:
300 mg/kg body weight
Teratogenicity: No observed adverse effect level: 600 mg/kg

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

body weight

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver, kidney, brain, respiratory system, blood, and/or bone marrow in laboratory animals

Animal studies have shown Xylene to cause fetotoxic effects at dosage levels at or near maternal toxicity levels.

Excessive inhalation of Xylene has caused hearing loss in laboratory animals. Hexane used in conjunction w/Xylene greatly increased this effect. Chronic skin contact w/Xylene has caused dermatitis. Ingestion of Ethanol can increase effects of overexposure to Xylene.

Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).

Inhalation (300 ppm)/ingestion (1600 mg/kg) dosages of Octamethylcyclotetrasiloxane has caused liver weight increases in laboratory animals. Liver weight changes via inhalation were reversible. A reproductive study (rats, inhalation: 700 ppm/70 days) showed a statistically significant reduction in mean litter size and implantation sites. The relevance of this data to humans is uncertain.

Remarks: No data available

Components:**122-99-6 2-Phenoxyethanol:**

Species: Rat

NOAEL: 700 mg/kg

Application Route: Oral

Method: OECD Test Guideline 408

Species: Rat

NOAEL: 0.0482 mg/l

Application Route: Inhalation

Method: OECD Test Guideline 412

Target Organs: Respiratory organs

Aspiration toxicity**Product:**

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

No data available

Experience with human exposure
Product:

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.

Further information
Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Toxicity to fish

:

Remarks: No data available

Toxicity to daphnia and other
aquatic invertebrates

:

Remarks: No data available

Persistence and degradability
Product:

Biodegradability

:

Remarks: No data available

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

Bioaccumulative potential
Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

 EPA Hazardous Waste Code(s) : D001: Ignitable
D018: Benzene

 Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

 Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA-DGR

 UN/ID No. : UN 1993
 Proper shipping name : Flammable liquid, n.o.s.
(Xylene, Ethylbenzene)
 Class : 3
 Packing group : III
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 366

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

Packing instruction : 355
(passenger aircraft)

IMDG-Code

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (XYLENE, Ethylbenzene)
 :)
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no
 Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

UN/ID/NA number : UN 1993
 Proper shipping name : Flammable liquids, n.o.s.
 (Xylene, Ethylbenzene)
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 128
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	189

SARA 304 - Emergency Release Notification

Calculated RQ exceeds reasonably attainable upper limit.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026

and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene	1330-20-7	53.0 %
2-Phenoxyethanol	122-99-6	20 %
Ethyl benzene	100-41-4	12.6 %
Cumene	98-82-8	.6 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	53.0 %
2-Phenoxyethanol	122-99-6	20 %
Ethyl benzene	100-41-4	12.6 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	53.0 %
2-Phenoxyethanol	122-99-6	20 %
Ethyl benzene	100-41-4	12.6 %

Non-volatile (Wt) : 11.5 - 13.5 %
 Method: 24 (30min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

US State Regulations
Massachusetts Right To Know

Xylene	1330-20-7
Ethyl benzene	100-41-4
Benzene	71-43-2
Hydrogen Chloride	7647-01-0

BYK-306 SG

Version 1

Revision Date 03/18/2026

Print Date 05/14/2026


Pennsylvania Right To Know

Xylene	1330-20-7
2-Phenoxyethanol	122-99-6
Ethyl benzene	100-41-4
Polyether modified polydimethylsiloxane	-
Cumene	98-82-8
Toluene	108-88-3

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-6462

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 03/18/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.