

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

SECTION 1: Identification of the hazardous chemical and of the supplier**Product identifier**

Product name : BYK-310 SG

Recommended use : Surface Additive

Manufacturer or supplier's details

Company : BYK USA LLC

Address : South Cherry Street 524
06492 Wallingford

Telephone : +1 203-265-2086

Telefax :

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone number : +60 3 6207 4347 (Malay and English)
+65 3158 1074 (All languages)**SECTION 2: Hazards identification****Classification of the hazardous chemical**

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye
irritation : Category 2Specific target organ toxicity -
single exposure : Category 3 (Respiratory system)Specific target organ toxicity -
repeated exposure : Category 2

Aspiration hazard : Category 1

Hazardous to the aquatic
environment - chronic hazard : Category 3**Label elements**

Hazard pictograms :



Signal word : Danger

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

- Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 + H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
- Response:**
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

- Substance / Mixture : Mixture
Chemical nature : Solution of a polyester modified polydimethylsiloxane

Components

Chemical name	CAS-No.	Concentration (% w/w)
Xylene, mixture of isomers	1330-20-7	>= 50 -<= 100
ethylbenzene	100-41-4	>= 12.5 -< 20
toluene	108-88-3	>= 0.25 -< 0.5

SECTION 4: First aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

If swallowed	:	Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
		Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	No information available.
Notes to physician	:	No information available.

SECTION 5: Firefighting measures**Extinguishing media**

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	High volume water jet

Physicochemical hazards arising from the chemical

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling****Precautions for safe handling**

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Storage**Conditions for safe storage, including any incompatibilities**

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection**Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	TWA	100 ppm 434 mg/m3	MY PEL
		TWA	20 ppm	ACGIH

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m ³	MY PEL
		TWA	20 ppm	ACGIH
toluene	108-88-3	TWA	50 ppm 188 mg/m ³	MY PEL
	Further information: Skin			
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hand protection

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

Material : Fluorinated rubber
Break through time : ≥ 480 min
Glove thickness : 0.4 mm

Remarks : Wear suitable gloves.
Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : aromatic

Odour Threshold : No data available

pH : 7 (20 °C)
Concentration: 1 %
Method: Universal pH-value indicator

Melting point/ range : < 0 °C
Method: derived

Initial boiling point : 137.00 °C
Method: derived

Flash point : 25.00 °C
Method: 48 (Abel-Pensky) DIN 51755

Evaporation rate : No data available

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : 7.00 %(V)

Lower explosion limit / Lower flammability limit : 1.00 %(V)

Vapour pressure : 8 hPa (20 °C)
Method: derived

Relative vapour density : No data available

Relative density : No data available

Density : 0.9050 g/cm³ (20.00 °C)
Method: 4 (20°C oscillating U-tube)

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: > 200 °C Method: DIN 51 794/ DIN prEN 14 522
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: ca. 2 mm ² /s (40.00 °C)

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity**Product:**

Acute oral toxicity	: Remarks: No data available
Acute inhalation toxicity	: Acute toxicity estimate: 15.01 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: 1,860 mg/kg Method: Calculation method

Components:**Xylene, mixture of isomers:**

Acute oral toxicity	: LD50 (Rat): 4,300 mg/kg Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral) GLP: no
Acute dermal toxicity	: LD50 (Rabbit): > 4,200 mg/kg

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

GLP: No information available.

Skin corrosion/irritation**Product:**

Remarks : May irritate skin.
May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product:**

Remarks : Causes serious eye irritation.

Respiratory or skin sensitisation**Product:**

Remarks : No data available

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks : No data available

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks : No data available

STOT - repeated exposure**Product:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

Aspiration toxicity**Product:**

No data available

Further information**Product:**

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity****Product:**Toxicity to fish :
Remarks: No data availableToxicity to daphnia and other :
aquatic invertebrates Remarks: No data available**Components:****Xylene, mixture of isomers:**Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1 mg/l
aquatic invertebrates Exposure time: 24 h
Test Type: Immobilization
Method: OECD Test Guideline 202Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 2.2 mg/l
plants Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yesNOEC (Pseudokirchneriella subcapitata (green algae)): 0.44
mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201Toxicity to fish (Chronic : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
toxicity) Exposure time: 56 dToxicity to daphnia and other : NOEC (Daphnia sp. (water flea)): 1.17 mg/l
aquatic invertebrates Exposure time: 7 d
(Chronic toxicity)NOEC (Daphnia sp. (water flea)): 0.96 mg/l
Exposure time: 7 d**Persistence and degradability****Product:**

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

Biodegradability : Remarks: No data available

Components:**Xylene, mixture of isomers:**

Biodegradability : aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**Xylene, mixture of isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 25.9
Exposure time: 56 d
GLP: no

Partition coefficient: n-
octanol/water : Pow: 3.2 (20 °C)
pH: 7

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological
information : An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal information**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

SECTION 14: Transport information**International Regulations****IATA-DGR**

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Xylene, Ethylbenzene)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Ethylbenzene)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information**Safety, health, and environmental regulations specific for the hazardous chemical**

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health)

BYK-310 SG

Product code: 000000000000113557

Version 3.0 SDS_APJ_MY

Revision Date 22.01.2026

Print Date 28.01.2026

Regulations 2000.

ACGIH / TWA : 8-hour, time-weighted average
MY PEL / TWA : Eight-hour time-weighted average airborne concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN