

# BYK-349

Silicone surfactant for aqueous coatings, adhesives and maintenance products with a considerable reduction in the surface tension and therefore good substrate wetting. Does not increase the surface slip. Suitable for systems that do not contain co-solvents. All-purpose.

## Product Data

### Composition

Polyether-modified siloxane

### Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Active substance: 100 %

Density (20 °C): 1.04 g/ml

### Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit [www.byk.com](http://www.byk.com) for further information.

### Special Note

The additive is also suitable for systems that do not contain organic co-solvents. If the system contains increased quantities of co-solvents, the silicone surfactant will not be as effective. In such formulations, we recommend the use of a polysiloxane, e.g. BYK-333.

## Applications

### Coatings Industry

#### Special Features and Benefits

The additive produces a significant decrease in the surface tension in aqueous coatings and therefore particularly improves substrate wetting and leveling. It only marginally, if at all, stabilizes foam and the recoatability is not impaired. The additive does not increase the surface slip. If a greater surface slip is required, we recommend that it is combined with a polysiloxane such as BYK-333.

**Recommended Use**

Automotive coatings	<input checked="" type="checkbox"/>
Architectural coatings	<input checked="" type="checkbox"/>
Wood and furniture coatings	<input checked="" type="checkbox"/>
Industrial coatings	<input checked="" type="checkbox"/>
Can coatings	<input checked="" type="checkbox"/>
Coil coatings	<input checked="" type="checkbox"/>
Protective systems	<input checked="" type="checkbox"/>
Leather finishes	<input type="checkbox"/>

Particularly recommended     Recommended

The additive is especially recommended for all aqueous coatings that do not contain co-solvents, particularly those based on styrene-acrylic, pure acrylate, acrylate/polyurethane combinations, polyurethanes, and also for baking systems.

**Recommended Levels**

0.05-0.5 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. Optimal dosage levels are determined through a series of laboratory tests.

**Incorporation and Processing Instructions**

It is preferable to add the additive to the finished coating. However, it can be used at any stage during the coating manufacture.

**Adhesives & Sealants**

**Special Features and Benefits**

BYK-349 is a highly effective silicone surfactant. The additive causes a considerable reduction in the surface tension in aqueous adhesive systems. It thereby improves the wetting of critical substrates.

**Recommended Levels**

0.05-0.5 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. Optimal dosage levels are determined through a series of laboratory tests.

**Incorporation and Processing Instructions**

It is preferable to add the additive to the finished formulation. However, it can be used at any stage during manufacture.

## Care Products and Polishes

### Special Features and Benefits

BYK-349 is a highly effective silicone surfactant with a considerable reduction in the surface tension to improve the substrate wetting and leveling in aqueous maintenance products. It only marginally, if at all, stabilizes the foam, does not impair the subsequent layer and does not increase the surface slip.

### Recommended Use

The additive is particularly recommended for plasticizer-free floor care products and wax cleaning agents.

### Recommended Levels

0.05-0.5 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. Optimal dosage levels are determined through a series of laboratory tests.

### Incorporation and Processing Instructions

It is preferable to add the additive to the already completed formulation. However, it can be used at any stage during the coating manufacture.



Additive Guide



**BYK-Chemie GmbH**  
Postfach 10 02 45  
46462 Wesel  
Deutschland  
Tel +49 281 670-0  
Fax +49 281 65735

**info@byk.com**  
**www.byk.com**

ACTAL®, ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PAPERBYK®, PERMONT®, PRIEX®, PURE THIX®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® und Y 25® **sind eingetragene Warenzeichen der BYK Gruppe.**

Die vorstehenden Angaben entsprechen unserem derzeitigen Kenntnisstand. Sie beschreiben abschließend die Beschaffenheit unserer Produkte, stellen jedoch keine Garantie im Rechtssinne dar. Vor der Verwendung unserer Produkte obliegt es dem Verwender, die Qualität und Eignung unserer Produkte für die von ihm geplante Verarbeitung und Anwendung zu prüfen. Dies gilt auch für eine etwaige Verletzung von Schutzrechten Dritter. Wir behalten uns Änderungen der vorstehenden Angaben aufgrund des technischen Fortschritts und betrieblicher Weiterentwicklungen vor.

Diese Ausgabe ersetzt alle bisherigen Versionen – Gedruckt in Deutschland