

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYK-3550

UFI : D265-U0J7-F008-07GP

Product code : 000000000000145735

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Leveling Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel

Telephone : +49 281 670-0

Telefax : +49 281 65735

Information : Regulatory Affairs

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous components which must be listed on the label:

- 108-65-6 2-methoxy-1-methylethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : solution of a silicone-macromer-modified polyacrylate

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-methoxy-1-methylethyl acetate	108-65-6	STOT SE 3; H336	>= 30 - < 50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

	203-603-9 01-2119475791-29	Flam. Liq. 3; H226	
--	-------------------------------	--------------------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	CH SUVA
	Further information: Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	50 ppm 275 mg/m ³	CH SUVA

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Further information: Harm to the unborn child is not to be expected when the OEL-value is respected

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
2-methoxy-1-methylethyl acetate	Workers	Skin contact	Long-term systemic effects	796 mg/kg
	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Acute local effects	33 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent releases	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg
	Marine sediment	0,329 mg/kg
	Soil	0,29 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection
Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0,7 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available
Melting point/ range	:	< 0 °C Method: derived
Initial boiling point	:	146 °C Method: derived
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	45 °C Method: 48 (Abel-Pensky) DIN 51755
Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	7 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity		
Viscosity, dynamic	:	80 mPa.s (20 °C) Method: 11 (NV, 20°C)
Viscosity, kinematic	:	No data available
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

octanol/water

Vapour pressure	:	355 Pa (20 °C) Method: derived
Relative density	:	No data available
Density	:	1,006 g/cm ³ (20 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube)
Relative vapour density	:	No data available

9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No decomposition if stored and applied as directed.
		Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

10.5 Incompatible materials

Materials to avoid	:	Strong oxidizing agents
--------------------	---	-------------------------

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity	:	Remarks: No data available
---------------------	---	----------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Components:

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:

2-methoxy-1-methylethyl acetate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

STOT - repeated exposure

Not classified due to lack of data.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

Aspiration toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Product:

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Components:

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)
octanol/water pH: 6,8
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological : No data available
information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3272
ADR : UN 3272
RID : UN 3272
IMDG : UN 3272
IATA : UN 3272

14.2 UN proper shipping name

ADN : ESTERS, N.O.S.
(1-Methoxy-2-propanol acetate)
ADR : ESTERS, N.O.S.
(1-Methoxy-2-propanol acetate)
RID : ESTERS, N.O.S.
(1-Methoxy-2-propanol acetate)
IMDG : ESTERS, N.O.S.
(1-Methoxy-2-propanol acetate)
IATA : Esters, n.o.s.
(1-Methoxy-2-propanol acetate)

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-D
Remarks : IMDG Code segregation group - none

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355
(passenger aircraft)
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries must be considered:: Number on list 3
		Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Fire Hazard Class	:	A II: Flash point 21 °C to 55 °C, at 15 °C not miscible in water
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FLAMMABLE LIQUIDS
Volatile organic compounds	:	Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC) Volatile organic compounds (VOC) content: 47,5 %

15.2 Chemical safety assessment

For further information see eSDS.

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Full text of H-Statements

H226 : Flammable liquid and vapour.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Flam. Liq. : Flammable liquids
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
CH SUVA : Switzerland. Limit values at the work place
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
CH SUVA / TWA : Time Weighted Average
CH SUVA / STEL : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3 H226

Classification procedure:

Based on product data or assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

STOT SE 3

H336

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Annex: Exposure Scenarios

Table of Contents

Number	Title
ES 1	Processing aid; Industrial uses (SU3).
ES 2	Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).
ES 3	Use in coatings; Industrial uses (SU3).
ES 4	Use in coatings; Professional uses (SU22).
ES 5	Cleaning; Industrial uses (SU3).
ES 6	Cleaning; Professional uses (SU22).
ES 7	Use in coatings; Consumer uses (SU21).
ES 8	Cleaning; Consumer uses (SU21).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 1: Processing aid; Industrial uses (SU3).

1.1. Title section

Exposure Scenario name	: Processing aid
Structured Short Title	: Processing aid; Industrial uses (SU3).

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or ERC4 onto article)	
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 7	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 8	Use as laboratory reagent	PROC15

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 2200 kg
Release type	: Continuous release

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Emission days	: 300
Technical and organisational conditions and measures	
Treat air emissions. Air - minimum efficiency of 87,3 %	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Dispose of waste product or used containers according to local regulations. Hazardous waste incineration
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases. Vapour recovery (e.g. adsorption) When not in use, keep containers tightly closed.	

1.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

1.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Clear transfer lines prior to de-coupling.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

1.2.8. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Release route	Release rate	Release estimation method
Soil		ESVOC SPERC 4.20.v1
Water		ESVOC SPERC 4.20.v1
Air		ESVOC SPERC 4.20.v1

Protection Target	Exposure estimate	RCR
-------------------	-------------------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Freshwater	0,0022 mg/L	0,004
Freshwater sediment	0,0114 mg/kg dry weight	0,004
Marine water	0,0004 mg/L	0,006
Marine sediment	0,0020 mg/kg dry weight	0,006
Soil	0,00127 mg/kg dry weight	0,005

1.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,06 mg/m ³ (ECETOC TRA worker v2.0)	
dermal	systemic	long-term	0,34 mg/kg bw/day	

1.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5,51 mg/m ³ (ECETOC TRA worker v2.0)	0,02
dermal	systemic	long-term	1,37 mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes				0,03

1.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	16,53 mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

combined routes				0,06
-----------------	--	--	--	------

1.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

1.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

1.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

1.3.8. Worker exposure: Use as laboratory reagent (PROC15)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,06 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,10

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 2: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).

2.1. Title section

Exposure Scenario name	: Formulation & (re)packing of substances and mixtures
Structured Short Title	: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).

Environment		
CS 1	Formulation into mixture	ERC2
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 8	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Tabletting, compression, extrusion, pelettisation, granulation	PROC14
CS 11	Use as laboratory reagent	PROC15

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Formulation into mixture (ERC2)

Product (article) characteristics	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 234666 kg
Release type	: Continuous release
Emission days	: 225
Conditions and measures related to sewage treatment plant	
STP type	: Onsite sewage treatment plant
STP type	: Municipal Sewage Treatment Plant
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Dispose of waste product or used containers according to local regulations. Hazardous waste incineration
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases. Vapour recovery (e.g. adsorption) When not in use, keep containers tightly closed. Prevent leaks and prevent soil / water pollution caused by leaks.	

2.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Assumes a good basic standard of occupational hygiene is implemented

2.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.9. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

2.2.10. Control of worker exposure: Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

2.2.11. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Formulation into mixture (ERC2)

Release route	Release rate	Release estimation method
Soil		CEPE SPERC 2.1b.v1
Water		CEPE SPERC 2.1b.v1
Air		CEPE SPERC 2.1b.v1

Protection Target	Exposure estimate	RCR
Freshwater	0,0022 mg/L	0,004
Freshwater sediment	0,011 mg/kg dry weight	0,004
Marine water	0,0004 mg/L	0,006
Marine sediment	0,00202 mg/kg dry weight	0,006
Soil	0,00127 mg/kg dry weight	0,010

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

2.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,06 mg/m ³ (ECETOC TRA worker v2.0)	
dermal	systemic	long-term	0,34 mg/kg bw/day	

2.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5,51 mg/m ³ (ECETOC TRA worker v2.0)	0,02
dermal	systemic	long-term	1,37 mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes				0,03

2.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	16,53 mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,06

2.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA	0,10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

			worker v2.0)	
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

2.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,70
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,79

2.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

2.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

2.3.9. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

2.3.10. Worker exposure: Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	3,43 mg/kg bw/day (ECETOC TRA worker v2.0)	0,02
combined routes				0,12

2.3.11. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,10

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 3: Use in coatings; Industrial uses (SU3).

3.1. Title section

Exposure Scenario name	: Use in coatings
Structured Short Title	: Use in coatings; Industrial uses (SU3).

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or ERC4 onto article)	
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Industrial spraying	PROC7
CS 8	Industrial spraying	PROC7
CS 9	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 10	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 11	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 12	Roller application or brushing	PROC10
CS 13	Treatment of articles by dipping and pouring	PROC13
CS 14	Tabletting, compression, extrusion, pelettisation, granulation	PROC14
CS 15	Use as laboratory reagent	PROC15

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 36000 kg
Release type	: Continuous release
Emission days	: 300
Technical and organisational conditions and measures	
Treat air emissions. Air - minimum efficiency of 98 %	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP type	: Onsite Sewage Treatment Plant
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Hazardous waste incineration External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases. Vapour recovery (e.g. adsorption) When not in use, keep containers tightly closed.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

3.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

3.2.7. Control of worker exposure: Industrial spraying (PROC7)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Carry out in a vented booth or extracted enclosure.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.8. Control of worker exposure: Industrial spraying (PROC7)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear a respirator conforming to EN140.	
Other conditions affecting workers exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.9. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.10. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.11. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.12. Control of worker exposure: Roller application or brushing (PROC10)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.13. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

Assumes a good basic standard of occupational hygiene is implemented

3.2.14. Control of worker exposure: Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

3.2.15. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,002 mg/L	
Freshwater sediment	0,012 mg/kg dry weight	
Marine water	0,0004 mg/L	
Marine sediment	0,0020 mg/kg dry weight	
Soil	0,00124 mg/kg dry weight	

3.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,06 mg/m ³ (ECETOC TRA worker v2.0)	
dermal	systemic	long-term	0,34 mg/kg bw/day	

3.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5,51 mg/m ³ (ECETOC TRA worker v2.0)	0,02
dermal	systemic	long-term	1,37 mg/kg bw/day	0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

			(ECETOC TRA worker v2.0)	
combined routes				0,03

3.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	16,53 mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,06

3.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

3.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,19

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

3.3.7. Worker exposure: Industrial spraying (PROC7)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	2,14 mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes				0,11

3.3.8. Worker exposure: Industrial spraying (PROC7)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	42,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,28
combined routes				0,48

3.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

3.3.10. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³	0,10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

			(ECETOC TRA worker v2.0)	
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

3.3.11. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

3.3.12. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	27,43 mg/kg bw/day (ECETOC TRA worker v2.0)	0,18
combined routes				0,38

3.3.13. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

3.3.14. Worker exposure: Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	3,43 mg/kg bw/day (ECETOC TRA worker v2.0)	0,02
combined routes				0,12

3.3.15. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,10

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 4: Use in coatings; Professional uses (SU22).

4.1. Title section

Exposure Scenario name	: Use in coatings
Structured Short Title	: Use in coatings; Professional uses (SU22).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	ERC8a
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Mixing or blending in batch processes	PROC5
CS 8	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 9	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 10	Non-industrial spraying	PROC11
CS 11	Roller application or brushing	PROC10
CS 12	Non-industrial spraying	PROC11
CS 13	Treatment of articles by dipping and pouring	PROC13
CS 14	Use as laboratory reagent	PROC15
CS 15	Manual activities involving hand contact	PROC19

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Product (article) characteristics	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 5000 kg
Release type	: Continuous release
Emission days	: 365
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP type	: Onsite Sewage Treatment Plant
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Hazardous waste incineration External treatment and disposal of waste should comply with applicable local and/or national regulations. External recovery and recycling of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

4.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

4.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.7. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure operation is undertaken outdoors.	
Other conditions affecting workers exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.9. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.10. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Carry out in a vented booth or extracted enclosure.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.11. Control of worker exposure: Roller application or brushing (PROC10)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

4.2.12. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear a respirator conforming to EN140.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

Assumes a good basic standard of occupational hygiene is implemented

4.2.13. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Vapour pressure : 0,5 kPa

Temperature : 20 °C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration : Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

No other specific measures identified.

Other conditions affecting workers exposure

Temperature : Assumes use at not more than 20°C above ambient temperature.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

Assumes a good basic standard of occupational hygiene is implemented

4.2.14. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Vapour pressure : 0,5 kPa

Temperature : 20 °C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration : Covers daily exposures up to 8 hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

4.2.15. Control of worker exposure: Manual activities involving hand contact (PROC19)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Soil		ESVOC SPERC 8.3b.v1
Water		ESVOC SPERC 8.3b.v1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Air		ESVOC SPERC 8.3b.v1
-----	--	---------------------

Protection Target	Exposure estimate	RCR
Freshwater	0,003 mg/L	0,004
Freshwater sediment	0,014 mg/kg dry weight	0,004
Marine water	0,0004 mg/L	0,007
Marine sediment	0,002 mg/kg dry weight	0,007
Soil	0,001 mg/kg dry weight	0,004

4.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,06 mg/m ³ (ECETOC TRA worker v2.0)	
dermal	systemic	long-term	0,34 mg/kg bw/day	

4.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes				0,11

4.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	16,53 mg/m ³ (ECETOC TRA worker v2.0)	0,06

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,06

4.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,24

4.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

4.3.7. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

4.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	137,71 mg/m ³ (ECETOC TRA worker v2.0)	0,50
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,59

4.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,24

4.3.10. Worker exposure: Non-industrial spraying (PROC11)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	2,14 mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes				0,11

4.3.11. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	137,71 mg/m ³	0,50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

			(ECETOC TRA worker v2.0)	
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,18
combined routes				0,68

4.3.12. Worker exposure: Non-industrial spraying (PROC11)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	107,14 mg/kg bw/day (ECETOC TRA worker v2.0)	0,70
combined routes				0,90

4.3.13. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

4.3.14. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

4.3.15. Worker exposure: Manual activities involving hand contact (PROC19)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	137,71 mg/m ³ (ECETOC TRA worker v2.0)	0,50
dermal	systemic	long-term	28,29 mg/kg bw/day (ECETOC TRA worker v2.0)	0,18
combined routes				0,69

4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 5: Cleaning; Industrial uses (SU3).

5.1. Title section

Exposure Scenario name	: Cleaning
Structured Short Title	: Cleaning; Industrial uses (SU3).

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or ERC4 onto article)	
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Industrial spraying	PROC7
CS 7	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 8	Roller application or brushing	PROC10
CS 9	Treatment of articles by dipping and pouring	PROC13

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 5000 kg
Release type	: Continuous release

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Emission days	: 20
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP type	: Onsite Sewage Treatment Plant
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Hazardous waste incineration External treatment and disposal of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases. Vapour recovery (e.g. adsorption) When not in use, keep containers tightly closed.	

5.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

Assumes a good basic standard of occupational hygiene is implemented

5.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.2.6. Control of worker exposure: Industrial spraying (PROC7)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration 240 min
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.2.8. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.2.9. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Release route	Release rate	Release estimation method
Soil		ESVOC SPERC 4.4a.v1
Water		ESVOC SPERC 4.4a.v1
Air		ESVOC SPERC 4.4a.v1

Protection Target	Exposure estimate	RCR
Freshwater	0,0024 mg/L	0,009
Freshwater sediment	0,0277 mg/kg dry weight	0,009
Marine water	0,0004 mg/L	0,011
Marine sediment	0,0037 mg/kg dry weight	0,011
Soil	0,001 mg/kg dry weight	0,004

5.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,06 mg/m ³ (ECETOC TRA	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

			worker v2.0)	
dermal	systemic	long-term	0,34 mg/kg bw/day	

5.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5,51 mg/m ³ (ECETOC TRA worker v2.0)	0,02
dermal	systemic	long-term	1,37 mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes				0,03

5.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	16,53 mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,06

5.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,14

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

5.3.6. Worker exposure: Industrial spraying (PROC7)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	231,35 mg/m ³ (ECETOC TRA worker v2.0)	0,84
dermal	systemic	long-term	8,57 mg/kg bw/day (ECETOC TRA worker v2.0)	0,06
combined routes				0,90

5.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

5.3.8. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	27,43 mg/kg bw/day (ECETOC TRA worker v2.0)	0,18
combined routes				0,38

5.3.9. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA	0,20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

			worker v2.0)	
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 6: Cleaning; Professional uses (SU22).

6.1. Title section

Exposure Scenario name	: Cleaning
Structured Short Title	: Cleaning; Professional uses (SU22).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	ERC8a
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 7	Roller application or brushing	PROC10
CS 8	Treatment of articles by dipping and pouring	PROC13
CS 9	Non-industrial spraying	PROC11
CS 10	Non-industrial spraying	PROC11

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Product (article) characteristics	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 5000 kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Release type	: Continuous release
Emission days	: 20
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP type	: Onsite Sewage Treatment Plant
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Hazardous waste incineration External treatment and disposal of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases. Vapour recovery (e.g. adsorption) When not in use, keep containers tightly closed.	

6.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

6.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

6.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

6.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

6.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure operation is undertaken outdoors.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

6.2.7. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

6.2.8. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

6.2.9. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Assumes a good basic standard of occupational hygiene is implemented	

6.2.10. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Vapour pressure	: 0,5 kPa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Ensure operation is undertaken outdoors.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Assumes a good basic standard of occupational hygiene is implemented

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Soil		ESVOC SPERC 8.4b.v1
Water		ESVOC SPERC 8.4b.v1
Air		ESVOC SPERC 8.4b.v1

Protection Target	Exposure estimate	RCR
Freshwater	0,0022 mg/L	0,004
Freshwater sediment	0,0114 mg/kg dry weight	0,004
Marine water	0,0004 mg/L	0,006
Marine sediment	0,0020 mg/kg dry weight	0,006
Soil	0,001 mg/kg dry weight	0,003

6.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,06 mg/m ³ (ECETOC TRA worker v2.0)	
dermal	systemic	long-term	0,34 mg/kg bw/day	

6.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	27,54 mg/m ³ (ECETOC TRA worker v2.0)	0,10
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA	0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

			worker v2.0)	
combined routes				0,11

6.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	16,53 mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	0,34 mg/kg bw/day (ECETOC TRA worker v2.0)	
combined routes				0,06

6.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	6,86 mg/kg bw/day (ECETOC TRA worker v2.0)	0,04
combined routes				0,24

6.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	96,40 mg/m ³ (ECETOC TRA worker v2.0)	0,35
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,44

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

6.3.7. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	137,71 mg/m ³ (ECETOC TRA worker v2.0)	0,50
dermal	systemic	long-term	27,43 mg/kg bw/day (ECETOC TRA worker v2.0)	0,18
combined routes				0,68

6.3.8. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	55,08 mg/m ³ (ECETOC TRA worker v2.0)	0,20
dermal	systemic	long-term	13,71 mg/kg bw/day (ECETOC TRA worker v2.0)	0,09
combined routes				0,29

6.3.9. Worker exposure: Non-industrial spraying (PROC11)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	165,25 mg/m ³ (ECETOC TRA worker v2.0)	0,60
dermal	systemic	long-term	21,43 mg/kg bw/day (ECETOC TRA worker v2.0)	0,14
combined routes				0,74

6.3.10. Worker exposure: Non-industrial spraying (PROC11)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	231,35 mg/m ³ (ECETOC TRA worker v2.0)	0,84

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

dermal	systemic	long-term	21,43 mg/kg bw/day (ECETOC TRA worker v2.0)	0,14
combined routes				0,98

6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 7: Use in coatings; Consumer uses (SU21).

7.1. Title section

Exposure Scenario name	: Use in coatings
Structured Short Title	: Use in coatings; Consumer uses (SU21).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	ERC8a
Consumer		
CS 2	Coatings and paints, thinners, paint removers	PC9a
CS 3	Ink and toners	PC18

7.2. Conditions of use affecting exposure

7.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Product (article) characteristics	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 0,52 kg
Release type	: Continuous release
Emission days	: 365
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

7.2.2. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

Product (article) characteristics	
Covers concentrations up to 10 %	
Physical form of product	: Liquid
Vapour pressure	: 10 Pa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 10 kg
Duration	: 132 min
Use frequency	: 1 uses per day
Other conditions affecting consumers exposure	
Room size	: 20 m3
Ventilation rate	: Covers use under typical household ventilation.

7.2.3. Control of consumer exposure: Ink and toners (PC18)

Product (article) characteristics	
Covers concentrations up to 10 %	
Physical form of product	: Liquid
Vapour pressure	: 10 Pa
Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,04 kg
Duration	: 30 min
Other conditions affecting consumers exposure	
Room size	: 20 m3
Ventilation rate	: Covers use under typical household ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

7.3. Exposure estimation and reference to its source

7.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Soil		ESVOC SPERC 8.3c.v1
Water		ESVOC SPERC 8.3c.v1
Air		ESVOC SPERC 8.3c.v1

Protection Target	Exposure estimate	RCR
Freshwater	0,0023 mg/L	0,004
Freshwater sediment	0,0116 mg/kg dry weight	0,004
Marine water	0,0004 mg/L	0,007
Marine sediment	0,0021 mg/kg dry weight	0,007
Soil	0,001 mg/kg dry weight	0,003

7.3.2. Consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	6,83 mg/m ³	0,60
dermal	systemic	long-term	6 mg/kg bw/day	0,11
combined routes				0,70

7.3.3. Consumer exposure: Ink and toners (PC18)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,181 mg/m ³	0,02
dermal	systemic	long-term	7,5 mg/kg bw/day	0,14
combined routes				0,16

7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1

SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025

Print Date: 28.07.2026

ES 8: Cleaning; Consumer uses (SU21).

8.1. Title section

Exposure Scenario name	: Cleaning
Structured Short Title	: Cleaning; Consumer uses (SU21).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	ERC8a
Consumer		
CS 2	Washing and cleaning products	PC35

8.2. Conditions of use affecting exposure

8.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Product (article) characteristics	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 0,27 kg
Emission days	: 365
Other conditions affecting environmental exposure	
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

8.2.2. Control of consumer exposure: Washing and cleaning products (PC35)

Product (article) characteristics	
Covers concentrations up to 10 %	
Physical form of product	: Liquid
Vapour pressure	: 10 Pa

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

Temperature	: 20 °C
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount used per event	: 0,016 kg
Duration	: 60 min
Other conditions affecting consumers exposure	
Room size	: 15 m ³
Ventilation rate	: Covers use under typical household ventilation.

8.3. Exposure estimation and reference to its source

8.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Release route	Release rate	Release estimation method
Soil		ESVOC SPERC 8.4c.v1
Water		ESVOC SPERC 8.4c.v1
Air		ESVOC SPERC 8.4c.v1

Protection Target	Exposure estimate	RCR
Freshwater	0,0022 mg/L	0,004
Freshwater sediment	0,011 mg/kg dry weight	0,004
Marine water	0,00039 mg/L	0,006
Marine sediment	0,0020 mg/kg dry weight	0,006
Soil	0,001 mg/kg dry weight	0,003

8.3.2. Consumer exposure: Washing and cleaning products (PC35)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,181 mg/m ³	0,02
dermal	systemic	long-term	7,5 mg/kg bw/day	0,14
combined routes				0,16

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-3550

Version: 11.1
SDB_CH

Revision Date: 20.07.2026

Date of last issue: 06.11.2025
Print Date: 28.07.2026

8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet.