

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYK-A 560 N  
UFI : WPFA-J03V-700G-TW5N  
Product code : 000000000000127039

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Defoamer  
Substance/Mixture

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735  
  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                                                                                      |                                                        |
|--------------------------------------------------------------------------------------|--------------------------------------------------------|
| Flammable liquids, Category 3                                                        | H226: Flammable liquid and vapour.                     |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.               |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                |
| Aspiration hazard, Category 1                                                        | H304: May be fatal if swallowed and enters airways.    |
| Long-term (chronic) aquatic hazard, Category 2                                       | H411: Toxic to aquatic life with long lasting effects. |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

|                                |   |                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard pictograms              | : |                                                                                       |
| Signal word                    | : | Danger                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Hazard statements              | : | H226 Flammable liquid and vapour.<br>H304 May be fatal if swallowed and enters airways.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H411 Toxic to aquatic life with long lasting effects.                                                                                                                                                                                        |
| Supplemental Hazard Statements | : | EUH066 Repeated exposure may cause skin dryness or cracking.                                                                                                                                                                                                                                                                                                                                                                 |
| Precautionary statements       | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P273 Avoid release to the environment.<br><b>Response:</b><br>P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.<br>P331 Do NOT induce vomiting.<br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.<br>P391 Collect spillage. |

### Hazardous components which must be listed on the label:

- 64742-95-6 Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Solution of polyolefins and polyacrylates

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0

SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025

Print Date 21.05.2025

### Components

| Chemical name                                                                      | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                                                                                                                            | Concentration<br>(% w/w) |
|------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified  | 64742-95-6<br>01-2119455851-35                        | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411<br>EUH066 | >= 50 - <= 100           |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha | 64742-48-9<br>01-2119463258-33                        | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>Asp. Tox. 1; H304<br>EUH066                                                                          | >= 7 - < 10              |
| 2-methoxy-1-methylethyl acetate                                                    | 108-65-6<br>203-603-9<br>01-2119475791-29             | Flam. Liq. 3; H226<br>STOT SE 3; H336                                                                                                                                     | >= 1 - < 3               |
| 2,6-di-tert-butyl-p-cresol                                                         | 128-37-0<br>204-881-4<br>01-2119565113-46             | Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br><br>M-Factor (Acute aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 1                              | >= 0,25 - < 0,5          |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : May be fatal if swallowed and enters airways.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0

SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025

Print Date 21.05.2025

from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                      | CAS-No.                                                                                                                     | Value type (Form of exposure) | Control parameters   | Basis      |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------|------------|
| 2-methoxy-1-methylethyl acetate | 108-65-6                                                                                                                    | TWA                           | 50 ppm<br>275 mg/m3  | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative                          |                               |                      |            |
|                                 |                                                                                                                             | STEL                          | 100 ppm<br>550 mg/m3 | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative                          |                               |                      |            |
|                                 |                                                                                                                             | TWA                           | 50 ppm<br>275 mg/m3  | MT OEL     |
|                                 | Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin. |                               |                      |            |
|                                 |                                                                                                                             | STEL                          | 100 ppm<br>550 mg/m3 | MT OEL     |
|                                 | Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin. |                               |                      |            |

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name                                                                    | End Use | Exposure routes | Potential health effects             | Value    |
|-----------------------------------------------------------------------------------|---------|-----------------|--------------------------------------|----------|
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | Workers | Skin contact    | Long-term exposure, Systemic effects | 25 mg/kg |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

|                                 |           |              |                                         |             |
|---------------------------------|-----------|--------------|-----------------------------------------|-------------|
|                                 | Workers   | Inhalation   | Long-term exposure,<br>Systemic effects | 150 mg/m3   |
|                                 | Consumers | Skin contact | Long-term exposure,<br>Systemic effects | 11 mg/kg    |
|                                 | Consumers | Inhalation   | Long-term exposure,<br>Systemic effects | 32 mg/m3    |
|                                 | Consumers | Ingestion    | Long-term exposure,<br>Systemic effects | 11 mg/kg    |
| 2-methoxy-1-methylethyl acetate | Workers   | Skin contact | Long-term systemic<br>effects           | 796 mg/kg   |
|                                 | Workers   | Inhalation   | Long-term systemic<br>effects           | 275 mg/m3   |
|                                 | Consumers | Skin contact | Long-term systemic<br>effects           | 320 mg/kg   |
|                                 | Consumers | Inhalation   | Long-term systemic<br>effects           | 33 mg/m3    |
|                                 | Consumers | Ingestion    | Long-term systemic<br>effects           | 36 mg/kg    |
|                                 | Workers   | Inhalation   | Acute local effects                     | 550 mg/m3   |
|                                 | Consumers | Inhalation   | Acute local effects                     | 33 mg/m3    |
| 2,6-di-tert-butyl-p-cresol      | Workers   | Inhalation   | Long-term systemic<br>effects           | 1,76 mg/m3  |
|                                 | Workers   | Skin contact | Long-term systemic<br>effects           | 0,5 mg/kg   |
|                                 | Consumers | Oral         | Long-term systemic<br>effects           | 0,25 mg/kg  |
|                                 | Consumers | Inhalation   | Long-term systemic<br>effects           | 0,435 mg/m3 |
|                                 | Consumers | Dermal       | Long-term systemic<br>effects           | 0,25 mg/kg  |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name                  | Environmental Compartment | Value         |
|---------------------------------|---------------------------|---------------|
| 2-methoxy-1-methylethyl acetate | Fresh water               | 0,635 mg/l    |
|                                 | Marine water              | 0,0635 mg/l   |
|                                 | Intermittent releases     | 6,35 mg/l     |
|                                 | Sewage treatment plant    | 100 mg/l      |
|                                 | Fresh water sediment      | 3,29 mg/kg    |
|                                 | Marine sediment           | 0,329 mg/kg   |
|                                 | Soil                      | 0,29 mg/kg    |
| 2,6-di-tert-butyl-p-cresol      | Fresh water               | 0,000199 mg/l |
|                                 | Marine water              | 0,00002 mg/l  |
|                                 | Soil                      | 0,04769 mg/l  |
|                                 | Intermittent releases     | 0,00199 mg/l  |
|                                 | Fresh water sediment      | 0,0996 mg/kg  |
|                                 | Marine sediment           | 0,00996 mg/kg |

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

### Hand protection

Material : Nitrile rubber  
Break through time : > 480 min

Remarks : The suitability for a specific workplace should be discussed  
with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and  
concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an  
approved filter.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : clear

Odour : not significant

Odour Threshold : No data available

Melting point/ range : < 0 °C  
Method: derived

Initial boiling point : 144 °C  
Method: derived

Upper explosion limit / Upper  
flammability limit : No data available

Lower explosion limit / Lower  
flammability limit : No data available

Flash point : 45 °C  
Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature : > 200 °C  
Method: DIN 51794

Decomposition temperature : No data available

pH : insoluble

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

|                                        |   |                                                                                   |
|----------------------------------------|---|-----------------------------------------------------------------------------------|
| Viscosity                              |   |                                                                                   |
| Viscosity, kinematic                   | : | 4,7 mm <sup>2</sup> /s (40 °C)                                                    |
| Solubility(ies)                        |   |                                                                                   |
| Water solubility                       | : | immiscible                                                                        |
| Solubility in other solvents           | : | No data available                                                                 |
| Partition coefficient: n-octanol/water | : | No data available                                                                 |
| Vapour pressure                        | : | 4 hPa (20 °C)<br>Method: derived                                                  |
| Relative density                       | : | No data available                                                                 |
| Density                                | : | 0,870 g/cm <sup>3</sup> (20 °C, 1.013 hPa)<br>Method: 4 (20°C oscillating U-tube) |
| Relative vapour density                | : | No data available                                                                 |

### 9.2 Other information

|                        |   |                     |
|------------------------|---|---------------------|
| Flammability (liquids) | : | Sustains combustion |
| Evaporation rate       | : | No data available   |
| Surface tension        | : | Not applicable      |

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

|                     |   |                                                     |
|---------------------|---|-----------------------------------------------------|
| Hazardous reactions | : | No decomposition if stored and applied as directed. |
|                     |   | Vapours may form explosive mixture with air.        |

### 10.4 Conditions to avoid

|                     |   |                          |
|---------------------|---|--------------------------|
| Conditions to avoid | : | Heat, flames and sparks. |
|---------------------|---|--------------------------|

### 10.5 Incompatible materials

|                    |   |                         |
|--------------------|---|-------------------------|
| Materials to avoid | : | Acids                   |
|                    |   | Strong oxidizing agents |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Product:

Acute oral toxicity : Remarks: No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3.160 mg/kg  
Method: OECD Test Guideline 402

##### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

##### **2,6-di-tert-butyl-p-cresol:**

Acute oral toxicity : LD50 (Rat): > 6.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

#### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

#### Product:

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

|         |                           |
|---------|---------------------------|
| Species | : Rabbit                  |
| Method  | : OECD Test Guideline 404 |
| Result  | : No skin irritation      |
| GLP     | : yes                     |

#### **2-methoxy-1-methylethyl acetate:**

|         |                           |
|---------|---------------------------|
| Species | : Rabbit                  |
| Method  | : OECD Test Guideline 404 |
| Result  | : No skin irritation      |
| GLP     | : yes                     |

#### **Serious eye damage/eye irritation**

Not classified due to lack of data.

### Product:

|         |                                                                              |
|---------|------------------------------------------------------------------------------|
| Remarks | : Vapours may cause irritation to the eyes, respiratory system and the skin. |
|---------|------------------------------------------------------------------------------|

|         |                     |
|---------|---------------------|
| Remarks | : No data available |
|---------|---------------------|

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

|         |                           |
|---------|---------------------------|
| Species | : Rabbit                  |
| Method  | : OECD Test Guideline 405 |
| Result  | : No eye irritation       |
| GLP     | : yes                     |

#### **2-methoxy-1-methylethyl acetate:**

|         |                           |
|---------|---------------------------|
| Species | : Rabbit                  |
| Method  | : OECD Test Guideline 405 |
| Result  | : No eye irritation       |
| GLP     | : yes                     |

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

Not classified due to lack of data.

##### **Respiratory sensitisation**

Not classified due to lack of data.

### Product:

|         |                     |
|---------|---------------------|
| Remarks | : No data available |
|---------|---------------------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

|                 |                                      |
|-----------------|--------------------------------------|
| Test Type       | : Maximisation Test                  |
| Exposure routes | : Dermal                             |
| Species         | : Guinea pig                         |
| Method          | : OECD Test Guideline 406            |
| Result          | : Does not cause skin sensitisation. |

#### **2-methoxy-1-methylethyl acetate:**

|         |                           |
|---------|---------------------------|
| Species | : Guinea pig              |
| Method  | : OECD Test Guideline 406 |
| Result  | : Not a skin sensitizer.  |
| GLP     | : yes                     |

### **Germ cell mutagenicity**

Not classified due to lack of data.

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

|                                       |                                                                                                       |
|---------------------------------------|-------------------------------------------------------------------------------------------------------|
| Germ cell mutagenicity-<br>Assessment | : Classified based on benzene content < 0.1% (Regulation (EC)<br>1272/2008, Annex VI, Part 3, Note P) |
|---------------------------------------|-------------------------------------------------------------------------------------------------------|

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

|                                       |                                                                                                       |
|---------------------------------------|-------------------------------------------------------------------------------------------------------|
| Germ cell mutagenicity-<br>Assessment | : Classified based on benzene content < 0.1% (Regulation (EC)<br>1272/2008, Annex VI, Part 3, Note P) |
|---------------------------------------|-------------------------------------------------------------------------------------------------------|

### **Carcinogenicity**

Not classified due to lack of data.

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

|                                 |                                                                                                       |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| Carcinogenicity -<br>Assessment | : Classified based on benzene content < 0.1% (Regulation (EC)<br>1272/2008, Annex VI, Part 3, Note P) |
|---------------------------------|-------------------------------------------------------------------------------------------------------|

#### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

|                                 |                                                                                                       |
|---------------------------------|-------------------------------------------------------------------------------------------------------|
| Carcinogenicity -<br>Assessment | : Classified based on benzene content < 0.1% (Regulation (EC)<br>1272/2008, Annex VI, Part 3, Note P) |
|---------------------------------|-------------------------------------------------------------------------------------------------------|

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

### STOT - repeated exposure

Not classified due to lack of data.

### Repeated dose toxicity

#### Product:

Remarks : No data available

### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

#### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

|                                                     |                                                                                                                          |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                    | : LL50 (Fish): 9,2 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203<br>GLP: yes                            |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): 3,2 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202<br>GLP: yes      |
| Toxicity to algae/aquatic plants                    | : EC50 (Pseudokirchneriella subcapitata): 2,6 mg/l<br>Exposure time: 72 h<br>Method: OECD Test Guideline 201<br>GLP: yes |

### 2-methoxy-1-methylethyl acetate:

|                                  |                                                                                                                                                                     |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                 | : LC50 (Fish): 100 - 180 mg/l<br>Exposure time: 96 h<br>Test Type: static test<br>Method: OECD Test Guideline 203<br>GLP: no                                        |
| Toxicity to algae/aquatic plants | : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l<br>Exposure time: 96 h<br>Test Type: static test<br>Method: OECD Test Guideline 201<br>GLP: no |

### 2,6-di-tert-butyl-p-cresol:

|                                     |                                                                                                                                                                            |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                    | : LC50 : 199 mg/l<br>Exposure time: 96 h                                                                                                                                   |
| Toxicity to algae/aquatic plants    | : EC50 (Desmodesmus subspicatus (green algae)): 0,42 mg/l<br>Exposure time: 72 h<br>Test Type: static test<br>Method: Regulation (EC) No. 440/2008, Annex, C.3<br>GLP: yes |
| M-Factor (Acute aquatic toxicity)   | : 1                                                                                                                                                                        |
| M-Factor (Chronic aquatic toxicity) | : 1                                                                                                                                                                        |

## 12.2 Persistence and degradability

### Product:

|                  |                              |
|------------------|------------------------------|
| Biodegradability | : Remarks: No data available |
|------------------|------------------------------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0

SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025

Print Date 21.05.2025

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F

#### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

### **12.3 Bioaccumulative potential**

#### Product:

Bioaccumulation : Remarks: No data available

### Components:

#### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n- : log Pow: 1,2 (20 °C)  
octanol/water pH: 6,8  
Method: OECD Test Guideline 117  
GLP: yes

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **12.6 Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### Product:

Additional ecological : An environmental hazard cannot be excluded in the event of  
information unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- |                        |   |                                                                                                                                                                                                                  |
|------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                | : | The product should not be allowed to enter drains, water courses or the soil.<br>Do not contaminate ponds, waterways or ditches with chemical or used container.<br>Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.<br>Dispose of as unused product.<br>Do not re-use empty containers.<br>Do not burn, or use a cutting torch on, the empty drum.                                                         |

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- |      |   |         |
|------|---|---------|
| ADR  | : | UN 1993 |
| IMDG | : | UN 1993 |
| IATA | : | UN 1993 |

#### 14.2 UN proper shipping name

- |      |   |                                                                             |
|------|---|-----------------------------------------------------------------------------|
| ADR  | : | FLAMMABLE LIQUID, N.O.S.<br>(Solvent naphtha, 1-Methoxy-2-propanol acetate) |
| IMDG | : | FLAMMABLE LIQUID, N.O.S.<br>(Solvent naphtha, 1-Methoxy-2-propanol acetate) |
| IATA | : | Flammable liquid, n.o.s.<br>(Solvent naphtha, 1-Methoxy-2-propanol acetate) |

#### 14.3 Transport hazard class(es)

- |      |   |   |
|------|---|---|
| ADR  | : | 3 |
| IMDG | : | 3 |
| IATA | : | 3 |

#### 14.4 Packing group

- |                              |   |     |
|------------------------------|---|-----|
| ADR                          |   |     |
| Packing group                | : | III |
| Classification Code          | : | F1  |
| Hazard Identification Number | : | 30  |
| Labels                       | : | 3   |
| Tunnel restriction code      | : | D/E |
| IMDG                         |   |     |
| Packing group                | : | III |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0

SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025

Print Date 21.05.2025

Labels : 3  
EmS Code : F-E, S-E  
Remarks : IMDG Code segregation group - none

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
  
Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0

SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025

Print Date 21.05.2025

Seveso III: Directive 2012/18/EU of the  
European Parliament and of the Council on the  
control of major-accident hazards involving  
dangerous substances.

P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

### 15.2 Chemical safety assessment

Not applicable

### SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the  
body of this document by two vertical lines.

#### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Flam. Liq. : Flammable liquids  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first  
list of indicative occupational exposure limit values  
MT OEL : Malta. Occupational Exposure Limits  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
MT OEL / TWA : Long term exposure limit  
MT OEL / STEL : Occupational exposure limit value Short-term, 15 minute

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland  
Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by  
Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the  
Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation;  
Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -  
Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada);  
ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -  
Concentration associated with x% response; ELx - Loading rate associated with x% response;  
EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0

SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025

Print Date 21.05.2025

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| STOT SE 3         | H336 |
| STOT SE 3         | H335 |
| Asp. Tox. 1       | H304 |
| Aquatic Chronic 2 | H411 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MT / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-A 560 N

Version 5.0  
SDB\_MT

Revision Date: 02.04.2025

Date of last issue: 12.03.2025  
Print Date 21.05.2025

## Annex: Exposure Scenarios

### Table of Contents

| Number | Title |
|--------|-------|
|--------|-------|