

BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : BYK-CATALYST 450

Product code : 000000000000105125

Manufacturer or supplier's details

Company : BYK-Chemie GmbH

Address : Abelstrasse 45
46483 Wesel

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

Emergency telephone number : 18000 74234 (toll –free number, access from Australia only)
+61 2 8014 4558

Importer

Company : IMCD Australia Pty Ltd
Level 1, 352 Wellington Road
Mulgrave
VIC 3170
Australia
Telephone: +61 3 8544 3100

Use of the Sub-
stance/Mixture : Acid Catalyst

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Specific target organ toxicity -
single exposure : Category 3 (Central nervous system)

Specific target organ toxicity -
repeated exposure : Category 2 (Liver)

Long-term (chronic) aquatic
hazard : Category 3

GHS label elements

Hazard pictograms :



BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H373 May cause damage to organs (Liver) through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe mist or vapours. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P314 Get medical advice/ attention if you feel unwell. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Solution of an amine salt of para-toluene sulfonic acid

Components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

1-methoxy-2-propanol	107-98-2	$\geq 50 - < 100$
pyridinium toluene-4-sulphonate	24057-28-1	$\geq 25 - < 30$
propane-1,2-diol	57-55-6	$\geq 5 - < 7$
pyridine	110-86-1	$\geq 1 - < 3$
2-methoxypropanol	1589-47-5	$\geq 0.1 - < 0.25$

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No information available. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Notes to physician	: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NO _x) Sulphur oxides
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment	: Wear self-contained breathing apparatus for firefighting if nec-



Version 1.2
SDS AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

for firefighters : essary.
Hazchem Code : •3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
---	---

Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
---------------------------	---

Methods and materials for containment and cleaning up	: Neutralize with chalk, alkali solution or ammonia. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
---	--

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Hygiene measures	:	Wash hands before breaks and at the end of workday.
Conditions for safe storage	:	No smoking.
		Keep container tightly closed in a dry and well-ventilated place.
		Containers which are opened must be carefully resealed and kept upright to prevent leakage.
		Observe label precautions.
		Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 369 mg/m ³	AU OEL
		STEL	150 ppm 553 mg/m ³	AU OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
propane-1,2-diol	57-55-6	TWA (particulate)	10 mg/m ³	AU OEL
		TWA (Total (vapour and particles))	150 ppm 474 mg/m ³	AU OEL
pyridine	110-86-1	TWA	5 ppm 16 mg/m ³	AU OEL
		TWA	1 ppm	ACGIH

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : butyl-rubber
Break through time : 120.00 min

Remarks : Wear suitable gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow - brown

Odour : amine-like

Odour Threshold : No data available

pH : 4 (20 °C)
Concentration: 10 %
Method: Universal pH-value indicator

Melting point/ range : < 0 °C
Method: derived

Initial boiling point : 120.00 °C
Method: derived

Flash point : 35.00 °C

BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

	Method: 48 (Abel-Pensky) DIN 51755
Evaporation rate	: No data available
Flammability (liquids)	: Sustains combustion
Upper explosion limit / Upper flammability limit	: 13.10 %(V)
Lower explosion limit / Lower flammability limit	: 1.80 %(V)
Vapour pressure	: 13 hPa (20 °C) Method: derived
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.0200 g/cm ³ (20.00 °C) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: completely miscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: > 200.00 °C Method: DIN 51794
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**1-methoxy-2-propanol:**

Acute oral toxicity : LD50 (Rat, male and female): 4,016 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.
GLP: yes

pyridinium toluene-4-sulphonate:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 4,000 mg/kg
Method: OECD Test Guideline 423
GLP: yes

Skin corrosion/irritation

Not classified due to lack of data.

Components:**1-methoxy-2-propanol:**

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : No skin irritation
GLP : yes

pyridinium toluene-4-sulphonate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

propane-1,2-diol:

BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:**1-methoxy-2-propanol:**

Species : Rabbit
Result : No eye irritation
Method : Directive 67/548/EEC, Annex V, B.5.
GLP : yes

pyridinium toluene-4-sulphonate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

propane-1,2-diol:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitisation**Skin sensitisation**

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**1-methoxy-2-propanol:**

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : Does not cause skin sensitisation.
GLP : yes

propane-1,2-diol:

Test Type : Mouse Local Lymph Node assay (LLNA)
Exposure routes : Dermal
Species : Mouse
Method : OECD Test Guideline 429

BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

Result : Does not cause skin sensitisation.

Chronic toxicity**Germ cell mutagenicity**

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

STOT - repeated exposure

May cause damage to organs (Liver) through prolonged or repeated exposure.

Product:

Remarks : No data available

Repeated dose toxicity**Product:**

Remarks : No data available

Aspiration toxicity

Not classified due to lack of data.

Product:

No data available

Further information**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Components:**1-methoxy-2-propanol:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6,812 mg/l
Exposure time: 96 h
Test Type: static test
Method: DIN 38412
GLP: no

propane-1,2-diol:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata): 34,100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Components:**1-methoxy-2-propanol:**

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301
GLP: yes

propane-1,2-diol:

Biodegradability : aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**1-methoxy-2-propanol:**Partition coefficient: n-octanol/water : log Pow: 0.37 (20 °C)
pH: 6.8
Method: OECD Test Guideline 117
GLP: No information available.**Mobility in soil**

No data available

Other adverse effects**Product:**Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Pyridine, 1-Methoxy-2-propanol)
Class : 3
Packing group : III
Labels : 3**IATA-DGR**UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.

BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

(Pyridine, 1-Methoxy-2-propanol)

Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Pyridine, 1-Methoxy-2-propanol)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Pyridine, 1-Methoxy-2-propanol)

Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

SECTION 16. OTHER INFORMATION

Revision Date : 17.12.2024
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

BYK-CATALYST 450

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 01.12.2023
Print Date 18.12.2024

taminants.

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
AU OEL / TWA	:	Exposure standard - time weighted average
AU OEL / STEL	:	Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN