

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

SECTION 1. IDENTIFICATION

Product name : BYK-MAX HS 4316

Manufacturer or supplier's details

Company : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086
Visit our web site : www.byk.com
E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Additive for plastics
Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Combustible dust :
Skin sensitisation : Category 1
Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P272 Contaminated work clothing should not be allowed out of the workplace.

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Organic heat stabilizer composition

Hazardous components

Component	CAS-No.	Concentration (%)
Antioxidant	10081-67-1	>= 30 - < 60
Vinyl acetate	108-05-4	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Vinyl acetate	108-05-4	TWA	10 ppm	ACGIH
Vinyl acetate		STEL	15 ppm	ACGIH
Vinyl acetate		TWA	10 ppm 30 mg/m ³	OSHA P0
Vinyl acetate		STEL	20 ppm 60 mg/m ³	OSHA P0
Vinyl acetate		C	4 ppm 15 mg/m ³	NIOSH REL

Hazardous components without workplace control parameters

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.

Hand protection
Material : Nitrile rubber
Break through time : > 120 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : pellet
Colour : colourless - light yellow
Odour : characteristic
pH : insoluble

Melting point/ range : No data available
Initial boiling point and boiling : No data available

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

range	
Vapour pressure	: No data available
Flash point	: Not applicable
Upper explosion limit	: Upper explosion limit No data available
Lower explosion limit	: Lower explosion limit No data available
Flammability (solid, gas)	: May form combustible dust concentrations in air during processing, handling or other means. Combustible Solids
Particle size	: No data available
Density	: 0.48 g/cm ³ (68 °F (20 °C))
Bulk density	: 0.5 g/cm ³ (68 °F (20 °C)) Method: 34 (bulk density)
Solubility(ies)	
Water solubility	: Not applicable
Ignition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

Inhalation
Ingestion
Eye contact
Skin contact

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

Components:**108-05-4 Vinyl acetate:**

Acute dermal toxicity : LD50 (Rabbit): 7,440 mg/kg
GLP: no

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Components:**108-05-4 Vinyl acetate:**

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

Serious eye damage/eye irritation**Product:**

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Components:**108-05-4 Vinyl acetate:**

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**108-05-4 Vinyl acetate:**

Test Type: Mouse Local Lymph Node assay (LLNA)
Exposure routes: Skin contact

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

Species: Mouse
Method: OECD Test Guideline 429
Result: Not a skin sensitizer.
GLP: yes

Carcinogenicity**IARC**

Group 2B: Possibly carcinogenic to humans

Vinyl acetate

108-05-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Repeated dose toxicity**Product:**

Remarks: No data available

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish

:

Remarks: No data available

Toxicity to daphnia and other
aquatic invertebrates

:

Remarks: No data available

Persistence and degradability**Product:**

Biodegradability

:

Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation

:

Remarks: No data available

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues

: Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act**

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

Calculated RQ exceeds reasonably attainable upper limit.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : The following components are subject to reporting levels established by SARA Title III, Section 302:

Vinyl acetate	108-05-4	.1 %
---------------	----------	------

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Vinyl acetate	108-05-4	.1 %
---------------	----------	------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations**Massachusetts Right To Know**

Vinyl acetate	108-05-4
---------------	----------

Pennsylvania Right To Know

Copolymer	-
-----------	---

BYK-MAX HS 4316

Version 1

Revision Date 09/21/2026

Print Date 09/24/2026

Antioxidant	10081-67-1
Wax	-
Vinyl acetate	108-05-4

New Jersey Right To Know

New Jersey Trade Secret : 800963-2026
Registry Number for the product (NJ TSRN)

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Vinyl acetate, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 09/21/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.