

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 1. IDENTIFICATION**

Product name : BYK-P 104 SG

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)Emergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting &amp; Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 2 (hearing organs, Kidney, Liver)

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H334 May cause allergy or asthma symptoms or breathing

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

difficulties if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs (hearing organs, Kidney, Liver) through prolonged or repeated exposure.

**Precautionary statements****: Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P285 In case of inadequate ventilation wear respiratory protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
 Chemical nature : Solution of a lower molecular weight unsaturated polycarboxylic acid polymer

**Hazardous components**

Component	CAS-No.	Concentration (%)
Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids	85711-46-2	>= 30 - < 60
Xylene	1330-20-7	>= 30 - < 60
Ethyl benzene	100-41-4	>= 5 - < 10
2,6-Dimethylheptan-4-one	108-83-8	>= 1 - < 5
Maleic anhydride	108-31-6	>= 0.1 - < 1
Cumene	98-82-8	>= 0.1 - < 1
Toluene	108-88-3	>= 0.1 - < 1

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : Call a physician or poison control centre immediately.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)

## BYK-P 104 SG

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Unsuitable extinguishing media	: Dry chemical : High volume water jet
Specific hazards during firefighting	: Cool closed containers exposed to fire with water spray. Will not explode on mechanical impact. Handle as an industrial chemical. Do not allow run-off from fire fighting to enter drains or water courses.  Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Neutralize with chalk, alkali solution or ammonia. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes.
-------------------------	--

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
Xylene		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
Xylene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
Xylene		TWA	20 ppm	ACGIH
Ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
Ethyl benzene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
Ethyl benzene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
Ethyl benzene		STEL	125 ppm 545 mg/m <sup>3</sup>	OSHA P0
Ethyl benzene		ST	125 ppm 545 mg/m <sup>3</sup>	NIOSH REL
2,6-Dimethylheptan-4-one	108-83-8	TWA	25 ppm	ACGIH
2,6-Dimethylheptan-4-one		TWA	50 ppm 290 mg/m <sup>3</sup>	OSHA Z-1
Maleic anhydride	108-31-6	TWA	0.25 ppm 1 mg/m <sup>3</sup>	OSHA Z-1
Maleic anhydride		TWA	0.25 ppm	NIOSH REL

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Maleic anhydride		TWA (Inhalable fraction and vapor)	1 mg/m <sup>3</sup> 0.01 mg/m <sup>3</sup>	ACGIH
Cumene	98-82-8	TWA	5 ppm	ACGIH
Cumene		TWA	50 ppm 245 mg/m <sup>3</sup>	OSHA Z-1
Cumene		TWA	50 ppm 245 mg/m <sup>3</sup>	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
Toluene		TWA	200 ppm	OSHA Z-2
Toluene		CEIL	300 ppm	OSHA Z-2
Toluene		Peak	500 ppm	OSHA Z-2
Toluene		TWA	100 ppm 375 mg/m <sup>3</sup>	OSHA P0
Toluene		STEL	150 ppm 560 mg/m <sup>3</sup>	OSHA P0

Hazardous components without workplace control parameters

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Physical state : liquid
- Colour : yellow
- Odour : aromatic
- Odour Threshold : No data available
- pH : 3, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
- Melting point/ range : < 41 °F (< 5 °C)  
Method: derived
- Initial boiling point : 278.60 °F (137.00 °C)

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

	Method: derived
Vapour pressure	: 9 hPa (68 °F (20 °C)) Method: derived
Flash point	: 82.40 °F (28.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: 7.60 %(V)
Lower explosion limit	: 0.80 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.9500 g/cm <sup>3</sup> (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 40 mm <sup>2</sup> /s (104.00 °F (40.00 °C))

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Vapours may form explosive mixture with air.

Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong oxidizing agents
Hazardous decomposition products	:	None expected

**SECTION 11. TOXICOLOGICAL INFORMATION**
**Information on likely routes of exposure**

Inhalation  
Ingestion  
Eye contact  
Skin contact

**Acute toxicity**
**Product:**

Acute oral toxicity	:	Acute toxicity estimate : 3,108 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate : 25.33 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate : 4,507 mg/kg Method: Calculation method

**Components:**
**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Acute oral toxicity	:	LD50 (Rat, female): > 2,000 mg/kg Method: OECD Test Guideline 423 GLP: yes
---------------------	---	--

**1330-20-7 Xylene:**

Acute oral toxicity	:	LD50 (Rat): 4,300 mg/kg Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral) GLP: no
Acute inhalation toxicity	:	LC50 (Rat): 5000 ppm Exposure time: 4 h
Acute dermal toxicity	:	LD50 (Rabbit): 1,700 mg/kg  LD50 (Rabbit): > 4,200 mg/kg GLP: No information available.

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**100-41-4 Ethyl benzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

**108-83-8 2,6-Dimethylheptan-4-one:**Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yesAcute inhalation toxicity : LC50 (Rat): > 14 mg/l  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: noAcute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes**108-31-6 Maleic anhydride:**Acute oral toxicity : LD50 (Rat, male and female): 1,090 mg/kg  
Method: OECD Test Guideline 401Acute dermal toxicity : LD50 (Rabbit): 398 mg/kg  
  
LD50 (Rabbit, female): 2,620 mg/kg  
GLP: No information available.**98-82-8 Cumene:**

Acute oral toxicity : LD50 (Rat): 1,400 mg/kg

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 : Remarks: No data available

**108-88-3 Toluene:**

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

Species: Rabbit

Assessment: No skin irritation

Method: OECD Test Guideline 404

Result: No skin irritation

**Components:**

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Species: EPISKIN human epidermis skin constructs  
Assessment: Irritating to skin.  
Method: OECD Test Guideline 439  
Result: Irritating to skin.  
GLP: yes

**1330-20-7 Xylene:**

Species: Rabbit  
Result: Moderate skin irritation

**100-41-4 Ethyl benzene:**

Species: Rabbit  
Result: Moderate skin irritation

**108-83-8 2,6-Dimethylheptan-4-one:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation  
GLP: yes

**108-31-6 Maleic anhydride:**

Species: Rabbit  
Method: No information available.  
Result: Corrosive to skin  
GLP: no

**Serious eye damage/eye irritation****Product:**

Remarks: Causes serious eye irritation.

Species: Rabbit  
Result: No eye irritation  
Assessment: No eye irritation  
Method: OECD Test Guideline 405

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
GLP: yes

**1330-20-7 Xylene:**

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Species: Rabbit  
Result: Eye irritation

**100-41-4 Ethyl benzene:**

Species: Rabbit  
Result: Moderate eye irritation

**108-83-8 2,6-Dimethylheptan-4-one:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
GLP: no

**108-31-6 Maleic anhydride:**

Species: Rabbit  
Result: Corrosive to eyes  
GLP: yes

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Components:****85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Test Type: Mouse Local Lymph Node assay (LLNA)  
Species: Mouse  
Assessment: May cause sensitisation by skin contact.  
Method: OECD Test Guideline 429  
Result: May cause sensitisation by skin contact.  
GLP: yes

**108-83-8 2,6-Dimethylheptan-4-one:**

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Not a skin sensitizer.  
GLP: yes

**108-31-6 Maleic anhydride:**

Test Type: Buehler Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Causes sensitisation.  
GLP: yes

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**Germ cell mutagenicity**
**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:**
**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Genotoxicity in vitro : Test Type: Ames test  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative  
 GLP: yes

: Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 476  
 Result: negative  
 GLP: yes

: Test Type: Chromosome aberration test in vitro  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 473  
 Result: negative  
 GLP: yes

**Carcinogenicity**
**Product:**

Remarks: No data available

**IARC**

Group 2B: Possibly carcinogenic to humans

Ethyl benzene 100-41-4

Cumene 98-82-8

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

Reasonably anticipated to be a human carcinogen

Cumene 98-82-8

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**Components:****85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**Effects on fertility :  
Species: Rat  
Sex: male and female  
Application Route: Oral  
NOAEL: 1,000 mg/kg,  
F1: > 1,000 mg/kg,  
Method: OECD Test Guideline 422  
GLP: yesEffects on foetal development : Species: Rat  
Application Route: Oral  
> 1,000 mg/kg  
1,000 mg/kg  
Method: OECD Test Guideline 422  
GLP: yes**STOT - single exposure****Product:**

Remarks: No data available

**STOT - repeated exposure****Product:**

Remarks: No data available

**Repeated dose toxicity****Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver, kidney, brain, respiratory system, blood, and/or bone marrow in laboratory animals

Animal studies have shown Xylene to cause fetotoxic effects at dosage levels at or near maternal toxicity levels.

Excessive inhalation of Xylene has caused hearing loss in laboratory animals. Hexane used in conjunction w/Xylene greatly increased this effect. Chronic skin contact w/Xylene has caused dermatitis. Ingestion of Ethanol can increase effects of overexposure to Xylene.

Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**Components:****85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Species: Rat, male and female

NOAEL: 1,000 mg/kg

Application Route: Oral

Method: OECD Test Guideline 422

GLP: yes

Target Organs: Stomach

**Aspiration toxicity****Product:**

No data available

**Experience with human exposure****Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue)., May cause respiratory tract sensitization.

Skin contact:

Symptoms:

Contact may cause irritation and sensitization.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**
**Product:**

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other :  
aquatic invertebrates : Remarks: No data available

**Persistence and degradability**
**Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential**
**Product:**

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : No data available  
information

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

EPA Hazardous Waste : D001: Ignitable  
Code(s) : D018: Benzene

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Xylene, Diisobutyl ketone)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, Diisobutyl ketone)  
: )  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : UN 1993  
Proper shipping name : Flammable liquids, n.o.s.  
(Xylene, Diisobutyl ketone)  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION**

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	285

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene	1330-20-7	35.0 %
Ethyl benzene	100-41-4	8.3 %
Cumene	98-82-8	.4 %

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	35.0 %
Ethyl benzene	100-41-4	8.3 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	35.0 %
Ethyl benzene	100-41-4	8.3 %

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Non-volatile (Wt) : 48 - 52 %  
 Method: 22 (10min/150°C)  
 DIN EN ISO 3251  
 Non-volatile information is not a specification.

**US State Regulations**
**Massachusetts Right To Know**

Xylene	1330-20-7
Ethyl benzene	100-41-4
2,6-Dimethylheptan-4-one	108-83-8
Benzene	71-43-2

**Pennsylvania Right To Know**

Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids	85711-46-2
Xylene	1330-20-7
Ethyl benzene	100-41-4
2,6-Dimethylheptan-4-one	108-83-8
Maleic anhydride	108-31-6
Cumene	98-82-8
Toluene	108-88-3

**New Jersey Right To Know**

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-6454

**California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**

**BYK-P 104 SG**

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.