

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYK-W 907
UFI : SQ55-T0SN-7008-CV5E
Product code : 000000000000157812

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel
Telephone : +49 281 670-0
Telefax : +49 281 65735

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

Hazard pictograms	:													
Signal Word	:	Warning												
Hazard Statements	:	<table><tr><td>H226</td><td>Flammable liquid and vapor.</td></tr><tr><td>H317</td><td>May cause an allergic skin reaction.</td></tr><tr><td>H319</td><td>Causes serious eye irritation.</td></tr><tr><td>H335</td><td>May cause respiratory irritation.</td></tr><tr><td>H411</td><td>Toxic to aquatic life with long lasting effects.</td></tr></table>	H226	Flammable liquid and vapor.	H317	May cause an allergic skin reaction.	H319	Causes serious eye irritation.	H335	May cause respiratory irritation.	H411	Toxic to aquatic life with long lasting effects.		
H226	Flammable liquid and vapor.													
H317	May cause an allergic skin reaction.													
H319	Causes serious eye irritation.													
H335	May cause respiratory irritation.													
H411	Toxic to aquatic life with long lasting effects.													
Precautionary Statements	:	Prevention: <table><tr><td>P210</td><td>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</td></tr><tr><td>P261</td><td>Avoid breathing mist or vapors.</td></tr><tr><td>P273</td><td>Avoid release to the environment.</td></tr><tr><td>P280</td><td>Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.</td></tr></table> Response: <table><tr><td>P370 + P378</td><td>In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.</td></tr><tr><td>P391</td><td>Collect spillage.</td></tr></table>	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	P261	Avoid breathing mist or vapors.	P273	Avoid release to the environment.	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.	P391	Collect spillage.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.													
P261	Avoid breathing mist or vapors.													
P273	Avoid release to the environment.													
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.													
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.													
P391	Collect spillage.													

Hazardous ingredients which must be listed on the label:

- 98-83-9 2-phenylpropene
- 868-77-9 2-hydroxyethyl methacrylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solution of a copolymer with filler affinic groups

Components

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-phenylpropene	98-83-9 202-705-0 01-2119472426-35	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit STOT SE 3; H335 ≥ 25 %	≥ 30 - < 50
2-hydroxyethyl methacrylate	868-77-9 212-782-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	≥ 1 - < 3
1-methoxy-2-propanol	107-98-2 203-539-1 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	≥ 1 - < 3

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|---|
| Symptoms | : No information available. |
| Risks | : May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|-----------------------------|
| Treatment | : No information available. |
|-----------|-----------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |

5.2 Special hazards arising from the substance or mixture

- | | |
|---------------------------------------|---|
| Specific hazards during fire fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Nitrogen oxides (NO _x)
Carbon oxides |

5.3 Advice for firefighters

- | | |
|--|---|
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- | | |
|----------------------|---|
| Personal precautions | : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. |
|----------------------|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible
absorbent material, (e.g. sand, earth, diatomaceous earth,
vermiculite) and place in container for disposal according to
local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national
regulations.
Persons susceptible to skin sensitization problems or asthma,
allergies, chronic or recurrent respiratory disease should not
be employed in any process in which this mixture is being
used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge
(which might cause ignition of organic vapors). Keep away
from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-
ventilated place. Containers which are opened must be
carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with
the technological safety standards.

Further information on : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0

SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025

Print Date: 16.12.2025

storage stability

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-phenylpropene	98-83-9	TWA	50 ppm 246 mg/m ³	2000/39/EC
	Further information: Indicative			
		STEL	100 ppm 492 mg/m ³	2000/39/EC
	Further information: Indicative			
		TWA	50 ppm 246 mg/m ³	MT OEL
		STEL	100 ppm 492 mg/m ³	MT OEL
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm 568 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	100 ppm 375 mg/m ³	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		STEL	150 ppm 568 mg/m ³	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Routes of exposure	Potential health effects	Value
2-phenylpropene	Workers	Inhalation	Long-term exposure	246 mg/m ³
	Workers	Skin contact	Long-term exposure	38 mg/kg
2-hydroxyethyl methacrylate	Workers	Inhalation	Long-term exposure	4,9 mg/m ³
	Workers	Skin contact	Long-term exposure	1,3 mg/kg
1-methoxy-2-propanol	Workers	Inhalation	Acute local effects	553,5 mg/m ³
	Workers	Skin contact	Long-term systemic effects	50,6 mg/kg
	Workers	Inhalation	Long-term systemic	369 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0

SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025

Print Date: 16.12.2025

			effects	
	Consumers	Skin contact	Long-term systemic effects	18,1 mg/kg
	Consumers	Inhalation	Long-term systemic effects	43,9 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,3 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2-phenylpropene	Fresh water	0,008 mg/l
	Sea water	0,0008 mg/l
	Intermittent releases	0,01645 mg/l
	Fresh water sediment	0,583 mg/kg
	Sea sediment	0,0583 mg/kg
	Soil	0,112 mg/kg
	Sewage treatment plant	66,15 mg/l
2-hydroxyethyl methacrylate	Fresh water	0,482 mg/l
1-methoxy-2-propanol	Fresh water	10 mg/l
	Sea water	1 mg/l
	Intermittent releases	100 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	41,6 mg/kg
	Sea sediment	4,17 mg/kg
	Soil	2,47 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapor formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	yellow - brown
Odor	:	characteristic
Odor Threshold	:	No data available
Solidification / Setting point	:	< 0 °C Method: derived
Initial boiling point	:	120 °C Method: derived
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	42 °C Method: 49 (Pensky-Martens)
Autoignition temperature	:	> 200 °C Method: M0062 (Analytics Wesel)
Decomposition temperature	:	No data available
pH	:	7 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity Viscosity, kinematic	:	No data available
Solubility(ies) Water solubility	:	partly soluble
Partition coefficient: n-octanol/water	:	No data available
Vapor pressure	:	11,5 mbar Method: derived
Density	:	0,994 g/cm ³ (20 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

Relative vapor density : No data available

9.2 Other information

Evaporation rate : No data available

Surface tension : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Free radical initiators
Oxidizing agents
Powdered metal salts

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Components:

1-methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat, male and female): 4.016 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2.000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.
GLP: yes

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

1-methoxy-2-propanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Causes serious eye irritation.

Components:

1-methoxy-2-propanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.5.
Result : No eye irritation
GLP : yes

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Product:

Remarks : Causes sensitization.

Components:

1-methoxy-2-propanol:

Test Type : Maximization Test
Routes of exposure : Dermal

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

Species	:	Guinea pig
Method	:	Directive 67/548/EEC, Annex V, B.6.
Result	:	Does not cause skin sensitization.
GLP	:	yes

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

STOT-single exposure

May cause respiratory irritation.

Product:

Remarks : No data available

STOT-repeated exposure

Not classified due to lack of data.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

Aspiration toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

Product:

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

2-phenylpropene:

Toxicity to fish : LC50 (Brachydanio rerio (Zebrafisch)): 2,97 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,645 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 2,26 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

EC50 (Desmodesmus subspicatus (green algae)): 11,441 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

Method: OECD Test Guideline 201
GLP: yes

2-hydroxyethyl methacrylate:

Toxicity to fish : LC50 (*Oryzias latipes* (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 380 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : ErC50 (*Selenastrum capricornutum* (green algae)): 836 mg/l
plants
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other : NOEC: 24,1 mg/l
aquatic invertebrates
(Chronic toxicity)
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

1-methoxy-2-propanol:

Toxicity to fish : LC50 (*Leuciscus idus* (Golden orfe)): 6.812 mg/l
Exposure time: 96 h
Test Type: static test
Method: DIN 38412
GLP: no

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

2-phenylpropene:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301D
GLP: yes

2-hydroxyethyl methacrylate:

Biodegradability : Test Type: aerobic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

Result: Readily biodegradable.
Method: OECD Test Guideline 301C
GLP: yes

1-methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

2-hydroxyethyl methacrylate:

Partition coefficient: n-octanol/water : log Pow: 0,42 (25 °C)
pH: > 5,9 - < 6,1
Method: OECD Test Guideline 107
GLP: yes

1-methoxy-2-propanol:

Partition coefficient: n-octanol/water : log Pow: 0,37 (20 °C)
pH: 6,8
Method: OECD Test Guideline 117
GLP: No information available.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0

SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025

Print Date: 16.12.2025

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1993
IMDG : UN 1993
IATA : UN 1993

14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, N.O.S.
(Isopropenylbenzene, 1-Methoxy-2-propanol)
IMDG : FLAMMABLE LIQUID, N.O.S.
(Isopropenylbenzene, 1-Methoxy-2-propanol)
IATA : Flammable liquid, n.o.s.
(Isopropenylbenzene, 1-Methoxy-2-propanol)

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0

SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025

Print Date: 16.12.2025

Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : IMDG Code segregation group - none

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355
(passenger aircraft)
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0

SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025

Print Date: 16.12.2025

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	:	This product does not contain substances of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FLAMMABLE LIQUIDS
	E2	ENVIRONMENTAL HAZARDS

15.2 Chemical Safety Assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226	:	Flammable liquid and vapor.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
MT OEL	:	Malta. Occupational Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
MT OEL / TWA	:	Long term exposure limit
MT OEL / STEL	:	Occupational exposure limit value Short-term, 15 minute

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MT / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 907

Version: 5.0
SDB_MT

Revision Date: 12.12.2025

Date of last issue: 12.12.2025
Print Date: 16.12.2025
