

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYK-W 974  
Product code : 000000000000144810

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735  
  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

Europe +44 1235 239670  
Middle East/Africa +44 1235 239671  
Americas +1 215 207 0061  
East/South East Asia +65 3158 1074  
(Local India: 000 800 100 7479)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                                                                                      |                                                                          |
|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| Flammable liquids, Category 3                                                        | H226: Flammable liquid and vapour.                                       |
| Skin irritation, Category 2                                                          | H315: Causes skin irritation.                                            |
| Eye irritation, Category 2                                                           | H319: Causes serious eye irritation.                                     |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                                  |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.                                 |
| Specific target organ toxicity - repeated exposure, Category 2                       | H373: May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard, Category 1                                                        | H304: May be fatal if swallowed and enters                               |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

Long-term (chronic) aquatic hazard,  
Category 3

airways.  
H412: Harmful to aquatic life with long lasting  
effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged  
or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open  
flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.

#### **Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON  
CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or  
alcohol-resistant foam to extinguish.

#### Hazardous components which must be listed on the label:

- 1330-20-7 Xylene, mixture of isomers
- 108-65-6 2-methoxy-1-methylethyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Solution of modified polyurethane

##### Components

| Chemical name                   | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                                                                                                                                                                               | Concentration<br>(% w/w) |
|---------------------------------|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Xylene, mixture of isomers      | 1330-20-7<br>01-2119488216-32                         | Eye Irrit. 2; H319<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br>Asp. Tox. 1; H304<br>Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Aquatic Chronic 3;<br>H412 | >= 20 - < 25             |
| 2-methoxy-1-methylethyl acetate | 108-65-6<br>203-603-9<br>01-2119475791-29             | STOT SE 3; H336<br>Flam. Liq. 3; H226                                                                                                                                                                                        | >= 12,5 - < 20           |
| n-butyl acetate                 | 123-86-4<br>204-658-1<br>01-2119485493-29             | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous<br>system)<br>EUH066                                                                                                                                               | >= 10 - < 12,5           |
| ethylbenzene                    | 100-41-4<br>202-849-4                                 | Flam. Liq. 2; H225<br>Acute Tox. 4; H332<br>STOT RE 2; H373<br>(hearing organs)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3;<br>H412                                                                                           | >= 7 - < 10              |

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

- Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

firefighting courses.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

- For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                      | CAS-No.                                                                                            | Value type (Form of exposure) | Control parameters               | Basis      |
|---------------------------------|----------------------------------------------------------------------------------------------------|-------------------------------|----------------------------------|------------|
| Xylene, mixture of isomers      | 1330-20-7                                                                                          | TWA                           | 50 ppm<br>221 mg/m <sup>3</sup>  | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |                               |                                  |            |
|                                 |                                                                                                    | STEL                          | 100 ppm<br>442 mg/m <sup>3</sup> | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |                               |                                  |            |
| 2-methoxy-1-methylethyl acetate | 108-65-6                                                                                           | TWA                           | 50 ppm<br>275 mg/m <sup>3</sup>  | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |                               |                                  |            |
|                                 |                                                                                                    | STEL                          | 100 ppm<br>550 mg/m <sup>3</sup> | 2000/39/EC |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

|                 |                                                                                                    |      |                      |              |
|-----------------|----------------------------------------------------------------------------------------------------|------|----------------------|--------------|
|                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |      |                      |              |
| n-butyl acetate | 123-86-4                                                                                           | STEL | 150 ppm<br>723 mg/m3 | 2019/1831/EU |
|                 | Further information: Indicative                                                                    |      |                      |              |
|                 |                                                                                                    | TWA  | 50 ppm<br>241 mg/m3  | 2019/1831/EU |
|                 | Further information: Indicative                                                                    |      |                      |              |
| ethylbenzene    | 100-41-4                                                                                           | TWA  | 100 ppm<br>442 mg/m3 | 2000/39/EC   |
|                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |      |                      |              |
|                 |                                                                                                    | STEL | 200 ppm<br>884 mg/m3 | 2000/39/EC   |
|                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |      |                      |              |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name                  | End Use   | Exposure routes | Potential health effects   | Value      |
|---------------------------------|-----------|-----------------|----------------------------|------------|
| Xylene, mixture of isomers      | Workers   | Inhalation      | Long-term systemic effects | 221 mg/m3  |
|                                 | Workers   | Inhalation      | Acute local effects        | 442 mg/m3  |
|                                 | Workers   | Dermal          | Long-term systemic effects | 212 mg/kg  |
|                                 | Consumers | Inhalation      | Long-term systemic effects | 65,3 mg/m3 |
|                                 | Consumers | Dermal          | Long-term systemic effects | 125 mg/kg  |
|                                 | Consumers | Oral            | Long-term systemic effects | 1,5 mg/kg  |
| 2-methoxy-1-methylethyl acetate | Consumers | Inhalation      | Acute local effects        | 260 mg/m3  |
|                                 | Workers   | Skin contact    | Long-term systemic effects | 796 mg/kg  |
|                                 | Workers   | Inhalation      | Long-term systemic effects | 275 mg/m3  |
|                                 | Consumers | Skin contact    | Long-term systemic effects | 320 mg/kg  |
|                                 | Consumers | Inhalation      | Long-term systemic effects | 33 mg/m3   |
|                                 | Consumers | Ingestion       | Long-term systemic effects | 36 mg/kg   |
| n-butyl acetate                 | Workers   | Inhalation      | Acute local effects        | 550 mg/m3  |
|                                 | Consumers | Inhalation      | Acute local effects        | 33 mg/m3   |
|                                 | Workers   | Inhalation      | Acute local effects        | 600 mg/m3  |
|                                 | Workers   | Inhalation      | Long-term local effects    | 300 mg/m3  |
|                                 | Consumers | Inhalation      | Acute local effects        | 300 mg/m3  |
|                                 | Consumers | Inhalation      | Long-term local effects    | 35,7 mg/m3 |
|                                 | Workers   | Dermal          | Long-term systemic effects | 11 mg/kg   |
|                                 |           |                 |                            |            |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

|  |           |        |                            |          |
|--|-----------|--------|----------------------------|----------|
|  | Workers   | Dermal | Acute systemic effects     | 11 mg/kg |
|  | Consumers | Dermal | Long-term systemic effects | 6 mg/kg  |
|  | Consumers | Dermal | Acute systemic effects     | 6 mg/kg  |
|  | Consumers | Oral   | Long-term systemic effects | 2 mg/m3  |
|  | Consumers | Oral   | Acute systemic effects     | 2 mg/m3  |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name                  | Environmental Compartment | Value        |
|---------------------------------|---------------------------|--------------|
| Xylene, mixture of isomers      | Fresh water               | 0,327 mg/l   |
|                                 | Marine water              | 0,327 mg/l   |
|                                 | Fresh water sediment      | 12,46 mg/kg  |
|                                 | Marine sediment           | 12,46 mg/kg  |
|                                 | Soil                      | 2,31 mg/kg   |
|                                 | Sewage treatment plant    | 6,58 mg/l    |
| 2-methoxy-1-methylethyl acetate | Intermittent releases     | 0,327 mg/l   |
|                                 | Fresh water               | 0,635 mg/l   |
|                                 | Marine water              | 0,0635 mg/l  |
|                                 | Intermittent releases     | 6,35 mg/l    |
|                                 | Sewage treatment plant    | 100 mg/l     |
|                                 | Fresh water sediment      | 3,29 mg/kg   |
| n-butyl acetate                 | Marine sediment           | 0,329 mg/kg  |
|                                 | Soil                      | 0,29 mg/kg   |
|                                 | Fresh water               | 0,18 mg/l    |
|                                 | Marine water              | 0,018 mg/l   |
|                                 | Intermittent releases     | 0,36 mg/l    |
|                                 | Fresh water sediment      | 0,981 mg/kg  |
|                                 | Marine sediment           | 0,0981 mg/kg |
|                                 | Soil                      | 0,0903 mg/kg |
|                                 | Sewage treatment plant    | 35,6 mg/l    |

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : Fluorinated rubber  
Break through time : > 480 min  
Glove thickness : >= 0,4 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

Respiratory protection : concentration of the dangerous substance at the work place.  
: In the case of vapour formation use a respirator with an approved filter.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : colourless  
light yellow

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : < 0 °C  
Method: derived

Initial boiling point : 125 °C  
Method: derived

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 26 °C  
Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature : > 200 °C  
Method: DIN 51794

Decomposition temperature : No data available

pH : 6 (20 °C)  
Concentration: 1 %  
Method: Universal pH-value indicator

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 92 mm<sup>2</sup>/s (20 °C)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

|                                        |                                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------|
| Solubility(ies)                        |                                                                                     |
| Water solubility                       | : immiscible                                                                        |
| Solubility in other solvents           | : No data available                                                                 |
| Partition coefficient: n-octanol/water | : No data available                                                                 |
| Vapour pressure                        | : 12 hPa (20 °C)<br>Method: derived                                                 |
| Relative density                       | : No data available                                                                 |
| Density                                | : 0,976 g/cm <sup>3</sup> (20 °C, 1.013 hPa)<br>Method: 4 (20°C oscillating U-tube) |
| Bulk density                           | : Not applicable                                                                    |
| Relative vapour density                | : No data available                                                                 |

### 9.2 Other information

|                        |                       |
|------------------------|-----------------------|
| Flammability (liquids) | : Sustains combustion |
| Evaporation rate       | : No data available   |

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

|                     |                                                       |
|---------------------|-------------------------------------------------------|
| Hazardous reactions | : No decomposition if stored and applied as directed. |
|                     | Vapours may form explosive mixture with air.          |

### 10.4 Conditions to avoid

|                     |                            |
|---------------------|----------------------------|
| Conditions to avoid | : Heat, flames and sparks. |
|---------------------|----------------------------|

### 10.5 Incompatible materials

|                    |                           |
|--------------------|---------------------------|
| Materials to avoid | : Strong oxidizing agents |
|--------------------|---------------------------|

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Product:

- |                           |                                                                                                                     |
|---------------------------|---------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity       | : Remarks: No data available                                                                                        |
| Acute inhalation toxicity | : Acute toxicity estimate: > 20 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour<br>Method: Calculation method |
| Acute dermal toxicity     | : Acute toxicity estimate: > 2.000 mg/kg<br>Method: Calculation method                                              |

##### Components:

##### Xylene, mixture of isomers:

- |                       |                                                                                                  |
|-----------------------|--------------------------------------------------------------------------------------------------|
| Acute oral toxicity   | : LD50 (Rat): 4.300 mg/kg<br>Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)<br>GLP: no |
| Acute dermal toxicity | : LD50 (Rabbit): > 4.200 mg/kg<br>GLP: No information available.                                 |

##### 2-methoxy-1-methylethyl acetate:

- |                     |                                                                                    |
|---------------------|------------------------------------------------------------------------------------|
| Acute oral toxicity | : LD50 (Rat, female): > 5.000 mg/kg<br>Method: OECD Test Guideline 401<br>GLP: yes |
|---------------------|------------------------------------------------------------------------------------|

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

##### n-butyl acetate:

- |                           |                                                                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity       | : LD50 (Rat, male): > 10.000 mg/kg<br>Method: OECD Test Guideline 423                                                                      |
| Acute inhalation toxicity | : LC50 (Rat, male and female): > 21,1 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour<br>Method: OECD Test Guideline 403<br>GLP: yes |
| Acute dermal toxicity     | : LD50 (Rabbit, male and female): > 14.000 mg/kg<br>Method: OECD Test Guideline 402                                                        |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### Skin corrosion/irritation

Causes skin irritation.

#### Product:

Remarks : May irritate skin.  
May cause skin irritation in susceptible persons.

#### Components:

##### 2-methoxy-1-methylethyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

##### n-butyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Product:

Remarks : Causes serious eye irritation.

#### Components:

##### 2-methoxy-1-methylethyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

##### n-butyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Product:

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### Components:

#### **2-methoxy-1-methylethyl acetate:**

|         |   |                         |
|---------|---|-------------------------|
| Species | : | Guinea pig              |
| Method  | : | OECD Test Guideline 406 |
| Result  | : | Not a skin sensitizer.  |
| GLP     | : | yes                     |

#### **n-butyl acetate:**

|           |   |                                    |
|-----------|---|------------------------------------|
| Test Type | : | Buehler Test                       |
| Species   | : | Guinea pig                         |
| Method    | : | OECD Test Guideline 406            |
| Result    | : | Does not cause skin sensitisation. |

### **Germ cell mutagenicity**

Not classified due to lack of data.

### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

### **Carcinogenicity**

Not classified due to lack of data.

### Product:

Remarks : No data available

### **Reproductive toxicity**

Not classified due to lack of data.

### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### **STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

### Product:

Remarks : No data available

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### **Product:**

Remarks : No data available

### **Repeated dose toxicity**

### **Product:**

Remarks : No data available

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Product:**

No data available

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

Not classified due to lack of data.

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

### **Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

### **Product:**

Toxicity to fish : Remarks: No data available

### **Components:**

### **Xylene, mixture of isomers:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l  
Exposure time: 24 h  
Test Type: Immobilization

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (*Selenastrum capricornutum* (green algae)): 2,2 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 0,44 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: *Oncorhynchus mykiss* (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: *Daphnia* sp. (water flea)

NOEC: 0,96 mg/l  
Exposure time: 7 d  
Species: *Daphnia* sp. (water flea)

### 2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: no

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: no

### n-butyl acetate:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (*Scenedesmus subspicatus*): 675 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other : NOEC: 23 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

aquatic invertebrates  
(Chronic toxicity)

End point: Reproduction  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

#### Components:

##### **Xylene, mixture of isomers:**

Biodegradability : Test Type: aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

##### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

##### **n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### **Xylene, mixture of isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Exposure time: 56 d  
Bioconcentration factor (BCF): 25,9  
GLP: no

Partition coefficient: n-octanol/water : Pow: 3,2 (20 °C)  
pH: 7

##### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8  
Method: OECD Test Guideline 117  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### **n-butyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 2,3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### **Product:**

Additional ecological  
information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### SECTION 14: Transport information

#### 14.1 UN number or ID number

|      |           |
|------|-----------|
| ADN  | : UN 1993 |
| ADR  | : UN 1993 |
| RID  | : UN 1993 |
| IMDG | : UN 1993 |
| IATA | : UN 1993 |

#### 14.2 UN proper shipping name

|      |                                                                      |
|------|----------------------------------------------------------------------|
| ADN  | : FLAMMABLE LIQUID, N.O.S.<br>(Xylene, 1-Methoxy-2-propanol acetate) |
| ADR  | : FLAMMABLE LIQUID, N.O.S.<br>(Xylene, 1-Methoxy-2-propanol acetate) |
| RID  | : FLAMMABLE LIQUID, N.O.S.<br>(Xylene, 1-Methoxy-2-propanol acetate) |
| IMDG | : FLAMMABLE LIQUID, N.O.S.<br>(XYLENE, 1-Methoxy-2-propanol acetate) |
| IATA | : Flammable liquid, n.o.s.<br>(Xylene, 1-Methoxy-2-propanol acetate) |

#### 14.3 Transport hazard class(es)

|      |     |
|------|-----|
| ADN  | : 3 |
| ADR  | : 3 |
| RID  | : 3 |
| IMDG | : 3 |
| IATA | : 3 |

#### 14.4 Packing group

|                              |       |
|------------------------------|-------|
| ADN                          |       |
| Packing group                | : III |
| Classification Code          | : F1  |
| Hazard Identification Number | : 30  |
| Labels                       | : 3   |
| ADR                          |       |
| Packing group                | : III |
| Classification Code          | : F1  |
| Hazard Identification Number | : 30  |
| Labels                       | : 3   |
| Tunnel restriction code      | : D/E |
| RID                          |       |
| Packing group                | : III |
| Classification Code          | : F1  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : IMDG Code segregation group - none

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries must be considered::  
Number on list 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

|                                                                                                                                                                  |                                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                  | Number on list 5: benzene                                                                                                    |
|                                                                                                                                                                  | Number on list 20: dibutyltin<br>dilaurate, tributyltin compounds                                                            |
|                                                                                                                                                                  | Number on list 72: benzene                                                                                                   |
|                                                                                                                                                                  | Number on list 75: If you intend to<br>use this product as tattoo ink, please<br>contact your vendor.                        |
| REACH - Candidate List of Substances of Very High<br>Concern for Authorisation (Article 59).                                                                     | : This product does not contain<br>substances of very high concern<br>(Regulation (EC) No<br>1907/2006 (REACH), Article 57). |
| REACH - List of substances subject to authorisation<br>(Annex XIV)                                                                                               | : Not applicable                                                                                                             |
| Fire Hazard Class                                                                                                                                                | : A II: Flash point 21 °C to 55 °C, at 15 °C not miscible in water                                                           |
| Seveso III: Directive 2012/18/EU of the<br>European Parliament and of the Council on the<br>control of major-accident hazards involving<br>dangerous substances. | P5c FLAMMABLE LIQUIDS                                                                                                        |

### 15.2 Chemical safety assessment

For further information see eSDS.

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the  
body of this document by two vertical lines.

### Full text of H-Statements

|        |                                                                         |
|--------|-------------------------------------------------------------------------|
| H225   | : Highly flammable liquid and vapour.                                   |
| H226   | : Flammable liquid and vapour.                                          |
| H304   | : May be fatal if swallowed and enters airways.                         |
| H312   | : Harmful in contact with skin.                                         |
| H315   | : Causes skin irritation.                                               |
| H319   | : Causes serious eye irritation.                                        |
| H332   | : Harmful if inhaled.                                                   |
| H335   | : May cause respiratory irritation.                                     |
| H336   | : May cause drowsiness or dizziness.                                    |
| H373   | : May cause damage to organs through prolonged or repeated<br>exposure. |
| H412   | : Harmful to aquatic life with long lasting effects.                    |
| EUH066 | : Repeated exposure may cause skin dryness or cracking.                 |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### Full text of other abbreviations

|                     |                                                                                                                        |
|---------------------|------------------------------------------------------------------------------------------------------------------------|
| Acute Tox.          | : Acute toxicity                                                                                                       |
| Aquatic Chronic     | : Long-term (chronic) aquatic hazard                                                                                   |
| Asp. Tox.           | : Aspiration hazard                                                                                                    |
| Eye Irrit.          | : Eye irritation                                                                                                       |
| Flam. Liq.          | : Flammable liquids                                                                                                    |
| Skin Irrit.         | : Skin irritation                                                                                                      |
| STOT RE             | : Specific target organ toxicity - repeated exposure                                                                   |
| STOT SE             | : Specific target organ toxicity - single exposure                                                                     |
| 2000/39/EC          | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values   |
| 2019/1831/EU        | : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| 2000/39/EC / TWA    | : Limit Value - eight hours                                                                                            |
| 2000/39/EC / STEL   | : Short term exposure limit                                                                                            |
| 2019/1831/EU / TWA  | : Limit Value - eight hours                                                                                            |
| 2019/1831/EU / STEL | : Short term exposure limit                                                                                            |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 974

Version: 11.1  
SDB\_REG\_EU

Revision Date: 20.07.2026

Date of last issue: 23.01.2026  
Print Date: 28.07.2026

### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| Skin Irrit. 2     | H315 |
| Eye Irrit. 2      | H319 |
| STOT SE 3         | H335 |
| STOT SE 3         | H336 |
| STOT RE 2         | H373 |
| Asp. Tox. 1       | H304 |
| Aquatic Chronic 3 | H412 |

### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG\_EU / EN