

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYK-W 995  
UFI : SUWC-S05P-A00T-RFPK  
Product code : 000000000000104402

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735  
  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

Europe +44 1235 239670  
Middle East/Africa +44 1235 239671  
Americas +1 215 207 0061  
East/South East Asia +65 3158 1074  
(Local India: 000 800 100 7479)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                                                                                      |                                                 |
|--------------------------------------------------------------------------------------|-------------------------------------------------|
| Flammable liquids, Category 3                                                        | H226: Flammable liquid and vapour.              |
| Skin corrosion, Sub-category 1B                                                      | H314: Causes severe skin burns and eye damage.  |
| Serious eye damage, Category 1                                                       | H318: Causes serious eye damage.                |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.        |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.         |
| Long-term (chronic) aquatic hazard,                                                  | H412: Harmful to aquatic life with long lasting |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Category 3

effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H314 Causes severe skin burns and eye damage.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Hazardous components which must be listed on the label:**

- 108-65-6 2-methoxy-1-methylethyl acetate
- 64742-95-6 Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified
- 7664-38-2 phosphoric acid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : solution of polymeric phosphoric acid ester

#### Components

| Chemical name                                                                     | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                                                                                                                                              | Concentration<br>(% w/w) |
|-----------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Phosphoric acid polyester                                                         | -                                                     | Eye Irrit. 2; H319                                                                                                                                                                          | >= 50 - <= 100           |
| 2-methoxy-1-methylethyl acetate                                                   | 108-65-6<br>203-603-9<br>01-2119475791-29             | STOT SE 3; H336<br>Flam. Liq. 3; H226                                                                                                                                                       | >= 20 - < 25             |
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | 64742-95-6<br>01-2119455851-35                        | STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Aquatic Chronic 2;<br>H411<br>Flam. Liq. 3; H226<br>Asp. Tox. 1; H304                             | >= 20 - < 25             |
| phosphoric acid                                                                   | 7664-38-2<br>231-633-2<br>01-2119485924-24            | Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br><br>specific concentration<br>limit<br>Skin Corr. 1B; H314<br>>= 25 %<br>Skin Irrit. 2; H315<br>10 - < 25 %<br>Eye Irrit. 2; H319<br>10 - < 25 % | >= 1 - < 3               |

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                         |   |                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice          | : | Move out of dangerous area.<br>Consult a physician.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.                                                                                                                                                                                                                                        |
| If inhaled              | : | Consult a physician after significant exposure.<br>If unconscious, place in recovery position and seek medical advice.                                                                                                                                                                                                                                                                        |
| In case of skin contact | : | Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.<br>If on skin, rinse well with water.<br>If on clothes, remove clothes.                                                                                                                                                                                              |
| In case of eye contact  | : | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.<br>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>Continue rinsing eyes during transport to hospital.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist. |
| If swallowed            | : | Keep respiratory tract clear.<br>Do NOT induce vomiting.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>Take victim immediately to hospital.                                                                                                                                              |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |                                                                                                                               |
|----------|---|-------------------------------------------------------------------------------------------------------------------------------|
| Symptoms | : | No information available.                                                                                                     |
| Risks    | : | Causes serious eye damage.<br>May cause respiratory irritation.<br>May cause drowsiness or dizziness.<br>Causes severe burns. |

#### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |                           |
|-----------|---|---------------------------|
| Treatment | : | No information available. |
|-----------|---|---------------------------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides  
Sulphur oxides  
Oxides of phosphorus

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

Store in original container.

- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

| Components                      | CAS-No.                                                                                            | Value type (Form of exposure) | Control parameters   | Basis      |
|---------------------------------|----------------------------------------------------------------------------------------------------|-------------------------------|----------------------|------------|
| 2-methoxy-1-methylethyl acetate | 108-65-6                                                                                           | TWA                           | 50 ppm<br>275 mg/m3  | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |                               |                      |            |
|                                 |                                                                                                    | STEL                          | 100 ppm<br>550 mg/m3 | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative |                               |                      |            |
| phosphoric acid                 | 7664-38-2                                                                                          | TWA                           | 1 mg/m3              | 2000/39/EC |
|                                 | Further information: Indicative                                                                    |                               |                      |            |
|                                 |                                                                                                    | STEL                          | 2 mg/m3              | 2000/39/EC |
|                                 | Further information: Indicative                                                                    |                               |                      |            |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name                                                                    | End Use   | Exposure routes | Potential health effects             | Value      |
|-----------------------------------------------------------------------------------|-----------|-----------------|--------------------------------------|------------|
| 2-methoxy-1-methylethyl acetate                                                   | Workers   | Skin contact    | Long-term systemic effects           | 796 mg/kg  |
|                                                                                   | Workers   | Inhalation      | Long-term systemic effects           | 275 mg/m3  |
|                                                                                   | Consumers | Skin contact    | Long-term systemic effects           | 320 mg/kg  |
|                                                                                   | Consumers | Inhalation      | Long-term systemic effects           | 33 mg/m3   |
|                                                                                   | Consumers | Ingestion       | Long-term systemic effects           | 36 mg/kg   |
|                                                                                   | Workers   | Inhalation      | Acute local effects                  | 550 mg/m3  |
|                                                                                   | Consumers | Inhalation      | Acute local effects                  | 33 mg/m3   |
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | Workers   | Skin contact    | Long-term exposure, Systemic effects | 25 mg/kg   |
|                                                                                   | Workers   | Inhalation      | Long-term exposure, Systemic effects | 150 mg/m3  |
|                                                                                   | Consumers | Skin contact    | Long-term exposure, Systemic effects | 11 mg/kg   |
|                                                                                   | Consumers | Inhalation      | Long-term exposure, Systemic effects | 32 mg/m3   |
|                                                                                   | Consumers | Ingestion       | Long-term exposure, Systemic effects | 11 mg/kg   |
| phosphoric acid                                                                   | Workers   | Inhalation      | Long-term local effects              | 1 mg/m3    |
|                                                                                   | Workers   | Inhalation      | Acute local effects                  | 2 mg/m3    |
|                                                                                   | Consumers | Inhalation      | Long-term local effects              | 0,73 mg/m3 |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|----------------|---------------------------|-------|
|----------------|---------------------------|-------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                 |                        |             |
|---------------------------------|------------------------|-------------|
| 2-methoxy-1-methylethyl acetate | Fresh water            | 0,635 mg/l  |
|                                 | Marine water           | 0,0635 mg/l |
|                                 | Intermittent releases  | 6,35 mg/l   |
|                                 | Sewage treatment plant | 100 mg/l    |
|                                 | Fresh water sediment   | 3,29 mg/kg  |
|                                 | Marine sediment        | 0,329 mg/kg |
|                                 | Soil                   | 0,29 mg/kg  |

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

#### Hand protection

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : 0,7 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

#### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : light yellow

Odour : odourless

Odour Threshold : No data available

Melting point/freezing point : < 0 °C  
Method: derived

Initial boiling point and boiling range : 146,00 °C  
Method: derived

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                  |   |                                                                                |
|--------------------------------------------------|---|--------------------------------------------------------------------------------|
| Upper explosion limit / Upper flammability limit | : | 10,80 %(V)                                                                     |
| Lower explosion limit / Lower flammability limit | : | 1,00 %(V)                                                                      |
| Flash point                                      | : | 42,00 °C<br>Method: 48 (Abel-Pensky) DIN 51755                                 |
| Auto-ignition temperature                        | : | > 200 °C<br>Method: DIN 51794                                                  |
| Decomposition temperature                        | : | No data available                                                              |
| pH                                               | : | 3,1 (20 °C)<br>Concentration: 1 %<br>Method: DIN 19268 (1% in water)           |
| Viscosity                                        |   |                                                                                |
| Viscosity, dynamic                               | : | No data available                                                              |
| Viscosity, kinematic                             | : | > 20,000 mm <sup>2</sup> /s (20,00 °C)<br>27,000 mm <sup>2</sup> /s (40,00 °C) |
| Solubility(ies)                                  |   |                                                                                |
| Water solubility                                 | : | immiscible                                                                     |
| Solubility in other solvents                     | : | No data available                                                              |
| Partition coefficient: n-octanol/water           | : | No data available                                                              |
| Vapour pressure                                  | : | 5 hPa (20,00 °C)<br>Method: derived                                            |
| Relative density                                 | : | No data available                                                              |
| Density                                          | : | 1,0250 g/cm <sup>3</sup> (20,00 °C)<br>Method: 4 (20°C oscillating U-tube)     |
| Bulk density                                     | : | Not applicable                                                                 |
| Relative vapour density                          | : | No data available                                                              |

### 9.2 Other information

|                        |   |                     |
|------------------------|---|---------------------|
| Flammability (liquids) | : | Sustains combustion |
| Evaporation rate       | : | No data available   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Gives off hydrogen by reaction with metals.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents  
Metals

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Product:

Acute oral toxicity : Remarks: No data available

##### Components:

##### Phosphoric acid polyester:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

##### 2-methoxy-1-methylethyl acetate:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3.160 mg/kg  
Method: OECD Test Guideline 402

### **phosphoric acid:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

### **Skin corrosion/irritation**

Causes severe burns.

### **Product:**

Species : EPISKIN human epidermis skin constructs  
Assessment : Causes burns.  
Method : OECD Test Guideline 431  
Result : Causes burns.  
GLP : yes

Remarks : Extremely corrosive and destructive to tissue.

### **Components:**

#### **Phosphoric acid polyester:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

#### **2-methoxy-1-methylethyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

### **phosphoric acid:**

Remarks : No data available

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Product:**

Remarks : May cause irreversible eye damage.

### **Components:**

#### **Phosphoric acid polyester:**

Species : Rabbit  
Assessment : Irritating to eyes.  
Result : Eye irritation  
GLP : yes

#### **2-methoxy-1-methylethyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### **phosphoric acid:**

Remarks : No data available

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified due to lack of data.

#### **Respiratory sensitisation**

Not classified due to lack of data.

### **Product:**

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### Components:

#### **2-methoxy-1-methylethyl acetate:**

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : yes

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

### Components:

#### **Phosphoric acid polyester:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Result: negative  
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse (male and female)  
Method: Mutagenicity (micronucleus test)  
Result: negative  
GLP: yes

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity- : Classified based on benzene content < 0.1% (Regulation (EC)  
Assessment 1272/2008, Annex VI, Part 3, Note P)

#### **Carcinogenicity**

Not classified due to lack of data.

### Product:

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Reproductive toxicity**

Not classified due to lack of data.

### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### **STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified due to lack of data.

### Product:

Remarks : No data available

#### **Repeated dose toxicity**

### Product:

Remarks : No data available

### Components:

#### **Phosphoric acid polyester:**

Species : Rat, male and female  
LOAEL : 4.000 mg/kg  
Application Route : Oral  
Method : OECD Test Guideline 407  
GLP : yes

#### **Aspiration toxicity**

Not classified due to lack of data.

### Product:

No data available

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### 11.2 Information on other hazards

#### Endocrine disrupting properties

Not classified due to lack of data.

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

#### Components:

##### Phosphoric acid polyester:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 770 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: DIN 38412  
GLP: no

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 130 mg/l  
Exposure time: 72 h  
GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 500 mg/l  
Exposure time: 16 h  
Test Type: Cell multiplication inhibition test  
Method: DIN 38412, L 8  
GLP: no

##### 2-methoxy-1-methylethyl acetate:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: no

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish : LL50 (Fish): 9,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata): 2,6 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

### **phosphoric acid:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

## **12.2 Persistence and degradability**

### **Product:**

Biodegradability : Remarks: No data available

### **Components:**

#### **Phosphoric acid polyester:**

Biodegradability : Result: Not readily biodegradable.  
Exposure time: 28 d

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Method: OECD Test Guideline 301  
GLP: no

### 2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation : Remarks: No data available

### Components:

#### 2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)  
octanol/water pH: 6,8  
Method: OECD Test Guideline 117  
GLP: yes

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological : An environmental hazard cannot be excluded in the event of

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

information

unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 2920  
IMDG : UN 2920  
IATA : UN 2920

#### 14.2 UN proper shipping name

- ADR : CORROSIVE LIQUID, FLAMMABLE, N.O.S.  
(Orthophosphoric acid, 1-Methoxy-2-propanol acetate)
- IMDG : CORROSIVE LIQUID, FLAMMABLE, N.O.S.  
(Orthophosphoric acid, 1-Methoxy-2-propanol acetate)
- IATA : Corrosive liquid, flammable, n.o.s.  
(Orthophosphoric acid, 1-Methoxy-2-propanol acetate)

#### 14.3 Transport hazard class(es)

- ADR : 8 (3)  
IMDG : 8 (3)  
IATA : 8 (3)

#### 14.4 Packing group

- ADR  
Packing group : II  
Classification Code : CF1  
Hazard Identification Number : 83  
Labels : 8 (3)  
Tunnel restriction code : D/E

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### IMDG

Packing group : II  
Labels : 8 (3)  
EmS Code : F-E, S-C  
Remarks : IMDG Code segregation group 1 - Acids

### IATA (Cargo)

Packing instruction (cargo aircraft) : 855  
Packing group : II  
Labels : Corrosives, Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 851  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosives, Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries must be considered:  
Number on list 3  
  
Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

REACH - List of substances subject to authorisation : Not applicable  
(Annex XIV)

Seveso III: Directive 2012/18/EU of the P5c FLAMMABLE LIQUIDS  
European Parliament and of the Council on the  
control of major-accident hazards involving  
dangerous substances.

### 15.2 Chemical safety assessment

For further information see eSDS.

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H314 : Causes severe skin burns and eye damage.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Corr. : Skin corrosion  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first  
list of indicative occupational exposure limit values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number -

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| Skin Corr. 1B     | H314 |
| Eye Dam. 1        | H318 |
| STOT SE 3         | H336 |
| STOT SE 3         | H335 |
| Aquatic Chronic 3 | H412 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Based on product data or assessment |
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG\_EU / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

## Annex: Exposure Scenarios

### Table of Contents

| Number | Title                                                                        |
|--------|------------------------------------------------------------------------------|
| ES 1   | Formulation & (re)packing of substances and mixtures; Industrial uses (SU3). |
| ES 2   | Use in coatings; Industrial uses (SU3).                                      |
| ES 3   | Use in coatings; Professional uses (SU22).                                   |
| ES 4   | Cleaning; Industrial uses (SU3).                                             |
| ES 5   | Cleaning; Professional uses (SU22).                                          |
| ES 6   | Use in laboratories; Industrial uses (SU3).                                  |
| ES 7   | Use in laboratories; Professional uses (SU22).                               |
| ES 8   | Cleaning; Consumer uses (SU21).                                              |
| ES 9   | Use in coatings; Consumer uses (SU21).                                       |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### ES 1: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).

#### 1.1. Title section

|                               |                                                                                   |
|-------------------------------|-----------------------------------------------------------------------------------|
| <b>Exposure Scenario name</b> | : Formulation & (re)packing of substances and mixtures                            |
| <b>Structured Short Title</b> | : Formulation & (re)packing of substances and mixtures;<br>Industrial uses (SU3). |

| Environment |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                 |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| <b>CS 1</b> | <b>Formulation into mixture, Use of non-reactive processing aid at industrial site (no inclusion into or onto article)</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ERC2, ERC4                                                                      |
| Worker      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                 |
| <b>CS 2</b> | <b>Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | PROC1                                                                           |
| <b>CS 3</b> | <b>Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | PROC2                                                                           |
| <b>CS 4</b> | <b>Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Mixing or blending in batch processes, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Transfer of substance or mixture into small containers (dedicated filling line, including weighing), Tableting, compression, extrusion, pelettisation, granulation, Use as laboratory reagent</b> | PROC3,<br>PROC4,<br>PROC5,<br>PROC8a,<br>PROC8b,<br>PROC9,<br>PROC14,<br>PROC15 |

#### 1.2. Conditions of use affecting exposure

##### 1.2.1. Control of environmental exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Product (article) characteristics                                              |          |
|--------------------------------------------------------------------------------|----------|
| Covers concentrations up to 100 %                                              |          |
| Physical form of product                                                       | : Liquid |
| Vapour pressure                                                                | : 50 hPa |
| Temperature                                                                    | : 20 °C  |
| Amount used (or contained in articles), frequency and duration of use/exposure |          |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                        |                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Annual amount per site                                                                 | : 730000 kg                                                                                                                                                                                                              |
| Release type                                                                           | : Continuous release                                                                                                                                                                                                     |
| Emission days                                                                          | : 100                                                                                                                                                                                                                    |
| <b>Conditions and measures related to sewage treatment plant</b>                       |                                                                                                                                                                                                                          |
| STP type                                                                               | : Municipal sewage treatment plant                                                                                                                                                                                       |
| STP sludge treatment                                                                   | : No application of sewage sludge to soil<br>Sewage sludge should be incinerated, contained or reclaimed.                                                                                                                |
| <b>Conditions and measures related to treatment of waste (including article waste)</b> |                                                                                                                                                                                                                          |
| Waste treatment                                                                        | : External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b>                               |                                                                                                                                                                                                                          |
| Local freshwater dilution factor                                                       | : 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                                                     | : 100                                                                                                                                                                                                                    |

### 1.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

|                                                                                       |                                                                |
|---------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                              |                                                                |
| Covers concentrations up to 100 %                                                     |                                                                |
| Physical form of product                                                              | : Liquid                                                       |
| Vapour pressure                                                                       | : 5 hPa                                                        |
| Temperature                                                                           | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b> |                                                                |
| Duration                                                                              | : 480 min                                                      |
| Use frequency                                                                         | : 5 days per week                                              |
| <b>Technical and organisational conditions and measures</b>                           |                                                                |
| Store substance within a closed system.                                               |                                                                |
| <b>Other conditions affecting workers exposure</b>                                    |                                                                |
| Temperature                                                                           | : Assumes use at not more than 20°C above ambient temperature. |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

**Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply**

Assumes a good basic standard of occupational hygiene is implemented

### 1.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

| Product (article) characteristics                                                             |                                                                |
|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 100 %                                                             |                                                                |
| Physical form of product                                                                      | : Liquid                                                       |
| Vapour pressure                                                                               | : 5 hPa                                                        |
| Temperature                                                                                   | : 20 °C                                                        |
| Amount used (or contained in articles), frequency and duration of use/exposure                |                                                                |
| Duration                                                                                      | : 480 min                                                      |
| Use frequency                                                                                 | : 5 days per week                                              |
| Technical and organisational conditions and measures                                          |                                                                |
| Store substance within a closed system.                                                       |                                                                |
| Other conditions affecting workers exposure                                                   |                                                                |
| Temperature                                                                                   | : Assumes use at not more than 20°C above ambient temperature. |
| Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                          |                                                                |

### 1.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Tableting, compression, extrusion, pelettisation, granulation (PROC14) / Use as laboratory reagent (PROC15)

| Product (article) characteristics |
|-----------------------------------|
| Covers concentrations up to 100 % |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                                      |                                                                |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Physical form of product                                                                             | : Liquid                                                       |
| Vapour pressure                                                                                      | : 5 hPa                                                        |
| Temperature                                                                                          | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>                |                                                                |
| Duration                                                                                             | : 480 min                                                      |
| Use frequency                                                                                        | : 5 days per week                                              |
| <b>Other conditions affecting workers exposure</b>                                                   |                                                                |
| Temperature                                                                                          | : Assumes use at not more than 20°C above ambient temperature. |
| <b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b> |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                                 |                                                                |

### 1.3. Exposure estimation and reference to its source

#### 1.3.1. Environmental release and exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 10 kg/day    |                           |
| Waste         | 0,2 kg/day   |                           |
| Soil          | 0,1 kg/day   |                           |

### 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### ES 2: Use in coatings; Industrial uses (SU3).

#### 2.1. Title section

|                        |                                           |
|------------------------|-------------------------------------------|
| Exposure Scenario name | : Use in coatings                         |
| Structured Short Title | : Use in coatings; Industrial uses (SU3). |

| Environment |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                   |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| CS 1        | Use of non-reactive processing aid at industrial site (no inclusion into or onto article)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | ERC4                                                                              |
| Worker      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                   |
| CS 2        | Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | PROC1                                                                             |
| CS 3        | Industrial spraying                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | PROC7                                                                             |
| CS 4        | Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Mixing or blending in batch processes, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Transfer of substance or mixture into small containers (dedicated filling line, including weighing), Roller application or brushing, Treatment of articles by dipping and pouring, Tableting, compression, extrusion, pelettisation, granulation, Use as laboratory reagent | PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15 |

#### 2.2. Conditions of use affecting exposure

##### 2.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Product (article) characteristics                                              |          |
|--------------------------------------------------------------------------------|----------|
| Covers concentrations up to 100 %                                              |          |
| Physical form of product                                                       | : Liquid |
| Vapour pressure                                                                | : 5 hPa  |
| Temperature                                                                    | : 20 °C  |
| Amount used (or contained in articles), frequency and duration of use/exposure |          |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                        |                                                                                                             |
|----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Release type                                                                           | : Continuous release                                                                                        |
| Emission days                                                                          | : 300                                                                                                       |
| <b>Conditions and measures related to sewage treatment plant</b>                       |                                                                                                             |
| STP type                                                                               | : Municipal Sewage Treatment Plant                                                                          |
| STP sludge treatment                                                                   | : Sewage sludge should be incinerated, contained or reclaimed.                                              |
| <b>Conditions and measures related to treatment of waste (including article waste)</b> |                                                                                                             |
| Waste treatment                                                                        | : External treatment and disposal of waste should comply with applicable local and/or national regulations. |
| Waste treatment                                                                        | : External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b>                               |                                                                                                             |
| Local freshwater dilution factor                                                       | : 10                                                                                                        |
| Local marine water dilution factor                                                     | : 100                                                                                                       |

### 2.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

|                                                                                                      |                                                                |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                                             |                                                                |
| Covers concentrations up to 100 %                                                                    |                                                                |
| Physical form of product                                                                             | : Liquid                                                       |
| Vapour pressure                                                                                      | : 5 hPa                                                        |
| Temperature                                                                                          | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>                |                                                                |
| Duration                                                                                             | : 480 min                                                      |
| Use frequency                                                                                        | : 5 days per week                                              |
| <b>Technical and organisational conditions and measures</b>                                          |                                                                |
| Store substance within a closed system.                                                              |                                                                |
| <b>Other conditions affecting workers exposure</b>                                                   |                                                                |
| Temperature                                                                                          | : Assumes use at not more than 20°C above ambient temperature. |
| <b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b> |                                                                |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Assumes a good basic standard of occupational hygiene is implemented

### 2.2.3. Control of worker exposure: Industrial spraying (PROC7)

| Product (article) characteristics                                                     |                                                                |
|---------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 100 %                                                     |                                                                |
| Physical form of product                                                              | : Liquid                                                       |
| Vapour pressure                                                                       | : 5 hPa                                                        |
| Temperature                                                                           | : 20 °C                                                        |
| Amount used (or contained in articles), frequency and duration of use/exposure        |                                                                |
| Duration                                                                              | : 480 min                                                      |
| Use frequency                                                                         | : 5 days per week                                              |
| Conditions and measures related to personal protection, hygiene and health evaluation |                                                                |
| Wear a respirator conforming to EN140.                                                |                                                                |
| Other conditions affecting workers exposure                                           |                                                                |
| Temperature                                                                           | : Assumes use at not more than 20°C above ambient temperature. |

**2.2.4. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9) / Roller application or brushing (PROC10) / Treatment of articles by dipping and pouring (PROC13) / Tableting, compression, extrusion, pelettisation, granulation (PROC14) / Use as laboratory reagent (PROC15)**

| Product (article) characteristics |          |
|-----------------------------------|----------|
| Covers concentrations up to 100 % |          |
| Physical form of product          | : Liquid |
| Vapour pressure                   | : 5 hPa  |
| Temperature                       | : 20 °C  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

| Amount used (or contained in articles), frequency and duration of use/exposure |                                                                |
|--------------------------------------------------------------------------------|----------------------------------------------------------------|
| Duration                                                                       | : 480 min                                                      |
| Use frequency                                                                  | : 5 days per week                                              |
| Other conditions affecting workers exposure                                    |                                                                |
| Temperature                                                                    | : Assumes use at not more than 20°C above ambient temperature. |

### 2.3. Exposure estimation and reference to its source

#### 2.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 980 kg/day   |                           |
| Waste         | 0,7 kg/day   |                           |
| Soil          | 0 kg/day     |                           |

### 2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### ES 3: Use in coatings; Professional uses (SU22).

#### 3.1. Title section

|                        |                                              |
|------------------------|----------------------------------------------|
| Exposure Scenario name | : Use in coatings                            |
| Structured Short Title | : Use in coatings; Professional uses (SU22). |

| Environment |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                       |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| CS 1        | Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor), Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ERC8a,<br>ERC8d                                                                                       |
| Worker      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                       |
| CS 2        | Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | PROC1                                                                                                 |
| CS 3        | Non-industrial spraying                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | PROC11                                                                                                |
| CS 4        | Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Mixing or blending in batch processes, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Roller application or brushing, Treatment of articles by dipping and pouring, Use as laboratory reagent, Manual activities involving hand contact | PROC2,<br>PROC3,<br>PROC4,<br>PROC5,<br>PROC8a,<br>PROC8b,<br>PROC10,<br>PROC13,<br>PROC15,<br>PROC19 |

#### 3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

| Product (article) characteristics |          |
|-----------------------------------|----------|
| Covers concentrations up to 100 % |          |
| Physical form of product          | : Liquid |
| Vapour pressure                   | : 5 hPa  |
| Temperature                       | : 20 °C  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### 3.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

| Product (article) characteristics                                              |                                                                |
|--------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 100 %                                              |                                                                |
| Physical form of product                                                       | : Liquid                                                       |
| Vapour pressure                                                                | : 5 hPa                                                        |
| Temperature                                                                    | : 20 °C                                                        |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                                |
| Duration                                                                       | : 480 min                                                      |
| Use frequency                                                                  | : 5 days per week                                              |
| Technical and organisational conditions and measures                           |                                                                |
| Store substance within a closed system.                                        |                                                                |
| Other conditions affecting workers exposure                                    |                                                                |
| Temperature                                                                    | : Assumes use at not more than 20°C above ambient temperature. |

### 3.2.3. Control of worker exposure: Non-industrial spraying (PROC11)

| Product (article) characteristics                                              |                   |
|--------------------------------------------------------------------------------|-------------------|
| Covers concentrations up to 100 %                                              |                   |
| Physical form of product                                                       | : Liquid          |
| Vapour pressure                                                                | : 5 hPa           |
| Temperature                                                                    | : 20 °C           |
| Amount used (or contained in articles), frequency and duration of use/exposure |                   |
| Duration                                                                       | : 480 min         |
| Use frequency                                                                  | : 5 days per week |
| Technical and organisational conditions and measures                           |                   |
| Handle in a fume cupboard or under extract ventilation.                        |                   |
| Other conditions affecting workers exposure                                    |                   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|             |                                                                |
|-------------|----------------------------------------------------------------|
| Temperature | : Assumes use at not more than 20°C above ambient temperature. |
|-------------|----------------------------------------------------------------|

**3.2.4. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Mixing or blending in batch processes (PROC5) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Roller application or brushing (PROC10) / Treatment of articles by dipping and pouring (PROC13) / Use as laboratory reagent (PROC15) / Manual activities involving hand contact (PROC19)**

| Product (article) characteristics                                              |                                                                |
|--------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 100 %                                              |                                                                |
| Physical form of product                                                       | : Liquid                                                       |
| Vapour pressure                                                                | : 5 hPa                                                        |
| Temperature                                                                    | : 20 °C                                                        |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                                |
| Duration                                                                       | : 480 min                                                      |
| Use frequency                                                                  | : 5 days per week                                              |
| Other conditions affecting workers exposure                                    |                                                                |
| Temperature                                                                    | : Assumes use at not more than 20°C above ambient temperature. |

### 3.3. Exposure estimation and reference to its source

**3.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)**

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 980 kg/day   |                           |
| Waste         | 10 kg/day    |                           |
| Soil          | 10 kg/day    |                           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

---

### 3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### ES 4: Cleaning; Industrial uses (SU3).

#### 4.1. Title section

|                        |                                    |
|------------------------|------------------------------------|
| Exposure Scenario name | : Cleaning                         |
| Structured Short Title | : Cleaning; Industrial uses (SU3). |

| Environment |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                     |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| CS 1        | Use of non-reactive processing aid at industrial site (no inclusion into or ERC4 onto article)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                     |
| Worker      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                     |
| CS 2        | Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | PROC1                                               |
| CS 3        | Industrial spraying                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | PROC7                                               |
| CS 4        | Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Transfer of substance or mixture (charging/discharging) at non dedicated-facilities, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Roller application or brushing, Treatment of articles by dipping and pouring | PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC13 |

#### 4.2. Conditions of use affecting exposure

##### 4.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Product (article) characteristics                                              |             |
|--------------------------------------------------------------------------------|-------------|
| Covers concentrations up to 100 %                                              |             |
| Physical form of product                                                       | : Liquid    |
| Vapour pressure                                                                | : 5 hPa     |
| Temperature                                                                    | : 20 °C     |
| Amount used (or contained in articles), frequency and duration of use/exposure |             |
| Annual amount per site                                                         | : 100000 kg |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                        |                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Release type                                                                           | : Continuous release                                                                                                                                                                                                     |
| Emission days                                                                          | : 20                                                                                                                                                                                                                     |
| <b>Conditions and measures related to sewage treatment plant</b>                       |                                                                                                                                                                                                                          |
| STP type                                                                               | : Municipal Sewage Treatment Plant                                                                                                                                                                                       |
| STP sludge treatment                                                                   | : No application of sewage sludge to soil<br>Sewage sludge should be incinerated, contained or reclaimed.                                                                                                                |
| <b>Conditions and measures related to treatment of waste (including article waste)</b> |                                                                                                                                                                                                                          |
| Waste treatment                                                                        | : External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b>                               |                                                                                                                                                                                                                          |
| Local freshwater dilution factor                                                       | : 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                                                     | : 1.000                                                                                                                                                                                                                  |

### 4.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

|                                                                                       |                                                                |
|---------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                              |                                                                |
| Covers concentrations up to 100 %                                                     |                                                                |
| Physical form of product                                                              | : Liquid                                                       |
| Vapour pressure                                                                       | : 5 hPa                                                        |
| Temperature                                                                           | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b> |                                                                |
| Duration                                                                              | : 480 min                                                      |
| Use frequency                                                                         | : 5 days per week                                              |
| <b>Technical and organisational conditions and measures</b>                           |                                                                |
| Store substance within a closed system.                                               |                                                                |
| <b>Other conditions affecting workers exposure</b>                                    |                                                                |
| Temperature                                                                           | : Assumes use at not more than 20°C above ambient temperature. |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

**Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply**

Assumes a good basic standard of occupational hygiene is implemented

### 4.2.3. Control of worker exposure: Industrial spraying (PROC7)

#### Product (article) characteristics

Covers concentrations up to 5 %

Physical form of product : Liquid

Vapour pressure : 5 hPa

Temperature : 20 °C

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration : 480 min

Use frequency : 5 days per week

#### Technical and organisational conditions and measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

#### Other conditions affecting workers exposure

Temperature : Assumes use at not more than 20°C above ambient temperature.

**Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply**

Assumes a good basic standard of occupational hygiene is implemented

**4.2.4. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Roller application or brushing (PROC10) / Treatment of articles by dipping and pouring (PROC13)**

#### Product (article) characteristics

Covers concentrations up to 100 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                                      |                                                                |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Physical form of product                                                                             | : Liquid                                                       |
| Vapour pressure                                                                                      | : 5 hPa                                                        |
| Temperature                                                                                          | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>                |                                                                |
| Duration                                                                                             | : 480 min                                                      |
| Use frequency                                                                                        | : 5 days per week                                              |
| <b>Other conditions affecting workers exposure</b>                                                   |                                                                |
| Temperature                                                                                          | : Assumes use at not more than 20°C above ambient temperature. |
| <b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b> |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                                 |                                                                |

### 4.3. Exposure estimation and reference to its source

#### 4.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 1.000 kg/day |                           |
| Waste         | 0,003 kg/day |                           |
| Soil          | 0 kg/day     |                           |

### 4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### ES 5: Cleaning; Professional uses (SU22).

#### 5.1. Title section

|                        |                                       |
|------------------------|---------------------------------------|
| Exposure Scenario name | : Cleaning                            |
| Structured Short Title | : Cleaning; Professional uses (SU22). |

| Environment |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                 |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| CS 1        | Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)                                                                                                                                                                                                                                                                                                                                                                                                                            | ERC8a                                           |
| CS 2        | Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)                                                                                                                                                                                                                                                                                                                                                                                                                           | ERC8d                                           |
| Worker      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                 |
| CS 3        | Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions                                                                                                                                                                                                                                                                                                                                                                                 | PROC1                                           |
| CS 4        | Transfer of substance or mixture (charging/discharging) at non dedicated-facilities                                                                                                                                                                                                                                                                                                                                                                                                                                  | PROC8a                                          |
| CS 5        | Roller application or brushing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | PROC10                                          |
| CS 6        | Non-industrial spraying                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | PROC11                                          |
| CS 7        | Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Chemical production where opportunity for exposure arises, Transfer of substance or mixture (charging/discharging) at dedicated facilities, Treatment of articles by dipping and pouring | PROC2,<br>PROC3,<br>PROC4,<br>PROC8b,<br>PROC13 |

#### 5.2. Conditions of use affecting exposure

##### 5.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Product (article) characteristics |          |
|-----------------------------------|----------|
| Covers concentrations up to 100 % |          |
| Physical form of product          | : Liquid |
| Vapour pressure                   | : 5 hPa  |
| Temperature                       | : 20 °C  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

| Amount used (or contained in articles), frequency and duration of use/exposure  |                                                                                                                                                                                                                          |
|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Annual amount per site                                                          | : 1000000 kg                                                                                                                                                                                                             |
| Release type                                                                    | : Continuous release                                                                                                                                                                                                     |
| Emission days                                                                   | : 365                                                                                                                                                                                                                    |
| Conditions and measures related to sewage treatment plant                       |                                                                                                                                                                                                                          |
| STP type                                                                        | : Municipal Sewage Treatment Plant                                                                                                                                                                                       |
| STP sludge treatment                                                            | : No application of sewage sludge to soil<br>Sewage sludge should be incinerated, contained or reclaimed.                                                                                                                |
| Conditions and measures related to treatment of waste (including article waste) |                                                                                                                                                                                                                          |
| Waste treatment                                                                 | : External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| Other conditions affecting environmental exposure                               |                                                                                                                                                                                                                          |
| Local freshwater dilution factor                                                | : 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                                              | : 100                                                                                                                                                                                                                    |

### 5.2.2. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

| Product (article) characteristics                                              |                                           |
|--------------------------------------------------------------------------------|-------------------------------------------|
| Covers concentrations up to 100 %                                              |                                           |
| Physical form of product                                                       | : Liquid                                  |
| Vapour pressure                                                                | : 5 hPa                                   |
| Temperature                                                                    | : 20 °C                                   |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                           |
| Annual amount per site                                                         | : 1000000 kg                              |
| Release type                                                                   | : Continuous release                      |
| Emission days                                                                  | : 365                                     |
| Conditions and measures related to sewage treatment plant                      |                                           |
| STP type                                                                       | : Municipal Sewage Treatment Plant        |
| STP sludge treatment                                                           | : No application of sewage sludge to soil |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                        |                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sewage sludge should be incinerated, contained or reclaimed.                           |                                                                                                                                                                                                                          |
| <b>Conditions and measures related to treatment of waste (including article waste)</b> |                                                                                                                                                                                                                          |
| Waste treatment                                                                        | : External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b>                               |                                                                                                                                                                                                                          |
| Local freshwater dilution factor                                                       | : 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                                                     | : 100                                                                                                                                                                                                                    |

### 5.2.3. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

|                                                                                                      |                                                                |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                                             |                                                                |
| Covers concentrations up to 100 %                                                                    |                                                                |
| Physical form of product                                                                             | : Liquid                                                       |
| Vapour pressure                                                                                      | : 5 hPa                                                        |
| Temperature                                                                                          | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>                |                                                                |
| Duration                                                                                             | : 480 min                                                      |
| Use frequency                                                                                        | : 5 days per week                                              |
| <b>Technical and organisational conditions and measures</b>                                          |                                                                |
| Store substance within a closed system.                                                              |                                                                |
| <b>Other conditions affecting workers exposure</b>                                                   |                                                                |
| Temperature                                                                                          | : Assumes use at not more than 20°C above ambient temperature. |
| <b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b> |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                                 |                                                                |

### 5.2.4. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

| Product (article) characteristics                                                             |                                                                |
|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 100 %                                                             |                                                                |
| Physical form of product                                                                      | : Liquid                                                       |
| Vapour pressure                                                                               | : 5 hPa                                                        |
| Temperature                                                                                   | : 20 °C                                                        |
| Amount used (or contained in articles), frequency and duration of use/exposure                |                                                                |
| Duration                                                                                      | : 240 min                                                      |
| Use frequency                                                                                 | : 5 days per week                                              |
| Other conditions affecting workers exposure                                                   |                                                                |
| Temperature                                                                                   | : Assumes use at not more than 20°C above ambient temperature. |
| Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                          |                                                                |

### 5.2.5. Control of worker exposure: Roller application or brushing (PROC10)

| Product (article) characteristics                                                             |                                                                |
|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 25 %                                                              |                                                                |
| Physical form of product                                                                      | : Liquid                                                       |
| Vapour pressure                                                                               | : 5 hPa                                                        |
| Temperature                                                                                   | : 20 °C                                                        |
| Other conditions affecting workers exposure                                                   |                                                                |
| Temperature                                                                                   | : Assumes use at not more than 20°C above ambient temperature. |
| Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                          |                                                                |

### 5.2.6. Control of worker exposure: Non-industrial spraying (PROC11)

| Product (article) characteristics |
|-----------------------------------|
|-----------------------------------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                                      |                                                                |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 1 %                                                                      |                                                                |
| Physical form of product                                                                             | : Liquid                                                       |
| Vapour pressure                                                                                      | : 5 hPa                                                        |
| Temperature                                                                                          | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>                |                                                                |
| Duration                                                                                             | : 480 min                                                      |
| Use frequency                                                                                        | : 5 days per week                                              |
| <b>Other conditions affecting workers exposure</b>                                                   |                                                                |
| Temperature                                                                                          | : Assumes use at not more than 20°C above ambient temperature. |
| <b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b> |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                                 |                                                                |

**5.2.7. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) / Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3) / Chemical production where opportunity for exposure arises (PROC4) / Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b) / Treatment of articles by dipping and pouring (PROC13)**

|                                                                                                      |                                                                |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                                             |                                                                |
| Covers concentrations up to 100 %                                                                    |                                                                |
| Physical form of product                                                                             | : Liquid                                                       |
| Vapour pressure                                                                                      | : 5 hPa                                                        |
| Temperature                                                                                          | : 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>                |                                                                |
| Duration                                                                                             | : 480 min                                                      |
| Use frequency                                                                                        | : 5 days per week                                              |
| <b>Other conditions affecting workers exposure</b>                                                   |                                                                |
| Temperature                                                                                          | : Assumes use at not more than 20°C above ambient temperature. |
| <b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b> |                                                                |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Assumes a good basic standard of occupational hygiene is implemented

### 5.3. Exposure estimation and reference to its source

#### 5.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 20 kg/day    |                           |
| Waste         | 0,001 kg/day |                           |
| Soil          | 0 kg/day     |                           |

#### 5.3.2. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 20 kg/day    |                           |
| Waste         | 0,001 kg/day |                           |
| Soil          | 0 kg/day     |                           |

### 5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### ES 6: Use in laboratories; Industrial uses (SU3).

#### 6.1. Title section

|                        |                                               |
|------------------------|-----------------------------------------------|
| Exposure Scenario name | : Use in laboratories                         |
| Structured Short Title | : Use in laboratories; Industrial uses (SU3). |

| Environment |                                                                                                                     |                |
|-------------|---------------------------------------------------------------------------------------------------------------------|----------------|
| CS 1        | Formulation into mixture, Use of non-reactive processing aid at industrial site (no inclusion into or onto article) | ERC2, ERC4     |
| Worker      |                                                                                                                     |                |
| CS 2        | Roller application or brushing, Use as laboratory reagent                                                           | PROC10, PROC15 |

#### 6.2. Conditions of use affecting exposure

##### 6.2.1. Control of environmental exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Product (article) characteristics                                               |                                                                                                           |
|---------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Covers concentrations up to 100 %                                               |                                                                                                           |
| Physical form of product                                                        | : Liquid                                                                                                  |
| Vapour pressure                                                                 | : 50 hPa                                                                                                  |
| Temperature                                                                     | : 20 °C                                                                                                   |
| Amount used (or contained in articles), frequency and duration of use/exposure  |                                                                                                           |
| Annual amount per site                                                          | : 730000 kg                                                                                               |
| Release type                                                                    | : Continuous release                                                                                      |
| Emission days                                                                   | : 100                                                                                                     |
| Conditions and measures related to sewage treatment plant                       |                                                                                                           |
| STP type                                                                        | : Municipal sewage treatment plant                                                                        |
| STP sludge treatment                                                            | : No application of sewage sludge to soil<br>Sewage sludge should be incinerated, contained or reclaimed. |
| Conditions and measures related to treatment of waste (including article waste) |                                                                                                           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                          |   |                                                                                                                                                                                                                        |
|----------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste treatment                                          | : | External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b> |   |                                                                                                                                                                                                                        |
| Local freshwater dilution factor                         | : | 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                       | : | 100                                                                                                                                                                                                                    |

### 6.2.2. Control of worker exposure: Roller application or brushing (PROC10) / Use as laboratory reagent (PROC15)

|                                                                                                      |   |                                                              |
|------------------------------------------------------------------------------------------------------|---|--------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                                             |   |                                                              |
| Covers concentrations up to 100 %                                                                    |   |                                                              |
| Physical form of product                                                                             | : | Liquid                                                       |
| Vapour pressure                                                                                      | : | 10 hPa                                                       |
| Temperature                                                                                          | : | 20 °C                                                        |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>                |   |                                                              |
| Duration                                                                                             | : | 480 min                                                      |
| Use frequency                                                                                        | : | 5 days per week                                              |
| <b>Other conditions affecting workers exposure</b>                                                   |   |                                                              |
| Temperature                                                                                          | : | Assumes use at not more than 20°C above ambient temperature. |
| <b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b> |   |                                                              |
| Assumes a good basic standard of occupational hygiene is implemented                                 |   |                                                              |

### 6.3. Exposure estimation and reference to its source

#### 6.3.1. Environmental release and exposure: Formulation into mixture (ERC2) / Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 10 kg/day    |                           |
| Waste         | 0,2 kg/day   |                           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|      |            |  |
|------|------------|--|
| Soil | 0,1 kg/day |  |
|------|------------|--|

### 6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### ES 7: Use in laboratories; Professional uses (SU22).

#### 7.1. Title section

|                               |                                                  |
|-------------------------------|--------------------------------------------------|
| <b>Exposure Scenario name</b> | : Use in laboratories                            |
| <b>Structured Short Title</b> | : Use in laboratories; Professional uses (SU22). |

| Environment |                                                                                                  |                   |
|-------------|--------------------------------------------------------------------------------------------------|-------------------|
| <b>CS 1</b> | <b>Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)</b> | ERC8a             |
| Worker      |                                                                                                  |                   |
| <b>CS 2</b> | <b>Roller application or brushing, Use as laboratory reagent</b>                                 | PROC10,<br>PROC15 |

#### 7.2. Conditions of use affecting exposure

##### 7.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Product (article) characteristics                                              |                                                                                                           |
|--------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Covers concentrations up to 100 %                                              |                                                                                                           |
| Physical form of product                                                       | : Liquid                                                                                                  |
| Vapour pressure                                                                | : 10 hPa                                                                                                  |
| Temperature                                                                    | : 20 °C                                                                                                   |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                                                                           |
| Annual amount per site                                                         | : 1 kg                                                                                                    |
| Release type                                                                   | : Continuous release                                                                                      |
| Emission days                                                                  | : 365                                                                                                     |
| Conditions and measures related to sewage treatment plant                      |                                                                                                           |
| STP type                                                                       | : Municipal Sewage Treatment Plant                                                                        |
| STP sludge treatment                                                           | : No application of sewage sludge to soil<br>Sewage sludge should be incinerated, contained or reclaimed. |
| Other conditions affecting environmental exposure                              |                                                                                                           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                    |       |
|------------------------------------|-------|
| Local freshwater dilution factor   | : 10  |
| Local marine water dilution factor | : 100 |

### 7.2.2. Control of worker exposure: Roller application or brushing (PROC10) / Use as laboratory reagent (PROC15)

| Product (article) characteristics                                                             |                                                                |
|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Covers concentrations up to 100 %                                                             |                                                                |
| Physical form of product                                                                      | : Liquid                                                       |
| Vapour pressure                                                                               | : 10 hPa                                                       |
| Temperature                                                                                   | : 20 °C                                                        |
| Amount used (or contained in articles), frequency and duration of use/exposure                |                                                                |
| Duration                                                                                      | : 480 min                                                      |
| Use frequency                                                                                 | : 5 days per week                                              |
| Other conditions affecting workers exposure                                                   |                                                                |
| Temperature                                                                                   | : Assumes use at not more than 20°C above ambient temperature. |
| Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply |                                                                |
| Assumes a good basic standard of occupational hygiene is implemented                          |                                                                |

### 7.3. Exposure estimation and reference to its source

#### 7.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 0,01 kg/day  |                           |
| Waste         | 0,01 kg/day  |                           |
| Soil          | 0 kg/day     |                           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

---

### 7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### ES 8: Cleaning; Consumer uses (SU21).

#### 8.1. Title section

|                               |                                   |
|-------------------------------|-----------------------------------|
| <b>Exposure Scenario name</b> | : Cleaning                        |
| <b>Structured Short Title</b> | : Cleaning; Consumer uses (SU21). |

| Environment  |                                                                                                   |       |
|--------------|---------------------------------------------------------------------------------------------------|-------|
| <b>CS 1</b>  | <b>Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)</b>  | ERC8a |
| <b>CS 2</b>  | <b>Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)</b> | ERC8d |
| Consumer     |                                                                                                   |       |
| <b>CS 3</b>  | Air care products                                                                                 | PC3   |
| <b>CS 4</b>  | Coatings and paints, thinners, paint removers                                                     | PC9a  |
| <b>CS 5</b>  | Coatings and paints, thinners, paint removers                                                     | PC9a  |
| <b>CS 6</b>  | Washing and cleaning products (including solvent based products)                                  | PC35  |
| <b>CS 7</b>  | Coatings and paints, thinners, paint removers                                                     | PC9a  |
| <b>CS 8</b>  | Washing and cleaning products                                                                     | PC35  |
| <b>CS 9</b>  | Washing and cleaning products (including solvent based products)                                  | PC35  |
| <b>CS 10</b> | Washing and cleaning products (including solvent based products)                                  | PC35  |

#### 8.2. Conditions of use affecting exposure

##### 8.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Product (article) characteristics                                              |          |
|--------------------------------------------------------------------------------|----------|
| Covers concentrations up to 100 %                                              |          |
| Physical form of product                                                       | : Liquid |
| Vapour pressure                                                                | : 10 hPa |
| Temperature                                                                    | : 20 °C  |
| Amount used (or contained in articles), frequency and duration of use/exposure |          |
| Annual amount per site                                                         | : 2,6 kg |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                        |                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Release type                                                                           | : Continuous release                                                                                                                                                                                                     |
| Emission days                                                                          | : 365                                                                                                                                                                                                                    |
| <b>Conditions and measures related to treatment of waste (including article waste)</b> |                                                                                                                                                                                                                          |
| Waste treatment                                                                        | : External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b>                               |                                                                                                                                                                                                                          |
| Local freshwater dilution factor                                                       | : 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                                                     | : 100                                                                                                                                                                                                                    |

### 8.2.2. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

|                                                                                        |                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                               |                                                                                                                                                                                                                          |
| Covers concentrations up to 100 %                                                      |                                                                                                                                                                                                                          |
| Physical form of product                                                               | : Liquid                                                                                                                                                                                                                 |
| Vapour pressure                                                                        | : 10 hPa                                                                                                                                                                                                                 |
| Temperature                                                                            | : 20 °C                                                                                                                                                                                                                  |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>  |                                                                                                                                                                                                                          |
| Annual amount per site                                                                 | : 2,6 kg                                                                                                                                                                                                                 |
| Release type                                                                           | : Continuous release                                                                                                                                                                                                     |
| Emission days                                                                          | : 365                                                                                                                                                                                                                    |
| <b>Conditions and measures related to treatment of waste (including article waste)</b> |                                                                                                                                                                                                                          |
| Waste treatment                                                                        | : External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b>                               |                                                                                                                                                                                                                          |
| Local freshwater dilution factor                                                       | : 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                                                     | : 100                                                                                                                                                                                                                    |

### 8.2.3. Control of consumer exposure: Air care products (PC3)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

Air care, continuous action (solid and liquid) (PC3\_2)

| Product (article) characteristics                                              |                                                   |
|--------------------------------------------------------------------------------|---------------------------------------------------|
| Covers concentrations up to 10 %                                               |                                                   |
| Physical form of product                                                       | : Liquid                                          |
| Vapour pressure                                                                | : 10 hPa                                          |
| Temperature                                                                    | : 20 °C                                           |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                   |
| Amount used per event                                                          | : 0,48 g/event                                    |
| Duration                                                                       | : 480 min                                         |
| Use frequency                                                                  | : 365 days per year                               |
| Other conditions affecting consumers exposure                                  |                                                   |
| Room size                                                                      | : 20 m3                                           |
| Ventilation rate                                                               | : Covers use under typical household ventilation. |

### 8.2.4. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Waterborne latex wall paint (PC9a\_1, PC15\_1)

| Product (article) characteristics                                              |                                                   |
|--------------------------------------------------------------------------------|---------------------------------------------------|
| Covers concentrations up to 1 %                                                |                                                   |
| Physical form of product                                                       | : Liquid                                          |
| Vapour pressure                                                                | : 10 hPa                                          |
| Temperature                                                                    | : 20 °C                                           |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                   |
| Amount used per event                                                          | : 2,760 kg                                        |
| Duration                                                                       | : 132 min                                         |
| Use frequency                                                                  | : 4 days per year                                 |
| Other conditions affecting consumers exposure                                  |                                                   |
| Room size                                                                      | : 20 m3                                           |
| Ventilation rate                                                               | : Covers use under typical household ventilation. |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### 8.2.5. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Solvent rich, high solid, water borne paint (PC9a\_2, PC15\_2)

| Product (article) characteristics                                              |                                                   |
|--------------------------------------------------------------------------------|---------------------------------------------------|
| Covers concentrations up to 27,5 %                                             |                                                   |
| Physical form of product                                                       | : Liquid                                          |
| Vapour pressure                                                                | : 10 hPa                                          |
| Temperature                                                                    | : 20 °C                                           |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                   |
| Amount used per event                                                          | : 0,744 kg                                        |
| Duration                                                                       | : 132 min                                         |
| Use frequency                                                                  | : 6 days per year                                 |
| Other conditions affecting consumers exposure                                  |                                                   |
| Room size                                                                      | : 20 m <sup>3</sup>                               |
| Ventilation rate                                                               | : Covers use under typical household ventilation. |

### 8.2.6. Control of consumer exposure: Washing and cleaning products (including solvent based products) (PC35)

Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) (PC8\_2, PC35\_2)

| Product (article) characteristics                                              |                   |
|--------------------------------------------------------------------------------|-------------------|
| Covers concentrations up to 50 %                                               |                   |
| Physical form of product                                                       | : Liquid          |
| Vapour pressure                                                                | : 10 hPa          |
| Temperature                                                                    | : 20 °C           |
| Amount used (or contained in articles), frequency and duration of use/exposure |                   |
| Amount used per event                                                          | : 0,215 kg        |
| Duration                                                                       | : 19,8 min        |
| Use frequency                                                                  | : 2 days per year |
| Other conditions affecting consumers exposure                                  |                   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                  |                                                   |
|------------------|---------------------------------------------------|
| Room size        | : 24 m3                                           |
| Ventilation rate | : Covers use under typical household ventilation. |

### 8.2.7. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Removers (paint-, glue-, wall paper-, sealant-remover) (PC9a\_4, PC15\_4)

| Product (article) characteristics                                              |                                                   |
|--------------------------------------------------------------------------------|---------------------------------------------------|
| Covers concentrations up to 50 %                                               |                                                   |
| Physical form of product                                                       | : Liquid                                          |
| Vapour pressure                                                                | : 10 hPa                                          |
| Temperature                                                                    | : 20 °C                                           |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                   |
| Amount used per event                                                          | : 0,491 kg                                        |
| Duration                                                                       | : 120 min                                         |
| Use frequency                                                                  | : 3 days per year                                 |
| Other conditions affecting consumers exposure                                  |                                                   |
| Room size                                                                      | : 20 m3                                           |
| Ventilation rate                                                               | : Covers use under typical household ventilation. |

### 8.2.8. Control of consumer exposure: Washing and cleaning products (PC35)

Laundry and dish washing products (PC35\_1, PC8\_1)

| Product (article) characteristics                                              |                     |
|--------------------------------------------------------------------------------|---------------------|
| Covers concentrations up to 5 %                                                |                     |
| Physical form of product                                                       | : Liquid            |
| Vapour pressure                                                                | : 10 hPa            |
| Temperature                                                                    | : 20 °C             |
| Amount used (or contained in articles), frequency and duration of use/exposure |                     |
| Amount used per event                                                          | : 15 g/event        |
| Duration                                                                       | : 30 min            |
| Use frequency                                                                  | : 365 days per year |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

### Other conditions affecting consumers exposure

Room size : 20 m3

### 8.2.9. Control of consumer exposure: Washing and cleaning products (including solvent based products) (PC35)

Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) (PC8\_2, PC35\_2)

#### Product (article) characteristics

Covers concentrations up to 5 %

Physical form of product : Liquid

Vapour pressure : 10 hPa

Temperature : 20 °C

#### Amount used (or contained in articles), frequency and duration of use/exposure

Amount used per event : 27 g/event

Duration : 19,8 min

Use frequency : 128 days per year

#### Other conditions affecting consumers exposure

Room size : 20 m3

Ventilation rate : Covers use under typical household ventilation.

### 8.2.10. Control of consumer exposure: Washing and cleaning products (including solvent based products) (PC35)

Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (PC8\_3, PC35\_3)

#### Product (article) characteristics

Covers concentrations up to 15 %

Physical form of product : Liquid

Vapour pressure : 10 hPa

Temperature : 20 °C

#### Amount used (or contained in articles), frequency and duration of use/exposure

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                      |                                                   |
|------------------------------------------------------|---------------------------------------------------|
| Amount used per event                                | : 35 g/event                                      |
| Duration                                             | : 10,2 min                                        |
| Use frequency                                        | : 128 days per year                               |
| <b>Other conditions affecting consumers exposure</b> |                                                   |
| Room size                                            | : 20 m <sup>3</sup>                               |
| Ventilation rate                                     | : Covers use under typical household ventilation. |

### 8.3. Exposure estimation and reference to its source

#### 8.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 950 kg/day   |                           |
| Waste         | 25 kg/day    |                           |
| Soil          | 25 kg/day    |                           |

#### 8.3.2. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 950 kg/day   |                           |
| Waste         | 25 kg/day    |                           |
| Soil          | 25 kg/day    |                           |

### 8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

For scaling see

<http://www.ecetoc.org/tra>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

---

Further details on scaling and control technologies are provided in SPERC factsheet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

### ES 9: Use in coatings; Consumer uses (SU21).

#### 9.1. Title section

|                               |                                          |
|-------------------------------|------------------------------------------|
| <b>Exposure Scenario name</b> | : Use in coatings                        |
| <b>Structured Short Title</b> | : Use in coatings; Consumer uses (SU21). |

| Environment |                                                                                                  |       |
|-------------|--------------------------------------------------------------------------------------------------|-------|
| <b>CS 1</b> | <b>Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)</b> | ERC8a |
| <b>CS 2</b> | <b>Wide dispersive indoor use of reactive substances in open systems</b>                         | ERC8b |
| Consumer    |                                                                                                  |       |
| <b>CS 3</b> | Adhesives, sealants                                                                              | PC1   |
| <b>CS 4</b> | Coatings and paints, thinners, paint removers                                                    | PC9a  |

#### 9.2. Conditions of use affecting exposure

##### 9.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Product (article) characteristics                                               |                                                                                                             |
|---------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Covers concentrations up to 100 %                                               |                                                                                                             |
| Physical form of product                                                        | : Liquid                                                                                                    |
| Vapour pressure                                                                 | : 10 hPa                                                                                                    |
| Temperature                                                                     | : 20 °C                                                                                                     |
| Amount used (or contained in articles), frequency and duration of use/exposure  |                                                                                                             |
| Annual amount per site                                                          | : 130 kg                                                                                                    |
| Daily amount per site                                                           | : 370 kg                                                                                                    |
| Regional use tonnage                                                            | : 270000 kg                                                                                                 |
| Release type                                                                    | : Continuous release                                                                                        |
| Emission days                                                                   | : 365                                                                                                       |
| Conditions and measures related to treatment of waste (including article waste) |                                                                                                             |
| Waste treatment                                                                 | : External treatment and disposal of waste should comply with applicable local and/or national regulations. |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

|                                                                                                           |       |
|-----------------------------------------------------------------------------------------------------------|-------|
| External recovery and recycling of waste should comply with applicable local and/or national regulations. |       |
| <b>Other conditions affecting environmental exposure</b>                                                  |       |
| Local freshwater dilution factor                                                                          | : 10  |
| Local marine water dilution factor                                                                        | : 100 |

### 9.2.2. Control of environmental exposure: Wide dispersive indoor use of reactive substances in open systems (ERC8b)

|                                                                                        |                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product (article) characteristics</b>                                               |                                                                                                                                                                                                                          |
| Covers concentrations up to 100 %                                                      |                                                                                                                                                                                                                          |
| Physical form of product                                                               | : Liquid                                                                                                                                                                                                                 |
| Vapour pressure                                                                        | : 10 hPa                                                                                                                                                                                                                 |
| Temperature                                                                            | : 20 °C                                                                                                                                                                                                                  |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b>  |                                                                                                                                                                                                                          |
| Annual amount per site                                                                 | : 130 kg                                                                                                                                                                                                                 |
| Daily amount per site                                                                  | : 370 kg                                                                                                                                                                                                                 |
| Regional use tonnage                                                                   | : 270000 kg                                                                                                                                                                                                              |
| Release type                                                                           | : Continuous release                                                                                                                                                                                                     |
| Emission days                                                                          | : 365                                                                                                                                                                                                                    |
| <b>Conditions and measures related to treatment of waste (including article waste)</b> |                                                                                                                                                                                                                          |
| Waste treatment                                                                        | : External treatment and disposal of waste should comply with applicable local and/or national regulations.<br>External recovery and recycling of waste should comply with applicable local and/or national regulations. |
| <b>Other conditions affecting environmental exposure</b>                               |                                                                                                                                                                                                                          |
| Local freshwater dilution factor                                                       | : 10                                                                                                                                                                                                                     |
| Local marine water dilution factor                                                     | : 100                                                                                                                                                                                                                    |

### 9.2.3. Control of consumer exposure: Adhesives, sealants (PC1)

Glues, hobby use (PC1\_1)

|                                          |
|------------------------------------------|
| <b>Product (article) characteristics</b> |
|------------------------------------------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1

SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026

Print Date: 28.07.2026

|                                                                                       |                                                   |
|---------------------------------------------------------------------------------------|---------------------------------------------------|
| Covers concentrations up to 30 %                                                      |                                                   |
| Physical form of product                                                              | : Liquid                                          |
| Vapour pressure                                                                       | : 10 hPa                                          |
| Temperature                                                                           | : 20 °C                                           |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b> |                                                   |
| Amount used per event                                                                 | : 9 g/event                                       |
| Duration                                                                              | : 240 min                                         |
| Use frequency                                                                         | : 365 days per year                               |
| <b>Other conditions affecting consumers exposure</b>                                  |                                                   |
| Room size                                                                             | : 20 m3                                           |
| Ventilation rate                                                                      | : Covers use under typical household ventilation. |

### 9.2.4. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

|                                                                                       |                                                   |
|---------------------------------------------------------------------------------------|---------------------------------------------------|
| <b>Product (article) characteristics</b>                                              |                                                   |
| Covers concentrations up to 50 %                                                      |                                                   |
| Physical form of product                                                              | : Liquid                                          |
| Vapour pressure                                                                       | : 10 hPa                                          |
| Temperature                                                                           | : 20 °C                                           |
| <b>Amount used (or contained in articles), frequency and duration of use/exposure</b> |                                                   |
| Amount used per event                                                                 | : 0,491 kg                                        |
| Duration                                                                              | : 120 min                                         |
| Use frequency                                                                         | : 3 days per year                                 |
| <b>Other conditions affecting consumers exposure</b>                                  |                                                   |
| Room size                                                                             | : 20 m3                                           |
| Ventilation rate                                                                      | : Covers use under typical household ventilation. |

### 9.2.5. Control of consumer exposure:

Plasters and floor equalizers (PC9b\_2)

Fillers and putty (PC9b\_1)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

| Product (article) characteristics                                              |                                                   |
|--------------------------------------------------------------------------------|---------------------------------------------------|
| Covers concentrations up to 2 %                                                |                                                   |
| Physical form of product                                                       | : Liquid                                          |
| Vapour pressure                                                                | : 10 hPa                                          |
| Temperature                                                                    | : 20 °C                                           |
| Amount used (or contained in articles), frequency and duration of use/exposure |                                                   |
| Amount used per event                                                          | : 13,8 kg                                         |
| Duration                                                                       | : 120 min                                         |
| Use frequency                                                                  | : 12 days per year                                |
| Other conditions affecting consumers exposure                                  |                                                   |
| Room size                                                                      | : 20 m <sup>3</sup>                               |
| Ventilation rate                                                               | : Covers use under typical household ventilation. |

### 9.3. Exposure estimation and reference to its source

#### 9.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 985 kg/day   |                           |
| Waste         | 10 kg/day    |                           |
| Soil          | 5 kg/day     |                           |

#### 9.3.2. Environmental release and exposure: Wide dispersive indoor use of reactive substances in open systems (ERC8b)

| Release route | Release rate | Release estimation method |
|---------------|--------------|---------------------------|
| Air           | 985 kg/day   |                           |
| Waste         | 10 kg/day    |                           |
| Soil          | 5 kg/day     |                           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYK-W 995

Version: 7.1  
SDB\_IS

Revision Date: 20.07.2026

Date of last issue: 12.01.2026  
Print Date: 28.07.2026

---

### 9.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Estimated workplace exposures are not expected to exceed DNELs when the identified risk management measures are adopted.

<http://www.ecetoc.org/tra>

For scaling see

Further details on scaling and control technologies are provided in SPERC factsheet.