

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

SECTION 1. IDENTIFICATION

Product name : BYKETOL-OK

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Leveling Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)
- single exposure

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.Precautionary statements : **Prevention:**

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Combination of high boiling aromatics, ketones and esters
Hazardous components

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Component	CAS-No.	Concentration (%)
Solvent naphtha, petroleum, light aromatic	64742-95-6	>= 60 - < 80
2,6-Dimethylheptan-4-one	108-83-8	>= 20 - < 30
Hydrocarbons, terpene processing by-products	68956-56-9	>= 1 - < 5
Ethyl lactate	97-64-3	>= 1 - < 3
Hydroxy acetic acid butyl ester (Butyl glycolate)	7397-62-8	>= 1 - < 3

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : No information available.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.
Will not explode on mechanical impact.
- Do not allow run-off from fire fighting to enter drains or water courses.

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Hazardous combustion products	: Carbon oxides
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Conditions for safe storage	: No smoking.

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,6-Dimethylheptan-4-one	108-83-8	TWA	25 ppm	ACGIH
2,6-Dimethylheptan-4-one		TWA	50 ppm 290 mg/m ³	OSHA Z-1

Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.**Personal protective equipment**

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.
In the case of vapour formation use a respirator with an approved filter.

Hand protection
Material : Silver Shield gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid
Colour : colourless
Odour : aromatic
Odour Threshold : No data available

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

pH	: 5, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/freezing point	: < 32 °F (< 0 °C) Method: derived
Initial boiling point and boiling range	: 309.20 °F (154.00 °C) Method: derived
Vapour pressure	: 4 hPa (68 °F (20 °C)) Method: derived
Flash point	: 109.40 °F (43.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: 7.50 %(V)
Lower explosion limit	: 1.00 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.8600 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 2 mm ² /s (104.00 °F (40.00 °C))

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Surface tension : < 25.00 mN/m, ring dynamometer

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : None expected

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute oral toxicity : LD50 (Rat, male and female): 5,000.000000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute dermal toxicity : Acute toxicity estimate : 2,943 mg/kg
Method: Calculation method

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Acute oral toxicity : LD50 (Rat): > 4,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3670 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 3,480 mg/kg

108-83-8 2,6-Dimethylheptan-4-one:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Acute inhalation toxicity : LC50 (Rat): > 14 mg/l
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: no

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

97-64-3 Ethyl lactate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4900 ppm

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):

Acute oral toxicity : LD50 (Rat): 4,595 mg/kg

Skin corrosion/irritation**Product:**

Species: Rabbit
Assessment: No skin irritation
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

Remarks: May cause skin irritation and/or dermatitis.

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Species: Rabbit
Result: Moderate skin irritation

108-83-8 2,6-Dimethylheptan-4-one:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

97-64-3 Ethyl lactate:

Species: Rabbit
Result: Moderate skin irritation

7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):

Species: Rabbit
Result: Moderate skin irritation

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Serious eye damage/eye irritation**Product:**

Species: Rabbit

Result: No eye irritation

Assessment: No eye irritation

Method: OECD Test Guideline 405

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Species: Rabbit

Result: Eye irritation

108-83-8 2,6-Dimethylheptan-4-one:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: no

97-64-3 Ethyl lactate:

Species: Rabbit

Result: Eye irritation

7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):

Species: Rabbit

Result: Corrosive to eyes

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

108-83-8 2,6-Dimethylheptan-4-one:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Result: Not a skin sensitizer.
GLP: yes

7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):

Test Type: Maximisation Test
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.
GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Repeated dose toxicity**Product:**

Remarks: No data available

Aspiration toxicity**Product:**

No data available

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation; may cause skin sensitization.

Eye contact:

Symptoms:

Contact may cause irritation.

Ingestion:

Symptoms:

Ingestion will probably irritate the digestive tract; high dosages may cause CNS depression.

Further information**Product:**

Remarks: Skin contact with Dipentene may cause skin sensitization.

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates Remarks: No data available

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : There is no data available for this product.
information
No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste : D001: Ignitable
Code(s)

D018: Benzene

Waste from residues : Dispose of in accordance with applicable local/municipal,

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Contaminated packaging : state/provincial and federal regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Solvent naphtha, Diisobutyl ketone)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Solvent naphtha, Diisobutyl ketone)
:)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(Solvent naphtha, Diisobutyl ketone)
Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

ERG Code : 128
Marine pollutant : no
Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : <= 1.00 %
Method: 22 (10min/150°C)
DIN EN ISO 3251
Non-volatile information is not a specification.

BYKETOL-OK

Version 10

Revision Date 05/17/2026

Print Date 07/09/2026

Massachusetts Right To Know

2,6-Dimethylheptan-4-one	108-83-8
Ethyl lactate	97-64-3

Pennsylvania Right To Know

Solvent naphtha, petroleum, light aromatic	64742-95-6
2,6-Dimethylheptan-4-one	108-83-8
4,6-Dimethyl-2-heptanone	19549-80-5
Hydrocarbons, terpene processing by-products	68956-56-9
Ethyl lactate	97-64-3
Cumene	98-82-8
Naphthalene	91-20-3
Ethyl benzene	100-41-4

New Jersey Right To Know

New Jersey Trade Secret : Not applicable
Registry Number for the product (NJ TSRN)

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Cumene, Naphthalene, Ethyl benzene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.