

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYKUMEN N

UFI : PD1A-304A-R00S-9YUN

Product code : 000000000000145579

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel
Telephone : +49 281 670-0
Telefax : +49 281 65735

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 78-83-1 iso-butanol
- 108-31-6 maleic anhydride

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solution of a lower molecular weight unsaturated acidic polycarboxylic acid polyester

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9 265-150-3 01-2119457273-39	Asp. Tox. 1; H304	>= 30 - < 50
iso-butanol	78-83-1 201-148-0 01-2119484609-23	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 20 - < 25
maleic anhydride	108-31-6 203-571-6 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) EUH071 specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	>= 0,001 - < 0,1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible
tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty
of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water
courses.

Hazardous combustion products : Carbon oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if
necessary.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

- regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
iso-butanol	78-83-1	OELV - 8 hrs (TWA)	50 ppm 150 mg/m ³	IE OEL
		OELV - 15 min (STEL)	75 ppm 225 mg/m ³	IE OEL
maleic anhydride	108-31-6	OELV - 8 hrs (TWA) (Inhalable fraction and vapour)	0,01 ppm	IE OEL
Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
iso-butanol	Workers	Inhalation	Long-term local effects	310 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

	Consumers	Inhalation	Long-term local effects	55 mg/m3
maleic anhydride	Workers	Inhalation	Long-term systemic effects, Long-term local effects	0,081 mg/m3
	Workers	Inhalation	Systemic effects, Acute effects, Local effects	0,2 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
iso-butanol	Fresh water	0,4 mg/l
	Marine water	0,04 mg/l
	Fresh water sediment	1,56 mg/kg
	Marine sediment	0,156 mg/kg
	Soil	0,0765 mg/kg
	Sewage treatment plant	10 mg/l
maleic anhydride	Intermittent releases	11 mg/l
	Fresh water	0,038 mg/l
	Marine water	0,0038 mg/l
	Intermittent releases	0,379 mg/l
	Soil	0,037 mg/kg
	Fresh water sediment	0,296 mg/kg
Marine sediment	0,0296 mg/kg	
	Sewage treatment plant	44,6 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,4 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	light brown
Odour	:	slight
Odour Threshold	:	No data available
Melting point/ range	:	< 0 °C Method: derived
Initial boiling point	:	106,00 °C Method: derived
Upper explosion limit / Upper flammability limit	:	10,70 %(V)
Lower explosion limit / Lower flammability limit	:	0,60 %(V)
Flash point	:	33 °C Method: 48 (Abel-Pensky) DIN 51755
Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	3,7 (20 °C) Concentration: 1 % Method: DIN 19268 (1% in water)
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	80,000 mm ² /s (20,00 °C) 31,000 mm ² /s (40,00 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

Vapour pressure	:	9 hPa (20 °C) Method: derived
Relative density	:	No data available
Density	:	0,8830 g/cm ³ (20,00 °C) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Relative vapour density	:	No data available

9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available
Surface tension	:	28,1 mN/m, 20 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

Acute oral toxicity : Remarks: No data available

Components:

iso-butanol:

Acute oral toxicity : LD50 (Rat, male): > 2.830 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

maleic anhydride:

Acute oral toxicity : LD50 (Rat, male and female): 1.090 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, female): 2.620 mg/kg
GLP: No information available.

Skin corrosion/irritation

Product:

Remarks : May irritate skin.
May cause skin irritation and/or dermatitis.

Components:

iso-butanol:

Species : Rabbit
Result : Skin irritation

maleic anhydride:

Species : Rabbit
Method : No information available.
Result : Corrosive to skin
GLP : no

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

Components:

iso-butanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

GLP : yes

maleic anhydride:

Species : Rabbit
Result : Corrosive to eyes
GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : Causes sensitisation.

Components:

iso-butanol:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

maleic anhydride:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Causes sensitisation.
GLP : yes

Germ cell mutagenicity

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:

Germ cell mutagenicity-
Assessment : Classified based on benzene content < 0.1% (Regulation (EC)
1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:

Carcinogenicity -
Assessment : Classified based on benzene content < 0.1% (Regulation (EC)
1272/2008, Annex VI, Part 3, Note P)

Repeated dose toxicity

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

Remarks : No data available

Aspiration toxicity

Components:

iso-butanol:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

iso-butanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.430 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 1.100 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.799

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

plants : mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other : NOEC: 20 mg/l
aquatic invertebrates : End point: Reproduction
(Chronic toxicity) : Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test

maleic anhydride:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 75 mg/l
Exposure time: 96 h
Test Type: static test
GLP: no

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 42,81 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata): 74,35 mg/l
plants : Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other : NOEC: 10 mg/l
aquatic invertebrates : Exposure time: 21 d
(Chronic toxicity) : Species: Daphnia magna (Water flea)
GLP: no

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

iso-butanol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

maleic anhydride:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301B
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

iso-butanol:

Partition coefficient: n-
octanol/water : log Pow: 1
Method: OECD Test Guideline 117
GLP: yes

maleic anhydride:

Partition coefficient: n-
octanol/water : log Pow: -2,61 (19,8 °C)
pH: 4 - 9
Method: OECD Test Guideline 107
GLP: yes

12.4 Mobility in soil

Components:

maleic anhydride:

Distribution among
environmental compartments : Koc: 42, log Koc: 1,63

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological
information : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

- ADR : UN 1212
RID : UN 1212
IMDG : UN 1212
IATA : UN 1212

14.2 UN proper shipping name

- ADR : ISOBUTANOL, SOLUTION
RID : ISOBUTANOL, SOLUTION
IMDG : ISOBUTANOL, SOLUTION
IATA : Isobutyl alcohol, solution

14.3 Transport hazard class(es)

- ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

- ADR**
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E
- RID**
Packing group : III
Classification Code : F1
Hazard Identification Number : 30

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, S-D

Remarks : IMDG Code segregation group - none

IATA (Cargo)

Packing instruction (cargo aircraft) : 366

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Resp. Sens. : Respiratory sensitisation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference
(STEL) period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335

Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYKUMEN N

Version:
2.0

Revision Date:
10.03.2025

Date of last issue: 06.09.2024
Print Date: 21.05.2025

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN