

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

SECTION 1. IDENTIFICATION

Product name : CERACOL 83

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wax Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting
equipment.
P242 Use only non-sparking tools.

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Fischer Tropisch wax dispersion

Hazardous components

Component	CAS-No.	Concentration (%)
Isopropanol	67-63-0	>= 80 - < 100
Wax	8002-74-2	>= 10 - < 30

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

If inhaled	<p>Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.</p> <p>: Remove to fresh air. Get medical aid as soon as possible. If breathing has stopped, trained personnel should administer rescue breathing, and CPR if the heart has stopped. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.</p>
In case of skin contact	<p>: Remove contaminated clothing. Wash thoroughly with soap and water. If irritation develops, get medical aid. If on skin, rinse well with water. If on clothes, remove clothes.</p>
In case of eye contact	<p>: Immediately flush with plenty of water for at least 30 minutes. Get medical aid. Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.</p>
If swallowed	<p>: Do not induce vomiting; aspiration hazard. Dilute with 1-2 glasses of water. Get medical aid. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Never give anything by mouth to an unconscious person. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.</p>
Most important symptoms and effects, both acute and delayed	<p>: No information available.</p>

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	<p>: Foam Carbon dioxide (CO₂) Dry chemical Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical</p>
Unsuitable extinguishing media	<p>: No information available.</p>
Specific hazards during firefighting	<p>High volume water jet</p> <p>: Cool closed containers exposed to fire with water spray. Will not explode on mechanical impact.</p> <p>Do not allow run-off from fire fighting to enter drains or water courses.</p>
Hazardous combustion products	<p>: Carbon oxides</p>

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

- Further information : Keep away from heat and sources of ignition.
Keep away from oxidizing agents.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Eliminate all sources of ignition. Wear protective equipment: safety glasses, gloves and an appropriate respirator.
- : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.
- Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Stop leak. Dike and contain spill.
Absorb with suitable material and remove with sparkless shovel and/or scoop.
- Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Ensure all equipment is electrically grounded before beginning

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

- transfer operations.
 Containers should be grounded when being emptied.
 Vapours may travel to areas away from work site before igniting/flashing back to Vapour source.
 Keep container closed when not in use.
 Handle as an industrial chemical.
 Avoid formation of aerosol.
 Do not breathe vapours/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep in a dry, cool and well-ventilated place.
 Keep product and empty container away from heat and sources of ignition.
 Take measures to prevent the build up of electrostatic charge.
 No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isopropanol	67-63-0	TWA	200 ppm	ACGIH
Isopropanol		STEL	400 ppm	ACGIH
Isopropanol		TWA	400 ppm 980 mg/m ³	OSHA Z-1
Wax	8002-74-2	TWA (Fumes)	2 mg/m ³	ACGIH
Wax		TWA (Fumes)	2 mg/m ³	OSHA P0

Engineering measures : Use with local exhaust ventilation.

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

Personal protective equipment

- Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure. In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Material : Nitrile rubber
 - Break through time : > 480 min
 - Glove thickness : > 0.35 mm
 - Protective index : Class 6
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Safety glasses
Tightly fitting safety goggles
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Clean long legged, long sleeved work clothes.
If splashing is possible, wear chemically resistant protective clothing.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : dispersion
- Colour : white
- Odour : characteristic
- Odour Threshold : No data available
- pH : 6, Concentration: 10 % (68 °F (20 °C))
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : 180 °F (82 °C)
(1,013 hPa)
- Vapour pressure : No data available

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

Flash point	:	54 °F (12 °C) (1,013 hPa) Method: calculated
Upper explosion limit	:	12 %(V)
Lower explosion limit	:	2 %(V)
Evaporation rate	:	No data available
Relative vapour density	:	No data available
Relative Density/Specific Gravity	:	No data available
Density	:	0.8 g/cm ³ (68 °F (20 °C))
Solubility(ies)	:	
Water solubility	:	completely miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard. No decomposition if stored and applied as directed.
Chemical stability	:	Stable; polymerization will not occur No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No data available No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	No data available Heat, flames and sparks.
Incompatible materials	:	Strong acids and oxidizing agents
Hazardous decomposition	:	No hazardous decomposition products are known.

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

products

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation

Eyes

Skin contact

Skin Absorption

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

Components:**67-63-0 Isopropanol:**

Acute oral toxicity : LD50 (Rat): 5,840 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

8002-74-2 Wax:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation**Product:**

Remarks: No data available

Components:**67-63-0 Isopropanol:**

Species: Rabbit

Result: Moderate skin irritation

Serious eye damage/eye irritation**Product:**

Remarks: Causes serious eye irritation.

Components:**67-63-0 Isopropanol:**

Species: Rabbit

Result: Eye irritation

Respiratory or skin sensitisation**Product:**

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

Remarks: No data available

Components:**67-63-0 Isopropanol:**

Test Type: Buehler Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: No known chronic health effects.

Aspiration toxicity**Product:**

No data available

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations are irritating to the respiratory tract. Has caused headaches, dizziness, nausea, vomiting and CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause severe irritation.

Ingestion:

Symptoms:

Ingestion will probably irritate the digestive tract; high dosages may cause CNS depression.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Toxicity to fish :
Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates : Remarks: No data available

Persistence and degradability
Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential
Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : There is no data available for this product.
information
No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

EPA Hazardous Waste : D001: Ignitable
Code(s)

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.
Do not dispose of waste into sewer.

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

Contaminated packaging : Do not contaminate ponds, waterways or ditches with chemical or used container.
 : Send to a licensed waste management company.
 : Empty remaining contents.
 : Dispose of as unused product.
 : Do not re-use empty containers.
 : Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1219
 Proper shipping name : Isopropanol solution
 Class : 3
 Packing group : II
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 364
 Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1219
 Proper shipping name : ISOPROPANOL, SOLUTION
 Class : 3
 Packing group : II
 Labels : 3
 EmS Code : F-E, S-D
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1219
 Proper shipping name : Isopropanol, solution
 Class : 3
 Packing group : II
 Labels : FLAMMABLE LIQUID
 ERG Code : 129
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Isopropanol	67-63-0	80 %
-------------	---------	------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Non-volatile (Wt) : 20 %
 Method: 60min/125°C
 DIN EN ISO 3251
 Non-volatile information is not a specification.

Massachusetts Right To Know

Isopropanol	67-63-0
Wax	8002-74-2

Pennsylvania Right To Know

Isopropanol	67-63-0
Wax	8002-74-2

CERACOL 83

Version 4

Revision Date 05/17/2026

Print Date 06/11/2026

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5863

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.