

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CERAFK 106  
UFI : 9999-X0FJ-C00P-A539  
Product code : 00000000000111663

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wax Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK Netherlands BV  
Danzigweg 23  
7418 EN Deventer  
Telephone : +31 881 220 300  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:				
Signal word	:	Danger			
Hazard statements	:	H226	Flammable liquid and vapour.		
		H304	May be fatal if swallowed and enters airways.		
		H315	Causes skin irritation.		
		H318	Causes serious eye damage.		
		H335	May cause respiratory irritation.		
		H336	May cause drowsiness or dizziness.		
		H373	May cause damage to organs through prolonged or repeated exposure.		
		H412	Harmful to aquatic life with long lasting effects.		
Precautionary statements	:	<b>Prevention:</b>			
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
		P260	Do not breathe mist or vapours.		
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.		
		<b>Response:</b>			
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.		
		P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.		
		P331	Do NOT induce vomiting.		
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.		

#### Hazardous components which must be listed on the label:

- 123-86-4 n-butyl acetate
- 1330-20-7 Xylene, mixture of isomers
- 71-36-3 butan-1-ol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Dispersion based on ethylene-vinyl-acetate copolymer wax

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 30 - < 50
Xylene, mixture of isomers	1330-20-7 01-2119488216-32	Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Aquatic Chronic 3; H412	>= 25 - < 30
ethylbenzene	100-41-4 202-849-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 12,5
butan-1-ol	71-36-3 200-751-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) STOT SE 3; H336 (Central nervous system)	>= 5 - < 7

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

For explanation of abbreviations see section 16.

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep away from heat.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
------------	---------	-------------------------------	--------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAC 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

n-butyl acetate	123-86-4	TWA	50 ppm 240 mg/m <sup>3</sup>	CH SUVA
Further information: National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases, Harm to the unborn child is not to be expected when the OEL-value is respected				
		STEL	150 ppm 720 mg/m <sup>3</sup>	CH SUVA
Further information: National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases, Harm to the unborn child is not to be expected when the OEL-value is respected				
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
Xylene, mixture of isomers	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	50 ppm 220 mg/m <sup>3</sup>	CH SUVA
Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases				
		STEL	100 ppm 440 mg/m <sup>3</sup>	CH SUVA
Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases				
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	200 ppm 884 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	50 ppm 220 mg/m <sup>3</sup>	CH SUVA
Further information: noise amplifying ototoxicity, Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

	additional skin resorption a substancial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health			
		STEL	50 ppm 220 mg/m <sup>3</sup>	CH SUVA
	Further information: noise amplifying ototoxicity, Toxic by skin resorption possible; Substances, which are easily absored through the skin, can give by additional skin resorption a substancial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health			
butan-1-ol	71-36-3	TWA	100 ppm 310 mg/m <sup>3</sup>	CH SUVA
	Further information: National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	100 ppm 310 mg/m <sup>3</sup>	CH SUVA
	Further information: National Institute for Occupational Safety and Health, National Institute of Research and Safety for the prevention of work accidents and occupational diseases, Harm to the unborn child is not to be expected when the OEL-value is respected			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene, mixture of isomers	1330-20-7	methyl hippuric acids: 2 g/l (Urine)	Immediately after exposure or after working hours	CH BAT
ethylbenzene	100-41-4	mandelic acid and phenyl glyoxylic acid: 600 mg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT
butan-1-ol	71-36-3	n-butanol: 10 mg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT
		n-butanol: 2 mg/g creatinine (Urine)	Before next shift or 16 hours after last shift	CH BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	11 mg/kg
	Workers	Dermal	Acute systemic effects	11 mg/kg
	Consumers	Dermal	Long-term systemic	6 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

			effects	
	Consumers	Dermal	Acute systemic effects	6 mg/kg
	Consumers	Oral	Long-term systemic effects	2 mg/m3
	Consumers	Oral	Acute systemic effects	2 mg/m3
Xylene, mixture of isomers	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Dermal	Long-term systemic effects	212 mg/kg
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	125 mg/kg
	Consumers	Oral	Long-term systemic effects	1,5 mg/kg
	Consumers	Inhalation	Acute local effects	260 mg/m3
butan-1-ol	Workers	Inhalation	Long-term exposure, Local effects	310 mg/m3
	Consumers	Inhalation	Long-term exposure, Local effects	55 mg/m3
	Consumers	Ingestion	Long-term exposure, Systemic effects	3,125 mg/cm2

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Intermittent releases	0,36 mg/l
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,0903 mg/kg
	Sewage treatment plant	35,6 mg/l
Xylene, mixture of isomers	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Soil	2,31 mg/kg
	Sewage treatment plant	6,58 mg/l
	Intermittent releases	0,327 mg/l
butan-1-ol	Fresh water	0,082 mg/l
	Marine water	0,0082 mg/l
	Fresh water sediment	0,178 mg/kg
	Marine sediment	0,0178 mg/kg
	Soil	0,015 mg/kg
	Intermittent releases	2,25 mg/l
	Sewage treatment plant	2476 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : PVA  
Break through time : 480 min  
Protective index : Class 6

Remarks : The information is based on our own tests, on data from literature and information from protective glove producers or is based on data obtained from similar substances. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Filter type : Organic vapour type (A)

#### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : dispersion  
Colour : white  
Odour Threshold : No data available  
Melting point/freezing point : No data available  
Initial boiling point and boiling range : 130 °C  
Upper explosion limit / Upper flammability limit : 11 %(V)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

---

Lower explosion limit / Lower flammability limit	:	1 %(V)
Flash point	:	24 °C Method: 49 (Pensky-Martens), closed cup
Decomposition temperature	:	No data available
pH	:	insoluble
Viscosity		
Viscosity, dynamic	:	10 mPa.s Method: No information available.
Viscosity, kinematic	:	7 mm <sup>2</sup> /s (40 °C) Method: No information available.
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	0,9 g/cm <sup>3</sup> (20 °C, 1.013 hPa)
Relative vapour density	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

### 10.6 Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 (Rat, male): > 10.000 mg/kg  
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14.000 mg/kg  
Method: OECD Test Guideline 402

##### **Xylene, mixture of isomers:**

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 4.200 mg/kg  
GLP: No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAC 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

### **butan-1-ol:**

Acute oral toxicity : LD50 (Rat, female): 2.292 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, male): 3.430 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Product:**

Remarks : May irritate skin.  
May cause skin irritation in susceptible persons.

#### **Components:**

##### **n-butyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

##### **butan-1-ol:**

Species : Rabbit  
Method : Draize Test  
Result : Skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye damage.

#### **Product:**

Remarks : May cause irreversible eye damage.

#### **Components:**

##### **n-butyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

##### **butan-1-ol:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Risk of serious damage to eyes.  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Components:

##### n-butyl acetate:

Test Type	:	Buehler Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.

##### butan-1-ol:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
GLP	:	yes

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

### STOT - single exposure

May cause respiratory irritation.  
May cause drowsiness or dizziness.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### Components:

##### butan-1-ol:

No aspiration toxicity classification

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Scenedesmus subspicatus): 675 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l  
End point: Reproduction  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

##### **Xylene, mixture of isomers:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l  
Exposure time: 24 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

- NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: Daphnia sp. (water flea)
- NOEC: 0,96 mg/l  
Exposure time: 7 d  
Species: Daphnia sp. (water flea)
- butan-1-ol:**
- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.376 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.328 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes
- Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 225 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4,1 mg/l  
End point: Reproduction  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

### 12.2 Persistence and degradability

**Product:**

Biodegradability : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

### Components:

#### **n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D

#### **Xylene, mixture of isomers:**

Biodegradability : Test Type: aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes

#### **butan-1-ol:**

Biodegradability : Test Type: aerobic  
Result: Readily biodegradable.

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

### Components:

#### **n-butyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 2,3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

#### **Xylene, mixture of isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Exposure time: 56 d  
Bioconcentration factor (BCF): 25,9  
GLP: no

Partition coefficient: n-  
octanol/water : Pow: 3,2 (20 °C)  
pH: 7

#### **butan-1-ol:**

Partition coefficient: n-  
octanol/water : log Pow: 1 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1993  
ADR : UN 1993  
RID : UN 1993  
IMDG : UN 1993

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

**IATA** : UN 1993

### 14.2 UN proper shipping name

**ADN** : FLAMMABLE LIQUID, N.O.S.  
(BUTYL ACETATE, Xylene)

**ADR** : FLAMMABLE LIQUID, N.O.S.  
(n-Butylacetate, Xylene)

**RID** : FLAMMABLE LIQUID, N.O.S.  
(n-Butylacetate, Xylene)

**IMDG** : FLAMMABLE LIQUID, N.O.S.  
(BUTYL ACETATE, XYLENE)

**IATA** : Flammable liquid, n.o.s.  
(Butyl acetate, Xylene)

### 14.3 Transport hazard class(es)

**ADN** : 3

**ADR** : 3

**RID** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : D/E

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : IMDG Code segregation group - none

**IATA (Cargo)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
  
Number on list 5: benzene  
  
Number on list 72: benzene  
  
Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.  
  
Number on list 78:  
Polymers of vinyl acetate or of other

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

vinyl esters, in primary forms; other  
vinyl polymers in primary forms  
synthetic polymer microparticles  
(SPM) content: 5 - 10 %  
The synthetic polymer microparticles  
supplied is subject to conditions laid  
down by entry 78 of Annex XVII to  
Regulation (EC) No 1907/2006 of  
the European Parliament and of the  
Council

- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Fire Hazard Class : A II: Flash point 21 °C to 55 °C, at 15 °C not miscible in water

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

- Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC)  
Volatile organic compounds (VOC) content: 94 %

### 15.2 Chemical safety assessment

Not applicable

---

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

- H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H412	:	Harmful to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
CH BAT	:	Switzerland. List of BAT-values
CH SUVA	:	Switzerland. Limit values at the work place
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention;

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H335
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304

#### Classification procedure:

Based on product data or assessment
Calculation method

<b>Aquatic Chronic 3</b>	<b>H412</b>	<b>Calculation method</b>
--------------------------	-------------	---------------------------

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERAFAK 106

Version: 16.0  
SDB\_CH

Revision Date: 16.01.2026

Date of last issue: 26.09.2025  
Print Date: 20.01.2026

---

## Annex: Exposure Scenarios

### Table of Contents

Number	Title
--------	-------