

**CERAFK 106**Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : CERAFK 106  
Product code : 000000000000111663

**Manufacturer or supplier's details**

Company : BYK Netherlands BV  
Address : Danzigweg 23  
7418 EN Deventer  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com  
Emergency telephone number : 18000 74234 (toll –free number, access from Australia only)  
+61 2 8014 4558

**Importer**

Company : Alchemy Agencies Pty Ltd  
Level 15, 28 Freshwater Place  
Southbank, Victoria, Australia 3006  
Tel: +61 3 9116 6359

Use of the Sub-  
stance/Mixture : Wax Additive

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3  
Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)  
Specific target organ toxicity - repeated exposure : Category 2 (hearing organs)  
Aspiration hazard : Category 1  
Long-term (chronic) aquatic hazard : Category 3

## CERAFAK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

**GHS label elements**

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	<p>H226 Flammable liquid and vapour.  H304 May be fatal if swallowed and enters airways.  H315 Causes skin irritation.  H318 Causes serious eye damage.  H335 May cause respiratory irritation.  H336 May cause drowsiness or dizziness.  H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.  H412 Harmful to aquatic life with long lasting effects.</p>
Precautionary statements	:	<p><b>Prevention:</b>  P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  P233 Keep container tightly closed.  P240 Ground and bond container and receiving equipment.  P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  P242 Use non-sparking tools.  P243 Take action to prevent static discharges.  P260 Do not breathe mist or vapours.  P264 Wash skin thoroughly after handling.  P271 Use only outdoors or in a well-ventilated area.  P273 Avoid release to the environment.  P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.</p> <p><b>Response:</b>  P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  P314 Get medical advice/ attention if you feel unwell.  P331 Do NOT induce vomiting.  P332 + P313 If skin irritation occurs: Get medical advice/ attention.  P362 + P364 Take off contaminated clothing and wash it before reuse.  P370 + P378 In case of fire: Use dry sand, dry chemical or</p>

## CERAFAC 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
 Chemical nature : Dispersion based on ethylene-vinyl-acetate copolymer wax

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
n-butyl acetate	123-86-4	>= 30 -< 50
Xylene, mixture of isomers	1330-20-7	>= 25 -< 30
ethylbenzene	100-41-4	>= 10 -< 12.5
butan-1-ol	71-36-3	>= 5 -< 7

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this safety data sheet to the doctor in attendance.  
 Symptoms of poisoning may appear several hours later.  
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 Continue rinsing eyes during transport to hospital.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
 Do NOT induce vomiting.  
 Do not give milk or alcoholic beverages.

## CERAFAK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

Most important symptoms and effects, both acute and delayed	: Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. No information available. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Notes to physician	: No information available.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Hazchem Code	: •3Y

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against	: Do not spray on a naked flame or any incandescent material.
------------------------------	---

## CERAFK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

fire and explosion		Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
Conditions for safe storage	:	No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Further information on storage conditions	:	Keep away from heat.
Further information on storage stability	:	No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m <sup>3</sup>	AU OEL
		STEL	200 ppm 950 mg/m <sup>3</sup>	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Xylene, mixture of isomers	1330-20-7	TWA	80 ppm 350 mg/m <sup>3</sup>	AU OEL
		STEL	150 ppm 655 mg/m <sup>3</sup>	AU OEL
		TWA	20 ppm	ACGIH
		TWA	100 ppm 434 mg/m <sup>3</sup>	AU OEL
ethylbenzene	100-41-4	STEL	125 ppm	AU OEL

## CERAFAK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

			543 mg/m <sup>3</sup>	
		TWA	20 ppm	ACGIH
butan-1-ol	71-36-3	Peak limit	50 ppm 152 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		TWA	20 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection  
 Material : PVA  
 Break through time : 480 min  
 Protective index : Class 6

Remarks : Wear suitable gloves.  
 Eye protection : Eye wash bottle with pure water  
 Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : dispersion  
 Colour : white  
 Odour Threshold : No data available  
 pH : insoluble  
 Melting point/freezing point : No data available

## CERAFK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

---

Initial boiling point and boiling range	:	130 °C
Flash point	:	24 °C
		Method: 49 (Pensky-Martens), closed cup
Evaporation rate	:	No data available
Upper explosion limit / Upper flammability limit	:	11 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9 g/cm <sup>3</sup> (20 °C, 1,013 hPa)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	10 mPa.s
		Method: No information available.
Viscosity, kinematic	:	7 mm <sup>2</sup> /s ( 40 °C)
		Method: No information available.

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), dense black smoke.

## CERAFAC 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified due to lack of data.

**Product:**Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation methodAcute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method**Components:****n-butyl acetate:**Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg  
Method: OECD Test Guideline 423Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yesAcute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg  
Method: OECD Test Guideline 402**Xylene, mixture of isomers:**Acute oral toxicity : LD50 (Rat): 4,300 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: noAcute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg  
GLP: No information available.**butan-1-ol:**Acute oral toxicity : LD50 (Rat, female): 2,292 mg/kg  
Method: OECD Test Guideline 401Acute dermal toxicity : LD50 (Rabbit, male): 3,430 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes**Skin corrosion/irritation**

Causes skin irritation.

## CERAFAC 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026**Product:**

Remarks : May irritate skin.  
May cause skin irritation in susceptible persons.

**Components:****n-butyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**butan-1-ol:**

Species : Rabbit  
Method : Draize Test  
Result : Skin irritation

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Product:**

Remarks : May cause irreversible eye damage.

**Components:****n-butyl acetate:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

**butan-1-ol:**

Species : Rabbit  
Result : Risk of serious damage to eyes.  
Method : OECD Test Guideline 405  
GLP : yes

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified due to lack of data.

**Respiratory sensitisation**

Not classified due to lack of data.

**Components:****n-butyl acetate:**

Test Type : Buehler Test  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

## CERAFAC 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026**butan-1-ol:**

Test Type : Maximisation Test  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

**Chronic toxicity****Germ cell mutagenicity**

Not classified due to lack of data.

**Carcinogenicity**

Not classified due to lack of data.

**Reproductive toxicity**

Not classified due to lack of data.

**STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

**STOT - repeated exposure**

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Components:****butan-1-ol:**

No aspiration toxicity classification

**Further information****Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****n-butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 44 mg/l

## CERAFK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

aquatic invertebrates	Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Scenedesmus subspicatus): 675 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 23 mg/l End point: Reproduction Exposure time: 21 d Method: OECD Test Guideline 211
<b>Xylene, mixture of isomers:</b>	
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1 mg/l Exposure time: 24 h Test Type: Immobilization Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Selenastrum capricornutum (green algae)): 2.2 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes
	: NOEC (Pseudokirchneriella subcapitata (green algae)): 0.44 mg/l Exposure time: 72 h Test Type: Growth inhibition Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l Exposure time: 56 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia sp. (water flea)): 1.17 mg/l Exposure time: 7 d
	: NOEC (Daphnia sp. (water flea)): 0.96 mg/l Exposure time: 7 d
<b>butan-1-ol:</b>	
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1,328 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae/aquatic plants	: ErC50 (Selenastrum capricornutum (green algae)): 225 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 201

## CERAFAC 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 4.1 mg/l  
End point: Reproduction  
Exposure time: 21 d  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Components:****n-butyl acetate:**Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D**Xylene, mixture of isomers:**Biodegradability : aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
GLP: yes**butan-1-ol:**Biodegradability : aerobic  
Result: Readily biodegradable.**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Components:****n-butyl acetate:**Partition coefficient: n-octanol/water : log Pow: 2.3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes**Xylene, mixture of isomers:**Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 25.9  
Exposure time: 56 d  
GLP: noPartition coefficient: n-octanol/water : Pow: 3.2 (20 °C)  
pH: 7

## CERAFAK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026**butan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 1 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Butyl acetate, XYLENE)  
Class : 3  
Packing group : III  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Butyl acetate, Xylene)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

## CERAFK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026**IMDG-Code**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(BUTYL ACETATE, XYLENE)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no  
Remarks : IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Butyl acetate, Xylene)  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : •3Y

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**SECTION 16. OTHER INFORMATION**

Revision Date : 15.04.2026  
Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit  
AU OEL / Peak limit : Exposure standard - peak

## CERAFAK 106

Version 2.6  
SDS\_AU

Revision Date: 15.04.2026

Date of last issue: 16.01.2026  
Print Date 22.04.2026

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN