

CERAFLOUR 1000

Biodegradable, micronized polymer with wax-like properties based on renewable raw materials for aqueous, solvent-borne, solvent-free, and UV systems for matting and improving the surface protection and soft feel effect.

Product data

Composition

Micronized polyester

VOC-free (< 1500 ppm)
From bio-based raw
materials

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C):	1.25 g/cm ³
Melting point:	175 °C
Particle size distribution D50:	5 µm
Particle size distribution D90:	11 µm
Bio-based carbon content (ASTM D6866):	97 %
Delivery form:	micropowder

Storage and transportation

Product shelf life in unopened original packaging: 24 months

Temperature sensitive. To be stored and transported at a temperature below 50 °C.

Special note

CERAFLOUR 1000 is readily biodegradable and is therefore sensitive to microbial infestation if stored in open containers in a damp environment.

Applications

Coatings industry

Special features and benefits

CERAFLOUR 1000 enhances scratch resistance and improves the anti-blocking properties and soft feel effect. The additive has a matting effect, especially in radiation curable systems, and produces transparent coatings. It has no effect on the viscosity and surface slip, and does not cause foam stabilization. CERAFLOUR 1000 is readily biodegradable and is composed of > 97% renewable raw materials.

Recommended use

The additive is recommended for aqueous, solvent-borne, solvent-free, and UV systems.

Architectural coatings	<input checked="" type="checkbox"/>
General industrial coatings	<input checked="" type="checkbox"/>
Wood and furniture coatings	<input checked="" type="checkbox"/>

especially recommended recommended

Recommended levels

1-10% additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive should preferably be post-added to the coating using a low shear rate. Aqueous slurries of CERAFLOUR 1000 that will not be processed immediately must have a suitable preservative added so as to protect against microbial infestation.

Printing inks**Special features and benefits**

CERAFLOUR 1000 has a matting effect on aqueous and solvent-borne printing inks, overprint varnishes, and radiation curable systems, while simultaneously ensuring high transparency. The additive provides an excellent soft feel effect.

Recommended levels

1-5 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive should preferably be incorporated into the printing ink or overprint varnish at a medium shear rate at the end of the production process.

Paper coatings**Special features and benefits**

CERAFLOUR 1000 improves the anti-blocking properties and soft feel effect. The additive has a matting effect and has only a minor effect on transparency and viscosity. CERAFLOUR 1000 has no effect on foam stabilization.

Recommended levels

1-10 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive should preferably be incorporated into the coating at a low shear rate before adding the thickeners. Aqueous slurries of CERAFLOUR 1000 that will not be processed immediately must have a suitable preservative added so as to protect against microbial infestation. The slurry should be stirred thoroughly before use.

Leather finishes and coated fabrics

Special features and benefits

CERAFLOUR 1000 enhances scratch resistance and improves the anti-blocking properties and soft feel effect. The additive has a matting effect and produces highly transparent coatings. It has no effect on the viscosity and surface slip, and does not cause foam stabilization. CERAFLOUR 1000 is readily biodegradable and is composed of > 97 % renewable raw materials.

Recommended levels

1-10 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive should preferably be post-added to the coating using a low shear rate. Aqueous slurries of CERAFLOUR 1000 that will not be processed immediately must have a suitable preservative added so as to protect against microbial infestation.



Your local
contact

BYK-Chemie GmbH

Abelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
info@byk.com
www.byk.com



Download
our app:
byk.com/app

ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, NANOBYPK®, OPTIBENT®, OPTIGEL®, PURABYPK®, RECYCLOBYPK®, RHEOBYPK®, SCONA®, SILBYPK®, TIXOGEL® and VISCOBYPK® are registered trademarks of the BYK group.

The information contained herein is based on our current knowledge and experience. No warranties, guarantees and/or assurances of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. Any information about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. Contractual terms and conditions, in particular agreed product specifications, always take precedence. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. We reserve the right to make any changes and to update the information herein without notice.