

CERAMAT 250

Product code: 00000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

SECTION 1: Identification of the hazardous chemical and of the supplier**Product identifier**

Product name : CERAMAT 250
Recommended use : Wax Additive

Manufacturer or supplier's details

Company : BYK Netherlands BV
Address : Danzigweg 23
7418 EN Deventer
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com
Emergency telephone number : +60 3 6207 4347 (Malay and English)
+65 3158 1074 (All languages)

SECTION 2: Hazards identification**Classification of the hazardous chemical**

Flammable liquids : Category 3
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Label elements

Hazard pictograms :  

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

CERAMAT 250

Product code: 00000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture
Chemical nature : Fischer Tropsch wax dispersion

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--------------------------------------|-----------|-----------------------|
| n-butyl acetate | 123-86-4 | >= 50 -<= 100 |
| Paraffin waxes and Hydrocarbon waxes | 8002-74-2 | >= 30 -< 50 |

SECTION 4: First aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No information available.
No information available.

Notes to physician : No information available.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

CERAMAT 250

Product code: 00000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Physicochemical hazards arising from the chemical

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides

Special protective equipment and precautions for fire-fighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling****Precautions for safe handling**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

CERAMAT 250

Product code: 000000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Storage

Conditions for safe storage, including any incompatibilities

- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep away from heat.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection

Control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|-----------|----------------------------------|---|--------|
| n-butyl acetate | 123-86-4 | TWA | 150 ppm 713 mg/m ³ | MY PEL |
| | | TWA | 150 ppm | ACGIH |
| | | STEL | 200 ppm | ACGIH |
| Paraffin waxes and Hydrocarbon waxes | 8002-74-2 | TWA (Fumes) | 2 mg/m ³ | MY PEL |
| | | TWA (Fumes) | 2 mg/m ³ | ACGIH |

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
- Skin protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hand protection
Material : Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Remarks : Wear suitable gloves.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

- Appearance : dispersion

CERAMAT 250

Product code: 00000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

| | | |
|--|---|--|
| Colour | : | white |
| Odour | : | fruity |
| Odour Threshold | : | No data available |
| pH | : | insoluble |
| Melting point/freezing point | : | No data available |
| Boiling point/boiling range | : | 126 °C (1,013 hPa) |
| Flash point | : | 25 °C Method: 49 (Pensky-Martens), closed cup |
| Evaporation rate | : | No data available |
| Flammability (liquids) | : | Sustains combustion |
| Upper explosion limit / Upper flammability limit | : | 7.5 %(V) |
| Lower explosion limit / Lower flammability limit | : | 1.2 %(V) |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | 0.9 g/cm ³ (20 °C, 1,013 hPa) |
| Solubility(ies) | | |
| Water solubility | : | immiscible |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Auto-ignition temperature | : | not determined |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | 100 mPa.s Method: DIN 53019 |

SECTION 10: Stability and reactivity

| | | |
|--------------------|---|---|
| Reactivity | : | No decomposition if stored and applied as directed. |
| Chemical stability | : | No decomposition if stored and applied as directed. |

CERAMAT 250

Product code: 000000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

Components:**n-butyl acetate:**

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation**Product:**

Remarks : No data available

Components:**n-butyl acetate:**

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation**Product:**

Remarks : No data available

CERAMAT 250

Product code: 000000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Components:**n-butyl acetate:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Respiratory or skin sensitisation**Product:**

Remarks : No data available

Components:**n-butyl acetate:**

Test Type : Buehler Test
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks : No data available

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks : No data available

STOT - repeated exposure**Product:**

Remarks : No data available

CERAMAT 250

Product code: 000000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Repeated dose toxicity**Product:**

Remarks : No data available

Aspiration toxicity**Product:**

No data available

Further information**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity****Product:**Toxicity to fish :
Remarks: No data available**Components:****n-butyl acetate:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l
Exposure time: 48 hToxicity to algae/aquatic plants : ErC50 (Scenedesmus subspicatus): 675 mg/l
Exposure time: 72 hToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23 mg/l
End point: Reproduction
Exposure time: 21 d
Method: OECD Test Guideline 211**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

CERAMAT 250

Product code: 000000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Components:**n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**n-butyl acetate:**

Partition coefficient: n- : log Pow: 2.3 (25 °C)
octanol/water pH: 7
Method: OECD Test Guideline 117
GLP: yes

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological : No data available
information

SECTION 13: Disposal information**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**International Regulations****IATA-DGR**

UN/ID No. : UN 1123
Proper shipping name : Butyl acetates, solution
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo : 366
aircraft)
Packing instruction : 355

CERAMAT 250

Product code: 00000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

(passenger aircraft)

IMDG-Code

UN number : UN 1123
Proper shipping name : BUTYL ACETATES, solution
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information**Safety, health, and environmental regulations specific for the hazardous chemical**

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
MY PEL / TWA : Eight-hour time-weighted average airborne concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing

CERAMAT 250

Product code: 000000000000111744

Version 3.1 SDS_APJ_MY

Revision Date 04.03.2024

Print Date 10.04.2024

Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN