

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : CERAMAT 250

Product code : 000000000000111744

Manufacturer or supplier's details

Company : BYK Netherlands BV

Address : Danzigweg 23
7418 EN Deventer

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

Emergency telephone number : 18000 74234 (toll –free number, access from Australia only)
+61 2 8014 4558

Importer

Company : IMCD Australia Pty Ltd
Level 1, 352 Wellington Road
Mulgrave
VIC 3170
Australia
Telephone: +61 3 8544 3100

Use of the Sub-
stance/Mixture : Wax Additive

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Specific target organ toxicity -
single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Fischer Tropsch wax dispersion

Components

Chemical name	CAS-No.	Concentration (% w/w)
n-butyl acetate	123-86-4	>= 50 -<= 100
Paraffin waxes and Hydrocarbon waxes	8002-74-2	>= 30 -< 50

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

If inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	No information available. May cause drowsiness or dizziness.
Notes to physician	:	No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire-fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides
Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containment. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Hazchem Code	:	3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep away from heat.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m ³	AU OEL
		STEL	200 ppm 950 mg/m ³	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Paraffin waxes and Hydrocarbon waxes	8002-74-2	TWA (Fumes)	2 mg/m ³	AU OEL
		TWA	2 mg/m ³	ACGIH

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

		(Fumes)		
--	--	---------	--	--

Personal protective equipment

Respiratory protection	:	In the case of vapour formation use a respirator with an approved filter.
Hand protection	:	
Material	:	Polyvinyl alcohol or nitrile- butyl-rubber gloves
Remarks	:	Wear suitable gloves.
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	dispersion
Colour	:	white
Odour	:	fruity
Odour Threshold	:	No data available
pH	:	insoluble
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	126 °C (1,013 hPa)
Flash point	:	25 °C Method: 49 (Pensky-Martens), closed cup
Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	7.5 %(V)
Lower explosion limit / Lower flammability limit	:	1.2 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9 g/cm ³ (20 °C, 1,013 hPa)

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 100 mPa.s Method: DIN 53019

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Components:**n-butyl acetate:**

Acute oral toxicity	: LD50 (Rat, male): > 10,000 mg/kg Method: OECD Test Guideline 423
Acute inhalation toxicity	: LC50 (Rat, male and female): > 21.1 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 GLP: yes
Acute dermal toxicity	: LD50 (Rabbit, male and female): > 14,000 mg/kg Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified due to lack of data.

CERAMAT 250Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024**Product:**

Remarks : No data available

Components:**n-butyl acetate:**Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation**Serious eye damage/eye irritation**

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**n-butyl acetate:**Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes**Respiratory or skin sensitisation****Skin sensitisation**

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**n-butyl acetate:**Test Type : Buehler Test
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.**Chronic toxicity****Germ cell mutagenicity**

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

STOT - repeated exposure

Not classified due to lack of data.

Product:

Remarks : No data available

Repeated dose toxicity**Product:**

Remarks : No data available

Aspiration toxicity

Not classified due to lack of data.

Product:

No data available

Further information**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity**Product:**

Toxicity to fish :
Remarks: No data available

Components:**n-butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 44 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Scenedesmus subspicatus): 675 mg/l
plants Exposure time: 72 h

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 23 mg/l
aquatic invertebrates (Chron- End point: Reproduction
ic toxicity) Exposure time: 21 d
Method: OECD Test Guideline 211

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Components:**n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**n-butyl acetate:**

Partition coefficient: n- : log Pow: 2.3 (25 °C)
octanol/water pH: 7
Method: OECD Test Guideline 117
GLP: yes

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1123
Proper shipping name : BUTYL ACETATES SOLUTION
Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1123
Proper shipping name : Butyl acetates, solution
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1123
Proper shipping name : BUTYL ACETATES, solution
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024**ADG**

UN number : UN 1123
Proper shipping name : BUTYL ACETATES SOLUTION
Class : 3
Packing group : III
Labels : 3
Hazchem Code : 3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

SECTION 16. OTHER INFORMATION

Revision Date : 17.12.2024
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
AU OEL / TWA : Exposure standard - time weighted average
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect

CERAMAT 250

Version 1.2
SDS_AU

Revision Date: 17.12.2024

Date of last issue: 04.03.2024
Print Date 18.12.2024

Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN