

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 1. IDENTIFICATION**

Product name : DISPERBYK-162

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting &amp; Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Eye irritation : Category 2A

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposureSpecific target organ toxicity : Category 2 (hearing organs, Kidney, Liver)  
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.

## DISPERBYK-162

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

H373 May cause damage to organs (hearing organs, Kidney, Liver) through prolonged or repeated exposure.

### Precautionary statements

#### : **Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

#### **Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
 Chemical nature : Solution of modified polyurethane

## DISPERBYK-162

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

### Hazardous components

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate	108-65-6	>= 20 - < 30
Xylene	1330-20-7	>= 10 - < 20
n-Butyl Acetate	123-86-4	>= 10 - < 20
Ethyl benzene	100-41-4	>= 5 - < 10

### SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: No information available.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## DISPERBYK-162

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

Special protective equipment for firefighters : For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.  
: Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
Xylene	1330-20-7	TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
Xylene		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
Xylene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
Xylene		TWA	20 ppm	ACGIH
n-Butyl Acetate	123-86-4	TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA Z-1
n-Butyl Acetate		TWA	150 ppm 710 mg/m <sup>3</sup>	OSHA P0
n-Butyl Acetate		STEL	200 ppm 950 mg/m <sup>3</sup>	OSHA P0
n-Butyl Acetate		TWA	150 ppm 710 mg/m <sup>3</sup>	NIOSH REL
n-Butyl Acetate		ST	200 ppm 950 mg/m <sup>3</sup>	NIOSH REL
n-Butyl Acetate		TWA	50 ppm	ACGIH
n-Butyl Acetate		STEL	150 ppm	ACGIH
Ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
Ethyl benzene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
Ethyl benzene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
Ethyl benzene		STEL	125 ppm 545 mg/m <sup>3</sup>	OSHA P0
Ethyl benzene		ST	125 ppm 545 mg/m <sup>3</sup>	NIOSH REL

**Engineering measures** : Use with local exhaust ventilation.

**Personal protective equipment**

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.  
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Silver Shield gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	: liquid
Colour	: colourless
Odour	: ester-like
Odour Threshold	: No data available
pH	: 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/ range	: < 32 °F (< 0 °C) Method: derived
Initial boiling point	: 255.20 °F (124.00 °C) Method: derived
Vapour pressure	: 7 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 82.40 °F (28.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: 12.00 %(V)
Lower explosion limit	: 1.20 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.0050 g/cm <sup>3</sup> (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 450 mm <sup>2</sup> /s (104.00 °F (40.00 °C))

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.  Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: None expected

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Skin Absorption  
Inhalation  
Eyes  
Ingestion

**Acute toxicity****Product:**

Acute oral toxicity	: LD50 (Rat, male and female): > 10,000 mg/kg Method: OECD Test Guideline 401 GLP: yes
---------------------	--

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

Acute inhalation toxicity : Acute toxicity estimate : 36.79 mg/l  
 Exposure time: 4 h  
 Test atmosphere: vapour  
 Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
 Method: Calculation method

**Components:**
**108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg  
 Method: OECD Test Guideline 401  
 GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm  
 Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**1330-20-7 Xylene:**

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg  
 Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
 GLP: no

Acute inhalation toxicity : LC50 (Rat): 5000 ppm  
 Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg  
  
 LD50 (Rabbit): > 4,200 mg/kg  
 GLP: No information available.

**123-86-4 n-Butyl Acetate:**

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg  
 Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l  
 Exposure time: 4 h  
 Test atmosphere: vapour  
 Method: OECD Test Guideline 403  
 GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg  
 Method: OECD Test Guideline 402

**100-41-4 Ethyl benzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

**Skin corrosion/irritation****Product:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation  
GLP: yes

**1330-20-7 Xylene:**

Species: Rabbit  
Result: Moderate skin irritation

**123-86-4 n-Butyl Acetate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**100-41-4 Ethyl benzene:**

Species: Rabbit  
Result: Moderate skin irritation

**Serious eye damage/eye irritation****Product:**

Species: Rabbit  
Result: Irritating to eyes.  
Assessment: Irritating to eyes.  
Method: OECD Test Guideline 405  
GLP: yes

Remarks: Causes serious eye irritation.

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
GLP: yes

**1330-20-7 Xylene:**

Species: Rabbit  
Result: Eye irritation

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

**123-86-4 n-Butyl Acetate:**

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

**100-41-4 Ethyl benzene:**

Species: Rabbit

Result: Moderate eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks: No data available

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

GLP: yes

**123-86-4 n-Butyl Acetate:**

Test Type: Buehler Test

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Carcinogenicity****Product:**

Remarks: No data available

**IARC**

Group 2B: Possibly carcinogenic to humans

Ethyl benzene

100-41-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**STOT - single exposure****Product:**

Remarks: No data available

**STOT - repeated exposure****Product:**

Remarks: No data available

**Repeated dose toxicity****Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver, kidney, brain, respiratory system, blood, and/or bone marrow in laboratory animals

Animal studies have shown ingredients caused fetotoxic effects at or near maternally toxic levels. Excessive inhalation of Xylene has caused hearing loss in laboratory animals. Hexane used in conjunction w/Xylene increased this effect. Chronic skin contact w/Xylene has caused dermatitis. Ingestion of Ethanol can increase the effects of over-exposure to Xylene. Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).

**Aspiration toxicity****Product:**

No data available

**Experience with human exposure****Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

Eye contact:	Symptoms:	Contact may cause irritation.
	Symptoms:	Contact will probably cause irritation.
Ingestion:	Symptoms:	May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.

**Further information**
**Product:**

Remarks: Inhalation of n-Butyl acetate may cause narcosis.

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**
**Product:**

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : No data available

## DISPERBYK-162

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

information

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- EPA Hazardous Waste Code(s) : D001: Ignitable  
D018: Benzene
- Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.  
Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1993
- Proper shipping name : Flammable liquid, n.o.s.  
(Xylene, Butyl acetate)
- Class : 3
- Packing group : III
- Labels : Flammable Liquids
- Packing instruction (cargo aircraft) : 366
- Packing instruction (passenger aircraft) : 355

##### IMDG-Code

- UN number : UN 1993
- Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, BUTYL ACETATE)
- : )
- Class : 3
- Packing group : III
- Labels : 3
- EmS Code : F-E, S-E
- Marine pollutant : no
- Remarks : IMDG Code segregation group - none

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## DISPERBYK-162

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

### National Regulations

#### 49 CFR

UN/ID/NA number : UN 1993  
 Proper shipping name : Flammable liquids, n.o.s.  
 (Xylene, Butyl acetate)  
 Class : 3  
 Packing group : III  
 Labels : FLAMMABLE LIQUID  
 ERG Code : 128  
 Marine pollutant : no  
 Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	572

#### SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

#### US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene 1330-20-7 17.4 %

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

Ethyl benzene	100-41-4	7.1 %
---------------	----------	-------

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	17.4 %
Ethyl benzene	100-41-4	7.1 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	17.4 %
n-Butyl Acetate	123-86-4	11.8 %
Ethyl benzene	100-41-4	7.1 %

Non-volatile (Wt) : 37 - 39 %  
 Method: 23 (20min/150°C)  
 DIN EN ISO 3251  
 Non-volatile information is not a specification.

**Massachusetts Right To Know**

Xylene	1330-20-7
n-Butyl Acetate	123-86-4
Ethyl benzene	100-41-4
Benzene	71-43-2

**Pennsylvania Right To Know**

Copolymer	-
1-Methoxy-2-propanol acetate	108-65-6
Xylene	1330-20-7
n-Butyl Acetate	123-86-4
Ethyl benzene	100-41-4
Toluene	108-88-3
Cumene	98-82-8
n-Butanol	71-36-3

**New Jersey Right To Know**

**New Jersey Trade Secret** : 800963-5162  
**Registry Number for the product (NJ TSRN)**

**California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**DISPERBYK-162**

Version 9

Revision Date 05/17/2026

Print Date 06/18/2026

**The components of this product are reported in the following inventories:**

- TSCA : All substances listed as active on the TSCA inventory
- Section 5a : No substances are subject to a Significant New Use Rule.
- Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.
- DSL : We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.