

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

**SECTION 1. IDENTIFICATION**

Product name : DISPERBYK-163 TF

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting &amp; Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2B

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposureSpecific target organ toxicity : Category 2 (Kidney, Liver)  
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.  
H315 + H320 Causes skin and eye irritation.  
H336 May cause drowsiness or dizziness.

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure.

## Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
 Chemical nature : Solution of a high molecular weight block copolymer with pigment affinic groups

**Hazardous ingredients**

| Component                    | CAS-No.   | Concentration (%) |
|------------------------------|-----------|-------------------|
| Xylene                       | 1330-20-7 | >= 20 - < 30      |
| 1-Methoxy-2-propanol acetate | 108-65-6  | >= 10 - < 20      |
| n-Butyl Acetate              | 123-86-4  | >= 10 - < 20      |
| Ethyl benzene                | 100-41-4  | >= 5 - < 10       |

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Show this material safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : No information available.

Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)

## DISPERBYK-163 TF

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

|  |   |
|--|---|
| Unsuitable extinguishing media                 | : Dry chemical<br>: High volume water jet   |
| Specific hazards during fire fighting          | : Do not allow run-off from fire fighting to enter drains or water courses.   |
| Hazardous combustion products                  | : Carbon oxides<br>: Nitrogen oxides (NOx)  |
| Further information                            | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary.  |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

|   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.               |
| Environmental precautions   | : Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods and materials for containment and cleaning up               | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

### SECTION 7. HANDLING AND STORAGE

|                         |  |
|-------------------------|--|
| Advice on safe handling | : Avoid formation of aerosol.<br>Do not breathe vapors/dust.<br>Avoid contact with skin and eyes.<br>For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Take precautionary measures against static discharges.<br>Provide sufficient air exchange and/or exhaust in work rooms.<br>Open drum carefully as content may be under pressure.<br>Dispose of rinse water in accordance with local and national regulations. |
|-------------------------|--|

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

Conditions for safe storage : No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

| Components                   | CAS-No.   | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|------------------------------|-----------|-------------------------------|--|-----------|
| Xylene                       | 1330-20-7 | TWA                           | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA Z-1  |
| Xylene                       |           | STEL                          | 150 ppm<br>655 mg/m <sup>3</sup>               | OSHA P0   |
| Xylene                       |           | TWA                           | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA P0   |
| Xylene                       |           | TWA                           | 20 ppm   | ACGIH     |
| 1-Methoxy-2-propanol acetate | 108-65-6  | TWA                           | 50 ppm   | US WEEL   |
| n-Butyl Acetate              | 123-86-4  | TWA                           | 150 ppm<br>710 mg/m <sup>3</sup>               | OSHA Z-1  |
| n-Butyl Acetate              |           | TWA                           | 150 ppm<br>710 mg/m <sup>3</sup>               | OSHA P0   |
| n-Butyl Acetate              |           | STEL                          | 200 ppm<br>950 mg/m <sup>3</sup>               | OSHA P0   |
| n-Butyl Acetate              |           | TWA                           | 150 ppm<br>710 mg/m <sup>3</sup>               | NIOSH REL |
| n-Butyl Acetate              |           | ST                            | 200 ppm<br>950 mg/m <sup>3</sup>               | NIOSH REL |
| n-Butyl Acetate              |           | TWA                           | 50 ppm   | ACGIH     |
| n-Butyl Acetate              |           | STEL                          | 150 ppm  | ACGIH     |
| Ethyl benzene                | 100-41-4  | TWA                           | 20 ppm   | ACGIH     |
| Ethyl benzene                |           | TWA                           | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA Z-1  |
| Ethyl benzene                |           | TWA                           | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA P0   |
| Ethyl benzene                |           | STEL                          | 125 ppm<br>545 mg/m <sup>3</sup>               | OSHA P0   |
| Ethyl benzene                |           | ST                            | 125 ppm<br>545 mg/m <sup>3</sup>               | NIOSH REL |

**Engineering measures** : Use with local exhaust ventilation.

**Personal protective equipment**

Respiratory protection : In the case of vapor formation use a respirator with an

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

|                          |   |
|--------------------------|---|
| Hand protection          | approved filter.  |
| Material                 | : Impervious gloves   |
| Remarks                  | : The suitability for a specific workplace should be discussed with the producers of the protective gloves.                             |
| Eye protection           | : Eye wash bottle with pure water<br>Tightly fitting safety goggles   |
| Skin and body protection | : Impervious clothing<br>Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Hygiene measures         | : When using do not eat or drink.<br>When using do not smoke.<br>Wash hands before breaks and at the end of workday.                    |

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

|   |  |
|---|--|
| Appearance                              | : liquid   |
| Color                                   | : colorless  |
| Odor                                    | : ester-like   |
| pH                                      | : 5, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator     |
| Melting point/freezing point            | : < 32 °F (< 0 °C)<br>Method: derived  |
| Initial boiling point and boiling range | : 255 °F (124 °C)<br>Method: derived   |
| Vapor pressure                          | : 7 hPa (68 °F (20 °C))<br>Method: derived                                       |
| Flash point                             | : 84 °F (29 °C)<br>Method: 48 (Abel-Pensky) DIN 51755                            |
| Upper explosion limit                   | : No data available  |
| Lower explosion limit                   | : No data available  |
| Relative vapor density                  | : No data available  |
| Density                                 | : 0.998 g/cm <sup>3</sup> (68 °F (20 °C))<br>Method: 4 (20°C oscillating U-tube) |
| Bulk density                            | : Not applicable   |
| Solubility(ies)                         |  |

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

|  |   |  |
|--|---|--|
| Water solubility                       | : | immiscible   |
| Partition coefficient: n-octanol/water | : | No data available  |
| Ignition temperature                   | : | > 392 °F (> 200 °C)<br>Method: M0062 (Analytics Wesel)                 |
| Thermal decomposition                  | : | No data available  |
| Viscosity                              | : |  |
| Viscosity, dynamic                     | : | No data available  |
| Viscosity, kinematic                   | : | 141.1 mm <sup>2</sup> /s (104 °F (40 °C))<br>Method: <b>calculated</b> |

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |  |
|------------------------------------|---|--|
| Reactivity                         | : | No decomposition if stored and applied as directed.  |
| Chemical stability                 | : | No decomposition if stored and applied as directed.  |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed.<br><br>Vapors may form explosive mixture with air. |
| Conditions to avoid                | : | Heat, flames and sparks.   |
| Incompatible materials             | : | Strong oxidizing agents  |
| Hazardous decomposition products   | : | No decomposition if stored and applied as directed.  |

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Ingestion  
Eye contact  
Skin contact

**Acute toxicity****Product:**

|                           |   |   |
|---------------------------|---|---|
| Acute oral toxicity       | : | Acute toxicity estimate : > 5,000 mg/kg<br>Method: Calculation method   |
| Acute inhalation toxicity | : | Acute toxicity estimate : 31 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapor<br>Method: Calculation method |

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****1330-20-7 Xylene:**

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: no

Acute inhalation toxicity : LC50 (Rat): 5000 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg  
  
LD50 (Rabbit): > 4,200 mg/kg  
GLP: No information available.

**108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**123-86-4 n-Butyl Acetate:**

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg  
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg  
Method: OECD Test Guideline 402

**100-41-4 Ethyl benzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

**Skin corrosion/irritation****Components:****1330-20-7 Xylene:**

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

Species: Rabbit  
Result: Moderate skin irritation

**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation  
GLP: yes

**123-86-4 n-Butyl Acetate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**100-41-4 Ethyl benzene:**

Species: Rabbit  
Result: Moderate skin irritation

**Serious eye damage/eye irritation****Components:****1330-20-7 Xylene:**

Species: Rabbit  
Result: Eye irritation

**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
GLP: yes

**123-86-4 n-Butyl Acetate:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
GLP: yes

**100-41-4 Ethyl benzene:**

Species: Rabbit  
Result: Moderate eye irritation

**Respiratory or skin sensitization****Product:**

Remarks: No data available

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig  
Method: OECD Test Guideline 406

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

Result: Not a skin sensitizer.  
GLP: yes

**123-86-4 n-Butyl Acetate:**

Test Type: Buehler Test  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitization.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Carcinogenicity****Product:**

Remarks: No data available

**IARC**

Group 2B: Possibly carcinogenic to humans

Ethyl benzene

100-41-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on fetal development : Remarks: No data available

**STOT-single exposure****Product:**

Remarks: No data available

**STOT-repeated exposure****Product:**

Remarks: No data available

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

**Repeated dose toxicity****Product:**

Remarks: No data available

**Aspiration toxicity****Product:**

No data available

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other :  
aquatic invertebrates : Remarks: No data available

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

## DISPERBYK-163 TF

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Xylene, 1-Methoxy-2-propanol acetate, Butyl acetate)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(XYLENE, 1-Methoxy-2-propanol acetate, BUTYL ACETATE)  
: )  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no  
Remarks : IMDG Code segregation group - none

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

**Domestic regulation**
**49 CFR**

UN/ID/NA number : UN 1993  
 Proper shipping name : Flammable liquids, n.o.s.  
 (Xylene, 1-Methoxy-2-propanol acetate, Butyl acetate)  
 Class : 3  
 Packing group : III  
 Labels : FLAMMABLE LIQUID  
 ERG Code : 128  
 Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know**
**US. EPA CERCLA Hazardous Substances (40 CFR 302)**

| Components | CAS-No.   | Component RQ<br>(lbs) | Calculated product RQ<br>(lbs) |
|------------|-----------|-----------------------|--------------------------------|
| Xylene     | 1330-20-7 | 100                   | 466                            |

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

|               |           |        |
|---------------|-----------|--------|
| Xylene        | 1330-20-7 | 21.4 % |
| Ethyl benzene | 100-41-4  | 8.8 %  |

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

|               |           |        |
|---------------|-----------|--------|
| Xylene        | 1330-20-7 | 21.4 % |
| Ethyl benzene | 100-41-4  | 8.8 %  |

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

|                 |           |        |
|-----------------|-----------|--------|
| Xylene          | 1330-20-7 | 21.4 % |
| n-Butyl Acetate | 123-86-4  | 11.8 % |
| Ethyl benzene   | 100-41-4  | 8.8 %  |

Non-volatile (Wt) : 45.0 %  
 Method: 23 (20min/150°C)  
 DIN EN ISO 3251

**Massachusetts Right To Know**

|                 |           |
|-----------------|-----------|
| Xylene          | 1330-20-7 |
| n-Butyl Acetate | 123-86-4  |
| Ethyl benzene   | 100-41-4  |
| Benzene         | 71-43-2   |

**Pennsylvania Right To Know**

|                              |            |
|------------------------------|------------|
| Polymer                      | -          |
| Xylene                       | 1330-20-7  |
| 1-Methoxy-2-propanol acetate | 108-65-6   |
| n-Butyl Acetate              | 123-86-4   |
| Ethyl benzene                | 100-41-4   |
| Toluene                      | 108-88-3   |
| Zinc neodecanoate            | 27253-29-8 |
| Cumene                       | 98-82-8    |
| n-Butanol                    | 71-36-3    |

**New Jersey Right To Know**

**New Jersey Trade Secret** : 800963-5416  
**Registry Number for the product (NJ TSRN)**

**California Prop. 65**

 **WARNING:** This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

**DISPERBYK-163 TF**

Version 3

Revision Date 09/05/2025

Print Date 05/07/2026

- Section 5a : No substances are subject to a Significant New Use Rule.
- Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.
- DSL : We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**

Revision Date : 09/05/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.