

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

SECTION 1. IDENTIFICATION

Product name : DISPERBYK-163 TF

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2B

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)
- single exposureSpecific target organ toxicity : Category 2 (hearing organs, Kidney, Liver)
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H315 + H320 Causes skin and eye irritation.
H335 May cause respiratory irritation.

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (hearing organs, Kidney, Liver) through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Solution of a high molecular weight block copolymer with pigment affinic groups

Hazardous components

Component	CAS-No.	Concentration (%)
Xylene	1330-20-7	>= 20 - < 30
1-Methoxy-2-propanol acetate	108-65-6	>= 10 - < 20
n-Butyl Acetate	123-86-4	>= 10 - < 20
Ethyl benzene	100-41-4	>= 5 - < 10

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : No information available.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
 Carbon dioxide (CO₂)

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Unsuitable extinguishing media	: Dry chemical : High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides : Nitrogen oxides (NOx)
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. : For safety reasons in case of fire, cans should be stored separately in closed containments. : Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. : Ensure adequate ventilation. : Remove all sources of ignition. : Evacuate personnel to safe areas. : Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. : Prevent further leakage or spillage if safe to do so. : If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. : Do not breathe vapours/dust. : Avoid contact with skin and eyes. : For personal protection see section 8. : Smoking, eating and drinking should be prohibited in the application area. : Take precautionary measures against static discharges. : Provide sufficient air exchange and/or exhaust in work rooms. : Open drum carefully as content may be under pressure. : Dispose of rinse water in accordance with local and national
-------------------------	--

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Conditions for safe storage : regulations.
 : No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
Xylene		STEL	150 ppm 655 mg/m ³	OSHA P0
Xylene		TWA	100 ppm 435 mg/m ³	OSHA P0
Xylene		TWA	20 ppm	ACGIH
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
n-Butyl Acetate	123-86-4	TWA	150 ppm 710 mg/m ³	OSHA Z-1
n-Butyl Acetate		TWA	150 ppm 710 mg/m ³	OSHA P0
n-Butyl Acetate		STEL	200 ppm 950 mg/m ³	OSHA P0
n-Butyl Acetate		TWA	150 ppm 710 mg/m ³	NIOSH REL
n-Butyl Acetate		ST	200 ppm 950 mg/m ³	NIOSH REL
n-Butyl Acetate		TWA	50 ppm	ACGIH
n-Butyl Acetate		STEL	150 ppm	ACGIH
Ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA Z-1
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA P0
Ethyl benzene		STEL	125 ppm 545 mg/m ³	OSHA P0
Ethyl benzene		ST	125 ppm 545 mg/m ³	NIOSH REL

Engineering measures : Use with local exhaust ventilation.

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Personal protective equipment

Respiratory protection	: In the case of vapour formation use a respirator with an approved filter.
Hand protection	
Material	: Impervious gloves
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: colourless
Odour	: ester-like
pH	: 5, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/freezing point	: < 32 °F (< 0 °C) Method: derived
Initial boiling point and boiling range	: 255 °F (124 °C) Method: derived
Vapour pressure	: 7 hPa (68 °F (20 °C)) Method: derived
Flash point	: 84 °F (29 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Relative vapour density	: No data available
Density	: 0.998 g/cm ³ (68 °F (20 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Solubility(ies) Water solubility	:	immiscible
Partition coefficient: n- octanol/water	:	No data available
Ignition temperature	:	> 392 °F (> 200 °C) Method: M0062 (Analytics Wesel)
Thermal decomposition	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	141.1 mm ² /s (104 °F (40 °C)) Method: calculated

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Ingestion
Eye contact
Skin contact

Acute toxicity**Product:**

Acute oral toxicity	:	Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate : 31 mg/l Exposure time: 4 h

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**1330-20-7 Xylene:**

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: no

Acute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

LD50 (Rabbit): > 4,200 mg/kg
GLP: No information available.

108-65-6 1-Methoxy-2-propanol acetate:

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

123-86-4 n-Butyl Acetate:

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg
Method: OECD Test Guideline 402

100-41-4 Ethyl benzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

Skin corrosion/irritation**Components:**

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

1330-20-7 Xylene:

Species: Rabbit

Result: Moderate skin irritation

108-65-6 1-Methoxy-2-propanol acetate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

123-86-4 n-Butyl Acetate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

100-41-4 Ethyl benzene:

Species: Rabbit

Result: Moderate skin irritation

Serious eye damage/eye irritation**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**1330-20-7 Xylene:**

Species: Rabbit

Result: Eye irritation

108-65-6 1-Methoxy-2-propanol acetate:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

123-86-4 n-Butyl Acetate:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

100-41-4 Ethyl benzene:

Species: Rabbit

Result: Moderate eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: No data available

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig
Method: OECD Test Guideline 406
Result: Not a skin sensitizer.
GLP: yes

123-86-4 n-Butyl Acetate:

Test Type: Buehler Test
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

Group 2B: Possibly carcinogenic to humans

Ethyl benzene 100-41-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: No data available

Aspiration toxicity**Product:**

No data available

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates Remarks: No data available

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste Code(s)	: D001: Ignitable
Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (Xylene, 1-Methoxy-2-propanol acetate, Butyl acetate)
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355
IMDG-Code	
UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (XYLENE, 1-Methoxy-2-propanol acetate, BUTYL ACETATE)
	:)
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

Marine pollutant : no
 Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

UN/ID/NA number : UN 1993
 Proper shipping name : Flammable liquids, n.o.s.
 (Xylene, 1-Methoxy-2-propanol acetate, Butyl acetate)
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 128
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	466

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene	1330-20-7	21.4 %
Ethyl benzene	100-41-4	8.8 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	21.4 %
Ethyl benzene	100-41-4	8.8 %

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	21.4 %
n-Butyl Acetate	123-86-4	11.8 %
Ethyl benzene	100-41-4	8.8 %

Non-volatile (Wt) : 45.0 %
 Method: 23 (20min/150°C)
 DIN EN ISO 3251

Massachusetts Right To Know

Xylene	1330-20-7
n-Butyl Acetate	123-86-4
Ethyl benzene	100-41-4
Benzene	71-43-2

Pennsylvania Right To Know

Polymer	-
Xylene	1330-20-7
1-Methoxy-2-propanol acetate	108-65-6
n-Butyl Acetate	123-86-4
Ethyl benzene	100-41-4
Toluene	108-88-3
Zinc neodecanoate	27253-29-8
Cumene	98-82-8
n-Butanol	71-36-3

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5416

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification

DISPERBYK-163 TF

Version 4

Revision Date 05/17/2026

Print Date 07/09/2026

requirements.

DSL

: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.