

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

SECTION 1. IDENTIFICATION

Product name : DISPERBYK-167

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.Precautionary statements : **Prevention:**

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting
equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON
CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately
all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air
and keep comfortable for breathing. Call a POISON CENTER/
doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water
for several minutes. Remove contact lenses, if present and easy
to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/
attention.

P337 + P313 If eye irritation persists: Get medical advice/
attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or
alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container
tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste
disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Solution of modified polyurethane
Hazardous components

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate	108-65-6	>= 34 - < 35
n-Butyl Acetate	123-86-4	>= 13 - < 14

SECTION 4. FIRST AID MEASURES

If inhaled	: Remove to fresh air. Administer artificial respiration if necessary. Get medical aid as soon as possible.
In case of skin contact	: Remove contaminated clothing. Wash thoroughly with soap and water.
In case of eye contact	: Immediately flush with plenty of water for at least 20 minutes. Get medical aid.
If swallowed	: Do not induce vomiting; aspiration hazard. Dilute with 1-2 glasses of water. Get medical aid. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Most important symptoms and effects, both acute and delayed	: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: No information available.
Specific hazards during firefighting	: Cool closed containers exposed to fire with water spray. Will not explode on mechanical impact.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NO _x)
Further information	: Keep away from heat and sources of ignition. Keep away from oxidizing agents.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Eliminate all sources of ignition. Ventilate area if indoors. Wear self-contained breathing apparatus and full protective clothing.
Environmental precautions	: Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.
Methods and materials for	: Stop leak. Dike and contain spill.

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

containment and cleaning up : Pump into salvage tanks and/or absorb with suitable material.
Use sparkless shovels to remove material.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Harmful in contact with skin.
Avoid contact with skin and eyes.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Handle as an industrial chemical.
Keep container tightly closed.

Conditions for safe storage : Avoid exposure to excessive heat, light, and air for prolonged periods of time.
Keep in a dry, cool and well-ventilated place.
Keep product and empty container away from heat and sources of ignition.
Take measures to prevent the build up of electrostatic charge.

Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
n-Butyl Acetate	123-86-4	TWA	150 ppm	ACGIH
n-Butyl Acetate		STEL	200 ppm	ACGIH
n-Butyl Acetate		TWA	150 ppm 710 mg/m ³	OSHA Z-1
n-Butyl Acetate		TWA	150 ppm 710 mg/m ³	OSHA P0
n-Butyl Acetate		STEL	200 ppm 950 mg/m ³	OSHA P0

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.

Hand protection
Material : Nitrile rubber

Eye protection : Safety Glasses
Goggles

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Clean long legged, long sleeved work clothes.

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : light yellow
Odour : ester-like
Odour Threshold : No data available

pH : 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator

Melting point/freezing point : < 32 °F (< 0 °C)
Method: derived

Initial boiling point and boiling range : 255.20 °F (124.00 °C)
Method: derived

Vapour pressure : 6 hPa (68.00 °F (20.00 °C))
Method: derived

Flash point : 95.00 °F (35.00 °C)
Method: 48 (Abel-Pensky)

Upper explosion limit : 7.00 %(V)

Lower explosion limit : 1.50 %(V)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Relative vapour density : No data available

Relative Density/Specific Gravity : No data available

Density : 1.0450 g/cm³ (68.00 °F (20.00 °C))
Method: 4 (20°C oscillating U-tube)

Solubility(ies)
Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

Ignition temperature : > 392 °F (> 200 °C)
Method: DIN 51794

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable; polymerization will not occur
Possibility of hazardous reactions : 1-Methoxy-2-propanol acetate may form peroxides of unknown stability.

Conditions to avoid : Prolonged heat/light/air exposure
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : None expected

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

123-86-4 n-Butyl Acetate:

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l
Exposure time: 4 h

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

123-86-4 n-Butyl Acetate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation**Product:**

Remarks: No data available

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: yes

123-86-4 n-Butyl Acetate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig
Method: OECD Test Guideline 406
Result: Not a skin sensitizer.

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

GLP: yes

123-86-4 n-Butyl Acetate:

Test Type: Buehler Test

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Repeated dose toxicity**Product:**

Remarks: Solvent absorption by inhalation and/or repeated skin contact may cause injury to liver, kidney and respiratory system.

Studies suggest n-Butyl acetate has caused teratogenic effects in laboratory animals at maternally toxic doses.

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

		CNS depression (drowsiness, loss of coordination and fatigue); narcosis.
Skin contact:	Symptoms:	Contact will probably cause irritation.
Eye contact:	Symptoms:	Contact will probably cause irritation.
Ingestion:	Symptoms:	Ingestion will probably irritate the digestive tract; high dosages may cause CNS depression.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Toxicity to fish : Remarks: No data available

Persistence and degradability
Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential
Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects
Product:

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA-DGR

UN/ID No. : UN 3272

Proper shipping name : Esters, n.o.s.
(Butyl acetate, 1-Methoxy-2-propanol acetate)

Class : 3

Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo aircraft) : 366

Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 3272

Proper shipping name : ESTERS, N.O.S.
(BUTYL ACETATE, 1-Methoxy-2-propanol acetate)

:)

Class : 3

Packing group : III

Labels : 3

EmS Code : F-E, S-D

Marine pollutant : no

Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

UN/ID/NA number : UN 3272
 Proper shipping name : Esters, n.o.s.
 (Butyl acetate, 1-Methoxy-2-propanol acetate)
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 127
 Marine pollutant : no
 Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
n-Butyl Acetate	123-86-4	5000	36595

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

Non-volatile (Wt) : 50 - 55 %
 Method: 23 (20min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

Massachusetts Right To Know

n-Butyl Acetate 123-86-4

Pennsylvania Right To Know

Copolymer Not Assigned
 1-Methoxy-2-propanol acetate 108-65-6
 n-Butyl Acetate 123-86-4

New Jersey Right To Know

Copolymer Not Assigned
 1-Methoxy-2-propanol acetate 108-65-6
 n-Butyl Acetate 123-86-4

New Jersey Trade Secret : 800963-5211
Registry Number for the product (NJ TSRN)

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

TSCA Inventory Active List All components of this product are listed active and/or are exempt

DSL : The following component(s) is/are not listed on the DSL:

CEPA Category : Polymer
 Weight percent : 52 %
 NSN Filed : Schedule 9
 Max. NSN Required : Schedule 10

SECTION 16. OTHER INFORMATION

Revision Date : 08/20/2021
 The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

DISPERBYK-167

Version 7

Revision Date 08/20/2021

Print Date 01/06/2026

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.