

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

SECTION 1. IDENTIFICATION

Product name : DISPERBYK-170

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting
equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Solution of modified polyurethane

Hazardous components

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate	108-65-6	>= 30 - < 60
n-Butyl Acetate	123-86-4	>= 5 - < 10

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

If swallowed	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Cool closed containers exposed to fire with water spray. Will not explode on mechanical impact. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NO _x)
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
n-Butyl Acetate	123-86-4	TWA	150 ppm 710 mg/m ³	OSHA Z-1
n-Butyl Acetate		TWA	150 ppm 710 mg/m ³	OSHA P0
n-Butyl Acetate		STEL	200 ppm 950 mg/m ³	OSHA P0
n-Butyl Acetate		TWA	150 ppm 710 mg/m ³	NIOSH REL
n-Butyl Acetate		ST	200 ppm	NIOSH REL

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

			950 mg/m3	
n-Butyl Acetate		TWA	50 ppm	ACGIH
n-Butyl Acetate		STEL	150 ppm	ACGIH

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Impervious butyl rubber gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : light yellow
Odour : ester-like
Odour Threshold : No data available

pH : 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator

Melting point/freezing point : < 32 °F (< 0 °C)
Method: derived

Initial boiling point and boiling range : 255.20 °F (124.00 °C)
Method: derived

Vapour pressure : 5 hPa (68.00 °F (20.00 °C))
Method: derived

Flash point : 96.80 °F (36.00 °C)
Method: 48 (Abel-Pensky) DIN 51755

Upper explosion limit : 10.80 %(V)

Lower explosion limit : 1.50 %(V)

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

Evaporation rate	:	No data available
Relative vapour density	:	No data available
Relative Density/Specific Gravity	:	No data available
Density	:	1.0200 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Solubility(ies) Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Surface tension	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	1-Methoxy-2-propanol acetate may form peroxides of unknown stability. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Prolonged heat/light/air exposure Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	None expected

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

123-86-4 n-Butyl Acetate:

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

123-86-4 n-Butyl Acetate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation**Product:**

Remarks: Causes serious eye irritation.

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: yes

123-86-4 n-Butyl Acetate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig
Method: OECD Test Guideline 406
Result: Not a skin sensitizer.
GLP: yes

123-86-4 n-Butyl Acetate:

Test Type: Buehler Test
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

Germ cell mutagenicity**Product:**

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: Studies suggest that 2-Methoxy-1-propanol acetate is teratogenic in animals. There is also evidence of fetotoxicity.

Studies suggest n-Butyl acetate has caused teratogenic effects in laboratory animals at maternally toxic doses.

Solvent absorption by inhalation and/or repeated skin contact may cause injury to liver, kidney and respiratory system.

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

Aspiration toxicity

Product:

No data available

Experience with human exposure

Product:

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.

Further information

Product:

Remarks: Inhalation of n-Butyl acetate may cause narcosis.

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

:

Remarks: No data available

Persistence and degradability

Product:

Biodegradability

:

Remarks: No data available

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3272
Proper shipping name : Esters, n.o.s.
(1-Methoxy-2-propanol acetate, Butyl acetate)
Class : 3
Packing group : III
Labels : Flammable Liquids

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

Packing instruction (cargo aircraft) : 366

Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 3272

Proper shipping name : ESTERS, N.O.S.
(1-Methoxy-2-propanol acetate, BUTYL ACETATE)

:)

Class : 3

Packing group : III

Labels : 3

EmS Code : F-E, S-D

Marine pollutant : no

Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

UN/ID/NA number : UN 3272

Proper shipping name : Esters, n.o.s.
(Butyl acetate, 1-Methoxy-2-propanol acetate)

Class : 3

Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 127

Marine pollutant : no

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

n-Butyl Acetate	123-86-4	9.8 %
-----------------	----------	-------

Non-volatile (Wt) : 28.5 - 31.5 %
 Method: 23 (20min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

Massachusetts Right To Know

n-Butyl Acetate	123-86-4
-----------------	----------

Pennsylvania Right To Know

1-Methoxy-2-propanol acetate	108-65-6
Copolymer	-
n-Butyl Acetate	123-86-4
Isobutanol	78-83-1

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5166

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DISPERBYK-170

Version 5

Revision Date 02/12/2025

Print Date 05/07/2026

TSCA	:	We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).
Section 4 / 12(b)	:	Not applicable
TSCA Inventory Active List	:	All components of this product are listed active and/or are exempt
Section 5a	:	No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	:	No substances are subject to TSCA 12(b) export notification requirements.
DSL	:	The following component(s) is/are not listed on the DSL:
CEPA Category	:	Polymer
Weight percent	:	31 %
NSN Filed	:	Schedule 9
Max. NSN Required	:	Schedule 10

SECTION 16. OTHER INFORMATION

Revision Date : 02/12/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.