

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

SECTION 1. IDENTIFICATION

Product name : DISPERBYK-2001

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Kidney)

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Solution of cationic methacrylate copolymer
Hazardous components

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate	108-65-6	>= 20 - < 30
2-Butoxyethanol	111-76-2	>= 10 - < 20
1-Methoxy-2-propanol	107-98-2	>= 10 - < 20

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : No information available.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.
Will not explode on mechanical impact.
- Do not allow run-off from fire fighting to enter drains or water courses.

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Hazardous combustion products	: Carbon oxides Sulphur oxides Nitrogen oxides (NO _x) Oxides of phosphorus
Further information	: Keep away from heat and sources of ignition. Keep away from oxidizing agents. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: No smoking.

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from strong acids.
Keep away from strong bases.
Keep away from oxidizing agents.
Keep away from metals.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
2-Butoxyethanol		TWA	50 ppm 240 mg/m ³	OSHA Z-1
1-Methoxy-2-propanol	107-98-2	TWA	50 ppm	ACGIH
1-Methoxy-2-propanol		STEL	100 ppm	ACGIH

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
Material : Nitrile rubber

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Clean long legged, long sleeved work clothes.
Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: yellow
Odour	: ester-like
Odour Threshold	: No data available
pH	: 6, Concentration: 10 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/range	: < 32 °F (< 0 °C) Method: derived
Initial boiling point	: 248.00 °F (120.00 °C) Method: derived
Vapour pressure	: 5 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 95.00 °F (35.00 °C) Method: 48 (Abel-Pensky)
Upper explosion limit	: 13.10 %(V)
Lower explosion limit	: 1.10 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.0270 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: completely miscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Thermal decomposition : 365 °F (185 °C)
Method: Onset DSC - 100K

Viscosity
Viscosity, dynamic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : 1-Methoxy-2-propanol acetate/1-Methoxy-2-propanol may form peroxides of unknown stability.
Gives off hydrogen by reaction with metals.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Acids
Strong oxidizing agents
Alkalis
Metals

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : 2,423 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 57.74 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Method: Calculation method

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

111-76-2 2-Butoxyethanol:

Acute inhalation toxicity : LC50 (Guinea pig): 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour

107-98-2 1-Methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat, male and female): 4,016 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 1500 ppm

Acute dermal toxicity : LD50 (Rabbit): 13,000 mg/kg

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

111-76-2 2-Butoxyethanol:

Species: Rabbit
Result: Skin irritation

107-98-2 1-Methoxy-2-propanol:

Species: Rabbit
Method: Directive 67/548/EEC, Annex V, B.4.
Result: No skin irritation
GLP: yes

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Serious eye damage/eye irritation**Product:**

Remarks: Causes serious eye irritation.

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

111-76-2 2-Butoxyethanol:

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

GLP: yes

107-98-2 1-Methoxy-2-propanol:

Species: Rabbit

Result: No eye irritation

Method: Directive 67/548/EEC, Annex V, B.5.

GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

GLP: yes

111-76-2 2-Butoxyethanol:

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

GLP: yes

107-98-2 1-Methoxy-2-propanol:

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Does not cause skin sensitisation.

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure**Product:**

Remarks: No data available

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

Repeated dose toxicity

Product:

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver/kidney/blood in laboratory animals.
2-Butoxyethanol had both positive and negative results in in vitro mutagenicity studies.
Animal studies show that 1-Methoxy-2-propanol acetate has caused damage to the respiratory system.

Aspiration toxicity

Product:

No data available

Experience with human exposure

Product:

Inhalation:

Symptoms:	High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).
-----------	---

Skin contact:

Symptoms:	Contact will probably cause irritation.
-----------	---

Eye contact:

Symptoms:	Contact with liquid or vapor will probably cause irritation.
-----------	--

Ingestion:

Symptoms:	Ingestion may irritate the digestive tract and cause same symptoms as inhalation.
-----------	---

Further information

Product:

Remarks: Absorption of 2-Butoxyethanol may cause acute red blood cell damage and kidney effects. Inhalation of 2-Butoxyethanol has damaged the kidneys of laboratory animals. OSHA PEL-TWA for 2-butoxyethanol = 50 ppm (skin)

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Toxicity to fish :
Remarks: No data available

Persistence and degradability
Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential
Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

2-Butoxyethanol	111-76-2	19.0 %
-----------------	----------	--------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

2-Butoxyethanol	111-76-2	19.0 %
-----------------	----------	--------

Non-volatile (Wt) : 44 - 48 %
 Method: 23 (20min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

Massachusetts Right To Know

2-Butoxyethanol	111-76-2
1-Methoxy-2-propanol	107-98-2

DISPERBYK-2001

Version 8

Revision Date 02/13/2023

Print Date 01/06/2026

1,4-Dioxane	123-91-1
-------------	----------

Pennsylvania Right To Know

Acrylic copolymer	-
2-Butoxyethanol	111-76-2
1-Methoxy-2-propanol acetate	108-65-6
1-Methoxy-2-propanol	107-98-2
Acetonitrile	75-05-8

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5157

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including 1,4-Dioxane, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: On the inventory, or in compliance with the inventory
Section 4 / 12(b)	: Not applicable
TSCA Inventory Active List	: All components of this product are listed active and/or are exempt
DSL	: The following component(s) is/are not listed on the DSL:
CEPA Category	: Polymer
Weight percent	: 18.00 %
NSN Filed	: Schedule 9
Max. NSN Required	: Schedule 10
	Polymer
	28.00 %
	Schedule 9
	Schedule 10

SECTION 16. OTHER INFORMATION

Revision Date : 02/13/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.